TEST REPORT

Product Name	:	Android Tv Box
Brand Mark	:	Eon Samrt Box
FCC ID	:	2AUWA-ATV4K85198
Model No.	:	SDOTT0202
Report Number	:	BLA-EMC-202107-A7502
Date of Sample Receipt	:	2021/7/19
Date of Test	:	2021/7/19 to 2021/8/18
Date of Issue	:	2021/8/18
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Shenzhen SDMC Technology Co.,Ltd.
7/F, W2-A, Hi-Tech, Industrial Park, Nanshan District

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Sven

Review by:

Approved by:

Date: 2021/8/18

BlueAsia of Technical Services(Shenzhen) Co., Ltd. BLA

REPORT REVISE RECORD

Version No.	Date	Description
00	2021/8/18	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY....5
2 GENERAL INFORMATION....6
3 GENERAL DESCRIPTION OF E.U.T....6
4 TEST ENVIRONMENT....7
5 TEST MODE....7
6 MEASUREMENT UNCERTAINTY....7
7 DESCRIPTION OF SUPPORT UNIT....8
8 LABORATORY LOCATION....8
9 TEST INSTRUMENTS LIST....9
10 ANTENNA REQUIREMENT....13
10.1 CONCLUSION....13
11 CONDUCTED SPURIOUS EMISSIONS....14
11.1 LIMITS....14
11.2 BLOCK DIAGRAM OF TEST SETUP....14
11.3 TEST DATA....15
12 CONDUCTED PEAK OUTPUT POWER....16
12.1 LIMITS....16
12.2 BLOCK DIAGRAM OF TEST SETUP....16
12.3 TEST DATA....17
13 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS....18
13.1 LIMITS....18
13.2 BLOCK DIAGRAM OF TEST SETUP....19
13.3 PROCEDURE....19
13.4 TEST DATA....21
14 DWELL TIME....25
14.1 LIMITS....25
14.2 BLOCK DIAGRAM OF TEST SETUP....25
14.3 TEST DATA....26
15 HOPPING CHANNEL NUMBER....27

BlueAsia

15.1 LIMITS 27
15.2 BLOCK DIAGRAM OF TEST SETUP 27
15.3 TEST DATA 27

16 CARRIER FREQUENCIES SEPARATION 28

16.1 LIMITS 28
16.2 BLOCK DIAGRAM OF TEST SETUP 28
16.3 TEST DATA 28

17 20DB BANDWIDTH 29

17.1 BLOCK DIAGRAM OF TEST SETUP 29
17.2 TEST DATA 29

18 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 30

18.1 LIMITS 30
18.2 BLOCK DIAGRAM OF TEST SETUP 30
18.3 PROCEDURE 30
18.4 TEST DATA 32

19 RADIATED SPURIOUS EMISSIONS 34

19.1 LIMITS 34
19.2 BLOCK DIAGRAM OF TEST SETUP 35
19.3 PROCEDURE 35
19.4 TEST DATA 37

20 CONDUCTED BAND EDGES MEASUREMENT 45

20.1 LIMITS 45
20.2 BLOCK DIAGRAM OF TEST SETUP 45
20.3 TEST DATA 46

21 APPENDIX 47

APPENDIX A: PHOTOGRAPHS OF EUT 99

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass

BlueAsia

2 GENERAL INFORMATION

Applicant	Shenzhen SDMC Technology Co.,Ltd.
Address	7/F, W2-A, Hi-Tech, Industrial Park, Nanshan District
Manufacturer	Shenzhen SDMC Technology Co.,Ltd.
Address	7/F, W2-A, Hi-Tech, Industrial Park, Nanshan District
Factory	NA
Address	NA
Product Name	Android Tv Box
Test Model No.	SDOTT0202

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V2
Software Version	9.3.68 & 9.3.69

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	PCB Antenna
Antenna Gain:	3.04(provided by the applicant)

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC12V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: *DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned Only the 8-DPSK, of the worst mode would be recorded in this report.*	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC/DC ADAPTOR	Zhuzhou Dachuan Electronic Technology Co., Ltd.	DCT12W120100US-A0	PPPPPPPYYMMDDXXXXXX	100~240Vac 50/60Hz 0.3A Max. Output12V1A
Power adapter	Dongguan Sunun Power Co., Ltd	SA12BV-120100U	340-500-283	100~240Vac 50/60Hz 0.4A Max. Output12V1A
MONITOR	DELL	S2817Q	N/A	N/A
HDMI Cable	Shenzhen Xinhongya Electronics Co. , Ltd.	HDMI cable	D6243-X Y-H053	L=1500MM

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Peak Output Power					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Radiated Emissions which fall in the restricted bands					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25

BlueAsia

Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Dwell Time

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Hopping Channel Number

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Carrier Frequencies Separation

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11

BlueAsia

Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of 20dB Bandwidth					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of Radiated Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11

BlueAsia

broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

BlueAsia

10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

10.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.04dBi.

BlueAsia

11 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

12 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

12.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

12.2 BLOCK DIAGRAM OF TEST SETUP



BlueAsia

12.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

13 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX Low channel;TX high channel
Test Mode (Final Test)	TX Low channel;TX high channel
Tester	Sven
Temperature	25℃
Humidity	52%

13.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

13.2 BLOCK DIAGRAM OF TEST SETUP







13.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

13.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: ***Horizontal***
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	45.99	-4.61	41.38	74.00	-32.62	peak			
2		2390.000	44.70	-4.27	40.43	74.00	-33.57	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: ***Vertical***
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2310.000	45.17	-4.61	40.56	74.00	-33.44	peak			
2	*	2390.000	45.84	-4.27	41.57	74.00	-32.43	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: ***Horizontal***
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	69.02	-3.84	65.18	74.00	-8.82	peak			
2	*	2483.500	56.67	-3.84	52.83	54.00	-1.17	AVG			
3		2500.000	45.37	-3.78	41.59	74.00	-32.41	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	67.68	-3.84	63.84	74.00	-10.16	peak			
2		2500.000	47.54	-3.78	43.76	74.00	-30.24	peak			
3	*	2483.500	56.61	-3.84	52.77	54.00	-1.23	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

14 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

14.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

14.2 BLOCK DIAGRAM OF TEST SETUP



BlueAsia

14.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

15 HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

15.1 LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

16 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

16.1 LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: For Details

17 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

17.1 BLOCK DIAGRAM OF TEST SETUP



17.2 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

18 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

18.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

BlueAsia

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

18.4 TEST DATA

[TestMode: TX]; [Line: Line] [Power:120V/60Hz]



Site
Phase: *L1*
Temperature:
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1940	32.51	9.83	42.34	63.86	-21.52	QP	
2		0.1940	22.36	9.83	32.19	53.86	-21.67	AVG	
3		0.4980	39.29	9.87	49.16	56.03	-6.87	QP	
4	*	0.4980	33.03	9.87	42.90	46.03	-3.13	AVG	
5		0.5340	38.48	9.87	48.35	56.00	-7.65	QP	
6		0.5340	29.70	9.87	39.57	46.00	-6.43	AVG	
7		0.8980	30.90	9.91	40.81	56.00	-15.19	QP	
8		0.8980	22.09	9.91	32.00	46.00	-14.00	AVG	
9		1.1180	32.15	9.92	42.07	56.00	-13.93	QP	
10		1.1180	20.50	9.92	30.42	46.00	-15.58	AVG	
11		1.8300	28.73	9.94	38.67	56.00	-17.33	QP	
12		1.8300	18.98	9.94	28.92	46.00	-17.08	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX]; [Line: Neutral] [Power:120V/60Hz]



Site
Phase: N
Temperature:
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4980	35.31	9.79	45.10	56.03	-10.93	QP	
2	*	0.4980	31.03	9.79	40.82	46.03	-5.21	AVG	
3		0.5420	38.17	9.79	47.96	56.00	-8.04	QP	
4		0.5420	28.84	9.79	38.63	46.00	-7.37	AVG	
5		1.0500	28.45	9.84	38.29	56.00	-17.71	QP	
6		1.0500	15.03	9.84	24.87	46.00	-21.13	AVG	
7		1.5300	27.60	9.85	37.45	56.00	-18.55	QP	
8		1.5300	19.68	9.85	29.53	46.00	-16.47	AVG	
9		2.0460	29.59	9.86	39.45	56.00	-16.55	QP	
10		2.0460	18.47	9.86	28.33	46.00	-17.67	AVG	
11		18.9260	26.55	10.40	36.95	60.00	-23.05	QP	
12		18.9260	16.51	10.40	26.91	50.00	-23.09	AVG	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

19 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX middle channel;TX Low channel;TX high channel
Test Mode (Final Test)	TX middle channel;TX Low channel;TX high channel
Tester	Sven
Temperature	25℃
Humidity	52%

19.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

19.2 BLOCK DIAGRAM OF TEST SETUP







19.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

19.4 TEST DATA

[TestMode: TX]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab（RE #1）	Project: BLA-EMC-202107-A75-1
EUT: Android Tv Box	Test Engineer:
M/N: SDOTT0202	Temperature:
S/N:	Humidity:
Test Mode: TX	Test Voltage:
Note:	Test Data: 2021-08-04 09:34:38



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	115.239MHz	43.5	27.3	-16.2	5.1	22.2	QP	Hor		
2*	266.316MHz	46.0	28.2	-17.8	5.3	22.9	QP	Hor		
3*	411.938MHz	46.0	33.1	-12.9	5.7	27.4	QP	Hor		
4*	573.079MHz	46.0	35.3	-10.7	4.8	30.5	QP	Hor		
5*	653.831MHz	46.0	36.6	-9.4	5.0	31.6	QP	Hor		
6*	895.119MHz	46.0	38.2	-7.8	3.3	34.9	QP	Hor		

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab（RE #1）	Project: BLA-EMC-202107-A75-1
EUT: Android Tv Box	Test Engineer:
M/N: SDOTT0202	Temperature:
S/N:	Humidity:
Test Mode: TX	Test Voltage:
Note:	Test Data: 2021-08-04 09:31:47



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	81.774MHz	40.0	32.0	-8.0	12.3	19.7	QP	Ver		
2*	115.966MHz	43.5	32.5	-11.0	10.2	22.3	QP	Ver		
3*	161.435MHz	43.5	31.9	-11.6	8.7	23.2	QP	Ver		
4*	226.304MHz	46.0	29.5	-16.5	7.4	22.1	QP	Ver		
5*	411.089MHz	46.0	31.9	-14.1	4.5	27.4	QP	Ver		
6*	629.581MHz	46.0	35.4	-10.6	3.9	31.5	QP	Ver		

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: ***Horizontal***
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	42.50	3.71	46.21	74.00	-27.79	peak			
2		7206.000	41.86	5.96	47.82	74.00	-26.18	peak			
3	*	9608.000	39.95	9.29	49.24	74.00	-24.76	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	41.35	3.71	45.06	74.00	-28.94	peak			
2		7206.000	42.10	5.96	48.06	74.00	-25.94	peak			
3	*	9608.000	40.04	9.29	49.33	74.00	-24.67	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Android Tv Box	Distance:	
M/N: SDOTT0202		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	41.52	3.36	44.88	74.00	-29.12	peak			
2		7323.000	40.80	6.43	47.23	74.00	-26.77	peak			
3	*	9764.000	39.34	9.63	48.97	74.00	-25.03	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Android Tv Box	Distance:	
M/N: SDOTT0202		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	42.37	3.36	45.73	74.00	-28.27	peak			
2		7323.000	40.66	6.43	47.09	74.00	-26.91	peak			
3	*	9764.000	40.20	9.63	49.83	74.00	-24.17	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Android Tv Box	Distance:	
M/N: SDOTT0202		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4960.000	41.81	3.75	45.56	74.00	-28.44	peak			
2		7440.000	41.32	6.86	48.18	74.00	-25.82	peak			
3	*	9920.000	38.81	10.16	48.97	74.00	-25.03	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4960.000	42.05	3.75	45.80	74.00	-28.20	peak			
2		7440.000	41.94	6.86	48.80	74.00	-25.20	peak			
3	*	9920.000	39.50	10.16	49.66	74.00	-24.34	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

20 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

20.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

20.2 BLOCK DIAGRAM OF TEST SETUP



20.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

21 APPENDIX

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	4.115	21	Pass
NVNT	1-DH1	2441	Ant1	4.632	21	Pass
NVNT	1-DH1	2480	Ant1	5.433	21	Pass
NVNT	2-DH1	2402	Ant1	8.996	21	Pass
NVNT	2-DH1	2441	Ant1	8.918	21	Pass
NVNT	2-DH1	2480	Ant1	8.874	21	Pass
NVNT	3-DH1	2402	Ant1	9.633	21	Pass
NVNT	3-DH1	2441	Ant1	9.424	21	Pass
NVNT	3-DH1	2480	Ant1	9.316	21	Pass

Power NVNT 1-DH1 2402MHz Ant1



Power NVNT 1-DH1 2441MHz Ant1



Power NVNT 1-DH1 2480MHz Ant1



Power NVNT 2-DH1 2402MHz Ant1



Power NVNT 2-DH1 2441MHz Ant1



Power NVNT 2-DH1 2480MHz Ant1



Power NVNT 3-DH1 2402MHz Ant1



Power NVNT 3-DH1 2441MHz Ant1



Power NVNT 3-DH1 2480MHz Ant1



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.8596349618
NVNT	1-DH1	2441	Ant1	0.86333146
NVNT	1-DH1	2480	Ant1	0.8864240235
NVNT	2-DH1	2402	Ant1	1.188753033
NVNT	2-DH1	2441	Ant1	1.200826413
NVNT	2-DH1	2480	Ant1	1.188506232
NVNT	3-DH1	2402	Ant1	1.181453238
NVNT	3-DH1	2441	Ant1	1.176154363
NVNT	3-DH1	2480	Ant1	1.190955728

OBW NVNT 1-DH1 2402MHz Ant1



OBW NVNT 1-DH1 2441MHz Ant1



OBW NVNT 1-DH1 2480MHz Ant1



OBW NVNT 2-DH1 2402MHz Ant1



OBW NVNT 2-DH1 2441MHz Ant1



OBW NVNT 2-DH1 2480MHz Ant1



OBW NVNT 3-DH1 2402MHz Ant1



OBW NVNT 3-DH1 2441MHz Ant1



OBW NVNT 3-DH1 2480MHz Ant1



Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)
NVNT	1-DH1	2402	Ant1	No-Hopping	-58.74	-20
NVNT	1-DH1	2480	Ant1	No-Hopping	-60.6	-20
NVNT	2-DH1	2402	Ant1	No-Hopping	-61.2	-20
NVNT	2-DH1	2480	Ant1	No-Hopping	-60.95	-20
NVNT	3-DH1	2402	Ant1	No-Hopping	-61.84	-20
NVNT	3-DH1	2480	Ant1	No-Hopping	-59.57	-20

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref

Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2402MHz Ant1 Ref

Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Band Edge NVNT BLE 2M 2480MHz Ant1 Ref

Band Edge NVNT BLE 2M 2480MHz Ant1 Emission



Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Emission



BlueAsia

Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	-48.33	-20	Pass
NVNT	1-DH1	2441	Ant1	-49.31	-20	Pass
NVNT	1-DH1	2480	Ant1	-48.96	-20	Pass
NVNT	2-DH1	2402	Ant1	-50.41	-20	Pass
NVNT	2-DH1	2441	Ant1	-52	-20	Pass
NVNT	2-DH1	2480	Ant1	-51.78	-20	Pass
NVNT	3-DH1	2402	Ant1	-51.59	-20	Pass
NVNT	3-DH1	2441	Ant1	-51.8	-20	Pass
NVNT	3-DH1	2480	Ant1	-52.29	-20	Pass

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref

Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref

Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref

Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref

Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref

Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref

Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Ref

Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Ref

Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission



BlueAsia

-20dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.92	0	Pass
NVNT	1-DH1	2441	Ant1	0.928	0	Pass
NVNT	1-DH1	2480	Ant1	0.91	0	Pass
NVNT	2-DH1	2402	Ant1	1.339	0	Pass
NVNT	2-DH1	2441	Ant1	1.327	0	Pass
NVNT	2-DH1	2480	Ant1	1.337	0	Pass
NVNT	3-DH1	2402	Ant1	1.329	0	Pass
NVNT	3-DH1	2441	Ant1	1.311	0	Pass
NVNT	3-DH1	2480	Ant1	1.317	0	Pass

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1

-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1

-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1



Carrier Frequencies Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2401.9915	2403.0175	1.026	0.025	Pass
NVNT	1-DH1	Ant1	2440.963	2441.962	0.999	0.928	Pass
NVNT	2-DH1	Ant1	2441.0455	2442.106	1.0605	0.885	Pass
NVNT	3-DH1	Ant1	2441.032	2442.037	1.005	0.874	Pass

CFS NVNT 1-DH1 2402MHz Ant1

CFS NVNT 1-DH1 2441MHz Ant1

CFS NVNT 2-DH1 2441MHz Ant1

CFS NVNT 3-DH1 2441MHz Ant1

Number of Hopping Channel

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1

Hopping No. NVNT 2-DH1 2441MHz Ant1

Hopping No. NVNT 3-DH1 2441MHz Ant1

Dwell Time

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2402	Ant1	0.383	119.879	313	31600	400	Pass
NVNT	1-DH1	2441	Ant1	0.128	40.192	314	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.771	256.795	145	31600	400	Pass
NVNT	1-DH5	2441	Ant1	3.02	305.02	101	31600	400	Pass

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst



Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH3 2441MHz Ant1 One Burst



Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated



BlueAsia

Band Edge(Hopping)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	Hopping	-58.08	-20	Pass
NVNT	1-DH1	2480	Ant1	Hopping	-59.32	-20	Pass
NVNT	2-DH1	2402	Ant1	Hopping	-61.16	-20	Pass
NVNT	2-DH1	2480	Ant1	Hopping	-61.23	-20	Pass
NVNT	3-DH1	2402	Ant1	Hopping	-61.53	-20	Pass
NVNT	3-DH1	2480	Ant1	Hopping	-61.63	-20	Pass

Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Emission



BlueAsia

APPENDIX A: PHOTOGRAPHS OF EUT

(Reference to the report NO.BLA-EMC-202107-A7501)

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia