

Test Report

Prepared for: Preferred Security Components Inc. of PA DBA Cartell

Model: CW-HUB

Serial Number: 260101-00808, 260101-00807

Project No: p2640011

FCC ID: 2AUXCCWHUB

IC ID: 25651-CWHUB

Test Results: Pass

To

FCC Part 15.247

&

RSS Gen Issue 5 (April 2018)

RSS-247 Issue 4 (July 2025)

Date of Issue: May 28, 2026

On behalf of the applicant:

Preferred Security Components Inc. of PA DBA Cartell
510 W King St
Shippensburg, PA 17257


Attention of:

Troy Wenger
Ph: 717-535-0033 ext. 9327
E-mail: troyw@cartell.com

Prepared By:

Compliance Testing, LLC
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
ANAB Cert#: AT-2901
FCC Site Reg. #750616
ISED Site Reg. #2044A-2
CAB US-ID: US0122

Reviewed / Authorized By:



Harshith Devaraja, EMC Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing. All results contained herein relate only to the sample tested. All samples were selected by the customer.

Test Results Summary

Test Date Range: May 12, 2026 – May 28, 2026

Specification		Test Name	Pass, Fail, N/A	Comments
FCC	RSS			
15.247(a)(2)	RSS Gen 6.7 RSS 247 6.3.1(a)	Occupied Bandwidth	Pass	
15.247(b)(3)	RSS 247 6.3.2	Transmitter Output Power	Pass	
15.247(d)	RSS 247 6.6	Conducted Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	RSS Gen 8.9/8.10 RSS 247 6.6	Spurious Emissions	Pass	
15.247(e)	RSS 247 6.3.1(b)	Power Spectral density	Pass	
15.207	RSS Gen 8.8	A/C Powerline Conducted Emissions	Pass	
15.203	RSS Gen 6.8	Antenna Requirement	Pass	
Method Deviations/Additions: No				

Statements of conformity are reported as:

- Pass - the measured value is below the acceptance limit, *acceptance limit = test limit*.
- Fail - the measured value is above the acceptance limit, *acceptance limit = test limit*.

References/Methods	Description
ANSI C63.4-2014	Method and Measurements of Radio-Noise Emissions from low-Voltage Electrical and Electronic Equipment in the range 9kHz to 40GHz.
ANSI C63.10:2020+ Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
558074 D01 15.247 Meas Guidance v05r02	Guidance for Compliance Measurements on DTS, FHSS, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules
ISO/IEC 17025:2017	General requirements for the Competence of Testing and Calibrations Laboratories

Table of Contents

<u>Description</u>	<u>Page</u>
Test Results Summary	2
Test Report Revision History	4
EUT Description	5
Test and Measurement Data.....	7
Test Setup and Modes of Operation	8
Transmitter Output Power	10
15.209/15.205 Spurious Emissions.....	15
Occupied Bandwidth	41
Power Spectral Density.....	46
Conducted Spurious Emissions	51
A/C Powerline Conducted Emissions.....	58
Test Equipment Utilized	63
Measurement Uncertainty	63

Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	May 28, 2026	Harshith Devaraja	Original Document
2.0	July 2, 2026	Harshith Devaraja	CAB US-ID updated Reference method updated IC HVIN, PMN updated BLE operating frequency updated Added EIRP table

Current revision of the test report replaces any prior versions. Only the current version of the test report is valid.

EUT Description

Model:	CW-HUB
IC HVIN:	CWHUB
IC PMN:	CWHUB
Serial:	260101-00808 Simultaneous Transmission Sample: 260101-00807
Firmware:	1032/5019
Description:	Works with Cartell's wired and wireless device to enable notifications to the Cartell app.
Additional Information:	Radio Frequency Range and Operational Info: 2.402 – 2.48 GHz BLE GFSK (1 Mbps) BLE GFSK (2 Mbps) EUT can simultaneously transmit BLE and LoRa DTS LoRa Radio Frequency Range and Operational Info: 903 – 927 MHz LoRa DTS – CSS Modulation (Spread factor 12) Usage: Fixed/Mobile
Receipt of Sample(s):	May 8, 2026
EUT Condition:	Visual Damage No State of Development Production/Production Equivalent

The applicant has been cautioned as to the following

15.21 - Information to User

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) - Special Accessories

Equipment marked to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer without an additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Authorization Requirements

Intentional Radios may require authorization covered under the following rule parts or standards:

-47 CFR Part 2 Subpart J

Note: These notices are specific to the methods and standards related to the testing within this report. Customers should also consider and review additional legal regulations for import/export documentation and labeling for the countries and geographies under consideration by the manufacturer.

Test and Measurement Data

Subpart 2.1033(b)

All tests and measurement data shown were performed in accordance with FCC Rule Parts: 15.247.

Standard Engineering Practices

Unless otherwise indicated, the procedures contained in ANSI C63.10 and ANSI C63.4 were observed during testing.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing. Measurement results, unless otherwise noted, are worst case measurements.

Standard Test Conditions and Engineering Practices

Unless otherwise indicated in the specific measurement results, the ambient temperature was maintained within the range of 10° to 40°C (50° to 104°F) and the relative humidity levels were in the range of 10% to 90%.

Environmental Conditions		
Temperature (°C)	Humidity (%)	Barometric Pressure (mbar)
22.33 - 25.56	28.3 - 31.5	962.5 - 969.8

Test Setup and Modes of Operation

EUT Operation during Tests

EUT was connected to a test laptop to control power and channel selection. The EUT was operated to control the continuous transmission of low, mid and high channels in the 2.402-2.48 GHz frequency range (BLE).

In the simultaneous transmission mode, the EUT was placed in the worst-case mode and channel for BLE and the LoRa transmission was set to its worst-case channel (middle channel). [17% duty cycle transmission]

Accessories:

Qty	Description	Manufacturer	Model	S/N
1	Test Laptop	Dell	Latitude 7490	0VNCW A00
1	Wall power adapter	ShenZhen LuXiangYuan Technology Co, Ltd	LX050100	N/A

Cables:

Qty	Description	Length (M)	Ferrites (Y/N)	Shielding Y/N	Shielded Hood Y/N	Termination / Connection
1	USB Power Cable	0.8	N	N	N	Power adapter/ EUT

Software/Firmware:

Name	Description	Version	Installation Info
ESP RF Test Tool	Radio Control Software Application	v5.2	N/A
Tera term 5	Terminal Emulator	5.6.1	N/A

Modifications to EUT(s): N/A

15.203: Antenna Requirement:

BLE Antenna

- ☒ The antenna is permanently attached to the EUT
- ☐ The antenna uses a unique coupling
- ☐ The EUT must be professionally installed
- ☐ The antenna requirement does not apply

The antenna gain stated by the manufacturer:

RF Antenna: 3.96 dBi

LORA Antenna

- ☐ The antenna is permanently attached to the EUT
- ☒ The antenna uses a unique coupling
- ☐ The EUT must be professionally installed
- ☐ The antenna requirement does not apply

The antenna gain stated by the manufacturer:

RF Antenna: 2.0 dBi

Transmitter Output Power

Engineer: Harshith Devaraja


Test Date: 05/12/26

Test Procedure

Conducted Method

EUT, via a pigtail cable, was directly connected to the spectrum analyzer to verify that the EUT met the requirements for Output Power.

Test Setup



The Spectrum Analyzer was set to the following:

RBW $\geq$ OBW Bandwidth

VBW $\geq 3 \times$ RBW

Span $\geq 3 \times$ RBW

Sweep time = auto couple

Detector = peak

Trace Mode = max hold

Transmitter Output Power Summary Table

BLE 1 Mbps

Tuned Frequency (MHz)	Conducted Peak power (dBm)	Conducted peak power (mW)	Specification Limit	Result
2402	7.16	5.2	1 W (30 dBm)	Pass
2440	7.35	5.4	1 W (30 dBm)	Pass
2480	7.20	5.2	1 W (30 dBm)	Pass

Tuned Frequency (MHz)	Conducted Peak power (dBm)	Antenna Gain (dBi)	EIRP (W)	EIRP (dBm)	EIRP Limit	Result
2402	7.16	3.96	0.0129	11.12	4 W (36 dBm)	Pass
2440	7.35	3.96	0.0135	11.31	4 W (36 dBm)	Pass
2480	7.20	3.96	0.0131	11.16	4 W (36 dBm)	Pass


BLE 2 Mbps

Tuned Frequency (MHz)	Conducted Peak power (dBm)	Conducted peak power (mW)	Specification Limit	Result
2402	6.93	4.9	1 W (30 dBm)	Pass
2440	6.88	4.9	1 W (30 dBm)	Pass
2480	6.63	4.6	1 W (30 dBm)	Pass


Tuned Frequency (MHz)	Conducted Peak power (dBm)	Antenna Gain (dBi)	EIRP (W)	EIRP (dBm)	EIRP Limit	Result
2402	6.93	3.96	0.0123	10.89	4 W (36 dBm)	Pass
2440	6.88	3.96	0.0121	10.84	4 W (36 dBm)	Pass
2480	6.63	3.96	0.0115	10.59	4 W (36 dBm)	Pass

Output Power Plots


Low Channel 1 Mbps




Mid Channel 1 Mbps




High Channel 1 Mbps




Low Channel 2 Mbps



Mid Channel 2 Mbps



High Channel 2 Mbps



15.209/15.205 Spurious Emissions

Engineer: Harshith Devaraja

Test Date: 05/18/2026

Test Procedure

Radiated Method

The EUT was set up in a semi-anechoic test chamber set 3 m from the receiving antenna. The EUT was set to transmit on the lowest, middle and highest frequency of operation at the maximum power level while the RF port was terminated to 50 Ω load. The EUT was tested, in 3 orthogonal axes, by rotating it 360° with the receive antenna in both the vertical and horizontal orientation while raised from 1 to 4 meters to ensure the TX signal levels were maximized. EUT set in the Y axis was determined as the worst-case position. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated spurious Emissions. All emissions across the required range were evaluated and emissions within 20dB margin are reported.

- BLE 1 Mbps (Worst case reported)
- Worst Case BLE 1 Mbps Low Channel and LoRa middle channel simultaneous transmission reported.

Conducted Method

As per ANSI C63.10 Section 11.12.2

EUT, via a pigtail cable, were directly connected to the spectrum analyzer to verify that the EUT met the requirements for spurious emissions.

The conducted measurement plot reported below involves the resultant conversion from the EIRP to an equivalent electric field.


$$E = \text{EIRP} - 20 \log(3) + 104.8$$

The conversion is factored into the spectrum analyzer as the reference offset.


The maximum transmit antenna gain is set to 4.0 dB.as an offset on the analyzer.

The 10 dB attenuator and pigtail cable loss at 2.4GHz is accommodated as the negative external gain while the pigtail cable loss in the rest of the frequency spectrum is accommodated via a correction factor included in the spectrum analyzer.

Conducted Test Setup



Radiated basic Test Setup



	Settings Below 1GHz	Settings Above 1GHz
RBW	120 kHz	1 MHz
VBW	300 kHz	3 MHz
Detector	Quasi Peak	Peak / Average



Sample Calculations


Corrected Value = Measured Value + Correction factor

Correction factor = Antenna Correction Factor + Cable loss + Preamp/Attenuator Factor


Conducted Method Plots

BLE Low Channel 1 Mbps








BLE Mid Channel 1 Mbps






BLE High Channel 1 Mbps






BLE Low Channel 2 Mbps








BLE Mid Channel 2 Mbps



BLE High Channel 2 Mbps







Radiated Plots

BLE Low Channel 1 Mbps

30-1000 MHz




Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
47.347	353.00	105.00	54.66	-22.44	32.20	40.00	-7.80
65.808	220.00	100.00	49.02	-25.10	23.90	40.00	-16.10
748.066	167.00	175.00	25.53	-5.17	20.40	46.00	-25.60
949.53	239.00	340.00	24.18	-1.44	22.70	46.00	-23.30
Final = Raw + Path Loss							
Margin = Final - Limit							




Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
47.145	123.00	348.00	34.13	-20.94	13.20	40.00	-26.80
239.995	356.00	145.00	43.48	-18.73	24.70	46.00	-21.30
480	355.00	203.00	46.25	-11.46	34.80	46.00	-11.20
941.247	266.00	121.00	24.34	-1.77	22.60	46.00	-23.40
Final = Raw + Path Loss							
Margin = Final - Limit							

1 – 18 GHz Range

Vertical Polarity




Horizontal Polarity




18 - 26 GHz Range

Vertical Polarity




Horizontal Polarity




BLE Mid Channel 1 Mbps

30-1000 MHz




Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
46.939	81.00	100.00	53.37	-22.24	31.10	40.00	-8.90
66.021	72.00	100.00	47.79	-25.10	22.70	40.00	-17.30
552.719	113.00	129.00	27.12	-8.26	18.90	46.00	-27.10
Final = Raw + Path Loss							
Margin = Final - Limit							




Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
47.005	60.00	246.00	32.78	-20.87	11.90	40.00	-28.10
239.973	0.00	100.00	43.39	-18.73	24.70	46.00	-21.30
479.99	0.00	211.00	46.43	-11.46	35.00	46.00	-11.00
835.044	320.00	275.00	24.73	-4.18	20.60	46.00	-25.40
Final = Raw + Path Loss							
Margin = Final - Limit							

1 – 18 GHz Range

Vertical Polarity




Horizontal Polarity




18 - 26 GHz Range

Vertical Polarity




Horizontal Polarity




BLE High Channel 1 Mbps

30-1000 MHz




Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
47.744	65.00	100.00	50.32	-22.64	27.70	40.00	-12.30
64.985	33.00	100.00	46.98	-25.10	21.90	40.00	-18.10
552.569	234.00	231.00	27.14	-8.26	18.90	46.00	-27.10
842.466	346.00	121.00	24.61	-3.62	21.00	46.00	-25.00
Final = Raw + Path Loss							
Margin = Final - Limit							




Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
240.011	359.00	137.00	45.52	-18.73	26.80	46.00	-19.20
479.995	3.00	199.00	46.18	-11.46	34.70	46.00	-11.30
940.113	265.00	158.00	24.34	-1.79	22.50	46.00	-23.50
Final = Raw + Path Loss							
Margin = Final - Limit							

1 – 18 GHz Range

Vertical Polarity



Horizontal Polarity




18 - 26 GHz Range

Vertical Polarity




Horizontal Polarity




Worst Case BLE 1 Mbps Low Channel and LoRa middle channel simultaneous transmission plots

30-1000 MHz Range



Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
47.073	92.00	105.00	41.12	-22.30	18.80	40.00	-21.20
50.991	80.00	100.00	41.68	-24.05	17.60	40.00	-22.40
497.831	159.00	100.00	37.00	-11.22	25.80	46.00	-20.20
Final = Raw + Path Loss							
Margin = Final - Limit							



***915 MHz LoRa middle channel fundamental**



Frequency	Azimuth	Height	Raw QP	Correction	Final QP	Limit	QP Margin
MHz	deg	cm	dBuV	dB	dBuV/m	dBuV/m	dB
459.816	100.00	109.00	35.76	-12.06	23.70	46.00	-22.30
850.64	97.00	394.00	22.60	-3.80	18.80	46.00	-27.20
Final = Raw + Path Loss							
Margin = Final - Limit							


***915 MHz LoRa middle channel fundamental**

1 - 3.6 GHz Range




*BLE 2.402 GHz Fundamental

3.6 – 18 GHz Range



Frequency	Azimuth	Height	Raw Pk	Raw Avg	Correction	Final Pk	Pk Limit	Pk Margin	Final Avg	Avg Limit	Avg Margin
Hz	deg	cm	dBuV	dBuV	dB	dBuV/m	dBuV/m	dB	dBuV/m	dBuV/m	dB
6389059000	228.00	105.00	44.44	30.98	-0.08	44.36	74.00	-29.64	38.60	54	-15.40
Final Pk = Raw + Path Loss											
Final Avg = Raw + Path Loss + DCCF											
Margin = Final - Limit											



*DCCF = 7.7 dB (17% duty cycle)



Frequency	Azimuth	Height	Raw Pk	Raw Avg	Correction	Final Pk	Pk Limit	Pk Margin	Final Avg	Avg Limit	Avg Margin
Hz	deg	cm	dBuV	dBuV	dB	dBuV/m	dBuV/m	dB	dBuV/m	dBuV/m	dB
5459058000	146.00	109.00	46.11	32.74	-3.43	42.68	74.00	-31.32	37.01	54	-16.99
6396983000	100.00	325.00	44.67	31.10	-0.06	44.62	74.00	-29.39	38.74	54	-15.26
Final Pk = Raw + Path Loss											
Final Avg = Raw + Path Loss + DCCF											
Margin = Final - Limit											

*DCCF = 7.7 dB (17% duty cycle)

18 - 26 GHz Range



Occupied Bandwidth

Engineer: Harshith Devaraja


Test Date: 05/12/26

Test Procedure

Conducted Method

EUT, via a pigtail cable, were directly connected to the spectrum analyzer to verify that the EUT met the requirements for Occupied Bandwidth.

Test Setup



The Spectrum Analyzer was set to the following:

RBW = 1%-5% of the OWB but not less than 100 kHz

VBW $\geq 3 \times$ RBW

Peak Detector

Trace mode = max hold

Sweep = auto couple

Span = $(1.5 - 5) \times$ OBW

-6 dB Occupied Bandwidth Summary

BLE 1 Mbps

Frequency (MHz)	Measured Bandwidth (kHz)	Specification Limit (kHz)	Result
2402	668.830	> 500	Pass
2440	672.027	> 500	Pass
2480	669.345	> 500	Pass


BLE 2 Mbps

Frequency (MHz)	Measured Bandwidth (kHz)	Specification Limit (kHz)	Result
2402	1.354	> 500	Pass
2440	1.358	> 500	Pass
2480	1.349	> 500	Pass


-6 dB and 99% Bandwidth Plots

BLE 1 Mbps


Low Channel



Mid channel




High channel




BLE 2 Mbps


Low channel



Mid channel



High channel



Power Spectral Density

Engineer: Harshith Devaraja


Test Date:05/12/26

Test Procedure

Conducted Method

EUT, via a pigtail cable, were directly connected to the spectrum analyzer to verify that the EUT met the requirements for power spectral density.

Test Setup



The Spectrum Analyzer was set to the following:

RBW = 3 kHz

VBW $\geq 3 \times$ RBW

Peak Detector

Trace mode = max hold

Sweep = auto couple

Span $> 1.5 \times$ OBW

Power Spectral Density Summary

BLE 1 Mbps


Frequency (MHz)	PSD (dBm/3kHz)	Specification Limit (dBm/3kHz)	Result
2402	-9.48	8	Pass
2440	-9.76	8	Pass
2480	-9.95	8	Pass

BLE 2 Mbps


Frequency (MHz)	PSD (dBm/3kHz)	Specification Limit (dBm/3kHz)	Result
2402	-14.59	8	Pass
2440	-15	8	Pass
2480	-14.49	8	Pass

PSD Plots


BLE 1 Mbps Low channel




Mid channel




High channel




BLE 2 Mbps Low channel



Mid channel



High channel



Conducted Spurious Emissions

Engineer: Harshith Devaraja


Test Date: 05/14/26

Test Procedure

Conducted Method

EUT, via a pigtail cable, were directly connected to the spectrum analyzer to verify that the EUT met the requirements for out of band emission in the 100 kHz bandwidth.

Test Setup



The Spectrum Analyzer was set to the following:

RBW = 100 kHz

VBW $\geq 3 \times$ RBW



Peak Detector

Trace mode = max hold


Sweep = auto couple

Conducted Spurious emission plots



BLE 1 Mbps Low channel





Mid channel




High channel





BLE 2 Mbps Low channel



Mid channel



High channel



A/C Powerline Conducted Emissions


Engineer: Harshith Devaraja

Test Date: 05/28/2026

Test Procedure


The EUT power cable was connected to a LISN and the monitored output of the LISN was connected to a transient limiter, which then connected directly to a spectrum analyzer. The conducted emissions from 150 kHz to 30 MHz were measured and compared to the specification limits.

Basic Test Setup




1. Worst Case BLE 1 Mbps Low Channel reported.
2. Worst Case BLE 1 Mbps Low Channel and LoRa middle channel simultaneous transmission reported.

BLE 1 Mbps Low Channel Plot




Frequency (MHz)	Raw QP dBuV	Raw Avg dBuV	Path Loss dB	Final QP dBuV	Final Avg dBuV	QP Limit dBuV	QP Margin dB	Avg Limit dBuV	Avg Margin dB
531.65 KHz	32.60	16.50	9.80	42.40	26.30	56.00	-13.60	46.00	-19.70
21.745 MHz	20.80	5.30	10.20	31.10	15.60	60.00	-28.90	50.00	-34.40
Final = Raw + Path Loss									
Margin = Final - Limit									




Frequency (MHz)	Raw QP dBuV	Raw Avg dBuV	Path Loss dB	Final QP dBuV	Final Avg dBuV	QP Limit dBuV	QP Margin dB	Avg Limit dBuV	Avg Margin dB
505.22 KHz	28.63	19.10	9.80	38.40	28.90	56.00	-17.60	46.00	-17.10
22.299 MHz	20.32	5.80	10.30	30.70	16.20	60.00	-29.30	50.00	-33.80
Final = Raw + Path Loss									
Margin = Final - Limit									

BLE 1 Mbps Low Channel and LoRa middle channel simultaneous transmission plot



Frequency	Raw QP	Raw Avg	Path Loss	Final QP	Final Avg	QP Limit	QP Margin	Avg Limit	Avg Margin
(MHz)	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dB	dBuV	dB
153.19 KHz	22.00	9.00	9.50	31.40	18.40	65.90	-34.50	55.90	-37.50
523.63 KHz	32.40	17.20	9.80	42.20	27.00	56.00	-13.80	46.00	-19.00
Final = Raw + Path Loss									
Margin = Final - Limit									

Compliance Testing Conducted Emissions Line 2



Frequency (MHz)	Raw QP dBuV	Raw Avg dBuV	Path Loss dB	Final QP dBuV	Final Avg dBuV	QP Limit dBuV	QP Margin dB	Avg Limit dBuV	Avg Margin dB
543.75 KHz	25.29	20.80	9.80	35.10	30.60	56.00	-20.90	46.00	-15.40
546.94 KHz	25.68	21.60	9.80	35.50	31.40	56.00	-20.50	46.00	-14.60
543.75 KHz	25.29	20.80	9.80	35.10	30.60	56.00	-20.90	46.00	-15.40
Final = Raw + Path Loss									
Margin = Final - Limit									

Test Equipment Utilized

Description	Manufacturer	Model #	CT Asset #	Last Cal Date	Cal Due Date
Horn Antenna (1-18GHz)	ARA	DRG-118/A	i00271	8/9/24	8/9/26
Horn Antenna (18-40 Ghz)	EMCO	3116	I00085	3/18/25	3/18/27
Bi-Log Antenna	Schaffner	CBL 6111D	i00349	2/27/25	2/27/27
3 Meter Semi-Anechoic Chamber	Panashield	3 Meter Semi-Anechoic Chamber	i00428	7/13/23	7/13/26
44GHz EMI receiver	Keysight	N9038A	i00552	3/23/26	3/23/27
PSA Spectrum Analyzer	Agilent	E4448A	i00688	10/22/25	10/22/26
Temp./humidity/pressure monitor (Main Lab)	Omega Engineering	iBTHX-W-5	i00686	1/25/26	1/25/27
EMI Receiver	HP	85462A	i00033	6/25/25	6/25/26
Transient Limiter	Com-Power	LIT-153	i00123	Verified on: PTV	
AC Power Source	Behlman	BL 6000	i00362	NCR	
LISN	COM-Power	LI-125A	i00447	4/9/26	4/9/28
LISN	COM-Power	LI-125A	i00449	4/9/26	4/9/28
Preamplifier	COM-Power	PAM-103	i00734	Verified on: 04/23/26	
Preamplifier	Eravant	SBB-0115034019-2F2F-E3	i00756	Verified on: 04/23/26	

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the equipment described. Prior to testing these components were tested to verify proper operation.

Measurement Uncertainty

Measurement	U_{lab}
Radio Frequency	$\pm 3.3 \times 10^{-8}$
RF Power, conducted	± 1.5 dB
RF Power Density, conducted	± 1.0 dB
Conducted Emissions	± 1.8 dB
Radiated Emissions	± 4.5 dB
Temperature	± 1.5 deg C
Humidity	± 4.3 %
DC voltage	± 0.20 VDC
AC Voltage	± 1.2 VAC

The reported expanded uncertainty $\pm U_{lab}$ (dB) has been estimated at a 95% confidence level ($k=2$)

U_{lab} is less than or equal to U_{EMC} therefore;

- Compliance is deemed to occur if no measured disturbance exceeds the disturbance limit.
- Non-Compliance is deemed to occur if any measured disturbance exceeds the disturbance limit.

END OF TEST REPORT