

TEST REPORT

Test report no.: 1-1613-25-01-02_TR1-R01



Deutsche
Akkreditierungsstelle
D-PL-12047-01-00

Testing laboratory

cetecom advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://cetecomadvanced.com>

e-mail: mail@cetecomadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12047-01-00.

ISED Testing Laboratory Recognized Listing Number: DE0001
FCC designation number: DE0002

Applicant

Robert Bosch GmbH

Robert-Bosch-Straße 200
31139 Hildesheim / GERMANY

Phone:

Contact: Ganesha Kundadka

e-mail: K.Ganesha@in.bosch.com

Manufacturer

Robert Bosch GmbH

Business Unit PS-SC
Robert-Bosch-Platz 1
70839 Gerlingen / Germany

Test standard/s

FCC 47 CFR Part 22 Federal Communications Commission, 47 code of federal regulations,
- Subpart H Part 22: Subpart H, Cellular Radiotelephone Service

FCC 47 CFR Part 24 Federal Communications Commission, 47 code of federal regulations,
Part 24: Personal Communications Services

FCC 47 CFR Part 27 Federal Communications Commission, 47 code of federal regulations,
Part 27: Miscellaneous Wireless Communications Services

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: Telematics Control Unit Generation 2
Model name: TCU2 NA IP30 (Type: TCU2 NA IP30 C-Hub)
FCC ID: 2AUXS-TCU2NAIP30A
ISED certification number: 4441A-UMCSTD31BPN
Frequency: LTE bands 7, 12, 25, 26, 66, 71
Technology tested: LTE
Antenna: External antenna: MA285 Adhesive Mount 5-in-1
Power supply: 12.0 V DC by vehicle battery
Temperature range: -40°C to +65°C

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:

cn=Michael Dorongovski-Kerbusch, o, ou,
email=michael.dorongovski@cetecomadv
anced.com, c=DE
2026.08.06 08:59:30 +02'00'

Michael Dorongovski
Lab Manager
Regulatory Services Radio

Test performed:

cn=Steffen Sonntag, o=cetecom advanced
GmbH, ou=SON-240327,
email=steffen.sonntag@cetecomadvanced.co
m, c=DE
2026.08.06 09:09:13 +02'00'

Steffen Sonntag
Testing Manager
Regulatory Services Radio

1 Table of contents

1	Table of contents.....	2
2	General information.....	4
2.1	Notes and disclaimer	4
2.2	Application details	4
2.3	Test laboratories sub-contracted	4
3	Test standard/s, references and accreditations	5
4	Reporting statements of conformity – decision rule	6
5	Test environment	7
6	Test item	7
6.1	General description	7
6.2	Additional information	7
7	Description of the test setup.....	8
7.1	Shielded semi anechoic chamber	9
7.2	Shielded fully anechoic chamber.....	10
7.3	Radiated measurements > 18 GHz	12
8	Sequence of testing.....	13
8.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	13
8.2	Sequence of testing radiated spurious 30 MHz to 1 GHz	14
8.3	Sequence of testing radiated spurious 1 GHz to 18 GHz	15
8.4	Sequence of testing radiated spurious above 18 GHz.....	16
9	Measurement uncertainty	17
10	Summary of measurement results	18
10.1	Part 22/Part 90: LTE band 26.....	18
11	RF measurements	18
11.1	Description of test setup.....	18
11.2	Results LTE band 26	18
11.2.1	RF output power radiated.....	19
11.2.2	Spurious emissions radiated	20
12	Summary of measurement results	25
12.1	Part 24/RSS-133: LTE band 25	25
13	RF measurements	25
13.1	Description of test setup.....	25
13.2	Results LTE band 25	25
13.2.1	RF output power	26
13.2.2	Spurious emissions radiated	27
14	Summary of measurement results	33
14.1	Part 27/RSS-199: LTE band 7	33
14.2	Part 27/RSS-130: LTE band 12	33
14.3	Part 27/RSS-139: LTE band 66	34
14.4	Part 27/RSS-130: LTE band 71	34
15	RF measurements	35
15.1	Description of test setup.....	35

15.2	Results LTE band 7	35
15.2.1	RF output power	35
15.2.2	Spurious emissions radiated	36
15.3	Results LTE band 12	43
15.3.1	RF output power radiated	43
15.3.2	Spurious emissions radiated	44
15.4	Results LTE band 66	49
15.4.1	RF output power	49
15.4.2	Spurious emissions radiated	50
15.5	Results LTE band 71	55
15.5.1	RF output power	55
15.5.2	Spurious emissions radiated	56
15.6	Observations	60
16	Glossary	61
17	Document history	62

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order:	2026-05-21
Date of receipt of test item:	2020-00-00
Start of test:*	2026-07-08
End of test:*	2026-08-05
Person(s) present during the test:	-/-

*Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.

2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations

Test standard	Date	Description
FCC 47 CFR Part 22 - Subpart H	2014-12-05	Federal Communications Commission, 47 code of federal regulations, Part 22: Subpart H, Cellular Radiotelephone Service
FCC 47 CFR Part 24	-/-	Federal Communications Commission, 47 code of federal regulations, Part 24: Personal Communications Services
FCC 47 CFR Part 27	-/-	Federal Communications Commission, 47 code of federal regulations, Part 27: Miscellaneous Wireless Communications Services
FCC 47 CFR Part 90	-/-	Federal Communications Commission, 47 code of federal regulations, Part 90: Private land mobile radio services
RSS – 130 Issue 2	February 2019	Equipment Operating in the Frequency Bands 617-652 MHz, 663-698 MHz, 698-756 MHz and 777-787 MHz
RSS - 132 Issue 4	January 2023	Spectrum Management and Telecommunications Radio Standards Specification - Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz
RSS - 133 Issue 7	July 2024	Spectrum Management and Telecommunications Policy - Radio Standards Specifications, 2 GHz Personal Communication Services
RSS - 139 Issue 4	September 2022	Advanced Wireless Services (AWS) Equipment Operating in the Bands 1710-1780 MHz and 2110-2180 MHz
RSS – 199 Issue 4	July 2023	Broadband Radio Service (BRS) Equipment Operating in the Band 2500-2690 MHz


Guidance	Version	Description
ANSI C63.26-2015	-/-	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
Power Meas License Systems: KDB 971168 D01	v03r01	Measurement Guidance for Certification of Licensed Digital Transmitters

4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.

measured value, measurement uncertainty, verdict



5 Test environment

Temperature	:	T_{nom} 22 °C during room temperature tests T_{max} No tests under extreme temperature conditions performed. T_{min} No tests under extreme temperature conditions performed.
Relative humidity content	:	55 %
Barometric pressure	:	1021 hpa
Power supply	:	V_{nom} 12.0 V DC by external power supply V_{max} No tests under extreme voltage conditions performed. V_{min} No tests under extreme voltage conditions performed.

6 Test item

6.1 General description

Kind of test item	:	Telematics Control Unit Generation 2
Model name	:	TCU2 NA IP30 (Type: TCU2 NA IP30 C-Hub)
HMN	:	TCU2 NA IP30 C-Hub
PMN	:	Cellular module
HVIN	:	UMC-STD31BPN
FVIN	:	MOLY.LR12A.R3
S/N serial number	:	356953710031444
Hardware status	:	1361H06
Software status	:	CHUBTCU2.NA.R07.002.004
Firmware status	:	N/A
Frequency band	:	LTE bands 7, 12, 25, 26, 66, 71
Type of radio transmission	:	OFDM
Use of frequency spectrum	:	
Type of modulation	:	QPSK, 16 – QAM
Antenna	:	External antenna: MA285 Adhesive Mount 5-in-1
Power supply	:	12.0 V DC by vehicle battery
Temperature range	:	-40°C to +65°C

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report:

1-1613-25-01-01_TR1-A101-R01
 1-1613-25-01-01_TR1-A102-R01
 1-1613-25-01-01_TR1-A103-R01

7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).


Each block diagram listed can contain several test setup configurations. All devices belonging to a test setup are identified with the same letter syntax. For example: Column Setup and all devices with an A.

Agenda: Kind of Calibration

k/cal	calibration / calibrated	EK	limited calibration
Ne/cnn	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
Ev/chk	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress
cpu	check prior usage		

7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter, EMC32 software version: 11.70.00

FS = UR + CL + AF

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

FS [dB μ V/m] = 12.35 [dB μ V] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB μ V/m] (35.69 μ V/m) @ distance

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Switch-Unit	Switch-Unit 3488A	Hewlett Packard	2719A14505	50160	cpu	-/-	-/-
2	A	Power Supply	Power Supply 6032A	Hewlett Packard	2920A04466	50161	cnn	-/-	-/-
3	A	Antenna Tower	Antenna Tower 2175	ETS-Lindgren GmbH / Taufkirchen	64762	50279	cnn	-/-	-/-
4	A	Positioning Controller	Positioning Controller 2090	ETS-Lindgren GmbH / Taufkirchen	64672	50280	cnn	-/-	-/-
5	A	TRILOG Broadband Antenna	TRILOG Broadband Antenna VULB9163	Schwarzbeck Mess-Elektronik OHG / Schönaun	216	50226	cal	05.09.2025	30.09.2027
6	A	EMI Test Receiver	EMI Test Receiver ESR3	Rohde & Schwarz Messgerätebau GmbH / Memmingen	102587	50417	cal	08.12.2025	31.12.2026
7	A	Wideband Radio Communication Tester	CMW500	Rohde & Schwarz	170616	300006251	k	05.12.2025	31.12.2027

7.2 Shielded fully anechoic chamber



Measurement distance: tri-log antenna and horn antenna 3 meter; loop antenna 3 meter / 1 meter

$$FS = UR + CA + AF$$

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:

$$FS [dB\mu V/m] = 40.0 [dB\mu V] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dB\mu V/m] (71.61 \mu V/m) @ distance$$

$$OP = AV + D - G + CA$$

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance; G-antenna gain+amplifier gain; CA-loss signal path)


Example calculation:

$$OP [dBm] = -65.0 [dBm] + 50 [dB] - 20 [dBi] + 5 [dB] = -30 [dBm] (1 \mu W)$$

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Double-Ridged Waveguide Horn Antenna	Double-Ridged Waveguide Horn Antenna 3115	EMCO Elektronik GmbH Gilching	9107-3696	300001604	cal	15.04.2025	30.04.2027
2	A, B	Anechoic chamber	Anechoic chamber FAC 3/5m	MEC Import: MWB TDK	87400/02	300000996-0000	cpu	-/-	-/-
3	A, B	Switch / Control Unit	Switch / Control Unit 3488A	Hewlett Packard	*	300000199-0000	cnn	-/-	-/-
4	A	Band Reject filter	Band Reject filter WRCG1850/1910-1835/1925-40/8SS	Wainwright Instruments GmbH Andechs	7	300003350-0000	cpu	-/-	-/-
5	A	Highpass Filter	Highpass Filter WHKX2.9/18G-12SS	Wainwright Instruments GmbH Andechs	1	300003492-0000	cpu	-/-	-/-
6	A	Highpass Filter	Highpass Filter WHK1.1/15G-10SS	Wainwright Instruments GmbH Andechs	3	300003255-0000	cpu	-/-	-/-
7	A	Highpass Filter	Highpass Filter WHKX7.0/18G-8SS	Wainwright Instruments GmbH Andechs	19	300003790-0000	cnn	-/-	-/-
8	A	Broadband Amplifier 0.5-18 GHz	Broadband Amplifier 0.5-18 GHz CBLU5184540	MEC Import: CERNEX	22049	300004481-0000	cpu	-/-	-/-
9	A, B	4U RF Switch Platform	4U RF Switch Platform L4491A	Agilent Technologies Deutschland GmbH Böblingen	MY50000037	300004509-0000	cnn	-/-	-/-
10	A, B	NEXIO EMV-Software	NEXIO EMV-Software BAT EMC V2022.0.32.0	MEC Import: Nexio		300004682-0000	cnn	-/-	-/-
11	A	RF-Amplifier	RF-Amplifier AMF-6F06001800-30-10P-R	MEC Import: NARDA-MITEQ Inc	2011572	300005241-0000	cpu	-/-	-/-
12	A, B	Power Supply	Power Supply HMP2020	Rohde & Schwarz Messgerätebau GmbH Memmingen	120579	300006406-0000	cal	03.12.2025	31.12.2027
13	B	Active Loop Antenna	Active Loop Antenna 6502	EMCO Elektronik GmbH Gilching	8905-2342	300000256-0000	cal	16.07.2025	31.07.2027
15	A, B	EMI Test Receiver	EMI Test Receiver ESU26	Rohde & Schwarz Messgerätebau GmbH Memmingen	100037	300003555-0000	cal	11.12.2025	31.12.2026
16	A, B	Wideband Radio Communication Tester	Wideband Radio Communication Tester CMW500	Rohde & Schwarz Messgerätebau GmbH Memmingen	170866	300006281-0000	cal	10.12.2025	31.12.2027

7.3 Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

$$OP = AV + D - G + CA$$

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance;
G-antenna gain+amplifier gain; CA-loss signal path)

Example calculation:

$$OP \text{ [dBm]} = -59.0 \text{ [dBm]} + 44.0 \text{ [dB]} - 20.0 \text{ [dBi]} + 5.0 \text{ [dB]} = -30 \text{ [dBm]} \text{ (1 } \mu\text{W)}$$

Equipment table:

No.	Setup	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A, B	Std. Gain Horn Antenna 18.0-26.5 GHz	638	Narda	8205	300002442-0000	cal	16.01.2026	31.01.2028
2	A, B	Broadband Low Noise Amplifier 2-40 GHz				300004541	ev	-/-	-/-
3	A, B	Signal analyzer	Signal analyzer FSV40	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101042	300004517-0000	cal	08.01.2026	31.01.2027
4	A, B	RF-Cable	ST18/SMAM/SMAM /48	Huber & Suhner	Batch no. 600918	400001182	ev	-/-	-/-
5	A, B	DC-Blocker 0.1-40 GHz	8141A	Inmet	-/-	400001185	ev	-/-	-/-
6	A	Wideband radio communication tester	Wideband radio communication tester CMW500	Rohde & Schwarz Messgerätebau GmbH Memmingen	170615	300006252-0000	cal	04.12.2025	31.12.2027

8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.26.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.26) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.26).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*)Note: The sequence will be repeated three times with different EUT orientations.

8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.26.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.26) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.26).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.26.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.26) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.26).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.26.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.26).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

9 Measurement uncertainty

Measurement uncertainty		
Test case	Uncertainty	
Antenna gain	± 3 dB	
99 % bandwidth	$\pm$ RBW	
-26 dB bandwidth	$\pm$ RBW	
Frequency stability	10^{-6}	
Maximum output power conducted	± 1.56 dB	
Block edge compliance	± 1.56 dB	
Spurious emissions conducted	> 3.6 GHz	± 1.56 dB
	> 7 GHz	± 1.56 dB
	> 18 GHz	± 2.31 dB
	≥ 40 GHz	± 2.97 dB
Spurious emissions radiated below 30 MHz	± 3 dB	
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB	
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB	
Spurious emissions radiated above 12.75 GHz	± 4.5 dB	

10 Summary of measurement results

☐	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☒	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC: CFR Part 2 & Part 22 ISED: RSS-Gen, Issue 5 & RSS 132, Issue 4	See table!	2026-08-06	Tests according customer demand.

10.1 Part 22/Part 90: LTE band 26

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	☒	☐	☐	☐	Partial testing
Frequency Stability	Extreme	Extreme	☐	☐	☐	☒	-/-
Spurious Emissions Radiated	Nominal	Nominal	☒	☐	☐	☐	-/-
Spurious Emissions Conducted	Nominal	Nominal	☐	☐	☐	☒	-/-
Block Edge Compliance	Nominal	Nominal	☐	☐	☐	☒	-/-
Occupied Bandwidth	Nominal	Nominal	☐	☐	☐	☒	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

11 RF measurements

11.1 Description of test setup

For the spurious measurements, we use the substitution method according TIA/EIA 603.

11.2 Results LTE band 26

The EUT was set to transmit the maximum power.

11.2.1 RF output power radiated

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

Measurement parameters	
Detector:	Peak / RMS
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.1 B and 7.2 B
Measurement uncertainty:	see chapter 9
Measurement procedure	FCC: § 2.1046

Limits:

FCC
§ 90.635
b) The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).
Power: 50 (ERP) PAPR: -/-
FCC
§ 22.913(a)(5) & (d)
(a)(5) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 W.
(d) The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.
Power: 38.45 dBm (ERP) PAPR: 13 dB

Results:

Output Power radiated (ERP)			
Bandwidth (MHz)	Channel	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
10	Middle channel	19.2	-/-

11.2.2 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 844 MHz. Measurement made up to 9 GHz. The resolution bandwidth is set as outlined in Part 22.917. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to mid channel of the LTE band 26.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	2 s
Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.1 setup A and 7.2 setup A+B
Measurement uncertainty:	See chapter 9
Measurement procedure:	FCC: § 2.1053

Limits:

FCC	
§ 22.917(a) & (b)	§ 90.691 (a)(2)
(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. (b)(1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a RBW of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. (b)(2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz.	For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.
-13 dBm	

Results:**QPSK:**


SPURIOUS EMISSION LEVEL					
LOWEST CHANNEL		MIDDLE CHANNEL		HIGHEST CHANNEL	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	

16-QAM:


SPURIOUS EMISSION LEVEL					
LOWEST CHANNEL		MIDDLE CHANNEL		HIGHEST CHANNEL	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	

QPSK


Plot 1: MIDDLE CHANNEL (9 KHZ - 30 MHZ)



Plot 2: MIDDLE CHANNEL (30 MHz – 1 GHz)




Plot 3: MIDDLE CHANNEL (1 GHz – 12.75 GHz)




16-QAM


Plot 1: MIDDLE CHANNEL (9 KHZ - 30 MHZ)



Plot 2: MIDDLE CHANNEL (30 MHz – 1 GHz)



Plot 3: Mid channel (1 GHz – 12.75 GHz)



12 Summary of measurement results

☐	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☒	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC: CFR Part 2 & Part 24 ISED: RSS-Gen, Issue 5 RSS 133, Issue 7 & SRSP-510, Issue 5	See table!	2026-08-06	Tests according customer demand

12.1 Part 24/RSS-133: LTE band 25

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	☒	☐	☐	☐	Partial testing
Frequency Stability	Extreme	Extreme	☐	☐	☐	☒	-/-
Spurious Emissions Radiated	Nominal	Nominal	☒	☐	☐	☐	-/-
Spurious Emissions Conducted	Nominal	Nominal	☐	☐	☐	☒	-/-
Block Edge Compliance	Nominal	Nominal	☐	☐	☐	☒	-/-
Occupied Bandwidth	Nominal	Nominal	☐	☐	☐	☒	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

13 RF measurements

13.1 Description of test setup

For the spurious measurements we use the substitution method according TIA/EIA 603.

13.2 Results LTE band 25

The EUT was set to transmit the maximum power.

13.2.1 RF output power

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

Measurement parameters	
Detector:	Peak / RMS
Resolution bandwidth:	40 MHz
Used equipment:	See chapter 7.2 setup B
Measurement uncertainty:	See chapter 9
Measurement procedure:	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
§ 24.232(c)	RSS-133, 6.4 (referring to: SRSP-510, Issue 5)
(c) Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications. (d) In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	SRSP-510, 5.1: Mobile stations and hand-held portables are limited to 2 watts maximum EIRP. RSS-133, 6.4: In addition, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.
Power: 33 dBm EIRP PAPR: 13 dB	

Results:

Output Power radiated (ERP)			
Bandwidth (MHz)	Channel	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
10	Middle channel	22.7	-/-

13.2.2 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to mid channel of the LTE band 25.

Measurement:

Measurement parameters	
Detector:	Peak
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.1 setup A and 7.2 setup A+B and 7.3 setup A
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:

FCC	ISED
§ 24.238 (a) & (b)	RSS-133, 6.5
(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. (b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.	In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts). After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log(P) (watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.
-13 dBm	

Results:**QPSK:**


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	

16-QAM:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	


Plots (QPSK):

Plot 1: Middle channel (9 KHZ - 30 MHZ)






Plot 2: Middle channel (30 MHz – 1 GHz)




Plot 3: Middle channel (1 GHz – 18 GHz)

Frequency [MHz]	Limit [dBm]	Final result [dBm]	Margin [dB]	Result	Remark
1882.5		Carrier notched with 1.9 GHz rejection filter			
1962.5		Downlink of the test system			

Plot 4: Middle channel (18 GHz – 26 GHz), valid for both modulations

Plots (16-QAM):**Plot 1: Middle channel (9 kHz - 30 MHz)****Plot 2: Middle channel (30 MHz – 1 GHz)**

Plot 3: Middle channel (1 GHz – 18 GHz)

Frequency [MHz]	Limit [dBm]	Final result [dBm]	Margin [dB]	Result	Remark
1882.5	Carrier notched with 1.9 GHz rejection filter				
1962.5	Downlink of the test system				

14 Summary of measurement results

☐	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☒	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC: CFR Part 2 & Part 27 ISED: RSS-Gen, Issue 5 RSS-130, Issue 2 (LTE Bands 12, 71) RSS-139, Issue 4 (LTE Band 66) RSS-199; Issue 4 (LTE Band 7)	See table!	2026-08-06	Tests according customer demand

14.1 Part 27/RSS-199: LTE band 7

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	☒	☐	☐	☐	Partial testing
Frequency Stability	Extreme	Extreme	☐	☐	☐	☒	-/-
Spurious Emissions Radiated	Nominal	Nominal	☒	☐	☐	☐	-/-
Spurious Emissions Conducted	Nominal	Nominal	☐	☐	☐	☒	-/-
Block Edge Compliance	Nominal	Nominal	☐	☐	☐	☒	-/-
Occupied Bandwidth	Nominal	Nominal	☐	☐	☐	☒	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

14.2 Part 27/RSS-130: LTE band 12

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	☒	☐	☐	☐	Partial testing
Frequency Stability	Extreme	Extreme	☐	☐	☐	☒	-/-
Spurious Emissions Radiated	Nominal	Nominal	☒	☐	☐	☐	-/-
Spurious Emissions Conducted	Nominal	Nominal	☐	☐	☐	☒	-/-
Block Edge Compliance	Nominal	Nominal	☐	☐	☐	☒	-/-
Occupied Bandwidth	Nominal	Nominal	☐	☐	☐	☒	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

14.3 Part 27/RSS-139: LTE band 66

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	☒	☐	☐	☐	Partial testing
Frequency Stability	Extreme	Extreme	☐	☐	☐	☒	-/-
Spurious Emissions Radiated	Nominal	Nominal	☒	☐	☐	☐	-/-
Spurious Emissions Conducted	Nominal	Nominal	☐	☐	☐	☒	-/-
Block Edge Compliance	Nominal	Nominal	☐	☐	☐	☒	-/-
Occupied Bandwidth	Nominal	Nominal	☐	☐	☐	☒	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

14.4 Part 27/RSS-130: LTE band 71

Test Case	temperature conditions	power source voltages	C	NC	NA	NP	Remark
RF Output Power	Nominal	Nominal	☒	☐	☐	☐	Partial testing
Frequency Stability	Extreme	Extreme	☐	☐	☐	☒	-/-
Spurious Emissions Radiated	Nominal	Nominal	☒	☐	☐	☐	-/-
Spurious Emissions Conducted	Nominal	Nominal	☐	☐	☐	☒	-/-
Block Edge Compliance	Nominal	Nominal	☐	☐	☐	☒	-/-
Occupied Bandwidth	Nominal	Nominal	☐	☐	☐	☒	-/-

Notes:

C	Compliant	NC	Not compliant	NA	Not applicable	NP	Not performed
----------	-----------	-----------	---------------	-----------	----------------	-----------	---------------

15 RF measurements

15.1 Description of test setup

For the spurious measurements we use the substitution method according TIA/EIA 603.

15.2 Results LTE band 7

The EUT was set to transmit the maximum power.

15.2.1 RF output power

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

Measurement parameters	
Detector:	Peak / RMS
Resolution bandwidth:	40 MHz
Used equipment:	See chapter 7.4 setup B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
§ 27.50(h)(2)	RSS-199, 5.5
Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power	Subscriber equipment other than fixed subscriber equipment shall not exceed an EIRP of 2W per channel bandwidth. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.
Power: 33 dBm EIRP PAPR: 13 dB (Only ISED)	

Results:

Output Power radiated (ERP)			
Bandwidth (MHz)	Channel	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
10	Middle channel	22.5	-/-

15.2.2 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 2570 MHz. Measured up to 40 GHz (depends on the transmitter channel). The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to mid channel of the LTE band 7.

Measurement:

Measurement parameters	
Detector	Peak
Video bandwidth	Below 1 GHz: 100 kHz Above 1 GHz: 1 MHz
Resolution bandwidth	Below 1 GHz: 100 kHz Above 1 GHz: 1 MHz
Span	100 MHz Steps
Trace mode	Max Hold
Setup	See chapter 7.1 setup A & 7.2 setup A+B & 7.3 setup A
Measurement uncertainty	See chapter 9

Limits:

FCC	ISED										
§ 27.53(m) (4)	RSS-199, 5.6										
For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.	Table 5: <table border="1"> <thead> <tr> <th>Offset from the edge of the frequency block or frequency block group (MHz)</th><th>Unwanted emission limits</th></tr> </thead> <tbody> <tr> <td>0-1</td><td>-10 dBm/(2% of OB*)</td></tr> <tr> <td>1-5</td><td>-10 dBm/MHz</td></tr> <tr> <td>5-X**</td><td>-13 dBm/MHz</td></tr> <tr> <td>$\geq X$</td><td>-25 dBm/MHz</td></tr> </tbody> </table> In addition to complying with the limits in table 5, subscriber equipment other than fixed subscriber equipment shall not exceed -13 dBm/MHz on all frequencies between 2490.5 MHz and 2496 MHz, and -25 dBm/MHz at or below 2490.5 MHz.	Offset from the edge of the frequency block or frequency block group (MHz)	Unwanted emission limits	0-1	-10 dBm/(2% of OB*)	1-5	-10 dBm/MHz	5-X**	-13 dBm/MHz	$\geq X$	-25 dBm/MHz
Offset from the edge of the frequency block or frequency block group (MHz)	Unwanted emission limits										
0-1	-10 dBm/(2% of OB*)										
1-5	-10 dBm/MHz										
5-X**	-13 dBm/MHz										
$\geq X$	-25 dBm/MHz										
-25 dBm											

QPSK


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	

16-QAM:


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	



Plots (QPSK):



Plot 1: Middle channel (9 kHz - 30 MHz)




Plot 2: Middle channel (30 MHz – 1 GHz)



Plot 3: Middle channel (1 GHz – 18 GHz)**Plot 4:** Middle channel (18 GHz to 26 GHz), valid for both modulations

Plots (16-QAM):**Plot 1: Middle channel (9 kHz - 30 MHz)****Plot 2: Middle channel (30 MHz – 1 GHz)**

Plot 3: Middle channel (1 GHz – 18 GHz)



15.3 Results LTE band 12

The EUT was set to transmit the maximum power.

15.3.1 RF output power radiated

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

Measurement parameters	
Detector:	Peak / RMS
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.1 – B and 7.2 – B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
47 CFR 27.50(c)(9)	RSS-130, 4.6.1 & 4.6.3
Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.	4.6.1: The transmitter output power shall be measured in terms of average power. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission. 4.6.3: The ERP shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The ERP shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.
Power: 34.77 dBm (ERP) PAPR: 13 dB (ISED only)	

Results:

Output Power radiated (ERP)			
Bandwidth (MHz)	Channel	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
10	Middle channel	20.6	-/-

15.3.2 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 711 MHz. Measured up to 8 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band 12.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	2 sec.
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.1 setup A & 7.2 setup A+B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:



FCC	ISED
§ 27.53(g)	RSS-130, 4.7.1
For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	

Results:**QPSK**


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	

16-QAM:

Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	


Plots (QPSK):**Plot 1: Middle channel (9 kHz - 30 MHz)****Plot 2: Middle channel (30 MHz - 1 GHz)**

Plot 3: Middle channel (1 GHz – 12.75 GHz)




Plots (16-QAM):


Plot 1: Middle channel (9 kHz - 30 MHz)



Plot 2: Middle channel (30 MHz - 1 GHz)



Plot 3: Middle channel (1 GHz – 12.75 GHz)



15.4 Results LTE band 66

The EUT was set to transmit the maximum power.

15.4.1 RF output power

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

Measurement parameters	
Detector:	Peak / RMS
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.4 setup B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
§ 27.50(d)(4) & (5)	RSS-139, 6.5
(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. (5) In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	The equivalent isotropically radiated power (e.i.r.p.) for mobile and portable transmitters shall not exceed one watt. In addition, the peak to average power ratio (PAPR) of the equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal that corresponds to the highest PAPR during periods of continuous transmission.
Power: 33 dBm EIRP PAPR: 13 dB	

Results:

Output Power radiated (ERP)			
Bandwidth (MHz)	Channel	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
10	Middle channel	22.1	-/-

15.4.2 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1780 MHz. Measurement made up to 18 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to mid channel of the LTE band 66.

Measurement:

Measurement parameters	
Detector:	Peak
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.1 setup A & 7.2 setup A+B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:



FCC	ISED
§ 27.53(h)(1) & (3)	RSS-139, 6.6
(1) Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB. (3) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.	i. In the first 1.0 MHz bands immediately outside and adjacent to the equipment's smallest operating frequency block, which can contain the equipment's occupied bandwidth, the emission power per any 1% of the emission bandwidth shall be attenuated below the transmitter output power P (in dBW) by at least $43 + 10 \log_{10}(P)$ (watts) dB. ii. After the first 1.0 MHz outside the equipment's smallest operating frequency block, which can contain the equipment's occupied bandwidth, the emission power in any 1 MHz bandwidth shall be attenuated below the transmitter output power P (in dBW) by at least $43 + 10 \log_{10}(P)$ (watts) dB.
-13 dBm	

Results:**QPSK**


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	

16-QAM:

Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	


Plots (QPSK):**Plot 1: Middle channel (9 kHz - 30 MHz)****Plot 2: Middle channel (30 MHz to 1GHz)**

Plot 3: Middle channel (1 GHz to 18GHz)




Plots (16-QAM):


Plot 1: Middle channel (9 kHz - 30 MHz)



Plot 2: Middle channel (30 MHz to 1 GHz)



Plot 3: Middle channel (1 GHz to 18 GHz)



15.5 Results LTE band 71

The EUT was set to transmit the maximum power.

15.5.1 RF output power

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

Measurement parameters	
Detector:	Peak / RMS
Resolution bandwidth:	1 MHz
Used equipment:	See chapter 7.1 – B and 7.2 – B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1046 ISED: RSS-Gen, 6.12

Limits:

FCC	ISED
47 CFR 27.50(c)(9)	RSS-130, 4.6.1 & 4.6.3
Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.	4.6.1: The transmitter output power shall be measured in terms of average power. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission. 4.6.3: The ERP shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The ERP shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.
Power: 34.77 dBm (ERP) PAPR: 13 dB (ISED only)	

Results:

Output Power radiated (ERP)			
Bandwidth (MHz)	Channel	Average Output Power (dBm) QPSK	Average Output Power (dBm) 16-QAM
10	Middle channel	21.2	-/-

15.5.2 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2014 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 698 MHz. Measured up to 8 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band 71.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	2 sec.
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	100 MHz Steps
Trace mode:	Max Hold
Used equipment:	See chapter 7.1 setup A & 7.2 setup A+B
Measurement uncertainty:	See chapter 9
Measurement procedure	FCC: § 2.1053 ISED: RSS-Gen, 6.13

Limits:



FCC	ISED
§ 27.53(g)	RSS-130, 4.7.1
For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.	The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.
-13 dBm	

Results:**QPSK**


Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		1125 MHz	-60.6	NP	

16-QAM:

Spurious Emission Level					
Lowest channel		Middle channel		Highest channel	
Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]	Spurious emissions	Level [dBm]
NP		-/-	-/-	NP	


Plots (QPSK):**Plot 1: Middle channel (9 kHz - 30 MHz)****Plot 2: Middle channel (30 MHz to 1GHz)**



Plot 3: Middle channel (1 GHz to 12.75GHz)



Plots (16-QAM):

Plot 1: Middle channel (9 kHz - 30 MHz)



Plot 2: Middle channel (30 MHz to 1 GHz)**Plot 3:** Middle channel (1 GHz to 12.75 GHz)

15.6 Observations

No observations except those reported with the single test cases have been made.

16 Glossary

AVG	Average
C	Compliant
C/N₀	Carrier to noise-density ratio, expressed in dB-Hz
CAC	Channel availability check
CW	Clean wave
DC	Duty cycle
DFS	Dynamic frequency selection
DSSS	Dynamic sequence spread spectrum
DUT	Device under test
EN	European Standard
ETSI	European Telecommunications Standards Institute
EMC	Electromagnetic Compatibility
EUT	Equipment under test
FCC	Federal Communications Commission
FCC ID	Combination of Grantee Code and Equipment Product Code
FHSS	Frequency hopping spread spectrum
FVIN	Firmware version identification number
GNSS	Global Navigation Satellite System
GUE	GNSS User Equipment
HMN	Host marketing name
HVIN	Hardware version identification number
HW	Hardware
ISED	Innovation, Science and Economic Development Canada
Inv. No.	Inventory number
MC	Modulated carrier
NA	Not applicable
NC	Not compliant
NOP	Non occupancy period
NP	Not performed
OBW	Occupied bandwidth
OC	Operating channel
OCW	Operating channel bandwidth
OFDM	Orthogonal frequency division multiplexing
OOB	Out of band
OP	Occupancy period
PER	Packet error rate
PMN	Product marketing name
PP	Positive peak
QP	Quasi peak
RLAN	Radio local area network
S/N or SN	Serial number
SW	Software
UUT	Unit under test
WLAN	Wireless local area network

17 Document history

Version	Applied changes	Date of release
R01	Initial release	2026-08-06

END OF TEST REPORT