TEST REPORT

No. I22N02450-BT

for

Realme Chongqing Mobile Telecommunications Corp., Ltd.

Mobile Phone

Model Name: RMX3710

with

Hardware Version: 11

Software Version: ColorOS 13.0

FCC ID: 2AUYFRMX3710

Issued Date: 2022-12-19

Designation Number: CN1210

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn. www.saict.ac.cn

©Copyright. All rights reserved by SAICT.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I22N02450-BT	Rev.0	1st edition	2022-12-19

Note: the latest revision of the test report supersedes all previous versions.

©Copyright. All rights reserved by SAICT.

CONTENTS

CONTENTS 3
1. SUMMARY OF TEST REPORT 4
1.1. TEST ITEMS 4
1.2. TEST STANDARDS 4
1.3. TEST RESULT 4
1.4. TESTING LOCATION 4
1.5. PROJECT DATA 4
1.6. SIGNATURE 4
2. CLIENT INFORMATION 5
2.1. APPLICANT INFORMATION 5
2.2. MANUFACTURER INFORMATION 5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 6
3.1. ABOUT EUT 6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 6
3.4. GENERAL DESCRIPTION 7
4. REFERENCE DOCUMENTS 8
4.1. DOCUMENTS SUPPLIED BY APPLICANT 8
4.2. REFERENCE DOCUMENTS FOR TESTING 8
5. TEST RESULTS 9
5.1. TESTING ENVIRONMENT 9
5.2. TEST RESULTS 9
5.3. STATEMENTS 9
6. TEST EQUIPMENTS UTILIZED 10
7. LABORATORY ENVIRONMENT 11
8. MEASUREMENT UNCERTAINTY 12
ANNEX A: DETAILED TEST RESULTS 13
TEST CONFIGURATION 13
A.0 ANTENNA REQUIREMENT 16
A.1 MAXIMUM PEAK OUTPUT POWER 17
A.2 BAND EDGES COMPLIANCE 18
A.3 CONDUCTED EMISSION 25
A.4 RADIATED EMISSION 31
A.5 20DB BANDWIDTH 43
A.6 TIME OF OCCUPANCY (DWELL TIME) 49
A.7 NUMBER OF HOPPING CHANNELS 53
A.8 CARRIER FREQUENCY SEPARATION 55
A.9 AC POWER LINE CONDUCTED EMISSION 57

©Copyright. All rights reserved by SAICT.

1. Summary of Test Report

1.1. Test Items

Description	Mobile Phone
Model Name	RMX3710
Applicant's name	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Manufacturer's Name	Realme Chongqing Mobile Telecommunications Corp., Ltd.

1.2. Test Standards

FCC Part15-2021; ANSI C63.10-2013.

1.3. Test Result

Pass

Please refer to "5.2.Test Results"

1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000

1.5. Project data

Testing Start Date:	2022-11-23
Testing End Date:	2022-12-13

1.6. Signature

Lin Zechuang
(Prepared this test report)

An Ran
(Reviewed this test report)

Zhang Bojun
(Approved this test report)

©Copyright. All rights reserved by SAICT.

2. Client Information

2.1. Applicant Information

Company Name:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address:	No.178 Yulong Avenue,Yufengshan,Yubei District,Chongqing,China
Contact Person	Yang LiangPing
E-Mail	ylp@realme.net
Telephone:	(86)13798864426
Fax:	/

2.2. Manufacturer Information

Company Name:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address:	No.178 Yulong Avenue,Yufengshan,Yubei District,Chongqing,China
Contact Person	Yang LiangPing
E-Mail	ylp@realme.net
Telephone:	(86)13798864426
Fax:	/

©Copyright. All rights reserved by SAICT.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Mobile Phone
Model Name	RMX3710
Frequency Band	ISM 2400MHz~2483.5MHz
Equipment type	Bluetooth® BR/EDR
Type of Modulation	GFSK/π/4 DQPSK/8DPSK
Number of Channels	79
Antenna Type	Integrated antenna
Antenna Gain	-1.11dBi
Power Supply	3.87V DC by Battery
FCC ID	2AUYFRMX3710
Condition of EUT as received	No abnormality in appearance

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of Receipt
UT07aa	863851060019793 863851060019785	11	ColorOS 13.0	2022-11-22
UT01aa	863851060019934 863851060019926	11	ColorOS 13.0	2022-11-22

*EUT ID: is used to identify the test sample in the lab internally.

UT07aa is used for conduction test, UT01aa is used for radiation test and AC Power line Conducted Emission test.

3.3. Internal Identification of AE used during the test

AE No.	Description	AE ID*
AE1	Battery	/
AE2	Charger	/
AE3	USB Cable	/
AE4	Headset	/

AE1

Model	BLP875
Manufacturer	Sunwoda Electronic Co.Ltd.
Capacity	4880mAh
Nominal Voltage	3.87 V

AE2

Model	VCB3HDUH
Manufacturer	Shenzhen Huntkey Chiyuan Electric Co., LTD

©Copyright. All rights reserved by SAICT.

Specification	American Standard Charger
AE3	
Model	DL150
Manufacturer	/
AE4	
Model	MH156
Manufacturer	/

*AE ID and AE Label: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of Mobile Phone with integrated antenna and battery.
It consists of normal options: Lithium Battery, Charger, USB Cable and Headset.
Manual and specifications of the EUT were provided to fulfil the test.
Samples undergoing test were selected by the client.

©Copyright. All rights reserved by SAICT.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz	2021
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013

©Copyright. All rights reserved by SAICT.

5. Test Results

5.1. Testing Environment

Normal Temperature: 15~35℃

Relative Humidity: 20~75%

5.2. Test Results

No	Test cases	Sub-clause of Part 15C	Verdict
0	Antenna Requirement	15.203	**P**
1	Maximum Peak Output Power	15.247 (b)	**P**
2	Band Edges Compliance	15.247 (d)	**P**
3	Conducted Spurious Emission	15.247 (d)	**P**
4	Radiated Spurious Emission	15.247,15.205,15.209	**P**
5	Occupied 20dB bandwidth	15.247(a)	/
6	Time of Occupancy(Dwell Time)	15.247(a)	**P**
7	Number of Hopping Channel	15.247(a)	**P**
8	Carrier Frequency Separation	15.247(a)	**P**
9	AC Power line Conducted Emission	15.107,15.207	**P**

See **ANNEX A** for details.

5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacturer as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.

Disclaimer:

A. After confirmation with the customer, the sample information provided by the customer may affect the validity of the measurement results in this report, and the impact and consequences arising therefrom shall be borne by the customer.

B. The samples in this report are provided by the customer, and the test results are only applicable to the samples received.

©Copyright. All rights reserved by SAICT.

6. Test Equipments Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Vector Signal Analyzer	FSV40	100903	Rohde & Schwarz	2022-12-29	1 year
2	Power Sensor	U2021XA	MY55430013	Keysight	2022-12-29	1 year
3	Data Acquisition	U2531A	TW55443507	Keysight	/	/
4	RF Control Unit	JS0806-2	21C8060398	Tonscend	2023-05-08	1 year
5	Wireless Connective Tester	CMW270	100540	Rohde & Schwarz	2023-03-13	1 year
6	Shielding Room	S81	CT000986-1344	ETS-Lindgren	2026-09-12	5 years

Radiated test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Test Receiver	ESR7	101676	Rohde & Schwarz	2023-11-23	1 year
2	BiLog Antenna	3142E	0224831	ETS-Lindgren	2024-05-27	3 years
3	Horn Antenna	3117	00066577	ETS-Lindgren	2025-04-17	3 years
4	Anechoic Chamber	FACT3-2.0	1285	ETS-Lindgren	2023-05-29	2 years
5	Spectrum Analyzer	FSV40	101192	Rohde & Schwarz	2023-01-12	1 year
6	Loop Antenna	HLA6120	35779	TESEQ	2025-05-10	3 years
7	Horn Antenna	QSH-SL-18-26-S-20	17013	Q-par	2023-01-06	3 years
8	Test Receiver	ESCI	100702	Rohde & Schwarz	2023-01-12	1 year
9	LISN	ENV216	102067	Rohde & Schwarz	2023-07-14	1 year

Test software

No.	Equipment	Manufacturer	Version
1	JS1120-3	Tonscend	3.2
2	EMC32	Rohde & Schwarz	10.50.40

EUT is engineering software provided by the customer to control the transmitting signal.
The EUT was programmed to be in continuously transmitting mode.

©Copyright. All rights reserved by SAICT.

7. Laboratory Environment

Shielded room

Temperature	Min. = 15 ˚C, Max. = 35 ˚C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω

Anechoic chamber

Temperature	Min. = 15 ˚C, Max. = 35 ˚C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	<±4 dB, 3 m distance, from 30 to 1000 MHz
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

©Copyright. All rights reserved by SAICT.

8. Measurement Uncertainty

Test Name	Uncertainty (*k*=2)	
1. Maximum Peak Output Power	1.32dB	
2. Band Edges Compliance	1.92dB	
3. Transmitter Spurious Emission - Conducted	30MHz≤f<1GHz	1.41dB
	1GHz≤f<7GHz	1.92dB
	7GHz≤f<13GHz	2.31dB
	13GHz≤f≤26GHz	2.61dB
4.. Transmitter Spurious Emission - Radiated	9kHz≤f<30MHz	1.79dB
	30MHz≤f<1GHz	4.86dB
	1GHz≤f<18GHz	4.82dB
	18GHz≤f≤40GHz	2.90dB
5. 20dB Bandwidth	4.56kHz	
6. Time of Occupancy (Dwell Time) & Number of Hopping Channels	0.58ms	
7. Carrier Frequency Separation	4.56kHz	
8. AC Power line Conducted Emission	150kHz≤f≤30MHz	2.62dB

©Copyright. All rights reserved by SAICT.

ANNEX A: Detailed Test Results

Test Configuration

The measurement is made according to ANSI C63.10.

1) Conducted Measurements

1. Connect the EUT to the test system correctly.
2. Set the EUT to the required work mode.
3. Set the EUT to the required channel.
4. Set the EUT hopping mode (hopping on or hopping off).
5. Set the spectrum analyzer to start measurement.
6. Record the values.



2) Radiated Measurements

Test setup:

9kHz-30MHz:

The EUT are measured in a anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.



©Copyright. All rights reserved by SAICT.

30MHz-26.5GHz:

The EUT are measured in a anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving antenna is 1.0 meter to 4.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.

30MHz-1GHz:



1GHz-3GHz:



©Copyright. All rights reserved by SAICT.

3GHz-26.5GHz:



3) AC Power line Conducted Emission Measurement

The EUT is working as Bluetooth terminal. A communication link of Bluetooth is set up with a System Simulator (SS). The EUT is commanded to operate at maximum transmitting power.



©Copyright. All rights reserved by SAICT.

A.0 Antenna requirement

Measurement Limit:

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Conclusion: The Directional gains of antenna used for transmitting is -1.11dBi.
The RF transmitter uses an integrate antenna without connector.

©Copyright. All rights reserved by SAICT.

A.1 Maximum Peak Output Power

Method of Measurement: See ANSI C63.10-clause 7.8.5.

A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

Measurement Results:

Mode	Peak Conducted Output Power (dBm)			Conclusion
	2402MHz (CH0)	2441MHz (CH39)	2480MHz (CH78)	
GFSK	10.13	10.05	10.89	**P**
π/4 DQPSK	9.92	9.71	9.95	**P**
8DPSK	9.86	9.56	10.12	**P**

Conclusion: Pass

©Copyright. All rights reserved by SAICT.

A.2 Band Edges Compliance

Method of Measurement: See ANSI C63.10-clause 7.8.6.

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

Measurement Result:

Mode	Frequency (MHz)	Hopping	Test Results	Conclusion
GFSK	2402(CH0)	OFF	Fig.1	**P**
	2480(CH78)	OFF	Fig.2	**P**
	2402(CH0)	ON	Fig.3	**P**
	2480(CH78)	ON	Fig.4	**P**
π/4 DQPSK	2402(CH0)	OFF	Fig.5	**P**
	2480(CH78)	OFF	Fig.6	**P**
	2402(CH0)	ON	Fig.7	**P**
	2480(CH78)	ON	Fig.8	**P**
8DPSK	2402(CH0)	OFF	Fig.9	**P**
	2480(CH78)	OFF	Fig.10	**P**
	2402(CH0)	ON	Fig.11	**P**
	2480(CH78)	ON	Fig.12	**P**

See below for test graphs.

Conclusion: Pass

©Copyright. All rights reserved by SAICT.



Fig. 1 Band Edges (GFSK, CH0, Hopping OFF)



Fig. 2 Band Edges (GFSK, CH78, Hopping OFF)

©Copyright. All rights reserved by SAICT.



Fig. 3 Band Edges (GFSK, CH0, Hopping ON)



Fig. 4 Band Edges (GFSK, CH78, Hopping ON)

©Copyright. All rights reserved by SAICT.



Fig. 5 Band Edges (π/4 DQPSK, CH0, Hopping OFF)



Fig. 6 Band Edges (π/4 DQPSK, CH78, Hopping OFF)

©Copyright. All rights reserved by SAICT.



Fig. 7 Band Edges (π/4 DQPSK, CH0, Hopping ON)



Fig. 8 Band Edges (π/4 DQPSK, CH78, Hopping ON)

©Copyright. All rights reserved by SAICT.



Fig. 9 Band Edges (8DPSK, CH0, Hopping OFF)



Fig. 10 Band Edges (8DPSK, CH78, Hopping OFF)

©Copyright. All rights reserved by SAICT.



Fig. 11 Band Edges (8DPSK, CH0, Hopping ON)



Fig. 12 Band Edges (8DPSK, CH78, Hopping ON)

©Copyright. All rights reserved by SAICT.

A.3 Conducted Emission

Method of Measurement: See ANSI C63.10-clause 7.8.8.

Measurement Limit:

Standard	Limit (dBm)
FCC 47 CFR Part 15.247 (d)	20dBm below peak output power in 100kHz bandwidth

Measurement Results:

Mode	Frequency (MHz)	Frequency Range	Test Results	Conclusion
GFSK	2402(CH0)	1GHz-26.5GHz	Fig.13	**P**
	2441(CH39)	1GHz-26.5GHz	Fig.14	**P**
	2480(CH78)	1GHz-26.5GHz	Fig.15	**P**
π/4 DQPSK	2402(CH0)	1GHz-26.5GHz	Fig.16	**P**
	2441(CH39)	1GHz-26.5GHz	Fig.17	**P**
	2480(CH78)	1GHz-26.5GHz	Fig.18	**P**
8DPSK	2402(CH0)	1GHz-26.5GHz	Fig.19	**P**
	2441(CH39)	1GHz-26.5GHz	Fig.20	**P**
	2480(CH78)	1GHz-26.5GHz	Fig.21	**P**
/	All channels	30MHz -1GHz	Fig.22	**P**

See below for test graphs.

Conclusion: Pass

©Copyright. All rights reserved by SAICT.



Fig. 13 Conducted Spurious Emission (GFSK, CH0, 1GHz-26.5GHz)



Fig. 14 Conducted Spurious Emission (GFSK, CH39, 1GHz-26.5GHz)

©Copyright. All rights reserved by SAICT.



Fig. 15 Conducted Spurious Emission (GFSK, CH78, 1GHz-26.5GHz)



Fig. 16 Conducted Spurious Emission (π/4 DQPSK, CH0, 1GHz-26.5GHz)

©Copyright. All rights reserved by SAICT.



Fig. 17 Conducted Spurious Emission (π/4 DQPSK, CH39, 1GHz-26.5GHz)



Fig. 18 Conducted Spurious Emission (π/4 DQPSK, CH78, 1GHz-26.5GHz)

©Copyright. All rights reserved by SAICT.



Fig. 19 Conducted Spurious Emission (8DPSK, CH0, 1GHz-26.5GHz)



Fig. 20 Conducted Spurious Emission (8DPSK, CH39, 1GHz-26.5GHz)

©Copyright. All rights reserved by SAICT.



Fig. 21 Conducted Spurious Emission (8DPSK, CH78, 1GHz-26.5GHz)



Fig. 22 Conducted Spurious Emission (All Channels, 30MHz -1GHz)

©Copyright. All rights reserved by SAICT.

A.4 Radiated Emission

Method of Measurement: See ANSI C63.10-clause 6.3&6.4&6.5&6.6.

Measurement Limit:

Standard	Limit (dBm)
FCC 47 CFR Part 15.247, 15.205, 15.209	20dBm below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(μV/m)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Note: According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band from 9kHz to 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic. The measurement results include the horizontal polarization and vertical polarization measurements. For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

©Copyright. All rights reserved by SAICT.

Measurement Results:

Mode	Frequency (MHz)	Frequency Range	Test Results	Conclusion
GFSK	2402(CH0)	1 GHz ~18 GHz	Fig.23	**P**
	2441(CH39)	1 GHz ~18 GHz	Fig.24	**P**
	2480(CH78)	1 GHz ~18 GHz	Fig.25	**P**
	Restricted Band (CH0)	2.38 GHz ~ 2.45 GHz	Fig.26	**P**
	Restricted Band (CH78)	2.45 GHz ~ 2.5 GHz	Fig.27	**P**
π/4 DQPSK	2402(CH0)	1 GHz ~18 GHz	Fig.28	**P**
	2441(CH39)	1 GHz ~18 GHz	Fig.29	**P**
	2480(CH78)	1 GHz ~18 GHz	Fig.30	**P**
	Restricted Band (CH0)	2.38 GHz ~ 2.45 GHz	Fig.31	**P**
	Restricted Band (CH78)	2.45 GHz ~ 2.5 GHz	Fig.32	**P**
8DPSK	2402(CH0)	1 GHz ~18 GHz	Fig.33	**P**
	2441(CH39)	1 GHz ~18 GHz	Fig.34	**P**
	2480(CH78)	1 GHz ~18 GHz	Fig.35	**P**
	Restricted Band (CH0)	2.38 GHz ~ 2.45 GHz	Fig.36	**P**
	Restricted Band (CH78)	2.45 GHz ~ 2.5 GHz	Fig.37	**P**
/	All channels	9 kHz ~30 MHz	Fig.38	**P**
		30 MHz ~1 GHz	Fig.39	**P**
		18 GHz ~26.5 GHz	Fig.40	**P**

Worst Case Result

GFSK CH78 (1-18GHz)

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
4297.200000	45.66	74.00	28.34	V	2.9
5798.100000	48.08	74.00	25.92	H	4.4
8894.142857	45.48	74.00	28.52	H	6.5
12174.428572	48.12	74.00	25.88	H	10.8
17031.000000	54.35	74.00	19.65	V	18.4
17942.142857	54.71	74.00	19.29	V	19.0

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
4297.200000	34.47	54.00	20.53	V	2.9
5798.100000	36.51	54.00	18.49	H	4.4
8894.142857	34.21	54.00	20.79	H	6.5
12174.428572	36.83	54.00	18.17	H	10.8
17031.000000	43.20	54.00	11.80	V	18.4
17942.142857	42.53	54.00	11.47	V	19.0

π/4 DQPSK CH78 (1-18GHz)

©Copyright. All rights reserved by SAICT.

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
4568.700000	46.79	74.00	27.21	V	4.5
5986.800000	48.84	74.00	25.16	V	5.0
10413.857143	47.11	74.00	26.89	H	9.1
12209.142857	48.07	74.00	25.93	V	10.8
17032.285714	54.69	74.00	19.31	V	18.4
17932.285714	55.02	74.00	18.98	V	18.9

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
4568.700000	34.61	54.00	19.39	V	4.5
5986.800000	35.91	54.00	18.09	V	5.0
10413.857143	35.08	54.00	18.92	H	9.1
12209.142857	35.49	54.00	18.51	V	10.8
17032.285714	42.18	54.00	11.82	V	18.4
17932.285714	42.50	54.00	11.50	V	18.9

8DPSK CH78 (1-18GHz)

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
10419.428572	45.89	74.00	28.11	H	9.0
11178.857143	46.90	74.00	27.10	H	9.7
12612.000000	48.15	74.00	25.85	H	11.2
14200.714286	48.73	74.00	25.27	V	11.1
15853.285714	50.08	74.00	23.92	V	14.0
16920.000000	52.55	74.00	21.45	H	18.1

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
10419.428572	37.08	54.00	16.92	H	9.0
11178.857143	37.52	54.00	16.48	H	9.7
12612.000000	37.61	54.00	16.39	H	11.2
14200.714286	37.93	54.00	16.07	V	11.1
15853.285714	41.94	54.00	12.06	V	14.0
16920.000000	44.21	54.00	9.80	H	18.1

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and Antenna Factor, the gain of the preamplifier, the cable loss. P_{Mea} is the field strength recorded from the instrument. The measurement results are obtained as described below:

Result= P_{Mea} +Cable Loss +Antenna Factor-Gain of the preamplifier.

See below for test graphs.

Conclusion: Pass

©Copyright. All rights reserved by SAICT.



Fig. 23 Radiated Spurious Emission (GFSK, CH0, 1GHz ~18GHz)



Fig. 24 Radiated Spurious Emission (GFSK, CH39, 1GHz ~18GHz)

©Copyright. All rights reserved by SAICT.



Fig. 25 Radiated Spurious Emission (GFSK, CH78, 1GHz ~18GHz)



Fig. 26 Radiated Band Edges (GFSK, CH0, 2.38GHz~2.45GHz)

©Copyright. All rights reserved by SAICT.



Fig. 27 Radiated Band Edges (GFSK, CH78, 2.45GHz~2.50GHz)



Fig. 28 Radiated Spurious Emission (π/4 DQPSK, CH0, 1GHz ~18GHz)

©Copyright. All rights reserved by SAICT.



Fig. 29 Radiated Spurious Emission (π/4 DQPSK, CH39, 1GHz ~18GHz)



Fig. 30 Radiated Spurious Emission (π/4 DQPSK, CH78, 1GHz ~18GHz)

©Copyright. All rights reserved by SAICT.



Fig. 31 Radiated Band Edges (π/4 DQPSK, CH0, 2.38GHz~2.45GHz)



Fig. 32 Radiated Band Edges (π/4 DQPSK, CH78, 2.45GHz~2.50GHz)

©Copyright. All rights reserved by SAICT.



Fig. 33 Radiated Spurious Emission (8DPSK, CH0, 1GHz ~18GHz)



Fig. 34 Radiated Spurious Emission (8DPSK, CH39, 1GHz ~18GHz)

©Copyright. All rights reserved by SAICT.



Fig. 35 Radiated Spurious Emission (8DPSK, CH78, 1GHz ~18GHz)



Fig. 36 Radiated Band Edges (8DPSK, CH0, 2.38GHz~2.45GHz)

©Copyright. All rights reserved by SAICT.



Fig. 37 Radiated Band Edges (8DPSK, CH78, 2.45GHz~2.50GHz)



Fig. 38 Radiated Spurious Emission (All Channels, 9kHz ~30MHz)

©Copyright. All rights reserved by SAICT.



Fig. 39 Radiated Spurious Emission (All Channels, 30MHz ~1GHz)



Fig. 40 Radiated Spurious Emission (All Channels, 18GHz ~26.5GHz)

©Copyright. All rights reserved by SAICT.

A.5 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 7.8.7.

Measurement Limit:

Standard	Limit (MHz)
FCC 47 CFR Part 15.247 (a)	/

Measurement Result:

Mode	Frequency (MHz)	20dB Bandwidth (MHz)		Conclusion
GFSK	2402(CH0)	Fig.41	0.81	/
	2441(CH39)	Fig.42	0.80	
	2480(CH78)	Fig.43	0.81	
π/4 DQPSK	2402(CH0)	Fig.44	1.26	/
	2441(CH39)	Fig.45	1.26	
	2480(CH78)	Fig.46	1.26	
8DPSK	2402(CH0)	Fig.47	1.26	/
	2441(CH39)	Fig.48	1.26	
	2480(CH78)	Fig.49	1.26	

See below for test graphs.

Conclusion: PASS

©Copyright. All rights reserved by SAICT.



Fig. 41 20dB Bandwidth (GFSK, CH0)



Fig. 42 20dB Bandwidth (GFSK, CH39)

©Copyright. All rights reserved by SAICT.



Fig. 43 20dB Bandwidth (GFSK, CH78)



Fig. 44 20dB Bandwidth (π/4 DQPSK, CH0)

©Copyright. All rights reserved by SAICT.



Fig. 45 20dB Bandwidth (π/4 DQPSK, CH39)



Fig. 46 20dB Bandwidth (π/4 DQPSK, CH78)

©Copyright. All rights reserved by SAICT.



Fig. 47 20dB Bandwidth (8DPSK, CH0)



Fig. 48 20dB Bandwidth (8DPSK, CH39)

©Copyright. All rights reserved by SAICT.



Fig. 49 20dB Bandwidth (8DPSK, CH78)

©Copyright. All rights reserved by SAICT.

A.6 Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4.

Measurement Limit:

Standard	Limit (s)
FCC 47 CFR Part 15.247(a)	< 0.4

Measurement Results:

Mode	Frequency (MHz)	Packet	Burst Width (ms)		Total Hops (Num)		Result (s)	Conclusion
GFSK	2441(CH39)	DH5	Fig.50	2.86	Fig.51	90	0.26	**P**
π/4 DQPSK	2441(CH39)	2-DH5	Fig.52	2.87	Fig.53	70	0.20	**P**
8DPSK	2441(CH39)	3-DH5	Fig.54	2.87	Fig.55	90	0.26	**P**

See below for test graphs.

Conclusion: Pass

©Copyright. All rights reserved by SAICT.



Fig. 50 BurstWidth (Dwell Time) (GFSK, CH39)



Fig. 51 Number of Burst in Observation Period (Dwell Time) (GFSK, CH39)

©Copyright. All rights reserved by SAICT.



Fig. 52 BurstWidth (Dwell Time) (π/4 DQPSK, CH39)



Fig. 53 Number of Burst in Observation Period (Dwell Time) (π/4 DQPSK, CH39)

©Copyright. All rights reserved by SAICT.



Fig. 54 BurstWidth (Dwell Time) (8DPSK, CH39)



Fig. 55 Number of Burst in Observation Period (Dwell Time) (8DPSK, CH39)

©Copyright. All rights reserved by SAICT.

A.7 Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3.

Measurement Limit:

Standard	Limit (Num)
FCC 47 CFR Part 15.247(a)	At least 15 non-overlapping channels

Measurement Results:

Mode	Packet	Number of Hopping Channels	Test results (Num)	Conclusion
GFSK	DH5	Fig.56	79	**P**
π/4 DQPSK	2-DH5	Fig.57	79	**P**
8DPSK	3-DH5	Fig.58	79	**P**

See below for test graphs.

Conclusion: Pass



Fig. 56 Number of Hopping Channels (GFSK, Hopping)

©Copyright. All rights reserved by SAICT.



Fig. 57 Number of Hopping Channels (π/4 DQPSK, Hopping)



Fig. 58 Number of Hopping Channels (8DPSK, Hopping)

©Copyright. All rights reserved by SAICT.

A.8 Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2.

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247(a)	By a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater

Measurement Results:

Mode	Frequency (MHz)	Packet	Separation of hopping channels	Test result (kHz)	Conclusion
GFSK	2441(CH39)	DH5	Fig.59	1000.00	**P**
π/4 DQPSK	2441(CH39)	2-DH5	Fig.60	1003.00	**P**
8DPSK	2441(CH39)	3-DH5	Fig.61	1003.00	**P**

See below for test graphs.

Conclusion: Pass



Fig. 59 Carrier Frequency Separation (GFSK, CH39)

©Copyright. All rights reserved by SAICT.



Fig. 60 Carrier Frequency Separation (π/4 DQPSK, CH39)



Fig. 61 Carrier Frequency Separation (8DPSK, CH39)

©Copyright. All rights reserved by SAICT.

A.9 AC Power line Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Average-peak Limit (dBμV)	Result (dBμV)		Conclusion
			Traffic	Idle	
0.15 to 0.5	66 to 56	56 to 46	Fig.62	Fig.63	**P**
0.5 to 5	56	46			
5 to 30	60	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.					

Note: The measurement results include the L1 and N measurements.

See below for test graphs.
Conclusion: Pass

©Copyright. All rights reserved by SAICT.



Fig. 62 AC Power line Conducted Emission (Traffic)

Measurement Results: Quasi Peak

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.354000	42.18	58.87	16.69	N	ON	10
0.518000	38.84	56.00	17.16	N	ON	10
1.802000	36.68	56.00	19.32	N	ON	10
2.186000	35.81	56.00	20.19	N	ON	10
3.726000	34.08	56.00	21.92	N	ON	10
9.202000	41.50	60.00	18.50	N	ON	10

Measurement Results: Average

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.262000	35.78	51.37	15.59	N	ON	10
1.914000	28.39	46.00	17.61	N	ON	10
2.170000	28.03	46.00	17.97	N	ON	10
4.058000	28.69	46.00	17.31	L1	ON	10
9.254000	36.25	50.00	13.75	N	ON	10
10.438000	33.24	50.00	16.76	N	ON	10

©Copyright. All rights reserved by SAICT.



Fig. 63 AC Power line Conducted Emission (Idle)

Measurement Results: Quasi Peak

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.358000	42.39	58.78	16.39	N	ON	10
0.530000	38.74	56.00	17.26	N	ON	10
0.854000	36.95	56.00	19.05	N	ON	10
1.818000	37.80	56.00	18.20	N	ON	10
2.122000	35.54	56.00	20.46	N	ON	10
9.194000	41.58	60.00	18.42	N	ON	10

Measurement Results: Average

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.366000	33.79	48.59	14.80	N	ON	10
1.810000	28.51	46.00	17.49	N	ON	10
3.382000	28.11	46.00	17.89	N	ON	10
4.046000	28.95	46.00	17.05	L1	ON	10
9.366000	36.18	50.00	13.82	N	ON	10
10.426000	33.29	50.00	16.71	N	ON	10

*****END OF REPORT*****

©Copyright. All rights reserved by SAICT.