TEST REPORT

APPLICANT	:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
PRODUCT NAME	:	Mobile Phone
MODEL NAME	:	RMX3941
BRAND NAME	:	realme
FCC ID	:	2AUYFRMX3941
STANDARD(S)	:	47 CFR Part 2 47 CFR Part 90, Subpart S
RECEIPT DATE	:	2024-10-16
TEST DATE	:	2024-10-18 to 2024-11-05
ISSUE DATE	:	2024-11-11

Edited by: Zeng Xiaoying (Rapporteur)

Approved by: Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB
Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Technical Information ····· 3
1.1. Applicant and Manufacturer Information ····· 3
1.2. Equipment Under Test (EUT) Description ····· 3
1.3. Maximum E.R.P./E.I.R.P. and Emission Designator ····· 4
1.4. Test Standards and Results ····· 5
1.5. Environmental Conditions ····· 6
2. 47 CFR Part 2, Part 90S Requirements ····· 7
2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P. ····· 7
2.2. Occupied Bandwidth ····· 16
2.3. Frequency Stability ····· 25
2.4. Conducted Spurious Emissions ····· 27
2.5. Band Edge ····· 30
2.6. Radiated Spurious Emissions ····· 34
Annex A Test Uncertainty ····· 43
Annex B Testing Laboratory Information ····· 44

Change History		
Version	Date	Reason for change
1.0	2024-11-11	First edition

1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Applicant Address:	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Manufacturer:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Manufacturer Address:	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Mobile Phone	
Sample No.:	2#, 10#	
Hardware Version:	11	
Software Version:	realme UI 5.0	
Modulation Type:	QPSK, 16QAM, 64QAM	
Operation Band:	Band 26	
Frequency Range:	LTE Band 26	Tx: 814MHz–824MHz
		Rx: 859MHz–869MHz
Channel Bandwidth	LTE Band 26	1.4MHz, 3MHz, 5MHz, 10MHz
Antenna Type:	Inverted F Antenna	
Antenna Gain:	LTE Band 26	ANT0: -8.40dBi; ANT1: -10.00dBi
Accessory Information:	Battery	
	Brand Name:	SUPERVOOC
	Model No.:	BLPB61
	Serial No.:	N/A
	Capacity:	Typical: 5828mAh, Rated: 5660mAh
	Rated Voltage:	3.92V
	Charge Limit:	4.53V
	Manufacturer:	Sunwoda Electronic Co., Ltd.

Accessory Information:	AC Adapter 1	
	Brand Name:	SUPERVOOC
	Model No.:	VCB4JAUH
	Serial No.:	N/A
	Rated Output:	5V⎓2A or 5V-11V⎓4.1A Max
	Rated Input:	100-240V～50/60Hz, 1.5A
	Manufacturer:	Huizhou Golden Lake Industrial Co., Ltd.
	AC Adapter 2	
	Brand Name:	SUPERVOOC
	Model No.:	VCB4JAUH
	Serial No.:	N/A
	Rated Output:	5V⎓2A or 5V-11V⎓4.1A Max
	Rated Input:	100-240V～50/60Hz, 1.5A
	Manufacturer:	Jiangsu Chenyang Electron Co.,Ltd.
	USB Cable	
	Model No.:	DL154

Note 1: SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

LTE Band 26	**Maximum E.R.P./E.I.R.P. (W)**			**Emission Designator (99%OBW)**		
BW(MHz)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10	0.019	0.016	0.012	8M95G7D	8M93W7D	8M94W7D
5	0.020	0.016	0.012	4M47G7D	4M47W7D	4M48W7D
3	0.019	0.015	0.012	2M69G7D	2M70W7D	2M70W7D
1.4	0.020	0.016	0.013	1M10G7D	1M10W7D	1M10W7D

1.4. Test Standards and Results

The objective of the report is to perform testing according to Part 2 and Part 90 for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 90	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
2.1046, 90.635(b)	Transmitter Conducted Output Power and ERP/EIRP	Nov. 05, 2024	Yu Zhizheng	PASS	No deviation
2.1049, 90.209	Occupied Bandwidth	Nov. 05, 2024	Gan Jing	PASS	No deviation
2.1055, 90.213	Frequency Stability	Nov. 05, 2024	Gan Jing	PASS	No deviation
2.1051, 90.691	Conducted Spurious Emissions	Nov. 05, 2024	Gan Jing	PASS	No deviation
2.1051, 90.691	Band Edge	Nov. 05, 2024	Gan Jing	PASS	No deviation
2.1053, 90.691	Radiated Spurious Emissions	Oct. 28, 2024	Zhong Xiangyun	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in KDB 971168 D01 v03 and ANSI/TIA-603-E-2016.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 2, Part 90S Requirements

2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P.

2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

According to FCC section 90.635(b) for LTE Band 26, the maximum output power of the transmitter for mobile stations is 100 watts.

2.1.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.1.3. Test procedure

KDB 971168 D01v03 Section 5.2 and ANSI/TIA-603-E-2016.

EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)
ERP (dBm) = EIPR (dBm) - 2.15

2.1.4. Result

Conducted Output Power

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				/	26740	/
Frequency (MHz)				/	819.0	/
10	QPSK	1	0	/	23.16	/
10	QPSK	1	25	/	23.26	/
10	QPSK	1	49	/	23.18	/
10	QPSK	25	0	/	22.39	/
10	QPSK	25	12	/	22.27	/
10	QPSK	25	25	/	22.44	/
10	QPSK	50	0	/	22.39	/
10	16QAM	1	0	/	22.60	/
10	16QAM	1	25	/	22.69	/
10	16QAM	1	49	/	22.64	/
10	16QAM	25	0	/	21.39	/
10	16QAM	25	12	/	21.36	/
10	16QAM	25	25	/	21.34	/
10	16QAM	50	0	/	21.41	/
10	64QAM	1	0	/	21.40	/
10	64QAM	1	25	/	21.44	/
10	64QAM	1	49	/	21.34	/
10	64QAM	25	0	/	20.18	/
10	64QAM	25	12	/	20.38	/
10	64QAM	25	25	/	20.37	/
10	64QAM	50	0	/	20.44	/

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26715	26740	26765
Frequency (MHz)				816.5	819.0	821.5
5	QPSK	1	0	23.26	23.24	23.21
5	QPSK	1	12	23.11	23.17	23.47
5	QPSK	1	24	23.28	23.25	23.24
5	QPSK	12	0	22.40	22.38	22.37
5	QPSK	12	7	22.50	22.49	22.44
5	QPSK	12	13	22.48	22.42	22.35
5	QPSK	25	0	22.43	22.41	22.41
5	16QAM	1	0	22.32	22.17	22.22
5	16QAM	1	12	22.63	22.50	22.27
5	16QAM	1	24	22.20	22.11	22.22
5	16QAM	12	0	21.37	21.33	21.38
5	16QAM	12	7	21.34	21.29	21.43
5	16QAM	12	13	21.30	21.33	21.38
5	16QAM	25	0	21.32	21.23	21.43
5	64QAM	1	0	21.32	21.07	20.91
5	64QAM	1	12	21.31	21.28	21.24
5	64QAM	1	24	21.14	21.05	21.09
5	64QAM	12	0	20.30	20.41	20.41
5	64QAM	12	7	20.39	20.34	20.51
5	64QAM	12	13	20.39	20.27	20.45
5	64QAM	25	0	20.23	20.27	20.43

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26705	26740	26775
Frequency (MHz)				815.5	819.0	822.5
3	QPSK	1	0	23.40	23.35	23.29
3	QPSK	1	8	23.39	23.35	23.35
3	QPSK	1	14	23.39	23.37	23.32
3	QPSK	8	0	22.45	22.42	22.37
3	QPSK	8	4	22.51	22.47	22.42
3	QPSK	8	7	22.47	22.43	22.42
3	QPSK	15	0	22.33	22.28	22.30
3	16QAM	1	0	22.23	22.13	22.24
3	16QAM	1	8	22.18	22.13	22.30
3	16QAM	1	14	22.17	22.08	22.24
3	16QAM	8	0	21.48	21.37	21.50
3	16QAM	8	4	21.44	21.39	21.44
3	16QAM	8	7	21.51	21.43	21.39
3	16QAM	15	0	21.47	21.40	21.36
3	64QAM	1	0	21.01	21.03	21.44
3	64QAM	1	8	21.03	21.10	21.34
3	64QAM	1	14	21.04	21.01	21.24
3	64QAM	8	0	20.19	20.36	20.39
3	64QAM	8	4	20.37	20.31	20.40
3	64QAM	8	7	20.45	20.48	20.45
3	64QAM	15	0	20.41	20.29	20.37

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26697	26740	26783
Frequency (MHz)				814.7	819.0	823.3
1.4	QPSK	1	0	23.24	23.29	23.29
1.4	QPSK	1	3	23.51	23.41	23.43
1.4	QPSK	1	5	23.38	23.29	23.30
1.4	QPSK	3	0	23.50	23.34	23.31
1.4	QPSK	3	1	23.32	23.27	23.28
1.4	QPSK	3	3	23.45	23.35	23.30
1.4	QPSK	6	0	22.42	22.27	22.29
1.4	16QAM	1	0	22.12	22.60	22.63
1.4	16QAM	1	3	22.30	22.70	22.72
1.4	16QAM	1	5	22.08	22.63	22.66
1.4	16QAM	3	0	22.46	22.40	22.40
1.4	16QAM	3	1	22.53	22.43	22.43
1.4	16QAM	3	3	22.46	22.41	22.37
1.4	16QAM	6	0	21.58	21.49	21.50
1.4	64QAM	1	0	21.19	21.44	21.51
1.4	64QAM	1	3	21.12	21.51	21.56
1.4	64QAM	1	5	21.17	21.37	21.51
1.4	64QAM	3	0	21.60	21.55	21.56
1.4	64QAM	3	1	21.69	21.56	21.62
1.4	64QAM	3	3	21.64	21.54	21.49
1.4	64QAM	6	0	20.44	20.43	20.40

Effective Radiated Power and Effective Isotropic Radiated Power

LTE Band 26				Measured E.R.P.			
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.	Middle Ch. / Freq.		High Ch. / Freq.
Channel				/	26740		/
Frequency (MHz)				/	819		/
				/	dBm	W	/
10	QPSK	1	0	/	12.61	0.018	/
10	QPSK	1	25	/	12.71	0.019	/
10	QPSK	1	49	/	12.63	0.018	/
10	QPSK	25	0	/	11.84	0.015	/
10	QPSK	25	12	/	11.72	0.015	/
10	QPSK	25	25	/	11.89	0.015	/
10	QPSK	50	0	/	11.84	0.015	/
10	16QAM	1	0	/	12.05	0.016	/
10	16QAM	1	25	/	12.14	0.016	/
10	16QAM	1	49	/	12.09	0.016	/
10	16QAM	25	0	/	10.84	0.012	/
10	16QAM	25	12	/	10.81	0.012	/
10	16QAM	25	25	/	10.79	0.012	/
10	16QAM	50	0	/	10.86	0.012	/
10	64QAM	1	0	/	10.85	0.012	/
10	64QAM	1	25	/	10.89	0.012	/
10	64QAM	1	49	/	10.79	0.012	/
10	64QAM	25	0	/	9.63	0.009	/
10	64QAM	25	12	/	9.83	0.010	/
10	64QAM	25	25	/	9.82	0.010	/
10	64QAM	50	0	/	9.89	0.010	/

LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26715		26740		26765	
Frequency (MHz)				816.5		819.0		821.5	
				dBm	W	dBm	W	dBm	W
5	QPSK	1	0	12.71	0.019	12.69	0.019	12.66	0.018
5	QPSK	1	12	12.56	0.018	12.62	0.018	12.92	0.020
5	QPSK	1	24	12.73	0.019	12.70	0.019	12.69	0.019
5	QPSK	12	0	11.85	0.015	11.83	0.015	11.82	0.015
5	QPSK	12	7	11.95	0.016	11.94	0.016	11.89	0.015
5	QPSK	12	13	11.93	0.016	11.87	0.015	11.80	0.015
5	QPSK	25	0	11.88	0.015	11.86	0.015	11.86	0.015
5	16QAM	1	0	11.77	0.015	11.62	0.015	11.67	0.015
5	16QAM	1	12	12.08	0.016	11.95	0.016	11.72	0.015
5	16QAM	1	24	11.65	0.015	11.56	0.014	11.67	0.015
5	16QAM	12	0	10.82	0.012	10.78	0.012	10.83	0.012
5	16QAM	12	7	10.79	0.012	10.74	0.012	10.88	0.012
5	16QAM	12	13	10.75	0.012	10.78	0.012	10.83	0.012
5	16QAM	25	0	10.77	0.012	10.68	0.012	10.88	0.012
5	64QAM	1	0	10.77	0.012	10.52	0.011	10.36	0.011
5	64QAM	1	12	10.76	0.012	10.73	0.012	10.69	0.012
5	64QAM	1	24	10.59	0.011	10.50	0.011	10.54	0.011
5	64QAM	12	0	9.75	0.009	9.86	0.010	9.86	0.010
5	64QAM	12	7	9.84	0.010	9.79	0.010	9.96	0.010
5	64QAM	12	13	9.84	0.010	9.72	0.009	9.90	0.010
5	64QAM	25	0	9.68	0.009	9.72	0.009	9.88	0.010

LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26705		26740		26775	
Frequency (MHz)				815.5		819.0		822.5	
				dBm	W	dBm	W	dBm	W
3	QPSK	1	0	12.85	0.019	12.80	0.019	12.74	0.019
3	QPSK	1	8	12.84	0.019	12.80	0.019	12.80	0.019
3	QPSK	1	14	12.84	0.019	12.82	0.019	12.77	0.019
3	QPSK	8	0	11.90	0.015	11.87	0.015	11.82	0.015
3	QPSK	8	4	11.96	0.016	11.92	0.016	11.87	0.015
3	QPSK	8	7	11.92	0.016	11.88	0.015	11.87	0.015
3	QPSK	15	0	11.78	0.015	11.73	0.015	11.75	0.015
3	16QAM	1	0	11.68	0.015	11.58	0.014	11.69	0.015
3	16QAM	1	8	11.63	0.015	11.58	0.014	11.75	0.015
3	16QAM	1	14	11.62	0.015	11.53	0.014	11.69	0.015
3	16QAM	8	0	10.93	0.012	10.82	0.012	10.95	0.012
3	16QAM	8	4	10.89	0.012	10.84	0.012	10.89	0.012
3	16QAM	8	7	10.96	0.012	10.88	0.012	10.84	0.012
3	16QAM	15	0	10.92	0.012	10.85	0.012	10.81	0.012
3	64QAM	1	0	10.46	0.011	10.48	0.011	10.89	0.012
3	64QAM	1	8	10.48	0.011	10.55	0.011	10.79	0.012
3	64QAM	1	14	10.49	0.011	10.46	0.011	10.69	0.012
3	64QAM	8	0	9.64	0.009	9.81	0.010	9.84	0.010
3	64QAM	8	4	9.82	0.010	9.76	0.009	9.85	0.010
3	64QAM	8	7	9.90	0.010	9.93	0.010	9.90	0.010
3	64QAM	15	0	9.86	0.010	9.74	0.009	9.82	0.010

LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26697		26740		26783	
Frequency (MHz)				814.7		819.0		823.3	
				dBm	W	dBm	W	dBm	W
1.4	QPSK	1	0	12.69	0.019	12.74	0.019	12.74	0.019
1.4	QPSK	1	3	12.96	0.020	12.86	0.019	12.88	0.019
1.4	QPSK	1	5	12.83	0.019	12.74	0.019	12.75	0.019
1.4	QPSK	3	0	12.95	0.020	12.79	0.019	12.76	0.019
1.4	QPSK	3	1	12.77	0.019	12.72	0.019	12.73	0.019
1.4	QPSK	3	3	12.90	0.019	12.80	0.019	12.75	0.019
1.4	QPSK	6	0	11.87	0.015	11.72	0.015	11.74	0.015
1.4	16QAM	1	0	11.57	0.014	12.05	0.016	12.08	0.016
1.4	16QAM	1	3	11.75	0.015	12.15	0.016	12.17	0.016
1.4	16QAM	1	5	11.53	0.014	12.08	0.016	12.11	0.016
1.4	16QAM	3	0	11.91	0.016	11.85	0.015	11.85	0.015
1.4	16QAM	3	1	11.98	0.016	11.88	0.015	11.88	0.015
1.4	16QAM	3	3	11.91	0.016	11.86	0.015	11.82	0.015
1.4	16QAM	6	0	11.03	0.013	10.94	0.012	10.95	0.012
1.4	64QAM	1	0	10.64	0.012	10.89	0.012	10.96	0.012
1.4	64QAM	1	3	10.57	0.011	10.96	0.012	11.01	0.013
1.4	64QAM	1	5	10.62	0.012	10.82	0.012	10.96	0.012
1.4	64QAM	3	0	11.05	0.013	11.00	0.013	11.01	0.013
1.4	64QAM	3	1	11.14	0.013	11.01	0.013	11.07	0.013
1.4	64QAM	3	3	11.09	0.013	10.99	0.013	10.94	0.012
1.4	64QAM	6	0	9.89	0.010	9.88	0.010	9.85	0.010

2.2. Occupied Bandwidth

2.2.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.Occupied bandwidth is also known as the 99% emission bandwidth.

2.2.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.2.3. Test procedure

KDB 971168 D01v03 Section 4.1 and ANSI/TIA-603-E-2016.

2.2.4. Test Result

LTE Band	BW(MHz)	Channel Level	Channel	Frequency (MHz)	Modulation	99% BW (MHz)	26dB BW (MHz)	Verdict
B26	1.4	Low	26697	814.7	QPSK	1.0938	1.2805	PASS
B26	1.4	Low	26697	814.7	16QAM	1.0934	1.2844	PASS
B26	1.4	Low	26697	814.7	64QAM	1.1008	1.2746	PASS
B26	1.4	Mid	26740	819	QPSK	1.0962	1.2728	PASS
B26	1.4	Mid	26740	819	16QAM	1.0986	1.2973	PASS
B26	1.4	Mid	26740	819	64QAM	1.0950	1.2881	PASS
B26	1.4	High	26783	823.3	QPSK	1.0968	1.2941	PASS
B26	1.4	High	26783	823.3	16QAM	1.1000	1.2926	PASS
B26	1.4	High	26783	823.3	64QAM	1.0979	1.2839	PASS
B26	3	Low	26705	815.5	QPSK	2.6882	2.9111	PASS
B26	3	Low	26705	815.5	16QAM	2.6865	2.9593	PASS
B26	3	Low	26705	815.5	64QAM	2.6967	2.9255	PASS
B26	3	Mid	26740	819	QPSK	2.6888	2.9167	PASS
B26	3	Mid	26740	819	16QAM	2.6921	2.9293	PASS
B26	3	Mid	26740	819	64QAM	2.6956	2.9185	PASS
B26	3	High	26775	822.5	QPSK	2.6877	2.9188	PASS
B26	3	High	26775	822.5	16QAM	2.6958	2.9340	PASS
B26	3	High	26775	822.5	64QAM	2.6991	2.9134	PASS
B26	5	Low	26715	816.5	QPSK	4.4702	4.8428	PASS
B26	5	Low	26715	816.5	16QAM	4.4688	4.7914	PASS
B26	5	Low	26715	816.5	64QAM	4.4811	4.8020	PASS
B26	5	Mid	26740	819	QPSK	4.4724	4.8386	PASS
B26	5	Mid	26740	819	16QAM	4.4741	4.8209	PASS
B26	5	Mid	26740	819	64QAM	4.4755	4.7827	PASS
B26	5	High	26765	821.5	QPSK	4.4693	4.8183	PASS
B26	5	High	26765	821.5	16QAM	4.4747	4.8259	PASS
B26	5	High	26765	821.5	64QAM	4.4787	4.8133	PASS
B26	10	Low	26740	819	QPSK	8.9529	9.5426	PASS
B26	10	Low	26740	819	16QAM	8.9267	9.4871	PASS
B26	10	Low	26740	819	64QAM	8.9337	9.5141	PASS
B26	10	Mid	26740	819	QPSK	8.9421	9.5731	PASS
B26	10	Mid	26740	819	16QAM	8.9243	9.5945	PASS
B26	10	Mid	26740	819	64QAM	8.9399	9.5499	PASS

B26	10	High	26740	819	QPSK	8.9486	9.6362	PASS
B26	10	High	26740	819	16QAM	8.9302	9.5125	PASS
B26	10	High	26740	819	64QAM	8.9305	9.5557	PASS



B26 Part90 / 1.4MHz / QPSK/ Low CH



B26 Part90 / 1.4MHz / 16QAM/ Low CH



B26 Part90 / 1.4MHz / 64QAM/ Low CH



B26 Part90 / 1.4MHz / QPSK/ Mid CH



B26 Part90 / 1.4MHz / 16QAM/ Mid CH



B26 Part90 / 1.4MHz / 64QAM/ Mid CH



B26 Part90 / 1.4MHz / QPSK/ High CH



B26 Part90 / 1.4MHz / 16QAM/ High CH



B26 Part90 / 1.4MHz / 64QAM/ High CH



B26 Part90 / 3MHz / QPSK/ Low CH



B26 Part90 / 3MHz / 16QAM/ Low CH



B26 Part90 / 3MHz / 64QAM/ Low CH



B26 Part90 / 3MHz / QPSK/ Mid CH



B26 Part90 / 3MHz / 16QAM/ Mid CH



B26 Part90 / 3MHz / 64QAM/ Mid CH



B26 Part90 / 3MHz / QPSK/ High CH



B26 Part90 / 3MHz / 16QAM/ High CH



B26 Part90 / 3MHz / 64QAM/ High CH



B26 Part90 / 5MHz / QPSK/ Low CH



B26 Part90 / 5MHz / 16QAM/ Low CH



B26 Part90 / 5MHz / 64QAM/ Low CH



B26 Part90 / 5MHz / QPSK/ Mid CH



B26 Part90 / 5MHz / 16QAM/ Mid CH



B26 Part90 / 5MHz / 64QAM/ Mid CH



B26 Part90 / 5MHz / QPSK/ High CH



B26 Part90 / 5MHz / 16QAM/ High CH



B26 Part90 / 5MHz / 64QAM/ High CH



B26 Part90 / 10MHz / QPSK/ Low CH



B26 Part90 / 10MHz / 16QAM/ Low CH



B26 Part90 / 10MHz / 64QAM/ Low CH



B26 Part90 / 10MHz / QPSK/ Mid CH



B26 Part90 / 10MHz / 16QAM/ Mid CH



B26 Part90 / 10MHz / 64QAM/ Mid CH



B26 Part90 / 10MHz / QPSK/ High CH



B26 Part90 / 10MHz / 16QAM/ High CH



B26 Part90 / 10MHz / 64QAM/ High CH

2.3. Frequency Stability

2.3.1. Requirement

According to FCC section 2.1055 & 90.213, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

(a) The temperature is varied from -30°C to +50°C at intervals of not more than 10°C.

(b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

Note: The operating temperature of EUT is from 0°C to 35°C, which are specified by the applicant.

2.3.2. Test Description



The EUT which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power. A call is established between the EUT and the SS via a Common Antenna.

2.3.3. Test procedure

KDB 971168 D01v03 Section 9.0 and ANSI/TIA-603-E-2016.

2.3.4. Test Result

The nominal, highest and lowest extreme voltages are separately 3.92V, 4.53V and 3.60V, which are specified by the applicant; the normal temperature here used is 20°C.

LTE Band 26, QPSK, Channel 26740, Frequency 819MHz Limit =±2.5ppm					
Voltage (%)	**Power (VDC)**	**Temp(°C)**	**Fre. Dev.(Hz)**	**Deviation (ppm)**	**Result**
Normal	3.92	+20(Ref)	15	0.018	PASS
Normal		0	9	0.011	
Normal		+10	14	0.017	
Normal		+20	13	0.016	
Normal		+30	22	**0.027**	
Normal		+40	8	0.010	
High	4.53	+20	15	0.018	
BATT.ENDPOINT	3.60	+20	-7	-0.009	

2.4. Conducted Spurious Emissions

2.4.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

2.4.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.4.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.

2.4.4. Test Result



B26 Part90 / 1.4MHz / Low CH / QPSK



B26 Part90 / 1.4MHz / Mid CH / QPSK



B26 Part90 / 1.4MHz / High CH / QPSK

B26 Part90 / 3MHz / Low CH / QPSK



B26 Part90 / 3MHz / Mid CH / QPSK

B26 Part90 / 3MHz / High CH / QPSK



B26 Part90 / 5MHz / Low CH / QPSK



B26 Part90 / 5MHz / Mid CH / QPSK



B26 Part90 / 5MHz / High CH / QPSK



B26 Part90 / 10MHz / Low CH / QPSK



B26 Part90 / 10MHz / Mid CH / QPSK



B26 Part90 / 10MHz / High CH / QPSK

2.5. Band Edge

2.5.1. Requirement

Band26
According to FCC section 90.961(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

2.5.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.5.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.

2.5.4. Test Result



B26/ 1.4MHz / Low CH / QPSK / 1 RB



B26/ 1.4MHz / Low CH / QPSK / FULL RB



B26/ 1.4MHz / High CH / QPSK / 1 RB



B26/ 1.4MHz / High CH / QPSK / FULL RB



B26/ 3MHz / Low CH / QPSK / 1 RB



B26/ 3MHz / Low CH / QPSK / FULL RB



B26/ 3MHz / High CH / QPSK / 1 RB



B26/ 3MHz / High CH / QPSK / FULL RB



B26/ 5MHz / Low CH / QPSK / 1 RB



B26/ 5MHz / Low CH / QPSK / FULL RB



B26/ 5MHz / High CH / QPSK / 1 RB



B26/ 5MHz / High CH / QPSK / FULL RB



B26/ 10MHz / Low CH / QPSK / 1 RB



B26/ 10MHz / Low CH / QPSK / FULL RB



B26/ 10MHz / High CH / QPSK / 1 RB



B26/ 10MHz / High CH / QPSK / FULL RB

2.6. Radiated Spurious Emissions

2.6.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

2.6.2. Test Description



(For the test frequency from 30MHz to1GHz)



(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading.
A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power, and only the test result of the maximum output power was recorded.
In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360°to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

Note: when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.6.3. Test procedure

KDB 971168 D01v03 Section 5.8 and ANSI/TIA-603-E-2016.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.

2.6.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$

$A_{TOT} = L_{CABLES} + A_{SUBST}$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

P_{SUBST_TX} is signal generator level,

P_{SUBST_RX} is receiver level,

L_{SUBST_CABLES} is cable losses including TX cable,

$G_{SUBST_TX_ANT}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of A_{TOT}.

Note1: The power of the EUT transmitting frequency should be ignored.

Note2: All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note3: All bandwidth and modulation were considered and evaluated respectively by performing full test for each band, only the worst cases (Max Bandwidth and QPSK mode) were recorded in this test report.

Note 4: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

Note 5: The amplitude of emissions (18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.

ANT0

LTE Band 26, 5MHz BW, Low Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	814.730	-49.62	-13.00	Horizontal	N/A
2	1217.687	-38.29	-13.00	Horizontal	PASS
3	2267.067	-36.87	-13.00	Horizontal	PASS
4	4905.392	-48.48	-13.00	Horizontal	PASS
5	7402.746	-43.61	-13.00	Horizontal	PASS
6	10970.658	-38.52	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	862.260	-59.27	-13.00	Vertical	N/A
2	1368.147	-38.35	-13.00	Vertical	N/A
3	2254.902	-36.91	-13.00	Vertical	PASS
4	4763.266	-49.24	-13.00	Vertical	PASS
5	7858.656	-44.01	-13.00	Vertical	PASS
6	10204.655	-38.79	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, Mid Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	828.310	-51.66	-13.00	Horizontal	N/A
2	2265.786	-36.11	-13.00	Horizontal	PASS
3	4755.883	-49.12	-13.00	Horizontal	PASS
4	7332.606	-44.82	-13.00	Horizontal	PASS
5	9852.109	-39.56	-13.00	Horizontal	PASS
6	11170.004	-38.97	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	828.310	-59.18	-13.00	Vertical	N/A
2	878.750	-52.06	-13.00	Vertical	N/A
3	2264.506	-36.27	-13.00	Vertical	PASS
4	4901.700	-48.65	-13.00	Vertical	PASS
5	7275.386	-44.88	-13.00	Vertical	PASS
6	11195.845	-38.85	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	848.680	-49.94	-13.00	Horizontal	N/A
2	1350.220	-37.20	-13.00	Horizontal	PASS
3	2254.902	-36.75	-13.00	Horizontal	PASS
4	4899.855	-48.88	-13.00	Horizontal	PASS
5	7321.531	-44.89	-13.00	Horizontal	PASS
6	10933.742	-39.26	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	887.480	-54.53	-13.00	Vertical	N/A
2	2256.823	-36.24	-13.00	Vertical	PASS
3	4772.495	-48.81	-13.00	Vertical	PASS
4	7330.760	-45.29	-13.00	Vertical	PASS
5	10237.880	-38.43	-13.00	Vertical	PASS
6	10983.579	-38.89	-13.00	Vertical	PASS

ANT1

LTE Band 26, 5MHz BW, Low Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	814.730	-40.52	-13.00	Horizontal	N/A
2	2251.060	-37.44	-13.00	Horizontal	PASS
3	4567.612	-50.13	-13.00	Horizontal	PASS
4	7328.914	-43.85	-13.00	Horizontal	PASS
5	8019.240	-43.46	-13.00	Horizontal	PASS
6	10293.253	-39.04	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-44.65	-13.00	Vertical	N/A
2	2265.146	-37.10	-13.00	Vertical	PASS
3	4748.500	-49.07	-13.00	Vertical	PASS
4	7216.321	-45.41	-13.00	Vertical	PASS
5	9359.284	-40.33	-13.00	Vertical	PASS
6	10289.562	-38.81	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, Mid Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	833.160	-37.40	-13.00	Horizontal	N/A
2	2247.859	-37.01	-13.00	Horizontal	PASS
3	4730.042	-49.56	-13.00	Horizontal	PASS
4	7415.666	-44.10	-13.00	Horizontal	PASS
5	9754.283	-39.97	-13.00	Horizontal	PASS
6	11168.158	-39.10	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	833.160	-41.53	-13.00	Vertical	N/A
2	2265.786	-36.21	-13.00	Vertical	PASS
3	4735.579	-48.93	-13.00	Vertical	PASS
4	7352.910	-44.72	-13.00	Vertical	PASS
5	9765.357	-39.51	-13.00	Vertical	PASS
6	11151.546	-38.30	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	847.710	-37.49	-13.00	Horizontal	N/A
2	2253.621	-40.54	-13.00	Horizontal	PASS
3	4735.579	-49.52	-13.00	Horizontal	PASS
4	7439.662	-43.45	-13.00	Horizontal	PASS
5	9743.208	-38.80	-13.00	Horizontal	PASS
6	11197.690	-38.56	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	844.800	-43.83	-13.00	Vertical	N/A
2	2267.067	-36.51	-13.00	Vertical	PASS
3	4672.822	-49.33	-13.00	Vertical	PASS
4	7332.606	-44.44	-13.00	Vertical	PASS
5	9752.437	-39.23	-13.00	Vertical	PASS
6	11155.237	-38.85	-13.00	Vertical	PASS

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	±2.22 dB
Bandwidth	±5%
Conducted Spurious Emission	±2.77 dB
Band Edge	±2.77 dB
Equivalent Isotropic Radiated Power	±2.22 dB
Radiated Spurious Emissions	±6 dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

4. Test Equipment Utilized

4.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2024.06.19	2025.06.18
Communication Test Station	6200995016	MT8820C	Anritsu	2024.09.11	2025.09.10
Temperature Chamber	S022177101 00089002	KMT-36LF 1A0	KOMEG	2024.09.11	2025.09.10

4.2 List of Software Used

Description	Manufacturer	Software Version
MOR-2023E Test System	MORLAB	V7.99
MORLAB EMCR	MORLAB	V1.2

4.3 Radiated Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
System Simulator	152038	CMW500	R&S	2024.09.11	2025.09.10
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Horn	9120D-963	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KK F-2	Qualwave	2024.07.03	2025.07.02
Preamplifier (10MHz-6GHz)	46732	S10M100L380 2	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L320 3	LUCIX CORP.	2024.05.30	2025.05.29
Notch Filter	N/A	WRCGV -LTE 26	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09

END OF REPORT