CBU Antenna test report

FTY Technology Co.,Ltd

CBU
Antenna test report

Office / Factory : 602, Building 1,
Aidimengtuo Industrial Park, the 4th
Industrial Zone, shutianpu Community,
Ma Tian Street, Guangming District,
Shenzhen CHINA

Website: www.phaten.com

Customer Approval

Company Shenzhen Phaten Technology Co., Ltd.

Signature

Date 2022-3-15

CONTENT

1. Product Description 2
2. General Description 2
3. Technical Information 2
4. Test Standards 3
5. Test Item 3
6. Test Photo 3
7. Darkroom test equipment and data 4
8. Appendix A Antenna Dimension 5
9. Appendix B SII/VSWR 5
10. Appendix C Gain and Efficiency 6
11. Appendix D Radiation Pattern(ID and 3D) 7
12. Appendix E Test Setup Photo 13

1. Product Description

Product Name	CBU
Antenna Type	PCB antenna
Maximum	Gain:1.96dBi
	Efficiency:44.48%

2. General Description

EUT Name	CBU Antenna
Wireless type	WIFI
Antenna Type	PCB antenna
Dimensions	Appendix A

3. Technical Information

Frequency Range	2402MHz~2480MHz
Test Frequency	2400,2410.....2500MHz

4. Test Standards

Identity	Document Title
IEEE 149-1979	IEEE Standard Test Procedures for Antennas

5. Test Item

Report Section	Description
Appendix B	S11A/SWR
Appendix C	Gain and Efficiency
Appendix D	Radiation Pattern (1D and 3D)

6. Test Photo

Report Section	Description
Appendix E	Test Setup Photo

7. Darkroom test equipment and data

5.0 Test Equipment

Test system: shielded darkroom

Test environment: temperature 22 ℃± 3 ℃, humidity 50% ± 15%

Test equipment: when testing passive data, use AgilentE5071C network analyzer； When testing the active data, use the comprehensive tester CMW500



8. Appendix A Antenna Dimension



9. Appendix B SII/VSWR

requency (MHz)	2400	2450	2500
eturn Loss	-9.46	-13	-11
SWR	1.8	1.5	1.8



10. Appendix C Gain and Efficiency

Passive Test For D44										
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHIS (%)	DHIS (%)	Max (dB)	Min (dB)	Attenut Hor	Attenut Ver
2400	40.43	-3.93	0.7	-1.45	16.061	24.371	0.7	-17.16	49.18	49.3
2410	39.54	-4.03	0.86	-1.29	15.756	23.785	0.86	-16.67	49.23	49.45
2420	40.88	-3.89	1.4	-0.75	16.635	24.243	1.4	-18.58	49.06	49.29
2430	42.5	-3.72	1.67	-0.48	17.57	24.935	1.67	-17.79	49.12	49.32
2440	44.48	-3.52	1.96	-0.19	18.796	25.689	1.96	-16.72	49.75	50.01
2450	43.2	-3.65	1.84	-0.31	18.687	24.512	1.84	-17.35	49.82	50.08
2460	41.57	-3.81	1.53	-0.62	18.485	23.085	1.53	-19.76	49.85	50.08
2470	38.01	-4.2	1.07	-1.08	17.234	20.774	1.07	-21.44	49.76	49.97
2480	38.23	-4.18	0.77	-1.38	17.723	20.511	0.77	-21.64	49.66	49.8
2490	35.02	-4.56	0.3	-1.85	16.519	18.504	0.3	-20.83	49.54	49.68
2500	28.21	-5.5	-0.77	-2.92	13.358	14.85	-0.77	-21.32	49.32	49.42





11. Appendix D Radiation Pattern(ID and 3D)













2410.000MHz E1



2410.000MHz E2



2420.000MHz E1



2420.000MHz E2



2430.000MHz



2430.000MHz H



2430.000MHz E1



2430.000MHz E2



2440.000MHz



2440.000MHz H



2440.000MHz E1



2440.000MHz E2




2450.000MHz
1.8
-0.1
-3.0
-5.8
-9.7
-13.5
-17.4


2450.000MHz H
5.00
0.00
-5.00
-10.00
-15.00
30
330
60
300
90
270
120
240
150
210
180


2450.000MHz E1
5.00
0.00
-5.00
-10.00
-15.00
30
330
60
300
90
270
120
240
150
210
180


2450.000MHz E2
5.00
0.00
-5.00
-10.00
-15.00
30
330
60
300
90
270
120
240
150
210
180


2460.000MHz
1.5
-0.6
-3.8
-7.0
-11.2
-15.5
-19.8


2460.000MHz H
5.00
0.00
-5.00
-10.00
-15.00
30
330
60
300
90
270
120
240
150
210
180

2460.000MHz E1



2460.000MHz E2



2470.000MHz



2470.000MHz H



2470.000MHz E1



2470.000MHz E2



2480.000MHz



2480.000MHz H



2490.000MHz



2490.000MHz H



2490.000MHz E1



2490.000MHz E2







12. Appendix E Test Setup Photo