

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Tablet

Trademark : ADVANCE

Model Name : SP5775

Family Model : N/A

Report No. : STR200903002008E

FCC ID : 2AV3BSP5775

Prepared for

TECHNOSOURCE HK LIMITED

2F, Building B, Sulandscape Industrial park, Shiyan Town, Bao'an District,
Shenzhen, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.

Tel.: 400-800-6106, 0755-3699 5508

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name**.....: TECHNOSOURCE HK LIMITEDAddress.....: 2F, Building B, Sulandscape Industrial park, Shiyan Town, Bao'an
District, Shenzhen, China**Manufacturer's Name**.....: TECHNOSOURCE HK LIMITEDAddress.....: 2F, Building B, Sulandscape Industrial park, Shiyan Town, Bao'an
District, Shenzhen, China**Product description**

Product name.....: Tablet

Trademark: ADVANCE

Model Name: SP5775

Family Model.....: N/A

FCC 47 CFR Part 2(2.1093)

ANSI/IEEE C95.1-1992

Standards.....: IEEE Std 1528-2013

Published RF exposure KDB procedures


This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.....: Sep. 09, 2020 ~ Sep. 15, 2020

Date of Issue: Sep. 16, 2020

Test Result: **Pass**Prepared By
(Test Engineer): 

(Cheng Jiawen)

Approved By
(Lab Manager): 

(Alex Li)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Sep. 16, 2020	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition.....	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	18
3.1. Power Reference	18
3.2. Area scan & Zoom scan.....	18
3.3. Description of interpolation/extrapolation scheme	20
3.4. Volumetric Scan	20
3.5. Power Drift	20
4. System Verification Procedure	21
4.1. Tissue Verification	21
4.1.1. Tissue Dielectric Parameter Check Results	22
4.2. System Verification Procedure	23
4.2.1. System Verification Results.....	24
5. SAR Measurement variability and uncertainty	25
5.1. SAR measurement variability.....	25
5.2. SAR measurement uncertainty	25
6. RF Exposure Positions	26
6.1. Tablet host platform exposure conditions.....	26
7. RF Output Power	27
7.1. GSM Conducted Power	27
7.2. GSM Conducted Power	27
7.3. LTE Conducted Power	28
7.4. WLAN & Bluetooth Output Power	35
7.4.1. Output Power Results Of WLAN	35
7.4.2. Output Power Results Of Bluetooth.....	36
8. Antenna Location.....	37

9. Stand-alone SAR test exclusion.....	43
10. SAR Results	44
10.1. SAR measurement results	44
10.1.1. SAR measurement Result of GSM850	44
10.1.2. SAR measurement Result of GSM1900	44
10.1.3. SAR measurement Result of WCDMA Band 2	45
10.1.4. SAR measurement Result of WCDMA Band 5	45
10.1.5. SAR measurement Result of LTE Band 2	45
10.1.6. SAR measurement Result of WCDMA Band 4	46
10.1.7. SAR measurement Result of WCDMA Band 7	46
10.1.8. SAR measurement Result of WLAN 2.4G	47
10.1.9. SAR measurement Result of WLAN 5.2G	47
10.2. SAR Summation Scenario.....	48
11. Appendix A. Photo documentation	53
12. Appendix B. System Check Plots	54
13. Appendix C. Plots of High SAR Measurement.....	67
14. Appendix D. Calibration Certificate	86

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Acer one 8 T2 are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)			
		PCE	DTS	NII	DSS
1-g Body (Separation distance of 0mm)		0.692	0.301	0.375	N/A
Max Simultaneous Tx	Body	1.067	0.993	1.067	0.928

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population / uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	Tablet		
Trade Name	ADVANCE		
Model Name	SP5775		
Family Model	N/A		
FCC ID	2AV3BSP5775		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna	PIFA Antenna		
Battery Information	DC 3.7V, 5000mAh		
Device Operating Configurations			
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/5, LTE Band 2/4/7, WLAN 2.4G/5.2G, Bluetooth		
Test Modulation	GSM(GMSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990

	LTE Band 4	1710-1755	2110-2155
	LTE Band 7	2500-2570	2620-2690
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 7)		
Test Channels (low-mid-high)	128-189-251(GSM 850)		
	512-661-810(GSM 1900)		
	9262-9400-9538(WCDMA Band 2)		
	4132-4182-4233(WCDMA Band 5)		
	18607-18900-19193(LTE Band 2 BW=1.4MHz)		
	18615-18900-19185(LTE Band 2 BW=3MHz)		
	18625-18900-19175(LTE Band 2 BW=5MHz)		
	18650-18900-19150(LTE Band 2 BW=10MHz)		
	18675-18900-19125(LTE Band 2 BW=15MHz)		
	18700-18900-19100(LTE Band 2 BW=20MHz)		
	19957-20175-20393(LTE Band 4 BW=1.4MHz)		
	19965-20175-20385(LTE Band 4 BW=3MHz)		
	19975-20175-20375(LTE Band 4 BW=5MHz)		
	20000-20175-20350(LTE Band 4 BW=10MHz)		
	20025-20175-20325(LTE Band 4 BW=15MHz)		
	20050-20175-20300(LTE Band 4 BW=20MHz)		
	20775-21100-21425(LTE Band 7 BW=5MHz)		
	20800-21100-21400(LTE Band 7 BW=10MHz)		
	20825-21100-21375(LTE Band 7 BW=15MHz)		
	20850-21100-21350(LTE Band 7 BW=20MHz)		
	1-3-6-9-11(WLAN 2.4G)		
	36-38-40-42-46-48(WLAN 5.2G)		

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 616217 D04 SAR for laptop and tablets

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.08 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 7mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm $\pm$ 0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μ m.

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Dec. 27, 2019	Dec. 26, 2020
☐	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Jul. 13, 2020	Jul. 12, 2021
☒	R&S	Wideband radio communication tester	CMW500	103917	Jul. 13, 2020	Jul. 12, 2021
☒	HP	Network Analyzer	8753D	3410J01136	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 13, 2020	Jul. 12, 2021

☒	Agilent	Power meter	E4419B	MY45102538	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	Power sensor	E9301A	MY41495644	Jul. 13, 2020	Jul. 12, 2021
☒	Agilent	Power sensor	E9301A	US39212148	Jul. 13, 2020	Jul. 12, 2021
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2020	Jul. 16, 2023

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.57	0.98	21.5 °C	Sep. 12, 2020
Body 1800	1800	53.30 (50.64~55.97)	1.52 (1.44~1.60)	54.10	1.51	21.2 °C	Sep. 09, 2020
Body 1900	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	54.31	1.53	21.4 °C	Sep. 12, 2020
Body 2450	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	51.59	1.88	21.5 °C	Sep. 15, 2020
Body 2600	2600	52.51 (49.88~55.14)	2.16 (2.05~2.27)	52.86	2.21	21.6 °C	Sep. 09, 2020
Body 5200	5200	49.00 (46.55~51.45)	5.30 (5.04~5.57)	49.70	5.25	21.5 °C	Sep. 13, 2020

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
835MHz Body	9.83 (8.85~10.81)	6.45 (5.81~7.10)	9.23	6.33	21.5 °C	Sep. 12, 2020
1800MHz Body	38.13 (34.32~41.94)	20.65 (18.59~22.72)	39.30	19.82	21.2 °C	Sep. 09, 2020
1900MHz Body	39.02 (35.12~42.92)	20.57 (18.51~22.63)	39.01	20.56	21.4 °C	Sep. 12 2020
2450MHz Body	52.90 (47.61~58.19)	24.09 (21.68~26.50)	53.46	24.77	21.5 °C	Sep. 15, 2020
2600MHz Body	52.49 (47.24~57.74)	23.74 (21.37~26.11)	56.12	23.34	21.6 °C	Sep. 09, 2020
5200MHz Body	156.85 (141.17~172.54)	55.20 (49.68~60.72)	159.67	56.57	21.5 °C	Sep. 13, 2020

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Tablet host platform exposure conditions

Refer to KDB616217 D04, when the modular approach is used, transmitters and modules must be initially tested for standalone operations in generic host conditions according to the following minimum test separation distance and antenna installation requirements for incorporation in the tablet platform. The separation distance required for incorporation in qualified hosts is described in KDB 447498; item 5) of section 4.1 and item 1) of section 5.2.2 etc.

- ≤ 5 mm between the antenna and user for both back surface and edge exposure conditions
- the antennas used by the host must have been tested for equipment approval or qualify for SAR test exclusion
- the antenna polarization, physical orientation, rotation and installation configurations used by the host must have been tested for compliance or qualify for test exclusion
- when the *SAR Test Exclusion Threshold* in KDB 447498 applies, a *test separation distance* of 5 mm is required to determine test exclusion for the tablet platform

The antennas embedded in tablets are typically ≤ 5 mm from the outer housing. The required antenna to user test separation distance is a “not to exceed test” distance required to apply the modular approach. Instead of the typical zero gap tablet edge test requirement between the edge of a tablet and the user, when an antenna has been tested at ≤ 5 mm according to the modular approach it can be incorporated into tablets with at least twice the tested distance from the outer housing of the tablet edge; otherwise, the tablet edge zero gap test requirement applies. When the dedicated host approach is applied, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.00	32.64	32.78	32.93	23.97	23.61	23.75	23.90
GPRS(GMSK, 1 TS)	33.00	32.65	32.78	32.97	23.97	23.62	23.75	23.94
GPRS(GMSK, 2 TS)	31.00	30.67	30.65	30.71	24.98	24.65	24.63	24.69
GPRS(GMSK, 3 TS)	29.00	28.69	28.69	28.75	24.74	24.43	24.43	24.49
GPRS(GMSK, 4 TS)	27.00	26.47	26.45	26.54	23.99	23.46	23.44	23.53
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	30.00	29.62	29.73	29.82	20.97	20.59	20.70	20.79
GPRS(GMSK, 1 TS)	30.00	29.64	29.75	29.84	20.97	20.61	20.72	20.81
GPRS(GMSK, 2 TS)	28.00	27.71	27.51	27.28	21.98	21.69	21.49	21.26
GPRS(GMSK, 3 TS)	26.00	26.00	25.99	25.73	21.74	21.74	21.73	21.47
GPRS(GMSK, 4 TS)	25.00	24.12	23.93	23.65	21.99	21.11	20.92	20.64

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. GSM Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	23.00	22.58	22.78	22.86
HSDPA Subtest-1	22.00	21.11	21.60	20.94
HSDPA Subtest-2	22.00	20.98	21.30	20.58
HSDPA Subtest-3	21.00	20.50	20.94	20.43
HSDPA Subtest-4	21.00	20.26	20.99	20.24
HSUPA Subtest-1	22.00	21.13	21.46	20.88
HSUPA Subtest-2	22.00	21.18	21.68	20.99
HSUPA Subtest-3	22.00	20.74	21.37	20.76

HSUPA Subtest-4	22.00	21.17	21.63	21.00
HSUPA Subtest-5	22.00	20.77	21.39	20.63
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	23.00	22.57	22.67	22.60
HSDPA Subtest-1	23.00	21.72	22.10	22.05
HSDPA Subtest-2	22.00	21.50	21.85	21.70
HSDPA Subtest-3	22.00	21.35	21.73	21.68
HSDPA Subtest-4	22.00	20.87	21.56	21.77
HSUPA Subtest-1	23.00	21.63	22.05	21.96
HSUPA Subtest-2	23.00	21.77	22.11	22.02
HSUPA Subtest-3	22.00	21.57	21.74	21.86
HSUPA Subtest-4	23.00	21.76	22.14	22.11
HSUPA Subtest-5	22.00	21.64	21.89	21.99

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	24.00	22.78	22.95	23.19
			1	2	24.00	22.89	22.95	23.09
			1	5	24.00	22.82	22.96	23.10
			3	0	24.00	22.80	22.91	23.09
			3	1	24.00	22.82	22.96	23.04
			3	2	24.00	22.71	22.85	23.01
		16QAM	6	0	22.00	21.69	21.86	21.99
			1	0	23.00	22.84	22.01	22.40
			1	2	23.00	22.76	21.98	22.48
			1	5	23.00	22.81	22.11	22.50
			3	0	23.00	22.02	21.96	22.54
			3	1	23.00	22.08	21.97	22.44
			3	2	23.00	21.95	21.97	22.42
			6	0	22.00	20.88	21.00	21.32
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5

LTE Band 2	3MHz	QPSK	1	0	24.00	22.78	23.01	23.15
			1	7	24.00	22.79	22.94	23.12
			1	14	24.00	22.71	22.97	23.08
			8	0	23.00	21.72	21.82	22.11
			8	4	23.00	21.72	21.82	22.06
			8	7	23.00	21.72	21.90	22.03
			15	0	23.00	21.75	21.97	22.07
		16QAM	1	0	23.00	22.87	21.98	22.52
			1	7	23.00	22.82	22.01	22.47
			1	14	23.00	22.89	22.03	22.42
			8	0	22.00	20.68	20.96	21.17
			8	4	22.00	20.69	20.94	21.12
			8	7	22.00	20.72	21.03	21.11
			15	0	22.00	20.90	20.91	21.22
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	24.00	22.66	23.03	22.84
			1	12	24.00	22.54	23.02	22.82
			1	24	24.00	22.59	23.02	22.84
			12	0	23.00	21.79	21.93	22.10
			12	6	23.00	21.73	21.98	21.95
			12	11	23.00	21.80	21.90	21.94
			25	0	22.00	21.85	21.84	21.98
		16QAM	1	0	23.00	22.05	21.65	22.02
			1	12	23.00	22.16	21.59	22.08
			1	24	23.00	22.09	21.62	22.00
			12	0	22.00	20.75	20.85	21.07
			12	6	22.00	20.81	20.97	21.03
			12	11	22.00	20.77	20.91	21.04
			25	0	22.00	20.90	21.05	21.10
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	24.00	22.67	22.94	23.26
			1	24	24.00	22.74	22.87	23.26
			1	49	24.00	22.77	22.98	23.26
			25	0	23.00	21.84	21.90	22.07

			25	12	23.00	21.87	21.93	22.01
			25	24	23.00	21.82	21.99	21.99
			50	0	22.00	21.82	21.84	21.95
		16QAM	1	0	23.00	22.97	21.98	22.19
			1	24	23.00	22.99	22.03	22.17
			1	49	23.00	23.00	22.03	22.18
			25	0	22.00	20.78	21.02	21.19
			25	12	22.00	20.80	21.10	21.10
			25	24	22.00	20.82	21.08	21.08
			50	0	22.00	20.83	21.14	21.11
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	24.00	22.78	23.05	22.93
			1	37	24.00	22.78	22.98	22.89
			1	74	24.00	22.79	23.12	22.86
			36	0	23.00	21.87	21.90	22.01
			36	18	23.00	21.84	21.95	22.05
			36	37	23.00	21.81	21.90	22.05
			75	0	23.00	21.80	21.93	22.12
		16QAM	1	0	24.00	23.06	22.11	22.77
			1	37	24.00	23.01	22.04	22.70
			1	74	24.00	23.17	22.04	22.71
			36	0	22.00	20.87	21.23	21.17
			36	18	22.00	20.96	21.10	21.19
			36	37	22.00	20.91	21.23	21.15
			75	0	22.00	20.94	21.08	21.14
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	24.00	22.93	22.91	23.11
			1	49	24.00	22.94	22.90	23.13
			1	99	24.00	23.04	22.93	23.09
			50	0	23.00	21.87	21.89	22.01
			50	24	23.00	21.85	21.94	22.03
			50	49	23.00	21.82	21.93	22.02
			100	0	23.00	21.84	21.88	22.02
		16QAM	1	0	23.00	21.56	21.62	22.01

			1	49	23.00	21.58	21.54	21.95
			1	99	23.00	21.65	21.63	21.94
			50	0	22.00	21.03	21.04	21.23
			50	24	22.00	20.98	21.07	21.04
			50	49	22.00	21.12	21.05	21.11
			100	0	22.00	20.95	21.07	21.20

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.00	22.73	22.69	22.95
			1	2	23.00	22.76	22.68	22.95
			1	5	23.00	22.72	22.73	22.93
			3	0	23.00	22.60	22.76	22.80
			3	1	23.00	22.66	22.81	22.73
			3	2	23.00	22.61	22.73	22.79
			6	0	22.00	21.59	21.67	21.71
		16QAM	1	0	23.00	22.79	22.34	22.32
			1	2	23.00	22.78	22.39	22.15
			1	5	23.00	22.82	22.40	22.29
			3	0	23.00	21.97	21.84	22.08
			3	1	23.00	21.93	21.85	22.03
			3	2	23.00	22.01	21.83	21.96
			6	0	21.00	21.00	20.78	20.93

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.00	22.92	22.65	22.92
			1	7	23.00	22.85	22.69	22.98
			1	14	23.00	22.89	22.69	23.00
			8	0	22.00	21.67	21.67	21.79
			8	4	22.00	21.59	21.69	21.67
			8	7	22.00	21.59	21.61	21.64
			15	0	22.00	21.68	21.65	21.78
		16QAM	1	0	23.00	22.81	22.39	22.25
			1	7	23.00	22.76	22.36	22.28
			1	14	23.00	22.76	22.34	22.26
			8	0	21.00	20.56	20.99	20.79

			8	4	21.00	20.61	21.00	20.74
			8	7	21.00	20.60	21.00	20.82
			15	0	21.00	20.84	20.83	20.69
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.00	22.66	22.78	22.63
			1	12	23.00	22.62	22.79	22.63
			1	24	23.00	22.63	22.77	22.61
			12	0	22.00	21.63	21.78	21.68
			12	6	22.00	21.71	21.72	21.69
			12	11	22.00	21.67	21.64	21.70
			25	0	22.00	21.58	21.73	21.69
		16QAM	1	0	23.00	21.84	21.34	22.00
			1	12	23.00	21.79	21.37	22.02
			1	24	23.00	21.82	21.42	22.02
			12	0	21.00	20.66	20.65	20.72
			12	6	21.00	20.59	20.65	20.70
			12	11	21.00	20.59	20.66	20.66
			25	0	21.00	20.84	20.80	20.74
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.00	22.86	22.73	22.96
			1	24	23.00	22.77	22.70	22.95
			1	49	23.00	22.87	22.73	23.00
			25	0	22.00	21.61	21.73	21.62
			25	12	22.00	21.68	21.69	21.75
			25	24	22.00	21.66	21.79	21.69
			50	0	22.00	21.61	21.77	21.58
		16QAM	1	0	23.00	22.71	21.80	21.91
			1	24	23.00	22.75	21.81	21.92
			1	49	23.00	22.84	21.85	21.87
			25	0	21.00	20.76	20.86	20.73
			25	12	21.00	20.74	20.82	20.78
			25	24	21.00	20.75	20.85	20.76
			50	0	21.00	20.73	20.82	20.73
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration					
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.00	22.88	22.65	22.55
			1	37	23.00	22.85	22.70	22.61
			1	74	23.00	22.93	22.70	22.60
			36	0	22.00	21.61	21.68	21.69
			36	18	22.00	21.64	21.72	21.63
			36	37	22.00	21.68	21.76	21.59
			75	0	22.00	21.69	21.69	21.75
		16QAM	1	0	23.00	22.82	21.79	22.45
			1	37	23.00	22.67	21.78	22.37
			1	74	23.00	22.77	21.81	22.37
			36	0	21.00	20.84	20.86	20.72
			36	18	21.00	20.79	20.96	20.74
			36	37	21.00	20.79	20.95	20.72
			75	0	21.00	20.69	20.80	20.88
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.00	22.91	22.85	22.63
			1	49	23.00	22.80	22.79	22.56
			1	99	23.00	22.90	22.86	22.61
			50	0	22.00	21.68	21.73	21.71
			50	24	22.00	21.64	21.64	21.68
			50	49	22.00	21.60	21.73	21.74
			100	0	22.00	21.66	21.70	21.71
		16QAM	1	0	23.00	21.77	21.59	22.04
			1	49	23.00	21.81	21.64	21.99
			1	99	23.00	21.96	21.73	22.01
			50	0	21.00	20.64	20.79	20.87
			50	24	21.00	20.79	20.80	20.80
			50	49	21.00	20.69	20.83	20.76
			100	0	21.00	20.69	20.83	20.68

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5

LTE Band 7	5MHz	QPSK	1	0	24.00	23.13	23.05	23.47
			1	12	24.00	23.17	23.11	23.41
			1	24	24.00	23.12	23.17	23.49
			12	0	23.00	22.16	22.13	22.39
			12	6	23.00	22.18	22.19	22.45
			12	11	23.00	22.09	22.18	22.36
			25	0	23.00	22.07	22.17	22.47
		16QAM	1	0	23.00	22.28	22.35	22.50
			1	12	23.00	22.28	22.47	22.53
			1	24	23.00	22.29	22.42	22.51
			12	0	22.00	21.02	21.25	21.38
			12	6	22.00	21.00	21.33	21.39
			12	11	22.00	21.07	21.31	21.34
			25	0	22.00	21.27	21.24	21.68
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	24.00	23.04	23.13	23.60
			1	24	24.00	22.18	23.21	23.66
			1	49	24.00	22.99	23.29	23.64
			25	0	23.00	22.03	22.17	22.37
			25	12	23.00	22.04	22.29	22.40
			25	24	23.00	22.08	22.21	22.49
			50	0	23.00	22.20	22.34	22.43
		16QAM	1	0	24.00	23.15	22.90	22.41
			1	24	24.00	23.14	22.90	22.49
			1	49	24.00	23.25	23.05	22.52
			25	0	22.00	21.12	21.29	21.48
			25	12	22.00	21.11	21.37	21.52
			25	24	22.00	21.10	21.36	21.48
			50	0	22.00	21.16	21.38	21.54
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	24.00	23.07	23.25	23.32
			1	37	24.00	23.01	23.29	23.30
			1	74	24.00	23.12	23.35	23.39
			36	0	23.00	22.02	22.13	22.35

			36	18	23.00	22.19	22.18	22.32
			36	37	23.00	22.14	22.25	22.37
			75	0	23.00	22.06	22.19	22.43
		16QAM	1	0	24.00	23.23	22.13	23.10
			1	37	24.00	23.23	22.19	23.06
			1	74	24.00	23.37	22.37	23.18
			36	0	22.00	21.25	21.40	21.40
			36	18	22.00	21.24	21.37	21.46
			36	37	22.00	21.24	21.42	21.52
			75	0	22.00	21.27	21.29	21.56
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	24.00	23.07	23.02	23.36
			1	49	24.00	23.15	23.15	23.26
			1	99	24.00	23.15	23.27	23.47
			50	0	23.00	22.21	22.26	22.35
			50	24	23.00	22.21	22.17	22.28
			50	49	23.00	22.20	22.25	22.46
			100	0	23.00	22.16	22.22	22.38
		16QAM	1	0	23.00	22.36	22.39	22.33
			1	49	23.00	22.40	22.49	22.32
			1	99	23.00	22.45	22.62	22.51
			50	0	22.00	21.22	21.24	21.51
			50	24	22.00	21.30	21.32	21.45
			50	49	22.00	21.34	21.43	21.56
			100	0	22.00	21.24	21.22	21.42

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	13.00	12.51
	6	2437	13.00	12.91
	11	2462	13.00	12.16
802.11g	1	2412	13.00	11.68
	6	2437	13.00	12.40
	11	2462	13.00	11.31

802.11n HT20	1	2412	13.00	11.79
	6	2437	13.00	12.44
	11	2462	13.00	11.41
802.11n HT40	3	2422	13.00	11.60
	6	2437	13.00	12.14
	9	2452	13.00	11.63

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	36	5180	10.00	8.68
	40	5200	10.00	8.91
	48	5240	10.00	9.05
802.11n HT20	36	5180	10.00	8.67
	40	5200	10.00	8.86
	48	5240	10.00	9.03
802.11n HT40	38	5190	9.00	8.74
	46	5230	9.00	8.32
802.11ac VHT20	36	5180	9.00	8.66
	40	5200	9.00	8.76
	48	5240	9.00	8.97
802.11ac VHT40	38	5190	9.00	8.88
	46	5230	9.00	8.24
802.11ac VHT80	42	5210	10.00	9.07


NOTE: Power measurement results of WLAN 5.2G.

7.4.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)				
	Data Rates	Tune-up	Channel		
			0CH	39CH	78CH
	1M	6.000	5.543	4.260	4.162
	2M	7.500	6.985	6.580	5.732
	3M	7.500	7.109	6.672	6.021

BLE	Channel	Tune-up	Output Power (dBm)	
			1M	2M
	0CH	3.000	2.063	1.126
	19CH	3.000	2.166	1.774
	39CH	2.000	1.223	0.397

8. Antenna Location



Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	5mm	5mm	238mm	5mm	8mm	78mm
WLAN & Bluetooth	5mm	5mm	238mm	5mm	128mm	6mm

Note: When the minimum separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Positions for SAR tests		
Test separation distances ≤ 50 mm		
Exposure Positions	Tune-up Maximum power of WLAN 2.4G	
	13dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	6.3
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	6.3
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	6.3
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	6
	SAR exclusion threshold	5.2
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WLAN 5.2G	
	10dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	4.6
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	4.6
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	4.6
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	6
	SAR exclusion threshold	3.8
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of GSM850	
	33dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	367.6
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	367.6
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5

	SAR exclusion threshold	367.6
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	229.8
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of GSM1900	
	30dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	276.4
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	276.4
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	276.4
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	172.7
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WCDMA Band 2	
	23dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	55.1
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	55.1
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	55.1
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	34.5
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WCDMA Band 5	
	23dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	36.8
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	36.8

	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	36.8
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	23.0
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 2	
	24dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	69.4
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	69.4
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	69.4
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	43.4
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 4	
	23dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	52.9
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	52.9
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	52.9
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	33.0
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 7	
	24dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	80.5
	SAR testing required?	YES

Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	80.5
	SAR testing required?	YES
Right Side	Antenna to user(mm)	5
	SAR exclusion threshold	80.5
	SAR testing required?	YES
Top Side	Antenna to user(mm)	8
	SAR exclusion threshold	50.3
	SAR testing required?	YES

NOTE: Refer to section 4.3.1 of KDB 447498 D01.

Positions for SAR tests		
Test separation distances > 50 mm		
Exposure Positions	Tune-up Maximum power of WLAN 2.4G	
	13dBm	19.95mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1976
	SAR testing required?	NO
Top Side	Antenna to user(mm)	128
	SAR exclusion threshold(mW)	876
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of WLAN 5.2G	
	10dBm	10.00mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1946
	SAR testing required?	NO
Top Side	Antenna to user(mm)	128
	SAR exclusion threshold(mW)	846
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of GSM 850	
	33dBm	1995.26mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1229
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	323
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of GSM 1900	
	30dBm	1000.00mW
Left Side	Antenna to user(mm)	238

	SAR exclusion threshold(mW)	1989
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	389
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WCDMA Band 2	
	23dBm	199.53mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1989
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	389
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of WCDMA Band 5	
	23dBm	199.53mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1229
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	323
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 2	
	24dBm	251.19mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1989
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	389
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 4	
	23dBm	199.53mW
Left Side	Antenna to user(mm)	238
	SAR exclusion threshold(mW)	1989
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	389
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 7	
	24dBm	251.19mW
Left Side	Antenna to user(mm)	238

Bottom Side	SAR exclusion threshold(mW)	1976
	SAR testing required?	NO
	Antenna to user(mm)	78
	SAR exclusion threshold(mW)	376
	SAR testing required?	NO

NOTE: Refer to section 4.3.1 of KDB 447498 D01.

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	7.50	5.62	5	2.480	1.77	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Body	7.50	5.62	5	2.480	7.5	0.236

NOTE: Estimated SAR calculation for Bluetooth.

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 2TS)	0.353	0.266	-1.03	30.65	31.00	0.383
Back Side	189/836.4	GPRS(GMSK 2TS)	0.469	0.352	0.78	30.65	31.00	0.508
Left Side	189/836.4	GPRS(GMSK 2TS)	0.165	0.116	2.87	30.65	31.00	0.179
Right Side	189/836.4	GPRS(GMSK 2TS)	0.332	0.243	3.99	30.65	31.00	0.360
Top Side	189/836.4	GPRS(GMSK 2TS)	0.232	0.175	3.99	30.65	31.00	0.251
Bottom Side	189/836.4	GPRS(GMSK 2TS)	0.183	0.137	3.12	30.65	31.00	0.198

NOTE: Body SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 3TS)	0.563	0.302	1.91	25.99	26.00	0.564
Back Side	661/1880	GPRS(GMSK 3TS)	0.690	0.368	-4.41	25.99	26.00	0.692
Right Side	661/1880	GPRS(GMSK 3TS)	0.543	0.292	3.61	25.99	26.00	0.544
Top Side	661/1880	GPRS(GMSK 3TS)	0.421	0.237	3.61	25.99	26.00	0.422
Bottom Side	661/1880	GPRS(GMSK 3TS)	0.267	0.140	-4.75	25.99	26.00	0.268

NOTE: Body SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.241	0.186	-2.37	22.78	23.00	0.254
Back Side	9400/1880	RMC12.2K	0.288	0.218	-0.72	22.78	23.00	0.303
Right Side	9400/1880	RMC12.2K	0.220	0.171	-4.19	22.78	23.00	0.231
Top Side	9400/1880	RMC12.2K	0.141	0.105	-3.55	22.78	23.00	0.148

NOTE: Body SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 5

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.263	0.142	0.62	22.67	23.00	0.284
Back Side	4182/836.4	RMC12.2K	0.332	0.183	0.47	22.67	23.00	0.358
Right Side	4182/836.4	RMC12.2K	0.248	0.138	-1.59	22.67	23.00	0.268
Top Side	4182/836.4	RMC12.2K	0.150	0.078	-1.48	22.67	23.00	0.162

NOTE: Body SAR test results of WCDMA Band 5

10.1.5. SAR measurement Result of LTE Band 2

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.240	0.194	4.72	22.90	24.00	0.309
Back Side	18900/1880	20M QPSK(1,49)	0.286	0.229	-1.08	22.90	24.00	0.368
Right Side	18900/1880	20M QPSK(1,49)	0.204	0.159	-4.50	22.90	24.00	0.263
Top Side	18900/1880	20M QPSK(1,49)	0.138	0.115	-2.23	22.90	24.00	0.178
50%								
Front Side	18900/1880	1.4M QPSK(3,0)	0.208	0.178	-4.05	22.91	24.00	0.267
Back Side	18900/1880	1.4M	0.246	0.213	-2.80	22.91	24.00	0.316

		QPSK(3,0)						
Right Side	18900/1880	1.4M QPSK(3,0)	0.188	0.149	-0.12	22.91	24.00	0.242
Top Side	18900/1880	1.4M QPSK(3,0)	0.128	0.106	2.24	22.91	24.00	0.165

NOTE: Body SAR test results of LTE Band 2

10.1.6. SAR measurement Result of WCDMA Band 4

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	20M QPSK(1,0)	0.286	0.219	1.79	22.85	23.00	0.296
Back Side	20175/1732.5	20M QPSK(1,0)	0.359	0.275	-1.15	22.85	23.00	0.372
Right Side	20175/1732.5	20M QPSK(1,0)	0.263	0.197	-1.87	22.85	23.00	0.272
Top Side	20175/1732.5	20M QPSK(1,0)	0.163	0.130	-2.98	22.85	23.00	0.169
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,1)	0.266	0.205	-0.60	22.81	23.00	0.278
Back Side	20175/1732.5	1.4M QPSK(3,1)	0.326	0.248	3.85	22.81	23.00	0.341
Right Side	20175/1732.5	1.4M QPSK(3,1)	0.242	0.184	-0.40	22.81	23.00	0.253
Top Side	20175/1732.5	1.4M QPSK(3,1)	0.150	0.115	4.07	22.81	23.00	0.157

NOTE: Body SAR test results of LTE Band 4

10.1.7. SAR measurement Result of WCDMA Band 7

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M	0.268	0.134	-0.85	23.27	24.00	0.317

		QPSK(1,99)						
Back Side	21100/2535	20M QPSK(1,99)	0.342	0.169	-1.22	23.27	24.00	0.405
Right Side	21100/2535	20M QPSK(1,99)	0.257	0.126	3.17	23.27	24.00	0.304
Top Side	21100/2535	20M QPSK(1,99)	0.154	0.072	0.69	23.27	24.00	0.182
50%RB								
Front Side	21100/2535	20M QPSK(50,49)	0.244	0.118	-3.47	22.25	23.00	0.290
Back Side	21100/2535	20M QPSK(50,49)	0.299	0.155	4.86	22.25	23.00	0.355
Right Side	21100/2535	20M QPSK(50,49)	0.238	0.113	-0.28	22.25	23.00	0.283
Top Side	21100/2535	20M QPSK(50,49)	0.135	0.066	2.54	22.25	23.00	0.160

NOTE: Body SAR test results of LTE Band 7

10.1.8. SAR measurement Result of WLAN 2.4G

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.179	0.110	0.72	12.91	13.00	0.183
Back Side	6/2437	802.11 b	0.295	0.170	-0.40	12.91	13.00	0.301
Right Side	6/2437	802.11 b	0.096	0.059	-3.94	12.91	13.00	0.098
Bottom Side	6/2437	802.11 b	0.073	0.039	-4.11	12.91	13.00	0.075

NOTE: Body SAR test results of WLAN 2.4G

10.1.9. SAR measurement Result of WLAN 5.2G

Test Position of Body with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	40/5200	802.11a	0.179	0.078	2.31	8.91	10.00	0.230
Back Side	40/5200	802.11a	0.292	0.127	-0.96	8.91	10.00	0.375
Right Side	40/5200	802.11a	0.089	0.044	0.69	8.91	10.00	0.114
Bottom Side	40/5200	802.11a	0.068	0.026	-2.10	8.91	10.00	0.087

NOTE: Body SAR test results of WLAN 5.2G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 2.4G			
Body	Front Side	0.383	0.183	0.566	N/A	N/A
	Back Side	0.508	0.301	0.809	N/A	N/A
	Left Side	0.179	N/A	0.179	N/A	N/A
	Right Side	0.360	0.098	0.458	N/A	N/A
	Top Side	0.251	N/A	0.251	N/A	N/A
	Bottom Side	0.198	0.075	0.273	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Body	Front Side	0.564	0.183	0.747	N/A	N/A
	Back Side	0.692	0.301	0.993	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.544	0.098	0.642	N/A	N/A
	Top Side	0.422	N/A	0.422	N/A	N/A
	Bottom Side	0.268	0.075	0.343	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			
Body	Front Side	0.254	0.183	0.437	N/A	N/A
	Back Side	0.303	0.301	0.604	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.231	0.098	0.329	N/A	N/A
	Top Side	0.148	N/A	0.148	N/A	N/A
	Bottom Side	N/A	0.075	0.075	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA	WLAN 2.4G			

		Band 5				
Body	Front Side	0.284	0.183	0.467	N/A	N/A
	Back Side	0.358	0.301	0.659	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.268	0.098	0.366	N/A	N/A
	Top Side	0.162	N/A	0.162	N/A	N/A
	Bottom Side	N/A	0.075	0.075	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 2.4G			
Body	Front Side	0.309	0.183	0.492	N/A	N/A
	Back Side	0.368	0.301	0.669	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.263	0.098	0.361	N/A	N/A
	Top Side	0.178	N/A	0.178	N/A	N/A
	Bottom Side	N/A	0.075	0.075	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 2.4G			
Body	Front Side	0.296	0.183	0.479	N/A	N/A
	Back Side	0.372	0.301	0.673	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.272	0.098	0.370	N/A	N/A
	Top Side	0.169	N/A	0.169	N/A	N/A
	Bottom Side	N/A	0.075	0.075	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 2.4G			
Body	Front Side	0.317	0.183	0.500	N/A	N/A
	Back Side	0.405	0.301	0.706	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.304	0.098	0.402	N/A	N/A
	Top Side	0.182	N/A	0.182	N/A	N/A
	Bottom Side	N/A	0.075	0.075	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 5.2G			
Body	Front Side	0.383	0.230	0.613	N/A	N/A

	Back Side	0.508	0.375	0.883	N/A	N/A
	Left Side	0.179	N/A	0.179	N/A	N/A
	Right Side	0.360	0.114	0.474	N/A	N/A
	Top Side	0.251	N/A	0.251	N/A	N/A
	Bottom Side	0.198	0.087	0.285	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 5.2G			
Body	Front Side	0.564	0.230	0.794	N/A	N/A
	Back Side	0.692	0.375	1.067	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.544	0.114	0.658	N/A	N/A
	Top Side	0.422	N/A	0.422	N/A	N/A
	Bottom Side	0.268	0.087	0.355	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 5.2G			
Body	Front Side	0.254	0.230	0.484	N/A	N/A
	Back Side	0.303	0.375	0.678	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.231	0.114	0.345	N/A	N/A
	Top Side	0.148	N/A	0.148	N/A	N/A
	Bottom Side	N/A	0.087	0.087	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 5.2G			
Body	Front Side	0.284	0.230	0.514	N/A	N/A
	Back Side	0.358	0.375	0.733	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.268	0.114	0.382	N/A	N/A
	Top Side	0.162	N/A	0.162	N/A	N/A
	Bottom Side	N/A	0.087	0.087	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 5.2G			
Body	Front Side	0.309	0.230	0.539	N/A	N/A

	Back Side	0.368	0.375	0.743	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.263	0.114	0.377	N/A	N/A
	Top Side	0.178	N/A	0.178	N/A	N/A
	Bottom Side	N/A	0.087	0.087	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 5.2G			
Body	Front Side	0.296	0.230	0.526	N/A	N/A
	Back Side	0.372	0.375	0.747	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.272	0.114	0.386	N/A	N/A
	Top Side	0.169	N/A	0.169	N/A	N/A
	Bottom Side	N/A	0.087	0.087	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 5.2G			
Body	Front Side	0.317	0.230	0.547	N/A	N/A
	Back Side	0.405	0.375	0.780	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.304	0.114	0.418	N/A	N/A
	Top Side	0.182	N/A	0.182	N/A	N/A
	Bottom Side	N/A	0.087	0.087	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Body	Front Side	0.383	0.236	0.619	N/A	N/A
	Back Side	0.508	0.236	0.744	N/A	N/A
	Left Side	0.179	N/A	0.179	N/A	N/A
	Right Side	0.360	0.236	0.596	N/A	N/A
	Top Side	0.251	N/A	0.251	N/A	N/A
	Bottom Side	0.198	0.236	0.434	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			
Body	Front Side	0.564	0.236	0.800	N/A	N/A
	Back Side	0.692	0.236	0.928	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A

	Right Side	0.544	0.236	0.780	N/A	N/A
	Top Side	0.422	N/A	0.422	N/A	N/A
	Bottom Side	0.268	0.236	0.504	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	Bluetooth			
Body	Front Side	0.254	0.236	0.490	N/A	N/A
	Back Side	0.303	0.236	0.539	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.231	0.236	0.467	N/A	N/A
	Top Side	0.148	N/A	0.148	N/A	N/A
	Bottom Side	N/A	0.236	0.236	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	Bluetooth			
Body	Front Side	0.284	0.236	0.520	N/A	N/A
	Back Side	0.358	0.236	0.594	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.268	0.236	0.504	N/A	N/A
	Top Side	0.162	N/A	0.162	N/A	N/A
	Bottom Side	N/A	0.236	0.236	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	Bluetooth			
Body	Front Side	0.309	0.236	0.545	N/A	N/A
	Back Side	0.368	0.236	0.604	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.263	0.236	0.499	N/A	N/A
	Top Side	0.178	N/A	0.178	N/A	N/A
	Bottom Side	N/A	0.236	0.236	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	Bluetooth			
Body	Front Side	0.296	0.236	0.532	N/A	N/A
	Back Side	0.372	0.236	0.608	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A

	Right Side	0.272	0.236	0.508	N/A	N/A
	Top Side	0.169	N/A	0.169	N/A	N/A
	Bottom Side	N/A	0.236	0.236	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	Bluetooth			
Body	Front Side	0.317	0.236	0.553	N/A	N/A
	Back Side	0.405	0.236	0.641	N/A	N/A
	Left Side	N/A	N/A	N/A	N/A	N/A
	Right Side	0.304	0.236	0.540	N/A	N/A
	Top Side	0.182	N/A	0.182	N/A	N/A
	Bottom Side	N/A	0.236	0.236	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and Bluetooth.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check- SID835 - Body
MEASUREMENT 2 System Performance Check- SID1800- Body
MEASUREMENT 3 System Performance Check- SID1900- Body
MEASUREMENT 4 System Performance Check- SID2450- Body
MEASUREMENT 5 System Performance Check- SID2600 - Body
MEASUREMENT 6 System Performance Check- SID5200 - Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	CW (Crest factor: 1.0)


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.571100
Relative permittivity (imaginary part)	21.163459
Conductivity (S/m)	0.980836
Variation (%)	-1.210000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.633023
SAR 1g (W/Kg)	0.923356



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	54.103510
Relative permittivity (imaginary part)	15.110016
Conductivity (S/m)	1.513096
Variation (%)	1.510000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	1.982239
SAR 1g (W/Kg)	3.930268



MEASUREMENT 3


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	54.310335
Relative permittivity (imaginary part)	14.461803
Conductivity (S/m)	1.530066
Variation (%)	0.120000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.056329
SAR 1g (W/Kg)	3.901402



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	51.591697
Relative permittivity (imaginary part)	13.833566
Conductivity (S/m)	1.882816
Variation (%)	0.420000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.477285
SAR 1g (W/Kg)	5.346270



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.860066
Relative permittivity (imaginary part)	15.330637
Conductivity (S/m)	2.213465
Variation (%)	-1.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.99 W/kg

SAR 10g (W/Kg)	2.334324
SAR 1g (W/Kg)	5.612188



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.699535
Relative permittivity (imaginary part)	18.175508
Conductivity (S/m)	5.250703
Variation (%)	4.490000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=6.00

SAR Peak: 49.61 W/kg

SAR 10g (W/Kg)	5.657184
SAR 1g (W/Kg)	15.967246



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Body
MEASUREMENT 2 GSM 1900 Body
MEASUREMENT 3 WCDMA Band 2 Body
MEASUREMENT 4 WCDMA Band 5 Body
MEASUREMENT 5 WLAN 5.2G Body
MEASUREMENT 6 WLAN 2.4G Body
MEASUREMENT 7 LTE Band 2 Body
MEASUREMENT 8 LTE Band 4 Body
MEASUREMENT 9 LTE Band 7 Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.579578
Relative permittivity (imaginary part)	21.142740
Conductivity (S/m)	0.982433
Variation (%)	0.780000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=14.00

SAR Peak: 0.59 W/kg

SAR 10g (W/Kg)	0.351854
SAR 1g (W/Kg)	0.469155



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.7)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.383900
Relative permittivity (imaginary part)	14.547700
Conductivity (S/m)	1.519426
Variation (%)	-4.410000

SURFACE SAR





VOLUME SAR



Maximum location: X=-16.00, Y=10.00

SAR Peak: 1.17 W/kg

SAR 10g (W/Kg)	0.367680
SAR 1g (W/Kg)	0.690165



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.383900
Relative permittivity (imaginary part)	14.547700
Conductivity (S/m)	1.519426
Variation (%)	-0.720000

SURFACE SAR





VOLUME SAR



Maximum location: X=8.00, Y=32.00

SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.218266
SAR 1g (W/Kg)	0.287989



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.579578
Relative permittivity (imaginary part)	21.142740
Conductivity (S/m)	0.982433
Variation (%)	0.470000

SURFACE SAR





VOLUME SAR



Maximum location: X=-21.00, Y=-9.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.183098
SAR 1g (W/Kg)	0.332068



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.699535
Relative permittivity (imaginary part)	18.175508
Conductivity (S/m)	5.250703
Variation (%)	-0.960000

SURFACE SAR





VOLUME SAR



Maximum location: X=1.00, Y=-32.00

SAR Peak: 0.94 W/kg

SAR 10g (W/Kg)	0.127478
SAR 1g (W/Kg)	0.291642



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	51.723701
Relative permittivity (imaginary part)	13.904400
Conductivity (S/m)	1.882501
Variation (%)	-0.400000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=-1.00

SAR Peak: 0.47 W/kg

SAR 10g (W/Kg)	0.169728
SAR 1g (W/Kg)	0.295420



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.383900
Relative permittivity (imaginary part)	14.547700
Conductivity (S/m)	1.519426
Variation (%)	-1.080000

SURFACE SAR





VOLUME SAR



Maximum location: X=-7.00, Y=19.00

SAR Peak: 0.34 W/kg

SAR 10g (W/Kg)	0.228646
SAR 1g (W/Kg)	0.285589



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	54.488365
Relative permittivity (imaginary part)	15.138220
Conductivity (S/m)	1.457054
Variation (%)	-1.150000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=36.00

SAR Peak: 0.44 W/kg

SAR 10g (W/Kg)	0.274880
SAR 1g (W/Kg)	0.358714



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	53.196945
Relative permittivity (imaginary part)	15.197840
Conductivity (S/m)	2.140362
Variation (%)	-1.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=20.00, Y=34.00

SAR Peak: 0.63 W/kg

SAR 10g (W/Kg)	0.169303
SAR 1g (W/Kg)	0.341988



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 08/16 EPGO287
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
5000-6000 MHz Dipole - SN 13/14 WGA 33



COMOSAR E-Field Probe Calibration Report

Ref : ACR.260.1.18.SATU.A

**SHENZHEN NTEK TESTING TECHNOLOGY
CO., LTD.**

**BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA**

MVG COMOSAR DOSIMETRIC E-FIELD PROBE

SERIAL NO.: SN 08/16 EPGO287

Calibrated at MVG US

2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 12/27/2019

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme LUC	Product Manager	12/27/2019	
<i>Checked by :</i>	Jérôme LUC	Product Manager	12/27/2019	
<i>Approved by :</i>	Kim RUTKOWSKI	Quality Manager	12/27/2019	

	<i>Customer Name</i>
<i>Distribution :</i>	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Date</i>	<i>Modifications</i>
A	12/27/2019	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.5	Boundary Effect	5
4	Measurement Uncertainty	5
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	7
5.4	Isotropy	8
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 08/16 EPGO287
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.209 MΩ Dipole 2: R2=0.196 MΩ Dipole 3: R3=0.197 MΩ

A yearly calibration interval is recommended.

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Field probe linearity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Combined standard uncertainty					5.831%
Expanded uncertainty 95 % confidence level k = 2					12.0%

Page: 5/10

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %


5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.66	0.75	0.58

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
93	93	98

Calibration curves $e_i=f(V)$ ($i=1,2,3$) allow to obtain H-field value using the formula:

$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

5.2 LINEARITY

Linearity: $\pm 1.89\%$ ($\pm 0.08\text{dB}$)

5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz $\pm$ 100MHz)	Permittivity	Epsilon (S/m)	ConvF
HL750	750	40.03	0.93	1.45
BL750	750	56.83	1.00	1.49
HL850	835	42.19	0.90	1.50
BL850	835	54.67	1.01	1.56
HL900	900	42.08	1.01	1.51
HL1800	1800	41.68	1.46	1.71
BL1800	1800	53.86	1.46	1.77
HL1900	1900	38.45	1.45	2.03
BL1900	1900	53.32	1.56	2.07
HL2000	2000	38.26	1.38	1.76
HL2450	2450	37.50	1.80	2.00
BL2450	2450	53.22	1.89	2.08
HL2600	2600	39.80	1.99	2.12
BL2600	2600	52.52	2.23	2.19
HL5200	5200	35.64	4.67	2.55
BL5200	5200	48.64	5.51	2.62
HL5400	5400	36.44	4.87	2.53
BL5400	5400	46.52	5.77	2.59
HL5600	5600	36.66	5.17	2.64
BL5600	5600	46.79	5.77	2.73
HL5800	5800	35.31	5.31	2.72
BL5800	5800	47.04	6.10	2.81

LOWER DETECTION LIMIT: 7mW/kg

Page: 7/10

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

5.4 ISOTROPY


HL900 MHz

- Axial isotropy: 0.04 dB
- Hemispherical isotropy: 0.07 dB



HL1800 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.08 dB






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

HL5600 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.08 dB





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2019	02/2022
Reference Probe	MVG	EP 94 SN 37/08	10/2019	10/2020
Multimeter	Keithley 2000	1188656	01/2017	01/2020
Signal Generator	Agilent E4438C	MY49070581	01/2017	01/2020
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	01/2017	01/2020
Power Sensor	HP ECP-E26A	US37181460	01/2017	01/2020
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Control Company	150798832	11/2017	11/2020



SAR Reference Dipole Calibration Report

Ref : ACR.109.2.18.SATU.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 835 MHZ

SERIAL NO.: SN 03/15 DIP 0G835-347

Calibrated at MVG US

2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 04/19/2018

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Checked by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Approved by :	Kim RUTKOWSKI	Quality Manager	4/19/2018	<i>Kim Rutkowski</i>

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Date	Modifications
A	4/19/2018	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Head Liquid Measurement	7
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	9
7.4	SAR Measurement Result With Body Liquid	10
8	List of Equipment	11



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.2.18.SATU.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 835 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID835
Serial Number	SN 03/15 DIP 0G835-347
Product Condition (new / used)	Used

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole