

TEST REPORT

Applicant: Shenzhen Zolon Technology Co., Ltd.
Address: 401, Building 3, Shenzhen Software Park, Maling Community, Yuehai Sub-district, Nanshan District, Shenzhen, Guangdong P.R. China
Equipment Type: Smart Computer
Model Name: MP10
Brand Name: ZOLON
FCC ID: 2AV5BMP10
Test Standard: FCC 47 CFR Part 2.1093 (refer to section 3.1)
Maximum SAR: Body (1 g@0mm): 1.17 W/kg
Sample Arrival Date: Jan. 22, 2026
Test Date: Mar. 14, 2026 - Mar. 15, 2026
Date of Issue: Apr. 01, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Song Gui**Checked by:** Xu Rui**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Mar. 26, 2026</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Apr. 01, 2026</u>	<u>1. Updated the attachment Ti-EE26010390-AP in Section 8 of the update report.</u> <u>2. Updated the test data in Section 9.1 of the report.</u> <u>3. Updated the calculation results of simultaneous transmission in Section 11 of the report.</u> <u>4. Updated the ANNEX G TUNE-UP PROCEDURE.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Ancillary Equipment	5
2.5	Technical Information	6
2.6	EUT Antenna Location Sketch	7
3	SUMMARY OF TEST RESULT	8
3.1	Test Standards	8
3.2	Device Category and SAR Limit	9
3.3	Test Result Summary	10
3.4	Test Uncertainty	11
4	MEASUREMENT SYSTEM	12
4.1	Specific Absorption Rate (SAR) Definition	12
4.2	DASY SAR System	13

5	SYSTEM VERIFICATION.....	20
5.1	Purpose of System Check.....	20
5.2	System Check Setup.....	20
6	TEST POSITION CONFIGURATIONS.....	21
6.1	Tablet Exposure Condition.....	21
7	MEASUREMENT PROCEDURE.....	22
7.1	Measurement Process Diagram.....	22
7.2	SAR Scan General Requirement	23
7.3	Measurement Procedure.....	24
7.4	Area & Zoom Scan Procedure	24
8	CONDUCTED RF OUTPUT POWER.....	25
9	TEST RESULT	26
9.1	Bluetooth	26
9.2	2.4G WIFI	26
9.3	5G WIFI.....	27
9.4	NFC SAR.....	28
10	SAR Measurement Variability.....	29
11	SIMULTANEOUS TRANSMISSION.....	30
11.1	Simultaneous Transmission Mode Considerations	30
11.2	Body Simultaneous Transmission SAR Evaluation for WLAN Antenna with Bluetooth	30
11.3	Highest Total Exposure Ratio of Simultaneous Transmission	31
12	TEST EQUIPMENTS LIST	32
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	33
ANNEX B	SYSTEM CHECK RESULT	34
ANNEX C	TEST DATA.....	35
ANNEX D	EUT EXTERNAL PHOTOS	35
ANNEX E	SAR TEST SETUP PHOTOS.....	35
ANNEX F	CALIBRATION REPORT	35
ANNEX G	TUNE-UP PROCEDURE	35

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☒ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No. 55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Zolon Technology Co., Ltd.
Address	401, Building 3, Shenzhen Software Park, Maling Community, Yuehai Sub-district, Nanshan District, Shenzhen, Guangdong P.R. China

2.2 Manufacturer Information

Manufacturer	Shenzhen Zolon Technology Co., Ltd.
Address	401, Building 3, Shenzhen Software Park, Maling Community, Yuehai Sub-district, Nanshan District, Shenzhen, Guangdong P.R. China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Smart Computer
Model Name Under Test	MP10
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	EM_T8132_V1.0 L20
Software Version	Android16
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No.	399588
	Serial No.	N/A
	Capacity	8000mAh
	Rated Voltage	3.85 V
	Limit Charge Voltage	4.4 V


2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n and 802.11ac NFC, GPS, GLONASS, BDS, Galileo, FM
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WLAN; Bluetooth	
Frequency Range	802.11b/g/n(HT20/HT40)	2412 ~ 2462 MHz
	802.11a	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11n(HT20/HT40)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11ac (VHT20/VHT40/VHT80)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
Antenna Type	Bluetooth	2400 ~ 2483.5 MHz
	NFC	13.56 MHz
	WLAN	FPC
Antenna Type	Bluetooth	FPC
	NFC	FPC
	WLAN	FPC
Exposure Category	General Population/Uncontrolled exposure	
EUT Type	Portable Device	

2.6 EUT Antenna Location Sketch



Antenna	Support Bands
Ant.0	WIFI2.4G&5G&Bluetooth

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI/IEEE C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01
4	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
5	KDB 865664 D02 v01r02	RF Exposure Reporting
6	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
7	KDB 616217 D04 v01r02	SAR for laptop and tablets

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR

Equipment Class	Band	Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)
		Body	Body
		(0mm)	(0mm)
		1g SAR	1g SAR
DTS	2.4G WIFI	1.04	1.17
NII	5.3G WIFI	1.12	
	5.6G WIFI	1.17	
	5.8G WIFI	1.12	
DSS	Bluetooth	0.26	
Limit (W/kg)		1.60	1.60
Verdict		Pass	

3.3.2 Highest Simultaneous Transmission SAR Values

Equipment Class	Maximum Simultaneous Transmission SAR
	(W/kg)
	Body1g (0mm)
NII	1.37
DSS	1.37
Limit (W/Kg)	1.60
Verdict	Pass

Note: The simultaneous transmission SAR detail please refer to section 11.

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.17 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$\text{SAR} = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)

E-Field Probe Calibration Process

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1/2 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω m
- The Inputs: Symmetrical and Floating
- Common Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left hand
- Right hand
- Flat phantom



4.2.6 Device Holder


The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS

6.1 Tablet Exposure Condition

This DUT was tested in five different positions. They are back side, left edge, right edge, top edge and bottom edge in these positions, the surface of DUT is touching with phantom 0mm.





Fig Illustration for Lap-touching Position

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm
Note:				
1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

Please refer the document “Ti-EE26010390-AP.pdf”.

9 TEST RESULT

9.1 Bluetooth

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Body														
Ant.0	DH5	Back Side	0	39	2441	-0.09	0.085	5.31	6.00	1.172	76.67	1.304	0.130	/
		Left Edge	0	39	2441	-0.08	0.003	5.31	6.00	1.172	76.67	1.304	0.005	/
		Right Edge	0	39	2441	-0.16	0.002	5.31	6.00	1.172	76.67	1.304	0.003	/
		Top Edge	0	390	2441	-0.13	0.022	5.31	6.00	1.172	76.67	1.304	0.034	/
		Bottom Edge	0	39	2441	0.12	0.004	5.31	6.00	1.172	76.67	1.304	0.006	/
		Back Side	0	0	2402	-0.12	0.070	4.13	6.00	1.537	76.67	1.304	0.140	/
		Back Side	0	78	2480	0.05	0.079	5.05	6.00	1.245	76.67	1.304	0.128	/
	BLE-1M	Back Side	0	19	2440	-0.04	0.131	7.26	8.00	1.186	60.81	1.644	0.255	1#
		Left Edge	0	19	2440	-0.06	0.004	7.26	8.00	1.186	60.81	1.644	0.008	/
		Right Edge	0	19	2440	0.06	0.003	7.26	8.00	1.186	60.81	1.644	0.006	/
		Top Edge	0	19	2440	-0.01	0.019	7.26	8.00	1.186	60.81	1.644	0.037	/
		Bottom Edge	0	19	2440	-0.14	0.003	7.26	8.00	1.186	60.81	1.644	0.006	/
		Back Side	0	0	2402	0.04	0.098	6.07	8.00	1.560	60.81	1.644	0.251	/
		Back Side	0	39	2480	-0.03	0.119	6.91	8.00	1.285	60.81	1.644	0.252	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

9.2 2.4G WIFI

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Body														
Ant.0	802.11b	Back Side	0	1	2412	0.00	0.811	14.21	14.50	1.069	98.05	1.020	0.884	/
		Left Edge	0	1	2412	-0.19	0.003	14.21	14.50	1.069	98.05	1.020	0.003	/
		Right Edge	0	1	2412	0.08	0.005	14.21	14.50	1.069	98.05	1.020	0.005	/
		Top Edge	0	1	2412	-0.15	0.269	14.21	14.50	1.069	98.05	1.020	0.293	/
		Bottom Edge	0	1	2412	0.15	0.002	14.21	14.50	1.069	98.05	1.020	0.002	/
		Back Side	0	6	2437	0.09	0.910	14.02	14.50	1.117	98.05	1.020	1.037	2#
		Back Side	0	11	2462	0.07	0.817	14.01	14.50	1.119	98.05	1.020	0.933	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

9.3 5G WIFI

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Body-5.3G														
Ant.0	802.11a	Back Side	0	60	5300	0.03	0.882	15.61	16.00	1.094	91.63	1.091	1.053	/
		Left Edge	0	60	5300	0.19	0.002	15.61	16.00	1.094	91.63	1.091	0.002	/
		Right Edge	0	60	5300	0.02	0.005	15.61	16.00	1.094	91.63	1.091	0.006	/
		Top Edge	0	60	5300	-0.03	0.496	15.61	16.00	1.094	91.63	1.091	0.592	/
		Bottom Edge	0	60	5300	-0.19	0.002	15.61	16.00	1.094	91.63	1.091	0.002	/
		Back Side	0	52	5260	0.03	0.925	15.57	16.00	1.104	91.63	1.091	1.115	3#
		Back Side	0	64	5320	-0.11	0.889	15.61	16.00	1.094	91.63	1.091	1.061	/
Body-5.6G														
Ant.0	802.11a	Back Side	0	140	5700	0.02	0.599	15.78	16.00	1.052	91.63	1.091	0.688	/
		Left Edge	0	140	5700	0.07	0.005	15.78	16.00	1.052	91.63	1.091	0.006	/
		Right Edge	0	140	5700	-0.02	0.003	15.78	16.00	1.052	91.63	1.091	0.003	/
		Top Edge	0	140	5700	0.09	1.020	15.78	16.00	1.052	91.63	1.091	1.171	4#
		Bottom Edge	0	140	5700	0.10	0.003	15.78	16.00	1.052	91.63	1.091	0.003	/
		Top Edge	0	100	5500	0.18	0.737	15.47	16.00	1.130	91.63	1.091	0.909	/
		Top Edge	0	116	5580	-0.04	0.895	15.55	16.00	1.109	91.63	1.091	1.083	/
Body-5.8G														
Ant.0	802.11a	Back Side	0	157	5785	-0.19	0.640	13.31	14.00	1.172	91.63	1.091	0.819	/
		Left Edge	0	157	5785	-0.02	0.113	13.31	14.00	1.172	91.63	1.091	0.145	/
		Right Edge	0	157	5785	0.05	0.009	13.31	14.00	1.172	91.63	1.091	0.012	/
		Top Edge	0	157	5785	-0.05	0.717	13.31	14.00	1.172	91.63	1.091	0.917	/
		Bottom Edge	0	157	5785	0.08	0.002	13.31	14.00	1.172	91.63	1.091	0.003	/
		Top Edge	0	149	5745	0.02	0.686	13.26	14.00	1.186	91.63	1.091	0.888	/
		Top Edge	0	165	5825	-0.05	0.815	13.02	14.00	1.253	91.63	1.091	1.115	5#
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

9.4 NFC SAR

According to the ANSI C63.10 clause 11.12.2.2:

The value of maximum peak output power is according to the method described in ANSI C63.10 clause 11.12.2.2 General procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies $\leq$ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies $>$ 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship: $E = \text{EIRP} - 20\log D + 104.8$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

Mode	f (MHz)	Max. E-Field strength (dB μ V/m)	D (m)	Ground reflection factor (dB)	ERP (dBm)
NFC (13.56MHz)	13.56	50.73	3	6	-38.53
Note: 1. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies $\leq$ 30 MHz). 2. ERP = $50.73 + 20 \cdot \log(3) - 104.8 + 6 = -38.53$ (dBm)					

According to the FCC KDB 447498 D04

Estimated SAR: SAR test = $1.6 \cdot P_{\text{ant}} / P_{\text{th}}$ [W/kg]

Estimated SAR	$1.6 \cdot P_{\text{ant}} / P_{\text{th}}$ [W/kg]		
P _{meas} (dBm)	-38.53	P _{meas} (mW)	0.00014
P _{th} (mW)	443.13		
NFC Estimated 1g SAR [W/kg]	<0.001		

10 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	RF Exposure Conditions	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Largest to Smallest SAR Ratio
2437	802.11b	Body	Back Side	0.910	Yes	0.901	1.01
2462	802.11b	Body	Back Side	0.817	Yes	0.796	1.03
5300	802.11a	Body	Back Side	0.882	Yes	0.866	1.02
5260	802.11a	Body	Back Side	0.925	Yes	0.904	1.02
5320	802.11a	Body	Back Side	0.889	Yes	0.851	1.04
5700	802.11a	Body	Top Edge	1.020	Yes	0.986	1.03
5580	802.11a	Body	Top Edge	0.895	Yes	0.883	1.01
5825	802.11a	Body	Top Edge	0.815	Yes	0.792	1.03

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is < 1.20 , the second repeated measurement is not required.

11 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According to KDB 447498 D04, simultaneous transmission:

- a) $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$ (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.
SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

11.1 Simultaneous Transmission Mode Considerations

No.	Simultaneous Tx Combination	Body
1	5GWIFI+BT	Yes

Note:

- WiFi 2.4G and Bluetooth share the same antenna, and can't transmit simultaneously.
- The maximum SAR summation is calculated based on the same configuration and test position.

11.2 Body Simultaneous Transmission SAR Evaluation for WLAN Antenna with Bluetooth

Position	Stand alone SAR		SUM SAR
	1	2	
	Max.5GWIFI	BT	WIFI5G+BT (1+2)
Back Side 0mm	1.115	0.255	1.370
Left Edge 0mm	0.145	0.008	0.153
Right Edge 0mm	0.012	0.006	0.018
Top Edge 0mm	1.171	0.037	1.208
Bottom Edge 0mm	0.003	0.006	0.009

Note:

1: The highest Summed 1g SAR is W/Kg 1.37 < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.

11.3 Highest Total Exposure Ratio of Simultaneous Transmission

NFC multi-transmit requires the use of the TER formula:

$$TER = \sum_{k=1}^{N_s} \left(\frac{SAR_k}{SAR_{lim}} \right) + \sum_{k=1}^{N_f} \left(\frac{MPE_{field, k}}{MPE_{field, lim}} \right)^2 + \sum_{k=1}^{N_{PD}} \left(\frac{MPE_{PD, k}}{MPE_{PD, lim}} \right)$$

The maximum SAR value transmitted simultaneously is 0.001 [watts per kilogram], and the worst $TER = (1.37 + 0.001) / 1.6 = 0.857 < 1$, meeting the simultaneous transmission SAR emission standard of NFC.

12 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY5	52.8.8.1222	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2024/05/07	2027/05/06
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2024/05/09	2027/05/08
Data Acquisition Electronics	Speag	DAE4	SN: 1711	2025/11/11	2026/11/10
E-Field Probe	Speag	EX3DV4	SN: 7510	2025/11/11	2026/11/10
Signal Generator	Keysight	N5173B	MY62150163	2025/07/15	2026/07/14
Power Meter	R&S	NRVD-B2	835843/014	2025/07/15	2026/07/14
Power Sensor	R&S	NRV-Z4	100381	2025/07/15	2026/07/14
Power Sensor	R&S	NRV-Z2	100211	2025/07/15	2026/07/14
Network Analyzer	Agilent	E5071C	MY46103472	2025/08/13	2026/08/12
Thermometer	Elitech	RC-4HC	EF7216002985	2025/10/30	2026/10/29
Thermometer	Elitech	RC-4HC	EF720B004811	2025/09/16	2026/09/15
Power Amplifier	Mini-Circuits	ZVA-183W-S+	932502132	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	SAM	SN: 1576	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5 Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2026.03.14	Head	2450	21.6	1.84	38.52	1.80	39.20	2.22	-1.73
2026.03.15	Head	5250	21.8	4.56	36.85	4.71	35.93	-3.18	2.56
2026.03.15	Head	5600	21.8	5.03	35.42	5.07	35.53	-0.79	-0.31
2026.03.15	Head	5750	21.8	5.11	35.86	5.22	35.36	-2.11	1.41
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2026.03.14	Head	2450	100	5.210	52.10	52.60	-0.95
2026.03.15	Head	5250	100	7.850	78.50	77.70	1.03
2026.03.15	Head	5600	100	8.060	80.60	81.30	-0.86
2026.03.15	Head	5750	100	7.730	77.30	77.60	-0.39

Note 1: The tolerance limit of System validation $\pm 10\%$.

Note 2: Please refer the document "Ti-EE26010390-ASC.pdf".

ANNEX C TEST DATA

Please refer the document “Ti-EE26010390-ATD.pdf”.

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “Ti-EE26010390-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “Ti-EE26010390-AS.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “Ti-EE26010390-AC.pdf”.

ANNEX G TUNE-UP PROCEDURE

Please refer the document “Ti-EE26010390-AT.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--