



MPE Calculation

Applicant:	Empowerment Technologies Inc.
Address:	Unit 2, 590 York Road, Niagara on the Lake, ON, Canada L0S 1J0
Product:	DEFENDER
FCC ID:	2AV6B-IP8DSCB1
Model No.:	IP8MDSCB1, IP8MDSCB2, IP8MDSCB3, IP8MDSCB4, IP8MDSCB1-64, IP8MDSCB2-64, IP8MDSCB3-64, IP8MDSCB4-64, EBIP8MDSCB2-128, EBIP8MDSCB1-128
Reference RF report #	709502501241-00B

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1,500	/	/	f/1500	30
1,500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4 \pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);



Calculated Data: Dipole antenna

Maximum peak output power at antenna input terminal (dBm):	18.81
Maximum peak output power at antenna input terminal (mW):	76.03
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	1.8
Maximum Antenna Gain (numeric):	1.5136
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.02289
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.00

The max power density 0.02289 (mW/cm²) < 1 (mW/cm²)

Result: Compliant

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG

Wenqiang LU

Chengjie GUO

EMC Section Manager

EMC Project Engineer

EMC Test Engineer

Date: 2025-04-14

Date: 2025-04-14

Date: 2025-04-14

-----End of Test Report-----