



TEST REPORT

No. I20D00056-EMC01

For

**Client : NetEase Youdao Information Technology
(Beijing) Co., Ltd.**

Production : Youdao Translator 3

Model Name : YDE031,YDE032

Brand Name: youdao

FCC ID: 2AV6G-YDE031

Hardware Version: V00A

Software Version: YDE031.0.0.2

Issued date: 2020-07-06

NOTE

1. The test results in this test report relate only to the devices specified in this report.
2. This report shall not be reproduced except in full without the written approval of East China Institute of Telecommunications
3. The measurement uncertainty is not taken into account when deciding conformity, and the results of measurement (or the average of measurement results) are directly used as the criterion for the stating conformity.

Test Laboratory:

East China Institute of Telecommunications

Add: Building 4, No. 766, Jingang Road, Pudong New District, Shanghai

Tel: +862163843300

E-Mail: welcome@ecit.org.cn

Revision Version

Report Number	Revision	Date	Memo
I20D00056-EMC01	00	2020-07-06	Initial creation of test report

CONTENTS

1. TEST LABORATORY	6
1.1. TESTING LOCATION	6
1.2. TESTING ENVIRONMENT	6
1.3. PROJECT DATA	6
1.4. SIGNATURE	6
2. CLIENT INFORMATION	7
2.1. APPLICANT INFORMATION	7
2.2. MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	8
4. REFERENCE DOCUMENTS.....	9
4.1 REFERENCE DOCUMENTS FOR TESTING	9
5. TEST RESULTS.....	10
5.1 SUMMARY OF TEST RESULTS	10
5.2 STATEMENTS.....	10
6. TEST EQUIPMENT UTILIZED	11
6.1 RADIATED EMISSION EQUIPMENT LIST	11
6.1 AC CONDUCTED EMISSION EQUIPMENT LIST	11
7. SYSTEM CONFIGURATION DURING TEST	12
7.1 TEST MODE.....	12
7.2 CONNECTION DIAGRAM OF TEST SYSTEM.....	14
8. MEASUREMENT RESULTS	15
8.1 RADIATED EMISSION 30MHZ-18GHZ.....	15

8.2 AC CONDUCTED EMISSION.....	28
ANNEX A ACCREDITATION CERTIFICATE	33

1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	Building 4, No. 766, Jingang Road, Pudong New District, Shanghai
Postal Code:	201206
Telephone:	(+86)-021-63843300
FCC registration No:	958356


1.2. Testing Environment

Normal Temperature:	15-35℃
Relative Humidity:	30-60% RH
Supply Voltage	120V/60Hz

1.3. Project data

Project Leader:	Xu Yuting
Testing Start Date:	2020-05-11
Testing End Date:	2020-06-10


1.4. Signature



Lu Huifang
(Prepared this test report)



You Jinjun
(Reviewed this test report)



Zheng Zhongbin
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name	NetEase Youdao Information Technology (Beijing) Co., Ltd.
Address	No.7 Building,Zhongguancun Software Park West,No.10 Xibeiwang East RD,Haidian District,Beijing,PRC
Telephone	13810968741
Postcode	100084

2.2. Manufacturer Information

Company Name	NetEase Youdao Information Technology (Beijing) Co., Ltd.
Address	No.7 Building,Zhongguancun Software Park West,No.10 Xibeiwang East RD,Haidian District,Beijing,PRC
Telephone	13810968741
Postcode	100084

3. Equipment under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Product Name	Youdao Translator 3
Model name	YDE031,YDE032
UMTS Frequency Band	Band I/ II/ VI/ V/ VI/ VIII/ XIX
LTE Frequency Band	LTE1/2/3/4/5/7/8/9/12/13/17/18/19/20/25/26/28/66/34/38/39/40/41
Additional Communication Function	BT4.2, 5.0;WLAN 802.11a,b,g,n,ac;

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N11 (Main supply_Version 1)	863589030041535	V00A	YDE031.0.0.2	2020-05-09
N12 (Main supply_Version 3)	863589030038028	V00A	YDE031.0.0.2	2020-05-27
N22 (Secondary supply_Version 2)	863589030036766	V00A	YDE031.0.0.2	2020-05-09
N14 (Secondary supply_Version 4)	863589030037335	V00A	YDE031.0.0.2	2020-06-04

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	SN
UA04	USB Cable	WM86	NA
AE1	Notebook PC	DELL Latitude E6510	NA
AE2	Desktop PC	OptiPlex 790 DT	X8RP1 A01 APCC
AE3	LAN Cable	NA	NA
AE4	VGA Cable	NA	NA
AE5	RS232 Cable	NA	NA
AE6	Keyboard	KB212-B	CN-0Y88XT-65890-12I-005Q-A00
AE7	Mouse	MS111-P	CN-011D3V-71581-19J-1A64
AE8	Monitor	Dell E1709Wc	NA
AE9	Adapter	LSD-D05V200E	NA

*AE ID: is used to identify the test sample in the lab internally.

*The AE were provided by the lab.

4. Reference Documents

4.1 Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	2020/3/31
ANSI C63.4	Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

5. Test Results

5.1 Summary of Test Results

Items	Test List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	Pass
2	AC Conducted Emission	15.107(a)	Pass

5.2 Statements

The YDE031,YDE032, supporting WCDMA/LTE.etc, manufactured by NetEase Youdao Information Technology (Beijing) Co., Ltd. is a new product for testing. ECIT only performed test cases which identified with Pass/Fail/Inc result in section 5.1.

ECIT has verified that the compliance of the tested device specified in section 3 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 4 of this test report.

Note: This project has four configuration sample, N11(Main supply_Version 1), N12(Main supply_Version 3), N22(Secondary supply_Version 2), and N14(Secondary supply_Version 4). The difference between Main supply and Secondary supply is Memory. We mainly tested N11 sample, and other sample versions tested N11 sample worst mode.

6. Test Equipment Utilized

6.1 Radiated Emission Equipment list

Item	Instrument Name	Type	Serial Number	Manufacturer	Cal. Date	Cal. interval
1	Universal Radio Communication Tester	CMU200	123126	R&S	2020-05-10	1 year
2	Universal Radio Communication Tester	CMW500	104178	R&S	2020-05-10	1 year
3	Test Receiver	ESU40	100307	R&S	2020-05-10	1 year
4	Trilog Antenna	VULB9163	VULB9163-515	Schwarzbeck	2020-02-28	2 years
5	Double Ridged Guide	ETS-3117	00135890	ETS	2020-02-28	2 years
6	EMI Test Software	EMC32 V9.15	NA	R&S	NA	NA

6.1 AC Conducted Emission Equipment list

Item	Instrument Name	Type	Serial Number	Manufacturer	Cal. Date	Cal. interval
1	Universal Radio Communication Tester	CMU200	123123	R&S	2020-05-10	1 year
2	Universal Radio Communication Tester	CMW500	104178	R&S	2020-05-10	1 year
3	Test Receiver	ESCI	101235	R&S	2020-05-10	1 year
4	2-Line V-Network	ENV216	101380	R&S	2020-05-10	1 year
5	EMI Test Software	EMC32 V10.35.02	NA	R&S	NA	NA

7. System Configuration during Test

7.1 Test Mode

N11 (Main supply_Version 1):

Test Item	Function Type
AC Conducted Emission	Mode 1: Adapter charging <Figure 2> Mode 2: USB cable (Data Link with PC) <Figure 1> Mode 3: LTE band 5 receiver <Figure 2>
Radiated Emission	Mode 1: Adapter charging <Figure 2> Mode 2: USB cable (Data Link with PC) <Figure 1> Mode 3: LTE band 5 receiver <Figure 2>
Remark: 1. All test modes are performed, only the worst cases test data are recorded in this report. 2. After laboratory verification, LTE band 5 is the worst mode among all receiving modes of 3G/4G and is recorded in the report. 3. Data Link with PC means data application transferred mode between EUT and PC.	

N12 (Main supply_Version 3):

Test Item	Function Type
AC Conducted Emission	Mode 1: Adapter charging <Figure 2>
Radiated Emission	Mode 2: USB cable (Data Link with PC) <Figure 1>
Remark: 1. All test modes are performed, only the worst cases test data are recorded in this report. 2. Data Link with PC means data application transferred mode between EUT and PC.	

N22 (Secondary supply_Version 2):


Test Item	Function Type
AC Conducted Emission	Mode 1: Adapter charging <Figure 2>
Radiated Emission	Mode 2: USB cable (Data Link with PC) <Figure 1>
Remark: 1. All test modes are performed, only the worst cases test data are recorded in this report. 2. Data Link with PC means data application transferred mode between EUT and PC.	

N14 (Secondary supply_Version 4):


Test Item	Function Type
AC Conducted Emission	Mode 1: Adapter charging <Figure 2>

Radiated Emission	Mode 2: USB cable (Data Link with PC) <Figure 1>
Remark: 1. All test modes are performed, only the worst cases test data are recorded in this report. 2. Data Link with PC means data application transferred mode between EUT and PC.	

7.2 Connection Diagram of Test System



<Figure 1>



<Figure 2>

8. Measurement Results

Only the worst test result was shown in this report.

8.1 Radiated Emission 30MHz-18GHz

Method of Measurement

For 30MHz -1000MHz, the EUT was placed on the top of a rotating 0.8m table above the ground at a semi-anechoic chamber. The distance between the EUT and the received antenna was 3 meters. The table was rotated 360 degree and the received antenna mounted on a variable-height antenna tower was varied from 1m to 4m to find the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set during the measurement. Tested in accordance with the procedures of ANSI C63.4-2014, section 8.3.

For 1000MHz-18000MHz, The maximal emission value was acquired by adjusting the antenna height, The table was rotated 360 degree to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set during the measurement.

Limits for Radiated Emission at a measuring distance of 3m

Frequency Range (MHz)	Quasi-Peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Frequency Range (MHz)	Peak (dBuV/m)	Average (dBuV/m)
Above 1000	74	54

Test conditions

Frequency Range (MHz)	RBW/VBW	Sweep Time (s)
30-1000	120kHz/300kHz	Auto
1000-18000	1MHz/3MHz	Auto

Uncertainty Measurement

The measurement uncertainty (30MHz-1000MHz) is 4.82 dB (k=2).


The measurement uncertainty (1000MHz-18000MHz) is 5.08 dB (k=2).

Test Results


Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier, the Emissions in the frequency band 18GHz-40GHz is more than 20dB below the limit are not report.

N11 (Main supply_Version 1):

Mode 2: USB cable (Data Link with PC) <Figure 1>



Mode 2: USB cable (Data Link with PC) <Figure 1>




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Band width	Height	Po l	Azimu th	Corr. (dB)
2985.600000	38.43	---	74.00	35.57	1.0	1000.	100.0	H	302.0	3.3
2985.600000	---	27.48	54.00	26.52	1.0	1000.	100.0	H	302.0	3.3
4666.200000	38.15	---	74.00	35.85	1.0	1000.	100.0	H	123.0	2.2
4666.200000	---	29.16	54.00	24.84	1.0	1000.	100.0	H	123.0	2.2
7896.000000	41.84	---	74.00	32.16	1.0	1000.	100.0	H	1.0	5.2
7896.000000	---	31.41	54.00	22.59	1.0	1000.	100.0	H	1.0	5.2
9224.400000	---	30.77	54.00	23.23	1.0	1000.	200.0	H	110.0	5.5
9224.400000	40.94	---	74.00	33.06	1.0	1000.	200.0	H	110.0	5.5
11770.400000	---	33.19	54.00	20.81	1.0	1000.	200.0	H	254.0	10.5
11770.400000	43.35	---	74.00	30.65	1.0	1000.	200.0	H	254.0	10.5
14985.000000	48.05	---	74.00	25.95	1.0	1000.	100.0	H	187.0	14.5
14985.000000	---	35.81	54.00	18.19	1.0	1000.	100.0	H	187.0	3.3

Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Bandwi dth	Heigh t	Po l	Azimu th	Corr. (dB)
2988.200000	37.44	---	74.00	36.56	1.0	1000.00	200.0	V	145.0	3.4
2988.200000	---	26.79	54.00	27.21	1.0	1000.00	200.0	V	145.0	3.4
4795.400000	---	29.01	54.00	24.99	1.0	1000.00	200.0	V	80.0	2.6
4795.400000	39.68	---	74.00	34.32	1.0	1000.00	200.0	V	80.0	2.6
7970.400000	40.81	---	74.00	33.19	1.0	1000.00	100.0	V	175.0	5.3
7970.400000	---	31.36	54.00	22.64	1.0	1000.00	100.0	V	175.0	5.3
10509.200000	---	31.32	54.00	22.68	1.0	1000.00	100.0	V	124.0	7.9
10509.200000	41.84	---	74.00	32.16	1.0	1000.00	100.0	V	124.0	7.9
12879.000000	---	34.40	54.00	19.60	1.0	1000.00	100.0	V	233.0	12.0
12879.000000	44.43	---	74.00	29.57	1.0	1000.00	100.0	V	233.0	12.0
17290.400000	48.85	---	74.00	25.15	1.0	1000.00	200.0	V	216.0	18.5
17290.400000	---	38.42	54.00	15.58	1.0	1000.00	200.0	V	216.0	18.5


Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

N12 (Main supply_Version 3):

Mode 2: USB cable (Data Link with PC) <Figure 1>

Frequency Range: 30MHz – 1GHz




Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
78.355848	5.46	40.00	34.54	1000.0	120.000	103.4	V	179.0	-19.0
105.911357	26.28	43.50	17.22	1000.0	120.000	225.0	H	0.0	-15.8
159.901752	26.85	43.50	16.65	1000.0	120.000	175.0	H	29.0	-17.2
383.998397	33.52	46.00	12.48	1000.0	120.000	100.0	H	308.0	-9.0
479.972605	33.25	46.00	12.75	1000.0	120.000	100.0	V	16.0	-8.1
726.116357	26.31	46.00	19.69	1000.0	120.000	103.4	H	216.0	-3.4

Note:

- 1.Emission level(QP)=Raw value by receiver + Corr(Antenna factor + cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

Mode 2: USB cable (Data Link with PC) <Figure 1>




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Band width	Height	Po l	Azimu th	Corr. (dB)
2988.000000	37.90	---	74.00	36.10	1.0	1000.	100.0	H	99.0	3.4
2988.000000	---	26.70	54.00	27.30	1.0	1000.	100.0	H	99.0	3.4
4301.200000	---	28.62	54.00	25.38	1.0	1000.	100.0	H	222.0	1.7
4301.200000	40.73	---	74.00	33.27	1.0	1000.	100.0	H	222.0	1.7
5365.800000	40.25	---	74.00	33.75	1.0	1000.	200.0	H	0.0	3.1
5365.800000	---	30.18	54.00	23.82	1.0	1000.	200.0	H	0.0	3.1
7049.200000	41.92	---	74.00	32.08	1.0	1000.	200.0	H	332.0	5.0
7049.200000	---	30.84	54.00	23.16	1.0	1000.	200.0	H	332.0	5.0
9271.800000	---	30.22	54.00	23.78	1.0	1000.	200.0	H	288.0	5.7
9271.800000	40.02	---	74.00	33.98	1.0	1000.	200.0	H	288.0	5.7
11689.200000	43.22	---	74.00	30.78	1.0	1000.	100.0	H	258.0	10.4
11689.200000	---	33.74	54.00	20.26	1.0	1000.	100.0	H	258.0	10.4

Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level



Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time	Bandwidth	Height	Po	Azimuth	Corr. (dB)
2996.200000	---	26.95	54.00	27.05	1.0	1000.00	200.0	V	348.0	3.2
2996.200000	39.13	---	74.00	34.87	1.0	1000.00	200.0	V	348.0	3.2
3600.200000	---	28.13	54.00	25.87	1.0	1000.00	200.0	V	320.0	1.9
3600.200000	38.15	---	74.00	35.85	1.0	1000.00	200.0	V	320.0	1.9
4195.200000	---	28.31	54.00	25.69	1.0	1000.00	100.0	V	1.0	1.4
4195.200000	37.12	---	74.00	36.88	1.0	1000.00	100.0	V	1.0	1.4
5053.000000	---	28.68	54.00	25.32	1.0	1000.00	200.0	V	192.0	6.1
5053.000000	38.77	---	74.00	35.23	1.0	1000.00	200.0	V	192.0	6.1
6394.800000	39.83	---	74.00	34.17	1.0	1000.00	200.0	V	284.0	3.5
6394.800000	---	29.65	54.00	24.35	1.0	1000.00	200.0	V	284.0	3.5
8040.600000	42.19	---	74.00	31.81	1.0	1000.00	100.0	V	61.0	5.3
8040.600000	---	31.32	54.00	22.68	1.0	1000.00	100.0	V	61.0	5.3


Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

N22 (Secondary supply_Version 2):

Mode 2: USB cable (Data Link with PC) <Figure 1>

Frequency Range: 30MHz – 1GHz




Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
104.321861	22.07	43.50	21.43	1000.0	120.000	120.7	H	324.0	-15.8
144.050011	16.23	43.50	27.27	1000.0	120.000	125.0	H	137.0	-17.8
166.232149	24.97	43.50	18.53	1000.0	120.000	125.0	H	96.0	-16.7
384.119115	14.08	46.00	31.92	1000.0	120.000	100.0	H	8.0	-9.0
479.984272	30.06	46.00	15.94	1000.0	120.000	175.0	H	244.0	-8.1
556.983120	22.68	46.00	23.32	1000.0	120.000	175.0	H	62.0	-5.2

Note:

- 1.Emission level(QP)=Raw value by receiver + Corr(Antenna factor + cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

Mode 2: USB cable (Data Link with PC) <Figure 1>




Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Band width	Height	Po l	Azimu th	Corr. (dB)
2985.600000	37.73	---	74.00	36.27	1.0	1000.	199.9	H	95.0	3.3
2985.600000	---	27.32	54.00	26.68	1.0	1000.	199.9	H	95.0	3.3
6698.000000	---	30.61	54.00	23.39	1.0	1000.	100.1	H	279.0	4.6
6698.000000	41.02	---	74.00	32.98	1.0	1000.	100.1	H	279.0	4.6
13271.400000	45.23	---	74.00	28.77	1.0	1000.	100.1	H	279.0	11.9
13271.400000	---	34.70	54.00	19.30	1.0	1000.	100.1	H	279.0	11.9
14986.800000	46.65	---	74.00	27.35	1.0	1000.	199.9	H	353.0	14.5
14986.800000	---	36.11	54.00	17.89	1.0	1000.	199.9	H	353.0	14.5
16813.800000	48.18	---	74.00	25.82	1.0	1000.	199.9	H	353.0	18.0
16813.800000	---	38.43	54.00	15.57	1.0	1000.	199.9	H	353.0	18.0
17674.200000	---	38.18	54.00	15.82	1.0	1000.	199.9	H	59.0	18.7
17674.200000	48.40	---	74.00	25.60	1.0	1000.	199.9	H	59.0	18.7

Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level



Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time	Bandwi dth	Heigh t	Po l	Azimu th	Corr. (dB)
2989.600000	37.00	---	74.00	37.00	1.0	1000.00	199.9	V	147.0	3.4
2989.600000	---	26.24	54.00	27.76	1.0	1000.00	199.9	V	147.0	3.4
4474.400000	---	28.64	54.00	25.36	1.0	1000.00	199.9	V	203.0	2.2
4474.400000	38.29	---	74.00	35.71	1.0	1000.00	199.9	V	203.0	2.2
7984.000000	---	31.02	54.00	22.98	1.0	1000.00	199.9	V	154.0	5.3
7984.000000	40.92	---	74.00	33.08	1.0	1000.00	199.9	V	154.0	5.3
15232.800000	47.72	---	74.00	26.28	1.0	1000.00	199.9	V	83.0	15.1
15232.800000	---	36.06	54.00	17.94	1.0	1000.00	199.9	V	83.0	15.1
16979.600000	49.16	---	74.00	24.84	1.0	1000.00	100.1	V	14.0	18.2
16979.600000	---	38.91	54.00	15.09	1.0	1000.00	100.1	V	14.0	18.2
17646.200000	48.08	---	74.00	25.92	1.0	1000.00	100.1	V	0.0	18.6
17646.200000	---	38.07	54.00	15.93	1.0	1000.00	100.1	V	0.0	18.6


Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

N14 (Secondary supply_Version 4):

Mode 2: USB cable (Data Link with PC) <Figure 1>

Frequency Range: 30MHz – 1GHz




Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
36.014872	24.11	40.00	15.89	1000.0	120.000	100.0	V	153.0	-16.6
49.430312	9.97	40.00	30.03	1000.0	120.000	100.0	V	-17.0	-15.5
102.955968	16.31	43.50	27.19	1000.0	120.000	181.4	H	172.0	-15.8
320.111331	15.99	46.00	30.01	1000.0	120.000	114.2	V	140.0	-10.8
572.889003	18.39	46.00	27.61	1000.0	120.000	175.0	V	228.0	-4.4
796.450403	26.95	46.00	19.05	1000.0	120.000	100.0	H	98.0	-2.1

Note:

- 1.Emission level(QP)=Raw value by receiver + Corr(Antenna factor + cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

Mode 2: USB cable (Data Link with PC) <Figure 1>




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Band width	Height	Po l	Azimu th	Corr. (dB)
2999.200000	37.90	---	74.00	36.10	1.0	1000.	199.9	H	298.0	3.2
2999.200000	---	27.34	54.00	26.66	1.0	1000.	199.9	H	298.0	3.2
4050.400000	39.30	---	74.00	34.70	1.0	1000.	100.1	H	211.0	1.7
4050.400000	---	28.70	54.00	25.30	1.0	1000.	100.1	H	211.0	1.7
5521.800000	41.48	---	74.00	32.52	1.0	1000.	199.9	H	256.0	3.2
5521.800000	---	30.80	54.00	23.20	1.0	1000.	199.9	H	256.0	3.2
7947.000000	---	31.40	54.00	22.60	1.0	1000.	100.1	H	182.0	5.4
7947.000000	41.58	---	74.00	32.42	1.0	1000.	100.1	H	182.0	5.4
13712.800000	44.77	---	74.00	29.23	1.0	1000.	100.1	H	68.0	12.1
13712.800000	---	34.70	54.00	19.30	1.0	1000.	100.1	H	68.0	12.1
2999.200000	37.90	---	74.00	36.10	1.0	1000.	199.9	H	298.0	3.2
2999.200000	---	27.34	54.00	26.66	1.0	1000.	199.9	H	298.0	3.2

Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level



Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time	Bandwi dth	Heigh t	Po l	Azimu th	Corr. (dB)
2986.000000	---	27.22	54.00	26.78	1.0	1000.00	100.1	V	291.0	3.3
2986.000000	37.13	---	74.00	36.87	1.0	1000.00	100.1	V	291.0	3.3
4226.000000	---	28.66	54.00	25.34	1.0	1000.00	100.1	V	82.0	1.7
4226.000000	38.38	---	74.00	35.62	1.0	1000.00	100.1	V	82.0	1.7
4994.000000	38.20	---	74.00	35.80	1.0	1000.00	100.1	V	24.0	5.2
4994.000000	---	27.63	54.00	26.37	1.0	1000.00	100.1	V	24.0	5.2
7851.400000	---	31.14	54.00	22.86	1.0	1000.00	199.9	V	156.0	4.7
7851.400000	40.83	---	74.00	33.17	1.0	1000.00	199.9	V	156.0	4.7
11675.600000	---	33.50	54.00	20.50	1.0	1000.00	100.1	V	219.0	10.4
11675.600000	43.45	---	74.00	30.55	1.0	1000.00	100.1	V	219.0	10.4
15223.200000	46.50	---	74.00	27.50	1.0	1000.00	100.1	V	118.0	15.0
15223.200000	---	36.17	54.00	17.83	1.0	1000.00	100.1	V	118.0	15.0

Note:

- 1.Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.

8.2 AC Conducted Emission

Method of Measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies with the band 150 kHz to 30MHz shall not exceed the limits. Both lines of the power mains connected to the EUT were checked for maximum conducted interference. Tested in accordance with the procedures of ANSI C63.4-2014, section 7.3

Limit of Conducted Emission

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

Test Condition in Charging Mode

Voltage (V)	Frequency (Hz)	RBW	Sweep Time (s)
120	60	9 kHz	Auto


Uncertainty Measurement

The measurement uncertainty is 3.58dB (k=2).

Test Results

N11 (Main supply_Version 1):

Mode 1: Adapter charging <Figure 2>



Frequency (MHz)	QuasiPeak (dB µ V)	Average (dB µ V)	Limit (dB µ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.161194	---	26.42	55.40	28.98	15000.	9.000	L1	ON	9.6
0.161194	40.06	---	65.40	25.34	15000.	9.000	L1	ON	9.6
0.183581	---	29.41	54.32	24.91	15000.	9.000	L1	ON	9.6
0.183581	41.87	---	64.32	22.46	15000.	9.000	L1	ON	9.6
0.508200	---	35.21	46.00	10.79	15000.	9.000	N	ON	9.8
0.508200	44.16	---	56.00	11.84	15000.	9.000	N	ON	9.8
0.601481	---	35.97	46.00	10.03	15000.	9.000	N	ON	9.8
0.601481	42.26	---	56.00	13.74	15000.	9.000	N	ON	9.8
1.198481	---	30.39	46.00	15.61	15000.	9.000	N	ON	9.8
1.198481	38.20	---	56.00	17.80	15000.	9.000	N	ON	9.8
16.690631	---	26.71	50.00	23.29	15000.	9.000	N	ON	9.9
16.690631	37.46	---	60.00	22.54	15000.	9.000	N	ON	9.9


Note:

- 1.Emission level(quasi-peak or Average peak)=Raw value by receiver + Corr(Insertion loss+ cable loss)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.
- 4.L1 and N line is all have been tested, the result of them is synthesized in the above data diagram.

N12 (Main supply_Version 3):

Mode 1: Adapter charging <Figure 2>

Frequency Range: 150kHz – 30MHz




Frequency (MHz)	QuasiPeak (dB µ V)	Average (dB µ V)	Limit (dB µ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.172388	---	25.97	54.85	28.88	15000.	9.000	L1	ON	9.6
0.172388	52.56	---	64.85	12.28	15000.	9.000	L1	ON	9.6
0.224625	---	25.56	52.65	27.09	15000.	9.000	L1	ON	9.6
0.224625	51.90	---	62.65	10.75	15000.	9.000	L1	ON	9.6
0.601481	---	26.88	46.00	19.12	15000.	9.000	L1	ON	9.6
0.601481	42.54	---	56.00	13.46	15000.	9.000	L1	ON	9.6
9.519169	---	17.08	50.00	32.92	15000.	9.000	L1	ON	9.9
9.519169	26.76	---	60.00	33.24	15000.	9.000	L1	ON	9.9
11.687025	---	17.83	50.00	32.17	15000.	9.000	N	ON	9.9
11.687025	28.00	---	60.00	32.00	15000.	9.000	N	ON	9.9
17.071219	---	23.79	50.00	26.21	15000.	9.000	N	ON	9.9
17.071219	36.18	---	60.00	23.82	15000.	9.000	N	ON	9.9

Note:

- 1.Emission level(quasi-peak or Average peak)=Raw value by receiver + Corr(Insertion loss+ cable loss)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.
- 4.L1 and N line is all have been tested, the result of them is synthesized in the above data diagram.

N22 (Secondary supply_Version 2):

Mode 1: Adapter charging <Figure 2>



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.168656	---	26.06	55.03	28.96	15000.	9.000	L1	ON	9.6
0.168656	39.07	---	65.03	25.96	15000.	9.000	L1	ON	9.6
0.362681	---	22.97	48.67	25.69	15000.	9.000	L1	ON	9.6
0.362681	35.55	---	58.67	23.12	15000.	9.000	L1	ON	9.6
0.500738	---	31.29	46.00	14.71	15000.	9.000	N	ON	9.8
0.500738	41.60	---	56.00	14.41	15000.	9.000	N	ON	9.8
0.594019	---	35.69	46.00	10.31	15000.	9.000	N	ON	9.8
0.594019	44.43	---	56.00	11.57	15000.	9.000	N	ON	9.8
1.127588	---	25.64	46.00	20.36	15000.	9.000	N	ON	9.8
1.127588	36.07	---	56.00	19.93	15000.	9.000	N	ON	9.8
2.896200	---	24.29	46.00	21.71	15000.	9.000	N	ON	9.9
2.896200	36.28	---	56.00	19.72	15000.	9.000	N	ON	9.9


Note:

- 1.Emission level(quasi-peak or Average peak)=Raw value by receiver + Corr(Insertion loss+ cable loss)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.
- 4.L1 and N line is all have been tested, the result of them is synthesized in the above data diagram.

N14 (Secondary supply_Version 4):

Mode 1: Adapter charging <Figure 2>

Frequency Range: 150kHz – 30MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.157463	49.98	---	65.60	15.61	15000.	9.000	N	ON	9.7
0.157463	---	32.03	55.60	23.57	15000.	9.000	N	ON	9.7
0.176119	---	33.08	54.67	21.58	15000.	9.000	N	ON	9.7
0.176119	49.90	---	64.67	14.77	15000.	9.000	N	ON	9.7
0.224625	46.48	---	62.65	16.17	15000.	9.000	N	ON	9.7
0.224625	---	32.04	52.65	20.60	15000.	9.000	N	ON	9.7
0.269400	---	27.97	51.14	23.16	15000.	9.000	L1	ON	9.6
0.269400	45.13	---	61.14	16.01	15000.	9.000	L1	ON	9.6
4.549144	---	26.16	46.00	19.84	15000.	9.000	N	ON	10.0
4.549144	35.96	---	56.00	20.04	15000.	9.000	N	ON	10.0
17.317481	---	26.93	50.00	23.07	15000.	9.000	N	ON	9.9
17.317481	36.70	---	60.00	23.30	15000.	9.000	N	ON	9.9

Note:

- 1.Emission level(quasi-peak or Average peak)=Raw value by receiver + Corr(Insertion loss+ cable loss)
- 2.The raw value is used to calculate by software which is not shown in the sheet.
- 3.Margin=limit value – emission level.
- 4.L1 and N line is all have been tested, the result of them is synthesized in the above data diagram.

Annex A Accreditation Certificate



Accredited Laboratory

A2LA has accredited

EAST CHINA INSTITUTE OF TELECOMMUNICATIONS
Shanghai, People's Republic of China


for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 6th day of May 2019.



Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 3682.01
Valid to February 28, 2021

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

*****END OF REPORT*****