Appendix E

RF Test Data for 5.8G WLAN (Conducted Measurement)

Product Name: Drive

Trade Mark: Opus IVS

Test Model: TAB-F1063-2

Environmental Conditions

Temperature:	24.3 ° C
Relative Humidity:	52.6%
ATM Pressure:	100.0 kPa
Test Engineer:	Li Huan
Supervised by:	Tom Liu

E.1 Duty Cycle

ANT0

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5785	100	0.00	0.01
11N20 SISO	5785	100	0.00	0.01
11N40 SISO	5755	100	0.00	0.01
11AC20 SISO	5785	100	0.00	0.01
11AC40 SISO	5755	100	0.00	0.01
11AC80 SISO	5775	100	0.00	0.01

On Time and Duty Cycle



IEEE 802.11a



IEEE 802.11n HT20



IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11AC40



IEEE 802.11AC80

ANT1

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5785	100	0.00	0.01
11N20 SISO	5785	100	0.00	0.01
11N40 SISO	5755	100	0.00	0.01
11AC20 SISO	5785	100	0.00	0.01
11AC40 SISO	5755	100	0.00	0.01
11AC80 SISO	5775	100	0.00	0.01

On Time and Duty Cycle



IEEE 802.11a



IEEE 802.11n HT20



IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11AC40



IEEE 802.11AC80

E.2 Maximum Conduct Output Power

ANT0

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	149	5745	5.33	0	5.33	30	Pass
	157	5785	5.44	0	5.44		Pass
	165	5825	5.45	0	5.45		Pass
11N20 SISO	149	5745	4.33	0	4.33	30	Pass
	157	5785	4.30	0	4.30		Pass
	165	5825	4.35	0	4.35		Pass
11N40 SISO	151	5755	4.28	0	4.28	30	Pass
	159	5795	4.46	0	4.46		Pass
11AC20 SISO	149	5745	4.41	0	4.41	30	Pass
	157	5785	4.29	0	4.29		Pass
	165	5825	4.26	0	4.26		Pass
11AC40 SISO	151	5755	4.13	0	4.13	30	Pass
	159	5795	4.17	0	4.17		Pass
11AC80 SISO	155	5775	4.40	0	4.40	30	Pass

ANT1

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	149	5745	5.61	0	5.61	30	Pass
	157	5785	5.13	0	5.13		Pass
	165	5825	5.30	0	5.30		Pass
11N20 SISO	149	5745	4.02	0	4.02	30	Pass
	157	5785	4.15	0	4.15		Pass
	165	5825	4.27	0	4.27		Pass
11N40 SISO	151	5755	4.38	0	4.38	30	Pass
	159	5795	4.16	0	4.16		Pass
11AC20 SISO	149	5745	4.10	0	4.10	30	Pass
	157	5785	4.26	0	4.26		Pass
	165	5825	4.18	0	4.18		Pass
11AC40 SISO	151	5755	4.44	0	4.44	30	Pass
	159	5795	4.32	0	4.32		Pass
11AC80 SISO	155	5775	4.19	0	4.19	30	Pass

ANT0+ANT1:

Test Mode	Channel	Frequency (MHz)	Duty Cycle Factor (dB)	Report Conducted Power (dBm)			Limit (dBm)	Verdict
				Ant0	Ant1	Sum		
11N20 MIMO	149	5745	0	4.33	4.02	7.19	27.99	Pass
	157	5785	0	4.30	4.15	7.24		Pass
	165	5825	0	4.35	4.27	7.32		Pass
11N40 MIMO	151	5755	0	4.28	4.38	7.34	27.99	Pass
	159	5795	0	4.46	4.16	7.32		Pass
11AC20 MIMO	149	5745	0	4.41	4.10	7.27	27.99	Pass
	157	5785	0	4.29	4.26	7.29		Pass
	165	5825	0	4.26	4.18	7.23		Pass
11AC40 MIMO	151	5755	0	4.13	4.44	7.30	27.99	Pass
	159	5795	0	4.17	4.32	7.26		Pass
11AC80 MIMO	155	5775	0	4.40	4.19	7.31	27.99	Pass

E.3 Power Spectral Density

ANT0

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
11A	149	5745	-5.92	0	2.218	-3.71	30	Pass
	157	5785	-6.48	0	2.218	-4.26		Pass
	165	5825	-5.93	0	2.218	-3.72		Pass
11N20 SISO	149	5745	-13.30	0	2.218	-11.08	30	Pass
	157	5785	-7.18	0	2.218	-4.96		Pass
	165	5825	-5.46	0	2.218	-3.24		Pass
11N40 SISO	151	5755	-9.30	0	2.218	-7.08	30	Pass
	159	5795	-8.94	0	2.218	-6.72		Pass
11AC20 SISO	149	5745	-6.38	0	2.218	-4.17	30	Pass
	157	5785	-5.13	0	2.218	-2.91		Pass
	165	5825	-5.45	0	2.218	-3.23		Pass
11AC40 SISO	151	5755	-9.55	0	2.218	-7.33	30	Pass
	159	5795	-8.94	0	2.218	-6.73		Pass
11AC80 SISO	155	5775	-14.17	0	2.218	-11.95	30	Pass

ANT1

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
11A	149	5745	-6.15	0	2.218	-3.94	30	Pass
	157	5785	-6.57	0	2.218	-4.35		Pass
	165	5825	-6.86	0	2.218	-4.64		Pass
11N20 SISO	149	5745	-6.43	0	2.218	-4.22	30	Pass
	157	5785	-6.86	0	2.218	-4.64		Pass
	165	5825	-6.78	0	2.218	-4.56		Pass
11N40 SISO	151	5755	-9.46	0	2.218	-7.25	30	Pass
	159	5795	-9.37	0	2.218	-7.15		Pass
11AC20 SISO	149	5745	-6.40	0	2.218	-4.18	30	Pass
	157	5785	-9.58	0	2.218	-7.36		Pass
	165	5825	-6.00	0	2.218	-3.78		Pass
11AC40 SISO	151	5755	-9.04	0	2.218	-6.82	30	Pass
	159	5795	-9.21	0	2.218	-6.99		Pass
11AC80 SISO	155	5775	-14.01	0	2.218	-11.80	30	Pass

ANT0+ANT1:

Test Mode	Channel	Frequency (MHz)	Duty Cycle Factor (dB)	Report Power Density (dBm/500KHz)			Limit (dBm)	Verdict
				Ant0	Ant1	Sum		
11N20 MIMO	149	5745	0	-11.08	-4.22	-3.41	27.99	Pass
	157	5785	0	-4.96	-4.64	-1.79		Pass
	165	5825	0	-3.24	-4.56	-0.84		Pass
11N40 MIMO	151	5755	0	-7.08	-7.25	-4.15	27.99	Pass
	159	5795	0	-6.72	-7.15	-3.92		Pass
11AC20 MIMO	149	5745	0	-4.17	-4.18	-1.16	27.99	Pass
	157	5785	0	-2.91	-7.36	-1.58		Pass
	165	5825	0	-3.23	-3.78	-0.49		Pass
11AC40 MIMO	151	5755	0	-7.33	-6.82	-4.06	27.99	Pass
	159	5795	0	-6.73	-6.99	-3.85		Pass
11AC80 MIMO	155	5775	0	-11.95	-11.80	-8.86	27.99	Pass

Power Spectral Density_ANT0



IEEE 802.11a / Channel 149 / 5745MHz



IEEE 802.11na / Channel 157 / 5785MHz



IEEE 802.11na / Channel 165 / 5825MHz

Power Spectral Density_ANT0



IEEE 802.11n20 / Channel 149 / 5745MHz



IEEE 802.11n20 / Channel 157 / 5785MHz



IEEE 802.11n20 / Channel 165 / 5825MHz

Power Spectral Density_ANT0



IEEE 802.11n40 / Channel 151 / 5755MHz



IEEE 802.11n40 / Channel 159 / 5795MHz



IEEE 802.11ac20 / Channel 149 / 5745MHz



IEEE 802.11ac20 / Channel 157 / 5785MHz



IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz



IEEE 802.11ac80 / Channel 155/ 5775MHz

Power Spectral Density_ANT1



IEEE 802.11a / Channel 149 / 5745MHz



IEEE 802.11na / Channel 157 / 5785MHz



IEEE 802.11na / Channel 165 / 5825MHz

Power Spectral Density_ANT1



IEEE 802.11n20 / Channel 149 / 5745MHz



IEEE 802.11n20 / Channel 157 / 5785MHz



IEEE 802.11n20 / Channel 165 / 5825MHz

Power Spectral Density_ANT1



IEEE 802.11n40 / Channel 151 / 5755MHz



IEEE 802.11n40 / Channel 159 / 5795MHz



IEEE 802.11ac20 / Channel 149 / 5745MHz



IEEE 802.11ac20 / Channel 157 / 5785MHz



IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz



IEEE 802.11ac80 / Channel 155/ 5775MHz

E.4 Emission Bandwidth

ANT0

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	149	5745	16.09	>=0.5	Pass
	157	5785	16.32		Pass
	165	5825	16.32		Pass
11N20 SISO	149	5745	17.60	>=0.5	Pass
	157	5785	17.38		Pass
	165	5825	17.00		Pass
11N40 SISO	151	5755	35.48	>=0.5	Pass
	159	5795	35.58		Pass
11AC20S ISO	149	5745	17.43	>=0.5	Pass
	157	5785	17.40		Pass
	165	5825	17.57		Pass
11AC40S ISO	151	5755	35.47	>=0.5	Pass
	159	5795	36.33		Pass
11AC80S ISO	155	5775	76.57	>=0.5	Pass

6dB Bandwidth



IEEE 802.11a / Channel 149 / 5745MHz



IEEE 802.11a / Channel 157 / 5785MHz



IEEE 802.11a / Channel 165 / 5825MHz

6dB Bandwidth



IEEE 802.11n20 / Channel 149 / 5745MHz



IEEE 802.11n20 / Channel 157 / 5785MHz



IEEE 802.11n20 / Channel 165 / 5825MHz

26dB Bandwidth



IEEE 802.11n40 / Channel 151 / 5755MHz



IEEE 802.11n40 / Channel 159 / 5795MHz



IEEE 802.11ac20 / Channel 149 / 5745MHz



IEEE 802.11ac20 / Channel 157/ 5785MHz



IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz



IEEE 802.11ac80 / Channel 155 / 5775MHz

ANT1

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	149	5745	16.07	>=0.5	Pass
	157	5785	16.29		Pass
	165	5825	15.83		Pass
11N20 SISO	149	5745	17.57	>=0.5	Pass
	157	5785	17.51		Pass
	165	5825	17.57		Pass
11N40 SISO	151	5755	35.34	>=0.5	Pass
	159	5795	36.01		Pass
11AC20S ISO	149	5745	17.60	>=0.5	Pass
	157	5785	17.37		Pass
	165	5825	17.60		Pass
11AC40S ISO	151	5755	35.40	>=0.5	Pass
	159	5795	35.24		Pass
11AC80S ISO	155	5775	76.57	>=0.5	Pass

6dB Bandwidth



IEEE 802.11a / Channel 149 / 5745MHz



IEEE 802.11a / Channel 157 / 5785MHz



IEEE 802.11a / Channel 165 / 5825MHz

6dB Bandwidth



IEEE 802.11n20 / Channel 149 / 5745MHz



IEEE 802.11n20 / Channel 157 / 5785MHz



IEEE 802.11n20 / Channel 165 / 5825MHz

26dB Bandwidth



IEEE 802.11n40 / Channel 151 / 5755MHz



IEEE 802.11n40 / Channel 159 / 5795MHz



IEEE 802.11ac20 / Channel 149 / 5745MHz



IEEE 802.11ac20 / Channel 157/ 5785MHz



IEEE 802.11ac20 / Channel 165 / 5825MHz



IEEE 802.11ac40 / Channel 151 / 5755MHz



IEEE 802.11ac40 / Channel 159 / 5795MHz



IEEE 802.11ac80 / Channel 155 / 5775MHz

E.5 Undesirable Emissions Measurement

ANT0

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11A	149	5650.0	-49.18	5.00	-44.18	Peak	-27.0	Pass
		5650.0	-60.46	5.00	-55.46	Average	-27.0	Pass
		5700.0	-48.63	5.00	-43.63	Peak	10	Pass
		5700.0	-59.94	5.00	-54.94	Average	10	Pass
		5720.0	-42.20	5.00	-37.20	Peak	15.6	Pass
		5720.0	-57.76	5.00	-52.76	Average	15.6	Pass
		5725.0	-32.75	5.00	-27.75	Peak	27.0	Pass
		5725.0	-52.91	5.00	-47.91	Average	27.0	Pass
	165	5850.0	-39.79	5.00	-34.79	Peak	27.0	Pass
		5850.0	-57.77	5.00	-52.77	Average	27.0	Pass
		5855.0	-46.76	5.00	-41.76	Peak	15.6	Pass
		5855.0	-58.68	5.00	-53.68	Average	15.6	Pass
		5875.0	-47.55	5.00	-42.55	Peak	10	Pass
		5875.0	-59.66	5.00	-54.66	Average	10	Pass
		5925.0	-48.29	5.00	-43.29	Peak	-27.0	Pass
		5925.0	-60.20	5.00	-55.20	Average	-27.0	Pass
11N20 SISO	149	5650.0	-49.33	5.00	-44.33	Peak	-27.0	Pass
		5650.0	-60.89	5.00	-55.89	Average	-27.0	Pass
		5700.0	-49.02	5.00	-44.02	Peak	10	Pass
		5700.0	-60.52	5.00	-55.52	Average	10	Pass
		5720.0	-46.99	5.00	-41.99	Peak	15.6	Pass
		5720.0	-60.68	5.00	-55.68	Average	15.6	Pass
		5725.0	-48.24	5.00	-43.24	Peak	27.0	Pass
		5725.0	-60.31	5.00	-55.31	Average	27.0	Pass
	165	5850.0	-42.36	5.00	-37.36	Peak	27.0	Pass
		5850.0	-56.97	5.00	-51.97	Average	27.0	Pass
		5855.0	-45.89	5.00	-40.89	Peak	15.6	Pass
		5855.0	-58.63	5.00	-53.63	Average	15.6	Pass
		5875.0	-48.64	5.00	-43.64	Peak	10	Pass
		5875.0	-59.69	5.00	-54.69	Average	10	Pass
		5925.0	-46.51	5.00	-41.51	Peak	-27.0	Pass
		5925.0	-60.25	5.00	-55.25	Average	-27.0	Pass

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11N40 SISO	151	5650.0	-48.37	5.00	-43.37	Peak	-27.0	Pass
		5650.0	-60.38	5.00	-55.38	Average	-27.0	Pass
		5700.0	-46.93	5.00	-41.93	Peak	10	Pass
		5700.0	-59.22	5.00	-54.22	Average	10	Pass
		5720.0	-33.46	5.00	-28.46	Peak	15.6	Pass
		5720.0	-51.33	5.00	-46.33	Average	15.6	Pass
		5725.0	-30.09	5.00	-25.09	Peak	27.0	Pass
		5725.0	-48.56	5.00	-43.56	Average	27.0	Pass
	159	5850.0	-47.16	5.00	-42.16	Peak	27.0	Pass
		5850.0	-58.67	5.00	-53.67	Average	27.0	Pass
		5855.0	-46.45	5.00	-41.45	Peak	15.6	Pass
		5855.0	-59.01	5.00	-54.01	Average	15.6	Pass
		5875.0	-47.71	5.00	-42.71	Peak	10	Pass
		5875.0	-59.63	5.00	-54.63	Average	10	Pass
		5925.0	-48.32	5.00	-43.32	Peak	-27.0	Pass
		5925.0	-60.11	5.00	-55.11	Average	-27.0	Pass
11AC20 SISO	149	5650.0	-46.72	5.00	-41.72	Peak	-27.0	Pass
		5650.0	-60.32	5.00	-55.32	Average	-27.0	Pass
		5700.0	-47.58	5.00	-42.58	Peak	10	Pass
		5700.0	-57.40	5.00	-52.40	Average	10	Pass
		5720.0	-41.64	5.00	-36.64	Peak	15.6	Pass
		5720.0	-59.77	5.00	-54.77	Average	15.6	Pass
		5725.0	-30.46	5.00	-25.46	Peak	27.0	Pass
		5725.0	-52.76	5.00	-47.76	Average	27.0	Pass
	165	5850.0	-41.99	5.00	-36.99	Peak	27.0	Pass
		5850.0	-56.87	5.00	-51.87	Average	27.0	Pass
		5855.0	-46.33	5.00	-41.33	Peak	15.6	Pass
		5855.0	-58.56	5.00	-53.56	Average	15.6	Pass
		5875.0	-48.41	5.00	-43.41	Peak	10	Pass
		5875.0	-59.65	5.00	-54.65	Average	10	Pass
		5925.0	-48.93	5.00	-43.93	Peak	-27.0	Pass
		5925.0	-60.25	5.00	-55.25	Average	-27.0	Pass
11AC40 SISO	151	5650.0	-48.44	5.00	-43.44	Peak	-27.0	Pass
		5650.0	-60.39	5.00	-55.39	Average	-27.0	Pass
		5700.0	-46.95	5.00	-41.95	Peak	10	Pass
		5700.0	-59.22	5.00	-54.22	Average	10	Pass
		5720.0	-34.47	5.00	-29.47	Peak	15.6	Pass
		5720.0	-51.44	5.00	-46.44	Average	15.6	Pass

		5725.0	-32.14	5.00	-27.14	Peak	27.0	Pass
		5725.0	-48.70	5.00	-43.70	Average	27.0	Pass
	159	5850.0	-46.89	5.00	-41.89	Peak	27.0	Pass
		5850.0	-58.68	5.00	-53.68	Average	27.0	Pass
		5855.0	-47.85	5.00	-42.85	Peak	15.6	Pass
		5855.0	-59.02	5.00	-54.02	Average	15.6	Pass
		5875.0	-48.79	5.00	-43.79	Peak	10	Pass
		5875.0	-59.59	5.00	-54.59	Average	10	Pass
		5925.0	-48.57	5.00	-43.57	Peak	-27.0	Pass
		5925.0	-60.10	5.00	-55.10	Average	-27.0	Pass
11AC80 SISO	155	5725.0	-39.45	5.00	-34.45	Peak	27.0	Pass
		5720.0	-38.37	5.00	-33.37	Peak	15.6	Pass
		5700.0	-41.73	5.00	-36.73	Peak	10	Pass
		5650.0	-47.80	5.00	-42.8	Peak	-27.0	Pass
		5725.0	-48.96	5.00	-43.96	Average	27.0	Pass
		5720.0	-50.02	5.00	-45.02	Average	15.6	Pass
		5700.0	-51.80	5.00	-46.8	Average	10	Pass
		5650.0	-58.68	5.00	-53.68	Average	-27.0	Pass
		5850.0	-38.06	5.00	-33.06	Peak	27.0	Pass
		5855.0	-37.09	5.00	-32.09	Peak	15.6	Pass
		5875.0	-43.76	5.00	-38.76	Peak	10	Pass
		5925.0	-48.89	5.00	-43.89	Peak	-27.0	Pass
		5850.0	-51.04	5.00	-46.04	Average	27.0	Pass
		5855.0	-52.19	5.00	-47.19	Average	15.6	Pass
		5875.0	-57.16	5.00	-52.16	Average	10	Pass
		5925.0	-59.64	5.00	-54.64	Average	-27.0	Pass

ANT1

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11A	149	5650.0	-48.27	5.00	-43.27	Peak	-27.0	Pass
		5650.0	-60.52	5.00	-55.52	Average	-27.0	Pass
		5700.0	-48.55	5.00	-43.55	Peak	10	Pass
		5700.0	-60.14	5.00	-55.14	Average	10	Pass
		5720.0	-46.49	5.00	-41.49	Peak	15.6	Pass
		5720.0	-58.79	5.00	-53.79	Average	15.6	Pass
		5725.0	-34.93	5.00	-29.93	Peak	27.0	Pass
		5725.0	-55.91	5.00	-50.91	Average	27.0	Pass
	165	5850.0	-47.31	5.00	-42.31	Peak	27.0	Pass

		5850.0	-58.46	5.00	-53.46	Average	27.0	Pass
		5855.0	-47.00	5.00	-42.00	Peak	15.6	Pass
		5855.0	-59.08	5.00	-54.08	Average	15.6	Pass
		5875.0	-48.26	5.00	-43.26	Peak	10	Pass
		5875.0	-59.75	5.00	-54.75	Average	10	Pass
		5925.0	-48.43	5.00	-43.43	Peak	-27.0	Pass
		5925.0	-60.25	5.00	-55.25	Average	-27.0	Pass
11N20 SISO	149	5650.0	-48.47	5.00	-43.47	Peak	-27.0	Pass
		5650.0	-60.54	5.00	-55.54	Average	-27.0	Pass
		5700.0	-48.05	5.00	-43.05	Peak	10	Pass
		5700.0	-58.82	5.00	-53.82	Average	10	Pass
		5720.0	-45.64	5.00	-40.64	Peak	15.6	Pass
		5720.0	-60.10	5.00	-55.10	Average	15.6	Pass
		5725.0	-37.17	5.00	-32.17	Peak	27.0	Pass
		5725.0	-56.50	5.00	-51.50	Average	27.0	Pass
	165	5850.0	-45.50	5.00	-40.50	Peak	27.0	Pass
		5850.0	-58.45	5.00	-53.45	Average	27.0	Pass
		5855.0	-47.85	5.00	-42.85	Peak	15.6	Pass
		5855.0	-59.36	5.00	-54.36	Average	15.6	Pass
		5875.0	-48.27	5.00	-43.27	Peak	10	Pass
		5875.0	-59.96	5.00	-54.96	Average	10	Pass
		5925.0	-48.29	5.00	-43.29	Peak	-27.0	Pass
		5925.0	-60.37	5.00	-55.37	Average	-27.0	Pass

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
11N40 SISO	151	5650.0	-48.32	5.00	-43.32	Peak	-27.0	Pass
		5650.0	-60.57	5.00	-55.57	Average	-27.0	Pass
		5700.0	-46.12	5.00	-41.12	Peak	10	Pass
		5700.0	-59.67	5.00	-54.67	Average	10	Pass
		5720.0	-38.19	5.00	-33.19	Peak	15.6	Pass
		5720.0	-54.88	5.00	-49.88	Average	15.6	Pass
		5725.0	-34.36	5.00	-29.36	Peak	27.0	Pass
		5725.0	-52.70	5.00	-47.7	Average	27.0	Pass
	159	5850.0	-47.52	5.00	-42.52	Peak	27.0	Pass
		5850.0	-58.80	5.00	-53.8	Average	27.0	Pass
		5855.0	-47.53	5.00	-42.53	Peak	15.6	Pass
		5855.0	-59.04	5.00	-54.04	Average	15.6	Pass
		5875.0	-47.70	5.00	-42.7	Peak	10	Pass
		5875.0	-59.51	5.00	-54.51	Average	10	Pass
		5925.0	-48.20	5.00	-43.2	Peak	-27.0	Pass
		5925.0	-59.97	5.00	-54.97	Average	-27.0	Pass
11AC20 SISO	149	5650.0	-47.70	5.00	-42.7	Peak	-27.0	Pass
		5650.0	-60.51	5.00	-55.51	Average	-27.0	Pass
		5700.0	-48.50	5.00	-43.5	Peak	10	Pass
		5700.0	-58.59	5.00	-53.59	Average	10	Pass
		5720.0	-45.48	5.00	-40.48	Peak	15.6	Pass
		5720.0	-60.04	5.00	-55.04	Average	15.6	Pass
		5725.0	-32.92	5.00	-27.92	Peak	27.0	Pass
		5725.0	-55.81	5.00	-50.81	Average	27.0	Pass
	165	5850.0	-43.89	5.00	-38.89	Peak	27.0	Pass
		5850.0	-57.96	5.00	-52.96	Average	27.0	Pass
		5855.0	-46.99	5.00	-41.99	Peak	15.6	Pass
		5855.0	-58.99	5.00	-53.99	Average	15.6	Pass
		5875.0	-48.32	5.00	-43.32	Peak	10	Pass
		5875.0	-59.81	5.00	-54.81	Average	10	Pass
		5925.0	-48.85	5.00	-43.85	Peak	-27.0	Pass
		5925.0	-60.36	5.00	-55.36	Average	-27.0	Pass
11AC40 SISO	151	5650.0	-48.22	5.00	-43.22	Peak	-27.0	Pass
		5650.0	-60.44	5.00	-55.44	Average	-27.0	Pass
		5700.0	-46.93	5.00	-41.93	Peak	10	Pass
		5700.0	-59.62	5.00	-54.62	Average	10	Pass
		5720.0	-38.78	5.00	-33.78	Peak	15.6	Pass
		5720.0	-55.03	5.00	-50.03	Average	15.6	Pass

		5725.0	-34.59	5.00	-29.59	Peak	27.0	Pass
		5725.0	-52.88	5.00	-47.88	Average	27.0	Pass
	159	5850.0	-48.52	5.00	-43.52	Peak	27.0	Pass
		5850.0	-59.39	5.00	-54.39	Average	27.0	Pass
		5855.0	-48.93	5.00	-43.93	Peak	15.6	Pass
		5855.0	-59.57	5.00	-54.57	Average	15.6	Pass
		5875.0	-48.31	5.00	-43.31	Peak	10	Pass
		5875.0	-60.00	5.00	-55.00	Average	10	Pass
		5925.0	-48.27	5.00	-43.27	Peak	-27.0	Pass
		5925.0	-60.38	5.00	-55.38	Average	-27.0	Pass
11AC80 SISO	155	5725.0	-44.65	5.00	-39.65	Peak	27.0	Pass
		5720.0	-41.44	5.00	-36.44	Peak	15.6	Pass
		5700.0	-47.03	5.00	-42.03	Peak	10	Pass
		5650.0	-49.35	5.00	-44.35	Peak	-27.0	Pass
		5725.0	-54.41	5.00	-49.41	Average	27.0	Pass
		5720.0	-55.42	5.00	-50.42	Average	15.6	Pass
		5700.0	-57.34	5.00	-52.34	Average	10	Pass
		5650.0	-60.35	5.00	-55.35	Average	-27.0	Pass
		5850.0	-41.92	5.00	-36.92	Peak	27.0	Pass
		5855.0	-41.48	5.00	-36.48	Peak	15.6	Pass
		5875.0	-47.60	5.00	-42.6	Peak	10	Pass
		5925.0	-48.87	5.00	-43.87	Peak	-27.0	Pass
		5850.0	-54.86	5.00	-49.86	Average	27.0	Pass
		5855.0	-55.58	5.00	-50.58	Average	15.6	Pass
		5875.0	-58.40	5.00	-53.4	Average	10	Pass
		5925.0	-59.89	5.00	-54.89	Average	-27.0	Pass

ANT0+ANT1:

Test Mode	Channel	Frequency (MHz)	Covert Radiated E Level At 3m (dBuV/m)			Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)	Verdict
			Ant0	Ant1	Sum					
11N20 MIMO	149	5650.0	-49.33	-48.47	-45.87	8.01	-37.86	Peak	-27.0	Pass
		5650.0	-60.89	-60.54	-57.70	8.01	-49.69	Average	-27.0	Pass
		5700.0	-49.02	-48.05	-45.50	8.01	-37.49	Peak	10	Pass
		5700.0	-60.52	-58.82	-56.58	8.01	-48.57	Average	10	Pass
		5720.0	-46.99	-45.64	-43.25	8.01	-35.24	Peak	15.6	Pass
		5720.0	-60.68	-60.10	-57.37	8.01	-49.36	Average	15.6	Pass
		5725.0	-48.24	-37.17	-36.84	8.01	-28.83	Peak	27.0	Pass
		5725.0	-60.31	-56.50	-54.99	8.01	-46.98	Average	27.0	Pass
	165	5850.0	-42.36	-45.50	-40.64	8.01	-32.63	Peak	27.0	Pass
		5850.0	-56.97	-58.45	-54.64	8.01	-46.63	Average	27.0	Pass
		5855.0	-45.89	-47.85	-43.75	8.01	-35.74	Peak	15.6	Pass
		5855.0	-58.63	-59.36	-55.97	8.01	-47.96	Average	15.6	Pass
		5875.0	-48.64	-48.27	-45.44	8.01	-37.43	Peak	10	Pass
		5875.0	-59.69	-59.96	-56.81	8.01	-48.80	Average	10	Pass
		5925.0	-46.51	-48.29	-44.30	8.01	-36.29	Peak	-27.0	Pass
		5925.0	-60.25	-60.37	-57.30	8.01	-49.29	Average	-27.0	Pass
11N40 MIMO	151	5650.0	-48.37	-48.32	-45.33	8.01	-37.32	Peak	-27.0	Pass
		5650.0	-60.38	-60.57	-57.46	8.01	-49.45	Average	-27.0	Pass
		5700.0	-46.93	-46.12	-43.50	8.01	-35.49	Peak	10	Pass
		5700.0	-59.22	-59.67	-56.43	8.01	-48.42	Average	10	Pass
		5720.0	-33.46	-38.19	-32.20	8.01	-24.19	Peak	15.6	Pass
		5720.0	-51.33	-54.88	-49.74	8.01	-41.73	Average	15.6	Pass
		5725.0	-30.09	-34.36	-28.71	8.01	-20.7	Peak	27.0	Pass
		5725.0	-48.56	-52.70	-47.14	8.01	-39.13	Average	27.0	Pass
	159	5850.0	-47.16	-47.52	-44.33	8.01	-36.32	Peak	27.0	Pass
		5850.0	-58.67	-58.80	-55.72	8.01	-47.71	Average	27.0	Pass
		5855.0	-46.45	-47.53	-43.95	8.01	-35.94	Peak	15.6	Pass
		5855.0	-59.01	-59.04	-56.01	8.01	-48.00	Average	15.6	Pass
		5875.0	-47.71	-47.70	-44.69	8.01	-36.68	Peak	10	Pass
		5875.0	-59.63	-59.51	-56.56	8.01	-48.55	Average	10	Pass
		5925.0	-48.32	-48.20	-45.25	8.01	-37.24	Peak	-27.0	Pass
		5925.0	-60.11	-59.97	-57.03	8.01	-49.02	Average	-27.0	Pass
11AC20 MIMO	149	5650.0	-46.72	-47.70	-44.17	8.01	-36.16	Peak	-27.0	Pass
		5650.0	-60.32	-60.51	-57.40	8.01	-49.39	Average	-27.0	Pass
		5700.0	-47.58	-48.50	-45.01	8.01	-37.00	Peak	10	Pass
		5700.0	-57.40	-58.59	-54.94	8.01	-46.93	Average	10	Pass
		5720.0	-41.64	-45.48	-40.14	8.01	-32.13	Peak	15.6	Pass
		5720.0	-59.77	-60.04	-56.89	8.01	-48.88	Average	15.6	Pass
		5725.0	-30.46	-32.92	-28.51	8.01	-20.5	Peak	27.0	Pass
		5725.0	-52.76	-55.81	-51.01	8.01	-43.00	Average	27.0	Pass
	165	5850.0	-41.99	-43.89	-39.83	8.01	-31.82	Peak	27.0	Pass
		5850.0	-56.87	-57.96	-54.37	8.01	-46.36	Average	27.0	Pass
		5855.0	-46.33	-46.99	-43.64	8.01	-35.63	Peak	15.6	Pass
		5855.0	-58.56	-58.99	-55.76	8.01	-47.75	Average	15.6	Pass
		5875.0	-48.41	-48.32	-45.35	8.01	-37.34	Peak	10	Pass
		5875.0	-59.65	-59.81	-56.72	8.01	-48.71	Average	10	Pass
		5925.0	-48.93	-48.85	-45.88	8.01	-37.87	Peak	-27.0	Pass
		5925.0	-60.25	-60.36	-57.29	8.01	-49.28	Average	-27.0	Pass
11AC40 MIMO	151	5650.0	-48.44	-48.22	-45.32	8.01	-37.31	Peak	-27.0	Pass
		5650.0	-60.39	-60.44	-57.40	8.01	-49.39	Average	-27.0	Pass
		5700.0	-46.95	-46.93	-43.93	8.01	-35.92	Peak	10	Pass
		5700.0	-59.22	-59.62	-56.41	8.01	-48.40	Average	10	Pass
		5720.0	-34.47	-38.78	-33.10	8.01	-25.09	Peak	15.6	Pass
		5720.0	-51.44	-55.03	-49.86	8.01	-41.85	Average	15.6	Pass
		5725.0	-32.14	-34.59	-30.18	8.01	-22.17	Peak	27.0	Pass
		5725.0	-48.70	-52.88	-47.30	8.01	-39.29	Average	27.0	Pass
	159	5850.0	-46.89	-48.52	-44.62	8.01	-36.61	Peak	27.0	Pass
		5850.0	-58.68	-59.39	-56.01	8.01	-48.00	Average	27.0	Pass
		5855.0	-47.85	-48.93	-45.35	8.01	-37.34	Peak	15.6	Pass
		5855.0	-59.02	-59.57	-56.28	8.01	-48.27	Average	15.6	Pass
		5875.0	-48.79	-48.31	-45.53	8.01	-37.52	Peak	10	Pass
		5875.0	-59.59	-60.00	-56.78	8.01	-48.77	Average	10	Pass
		5925.0	-48.57	-48.27	-45.41	8.01	-37.40	Peak	-27.0	Pass
		5925.0	-60.10	-60.38	-57.23	8.01	-49.22	Average	-27.0	Pass

11AC80 MIMO	155	5725.0	-39.45	-44.65	-38.30	8.01	-30.29	Peak	27.0	Pass
		5720.0	-38.37	-41.44	-36.63	8.01	-28.62	Peak	15.6	Pass
		5700.0	-41.73	-47.03	-40.61	8.01	-32.6	Peak	10	Pass
		5650.0	-47.80	-49.35	-45.50	8.01	-37.49	Peak	-27.0	Pass
		5725.0	-48.96	-54.41	-47.87	8.01	-39.86	Average	27.0	Pass
		5720.0	-50.02	-55.42	-48.92	8.01	-40.91	Average	15.6	Pass
		5700.0	-51.80	-57.34	-50.73	8.01	-42.72	Average	10	Pass
		5650.0	-58.68	-60.35	-56.42	8.01	-48.41	Average	-27.0	Pass
		5850.0	-38.06	-41.92	-36.56	8.01	-28.55	Peak	27.0	Pass
		5855.0	-37.09	-41.48	-35.74	8.01	-27.73	Peak	15.6	Pass
		5875.0	-43.76	-47.60	-42.26	8.01	-34.25	Peak	10	Pass
		5925.0	-48.89	-48.87	-45.87	8.01	-37.86	Peak	-27.0	Pass
		5850.0	-51.04	-54.86	-49.53	8.01	-41.52	Average	27.0	Pass
		5855.0	-52.19	-55.58	-50.55	8.01	-42.54	Average	15.6	Pass
		5875.0	-57.16	-58.40	-54.73	8.01	-46.72	Average	10	Pass
		5925.0	-59.64	-59.89	-56.75	8.01	-48.74	Average	-27.0	Pass

Undesirable Emissions Measurement_ANT0



IEEE 802.11a / Channel 149 / 5745MHz / Peak



IEEE 802.11a / Channel 148 / 5745MHz / Average

Undesirable Emissions Measurement_ANT0



IEEE 802.11a / Channel 165 / 5825MHz / Peak



IEEE 802.11a / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement_ANT0



IEEE 802.11n20 / Channel 149 / 5745MHz / Peak



IEEE 802.11n20 / Channel 149 / 5745MHz / Average

Undesirable Emissions Measurement_ANT0



IEEE 802.11n20 / Channel 165 / 5825MHz / Peak



IEEE 802.11n20 / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement_ANT0



IEEE 802.11n40 / Channel 151 / 5755MHz / Peak



IEEE 802.11n40 / Channel 151 / 5755MHz / Average

Undesirable Emissions Measurement_ANT0



IEEE 802.11n40 / Channel 159 / 5795MHz / Peak



IEEE 802.11n40 / Channel 159 / 5795MHz / Average



IEEE 802.11ac20 / Channel 149 / 5745MHz / Peak



IEEE 802.11ac20 / Channel 149 / 5745MHz / Average



IEEE 802.11ac20 / Channel 165 / 5825MHz / Peak



IEEE 802.11ac20 / Channel 165 / 5825MHz / Average



IEEE 802.11ac40 / Channel 151 / 5755MHz / Peak



IEEE 802.11ac40 / Channel 151 / 5755MHz / Average



IEEE 802.11ac40 / Channel 159 / 5795MHz / Peak



IEEE 802.11ac40 / Channel 159 / 5795MHz / Average



IEEE 802.11ac80 / Channel 155 / 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average



IEEE 802.11ac80 / Channel 155/ 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average

Undesirable Emissions Measurement_ANT1



IEEE 802.11a / Channel 149 / 5745MHz / Peak



IEEE 802.11a / Channel 148 / 5745MHz / Average

Undesirable Emissions Measurement_ANT1



IEEE 802.11a / Channel 165 / 5825MHz / Peak



IEEE 802.11a / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement_ANT1



IEEE 802.11n20 / Channel 149 / 5745MHz / Peak



IEEE 802.11n20 / Channel 149 / 5745MHz / Average

Undesirable Emissions Measurement_ANT1



IEEE 802.11n20 / Channel 165 / 5825MHz / Peak



IEEE 802.11n20 / Channel 165 / 5825MHz / Average

Undesirable Emissions Measurement_ANT1



IEEE 802.11n40 / Channel 151 / 5755MHz / Peak



IEEE 802.11n40 / Channel 151 / 5755MHz / Average

Undesirable Emissions Measurement_ANT1



IEEE 802.11n40 / Channel 159 / 5795MHz / Peak



IEEE 802.11n40 / Channel 159 / 5795MHz / Average



IEEE 802.11ac20 / Channel 149 / 5745MHz / Peak



IEEE 802.11ac20 / Channel 149 / 5745MHz / Average



IEEE 802.11ac20 / Channel 165 / 5825MHz / Peak



IEEE 802.11ac20 / Channel 165 / 5825MHz / Average



IEEE 802.11ac40 / Channel 151 / 5755MHz / Peak



IEEE 802.11ac40 / Channel 151 / 5755MHz / Average



IEEE 802.11ac40 / Channel 159 / 5795MHz / Peak



IEEE 802.11ac40 / Channel 159 / 5795MHz / Average



IEEE 802.11ac80 / Channel 155 / 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average



IEEE 802.11ac80 / Channel 155/ 5775MHz / Peak



IEEE 802.11ac80 / Channel 155 / 5775MHz / Average