

MEASUREMENT REPORT

FCC PART 15.247 Bluetooth-LE

Report No.: S2025072297960102

Issue Date: 10-23-2025

Applicant: GUANGZHOU RANTION TECHNOLOGY CO., LTD.
Room 7002 and 7003,7th Floor,Digital Entertainment
Address: Industrial Park,Greater Bay Area,No. 28 Huangpu Park
West Road,Huangpu District,Guangzhou,China.
FCC ID: 2AV7N-MKSERIES
Product: DIGITAL PIANO
DDP-200,DDP-200 MK2,DDP-200 MK3,DDP-200 MK4,
Model No.: DDP-200 MK5, DDP-200 MK6, DDP-200 MK7,
DODN3020, DODN6671, DODN6682, DODN6683,
DODN6684, DODN6685, DODN6686
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (15.247)
Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v05r02
Result: Pass
Item Receipt Date: Sep. 09, 2025
Test Date: Sep. 16, ~ Oct. 10, 2025

Compiled By Chuang Li
(Chuang Li)
Senior Test Engineer
Approved By Line Chen
(Line Chen)
Engineer Manager

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s). The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd. Wuxi Branch.

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

Revision History

Report No.	Version	Description	Issue Date
S2025072297960102	Rev. 01	/	10-23-2025

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope	6
1.2. Fangguang Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description	7
2.2. Product Specification Subjective to this Report	7
2.3. Operation Frequency / Channel List	8
2.4. Device Capabilities	8
2.5. Description of Test Software	12
2.6. Test Mode	12
2.7. Test Configuration	12
2.8. EMI Suppression Device(s)/Modifications	12
2.9. EUT Photo	12
2.10. Labeling Requirements	12
2.11. Calculation with all conversion and correction factors used	12
3. DESCRIPTION OF TEST	14
3.1. Evaluation Procedure	14
3.2. AC Line Conducted Emissions	14
3.3. Radiated Emissions	15
4. ANTENNA REQUIREMENTS	16
5. TEST EQUIPMENT CALIBRATION DATE	17
6. MEASUREMENT UNCERTAINTY	19
7. TEST RESULT	20
7.1. Summary	20
7.2. 6dB Bandwidth Measurement	21
7.2.1. Test Limit	21
7.2.2. Test Procedure used	21
7.2.3. Test Setting	21
7.2.4. Test Setup	21
7.2.5. Test Result	22
7.3. Output Power Measurement	29

7.3.1.	Test Limit	29
7.3.2.	Test Procedure Used	29
7.3.3.	Test Setting	29
7.3.4.	Test Setup	30
7.3.5.	Test Result	30
7.4.	Power Spectral Density Measurement	34
7.4.1.	Test Limit	34
7.4.2.	Test Procedure Used	34
7.4.3.	Test Setting	34
7.4.4.	Test Setup	35
7.4.5.	Test Result	36
7.5.	Conducted Band Edge and Out-of-Band Emissions	40
7.5.1.	Test Limit	40
7.5.2.	Test Procedure Used	40
7.5.3.	Test Setting	40
7.5.4.	Test Setup	40
7.5.5.	Test Result	41
7.6.	Radiated Spurious Emission Measurement	53
7.6.1.	Test Limit	53
7.6.2.	Test Procedure Used	53
7.6.3.	Test Setting	53
7.6.4.	Test Setup	55
7.6.5.	Test Result	57
7.7.	Restricted Band Edge Measurement	93
7.7.1.	Test Limit	93
7.7.2.	Test Procedure Used	96
7.7.3.	Test Setting	96
7.7.4.	Test Setup	97
7.7.5.	Test Result	98
7.8.	AC Conducted Emissions Measurement	106
7.8.1.	Test Limit	106
7.8.2.	Test Setup	106
7.8.3.	Test Result	107
8.	CONCLUSION	109

§2.1033 General Information

Applicant:	GUANGZHOU RANTION TECHNOLOGY CO., LTD.
Applicant Address:	Room 7002 and 7003,7th Floor,Digital Entertainment Industrial Park,Greater Bay Area,No. 28 Huangpu Park West Road,Huangpu District,Guangzhou,China.
Manufacturer:	GUANGZHOU RANTION TECHNOLOGY CO., LTD.
Manufacturer Address:	Room 7002 and 7003,7th Floor,Digital Entertainment Industrial Park,Greater Bay Area,No. 28 Huangpu Park West Road,Huangpu District,Guangzhou,China.
Test Site:	Fanguang Inspection & Testing Co., Ltd
LAB ID:	CN5037
Test Site Address:	No.8 Ningyun Rd., Xinwu District Wuxi,Jiangsu 214000 China
FCC Rule Part(s):	Part 15 Subpart C (15.247)
FCC ID:	2AV7N-MKSERIES
Test Device Serial No.:	S/N: S20250722979601-1-1 ☐ Production ☒ Pre-Production ☐ Engineering
FCC Classification:	Digital Transmission System (DTS)

1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2. Fangguang Test Location

These measurement tests were performed at the Fangguang Inspection and testing Co.,LTD located at No.8 Ningyun Rd., Xinwu District Wuxi,Jiangsu 214000 China. The detailed description of the measurement facility was found to be in compliance with the requirements of ANSI C63.10-2013.

2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	DIGITAL PIANO
Main Test Model:	DDP-200
Additional Model:	DDP-200 MK2, DDP-200 MK3, DDP-200 MK4, DDP-200 MK5, DDP-200 MK6, DDP-200 MK7, DODN3020, DODN6671, DODN6682, DODN6683, DODN6684, DODN6685, DODN6686
Model Description:	EUT (DIGITAL PIANO) the main model no. DDP-200 and its additional models no. DDP-200 MK3,DDP-200MK4,DDP-200 MK5,DDP-200 MK6,DDP-200MK7, DODN3020, DODN6671, DODN6682, DODN6683, DODN6684, DODN6685, DODN6686 have the same technical construction-including circuit-diagram, PCB-LAYOUT, material of the shell, hardware version and software version identical, the model names different, which does not affect electromagnetic compatibility and electricalsafety performance. They only differ in model names.
Trade Mark:	DONNER
Input Voltage Range:	DC 12V by adapter
Adapter Specifications:	Model: HCX3601-1203000U Input: AC 100~240V, 50/60Hz 1.2A Max; Output: DC 12V 3.0A 36.0W
Bluetooth Version:	5.2
Software Version:	V1.1
Hardware Version:	V1.1
Note:	This information is provided by the Customer and its authenticity is the responsibility of the Customer.

2.2. Product Specification Subjective to this Report

Bluetooth Frequency	2402~2480MHz
Type of modulation	GFSK
Data Rate	1Mbps, 2Mbps
Antenna Type:	PCB Antenna
Antenna Gain:	4dBi

2.3. Operation Frequency / Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	--	--	--	--

2.4. Device Capabilities

This device contains the following capabilities:Bluetooth (5.2)

Note: The maximum achievable duty cycle was determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW =8MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Antenna	Channel	ON Time [ms]	Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2402	2.13	2.50	85.20
		2440	2.13	2.50	85.20
		2480	2.12	2.50	84.80
BLE_2M	Ant1	2402	1.08	1.25	86.40
		2440	1.08	1.25	86.40
		2480	1.08	1.25	86.40

Test Graphs







2.5. Description of Test Software

The test utility software used during testing was "BT FCC Tool.exe", Power Parameter Value:

Test Software	Test Mode	Power Setting
BT FCC Tool.exe V2.24	BLE	4

2.6. Test Mode

Test Mode	Mode 1: Transmit by BLE_1M
	Mode 2: Transmit by BLE_2M

2.7. Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.8. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.9. EUT Photo

The EUT external photo, internal photo and test setup photo, please refer to the plots in the S20250722979601-A1/A2/A3.

2.10. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

2.11. Calculation with all conversion and correction factors used

For AC Line Conducted Emissions Test:

Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

For Radiated Emissions Below 1GHz Test:

Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

For Radiated Emissions Above 1GHz Test:

Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB).

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. The turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-25GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- Use a unique coupling to the intentional radiator.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	FWXGJC-2016-181	1 year	2026/07/08
Two-Line V-Network	R&S	ENV 216	FWXGJC-2016-182	1 year	2026/07/09
Thermohygrometer	Yuhua	HTC-1	FWXDA-2016-385	1 year	2026/08/24

Radiated Emission

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Loop Antenna	Schwarzbeck	FMZB 1519B	FWXGJC-2018-015	3 year	2026/06/12
Bi-Log Antenna	R&S	VULB 9168	FWXGJC-2024-055	1 year	2026/06/21
Broadband Horn Antenna	R&S	HF907	FWXGJC-2016-267-07	1 year	2026/06/21
Broadband Horn Antenna	Schwarzbeck	BBHA9170	FWXGJC-2018-016	3 year	2026/06/21
EMI Receiver	R&S	ESR26	FWXGJC-2016-267-01	1 year	2026/07/16
Pre-Amplifier	Tonscend	TAP0118048	FWXGJC-2024-056	1 year	2026/06/21
Pre-Amplifier	R&S	EMC184055 SE	FWXGJC-2018-018	3 year	2026/07/16
Hygrothermograph	Mittel	HTC-1	FWXDA-2016-387	1 year	2026/08/24
Anechoic Chamber	SAEMC	FSAC318	FGZZ-2024-035	3 year	2027/06/02

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Keysight	N9010B	FWXGJC-2018-010	1 year	2026/07/16
RF Control Unit	Toncend	JS0806-2	FWXGJC-2018-013	1 year	2026/07/16
Thermohygrometer	Yuhua	HTC-1	FWXDA-2016-385	1 year	2026/08/24

Auxiliary Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Filter	Toncend	ZBSF6	07247867	1 year	2026/07/16
Filter	Toncend	ZHPF6	07233297	1 year	2026/07/16
Attenuator	Toncend	10dB	/	1 year	2026/07/16
RF Cable	Toncend	T-1	/	1 year	2026/07/16

Test Software

Test Software	Manufacturer	Version	Asset No.	Function
JS32	Tonscend	V5.0.0	FWXWA-2019-004	RE
RF Test Software	Tonscend	3.3.10	/	Conducted Test

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.68dB
Radiated Emission Measurement (9kHz - 30MHz)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 3.06dB
Radiated Emission Measurement (30MHz -1GHz)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 4.01dB
Radiated Emission Measurement (1-18GHz)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 4.97dB
Radiated Emission Measurement (18-40GHz)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 5.32dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 30MHz-1GHz: 1.00 dB 1GHz-12.75GHz: 1.30 dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.60dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.80dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.20MHz
Frequency Stability
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.1×10^{-6} MHz

7. TEST RESULT

7.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Band Edge	$\geq 20\text{dBc}$		Pass	Section 7.5
15.247(d)	Out-of-Band Emissions	$\geq 20\text{dBc}$		Pass	Section 7.5
15.205	Restricted Bands	Emissions in restricted bands must meet the radiated limits detailed in 15.205	Radiated	Pass	Section 7.7
15.209	General Field Strength Limits (Radiated Emission Limits)	Radiated Emission must meet the radiated limits detailed in 15.209 (RSS GEN [8.9])		Pass	Section 7.6
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits (RSS GEN [8.8])	Line Conducted	PASS	Section 7.8

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.2.2. Test Procedure used


ANSI C63.10-2013 Section 11.8.2 Option 1

KDB 558074 D01 v05r02 – Section 8.2

7.2.3. Test Setting

1. Set RBW = 100 kHz
2. VBW $\geq 3 \times$ RBW
3. Detector = peak
4. Trace mode = max hold
5. Sweep = auto couple
6. Allow the trace was allowed to stabilize
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


7.2.4. Test Setup




7.2.5. Test Result


Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	99% BW[MHz]	Verdict
BLE_1M	Ant1	2402	0.720	2401.636	2402.356	0.5	1.0550	PASS
		2440	0.716	2439.640	2440.356	0.5	1.0555	PASS
		2480	0.716	2479.636	2480.352	0.5	1.0571	PASS
BLE_2M	Ant1	2402	1.184	2401.404	2402.588	0.5	2.0715	PASS
		2440	1.184	2439.408	2440.592	0.5	2.0682	PASS
		2480	1.184	2479.404	2480.588	0.5	2.0785	PASS

Test Graphs of 6dB Bandwidth





BLE_1M_Ant1_2480



BLE_2M_Ant1_2402




BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



Test Graphs of Occupied Channel Bandwidth





BLE_2M_Ant1_2402



BLE_2M_Ant1_2440