



FCC 47 CFR MPE REPORT

GUANGZHOU RANTION TECHNOLOGY CO., LTD.

Amplifier

Model Number: MT-1

Additional Model: MT-2, MT-3, DDA-1000, DDA-200, DDA-300

FCC ID: 2AV7N-MT1

Applicant:	GUANGZHOU RANTION TECHNOLOGY CO., LTD.
Address:	Room 7002 and 7003,7th Floor, Digital Entertainment Industrial Park,
	Greater Bay Area, No.28 Huangpu Park West Road,
	Huangpu District, Guangzhou, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2504155
Date of Test:	Nov. 11, 2024~ Apr. 15, 2025
Date of Report:	Apr. 17, 2025

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	3.00	1.995
	2441	-0.40	0.912
	2480	-2.65	0.543
$\pi/4$ -DQPSK	2402	2.98	1.986
	2441	-0.50	0.891
	2480	-2.77	0.528
8-DPSK	2402	3.21	2.094
	2441	-0.12	0.973
	2480	-2.56	0.555
BLE 1M	2402	2.54	1.795
	2440	-0.94	0.805
	2480	-3.30	0.468

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	3.00	3±1	4	2.9	1.950	0.00097	1	Complies
π/4-DQPSK	2.98	2±1	3	2.9	1.950	0.00077	1	Complies
8-DPSK	3.21	3±1	4	2.9	1.950	0.00097	1	Complies
BLE 1M	2.54	2±1	3	2.9	1.950	0.00077	1	Complies

End of Test Report