FCC TEST REPORT

FCC ID: 2AVBN-D11WF

On Behalf of

SHENZHEN REDLEAF TECHNOLOGY CO., LTD.

Trail Camera

Model No.: D11WF, TC22, TC30, D11, D12, D13, D12WF, D13WF

Prepared for	:	SHENZHEN REDLEAF TECHNOLOGY CO., LTD.
Address	:	3F, Building E, Huichao Industrial Park, Gushu Road 2, Xixiang Town, Bao'an District, Shenzhen, China

Prepared By	:	Shenzhen Alpha Product Testing Co., Ltd.
Address	:	Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Report Number	:	A2305310-C01-R07
Date of Receipt	:	May 30, 2023
Date of Test	:	May 30, 2023- July 11, 2023
Date of Report	:	July 11, 2023
Version Number	:	V0

ALPHA's reports is using a digital certificate that is trusted on Adobe's official server. If there is no digital certificate or the digital certificate shows damaged in your report. Please do not accept the report.
E-mail: service@a-lab.cn Tel: 4008-3008-95 Website: http://www.a-lab.cn

TABLE OF CONTENTS

Description	Page
TABLE OF CONTENTS	**2**
1. Summary of Standards And Results	**5**
1.1. Description of Standards and Results	5
2. General Information	**6**
2.1. Description of Device (EUT)	6
2.2. Accessories of Device (EUT)	7
2.3. Tested Supporting System Details	7
2.4. Block Diagram of connection between EUT and simulators	7
2.5. Test Mode Description	7
2.6. Test Conditions	8
2.7. Test Facility	8
2.8. Measurement Uncertainty	8
2.9. Test Equipment List	9
3. Spurious Emission	**10**
3.1. Test Limits	10
3.2. Test Procedure	10
3.3. Test Setup	11
4. Power Line Conducted Emission	**22**
4.1. Test Limits	22
4.2. Test Procedure	22
4.3. Test Setup	22
4.4. Test Results	22
5. Conducted Maximum Output Power	**25**
5.1. Test limits	25
5.2. Test Procedure	25
5.3. Test Setup	25
5.4. Test Results	25
6. Peak Power Spectral Density	**26**
6.1. Test limits	26
6.2. Test Procedure	26
6.3. Test Setup	26
6.4. Test Results	26
7. Bandwidth	**31**
7.1. Test limits	31
7.2. Test Procedure	31
7.3. Test Setup	31
7.4. Test Results	31
8. Band Edge Check	**39**
8.1. Test limits	39
8.2. Test Procedure	39
8.3. Test Setup	39
8.4. Test Results	39
9. Antenna Requirement	**45**
9.1. Standard Requirement	45
9.2. Antenna Connected Construction	45
9.3. Results	45
10. Test setup photo	**46**
10.1. Photo of Radiated Emission test	46
10.2. Photo of Conducted Emission test	错误!未定义书签。

TEST REPORT DECLARATION

Applicant	:	SHENZHEN REDLEAF TECHNOLOGY CO., LTD.
Address	:	3F, Building E, Huichao Industrial Park, Gushu Road 2, Xixiang Town, Bao'an District, Shenzhen, China
Manufacturer	:	SHENZHEN REDLEAF TECHNOLOGY CO., LTD.
Address	:	3F, Building E, Huichao Industrial Park, Gushu Road 2, Xixiang Town, Bao'an District, Shenzhen, China
EUT Description	:	Trail Camera
		(A) Model No. D11WF, TC22, TC30, D11, D12, D13, D12WF, D13WF
		(B) Trademark Trail Camera

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....…..:	Yannis Wen Project Engineer	Yannis Wen
Approved by (name + signature)…....:	Reak Yang Project Manager	
Date of issue…… ……..:	July 11, 2023	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	July 11, 2023	Initial released Issue	Yannis Wen

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Test Requirement	Standards Paragraph	Result
Conducted Emission	FCC PART 15	15.207	P
6dB Bandwidth	FCC PART 15	15.247 (a)(2)	P
Output Power	FCC PART 15	15.247 (b)(3)	P
Radiated Spurious Emission	FCC PART 15	15.247 (c)	P
Conducted Spurious & Band Edge Emission	FCC PART 15	15.247 (d)	P
Power Spectral Density	FCC PART 15	15.247 (e)	P
Radiated Band Edge Emission	FCC PART 15	15.205	P
Antenna Requirement	FCC PART 15	15.203	P

Note: 1. P is an abbreviation for Pass.
2. F is an abbreviation for Fail.
3. N/A is an abbreviation for Not Applicable.
4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	:	Trail Camera
Model Number	:	D11WF, TC22, TC30, D11, D12, D13, D12WF, D13WF
Diff	:	There is no difference between the models except the appearance color and name of the model. So all the test were performed on the model D11WF.
Power supply	:	DC 5V from sun with DC 3.7V from battery.
Radio Technology	:	Bluetooth BLE
Operation frequency	:	2402-2480MHz
Channel No.	:	40 Channels
Channel spacing	:	2MHz
Rate	:	1Mbps, 2Mbps
Modulation type	:	GFSK
Antenna Type	:	Internal antenna, max gain -0.28dBi (Antenna information is provided by applicant.)
Software version	:	V1.0
Hardware version	:	V1.0
Connector cable loss	:	N/A
Intend use environment	:	Residential, commercial and light industrial environment

2.2. Accessories of Device (EUT)

Accessories : /

Manufacturer : /

Model : /

Ratings : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1	Notebook PC	Lenovo	ThinkPad E14	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel, and data rate information		
Mode	**Channel**	**Frequency (MHz)**
GFSK (1M/2Mbps)	Low :CH1	2402
	Middle: CH20	2440
	High: CH40	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
Registration Number: 293961

July 25, 2017 Certificated by IC
Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	**Uncertainty**
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13dB(Polarize: H)
	4.16dB(Polarize: V)
Uncertainty for radio frequency	5.4×10-8
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2℃
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2022.08.22	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2022.08.22	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-102082-Wa	2022.08.22	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2022.08.22	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2021.08.30	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2021.08.30	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00059	2021.08.30	2Year
RF Cable	Resenberger	Cable 1	/	RE1	2022.08.22	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2022.08.22	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2022.08.22	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2022.08.22	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2022.08.22	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2022.08.22	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2022.08.23	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	/	00946	2021.08.30	2 Year
Preamplifier	SKET	LNPA_1840-50	/	SK2018101801	2022.08.22	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2022.08.22	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2022.08.22	1 Year
Temp. & Humid. Chamber	Teelong	WHTH-1000-40-880	/	TL-20191205-01	2022.07.28	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2022.08.22	1 Year
Adjustable attenuator	MWRFtest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	Farad	Alpha-3A1
CE	EZ-EMC	Farad	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. SPURIOUS EMISSION

3.1. Test Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

NOTE:

a) The tighter limit applies at the band edges.
b) Emission Level(dB uV/m)=20log Emission Level(uv/m)

3.2. Test Procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GH and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation

The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured

If Peak value comply with QP limit Below 1GHz.The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.

3.3. Test Setup



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHZ~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the 10th harmonic from 9 kHz to the EUT.

Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: 1.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2. Only show the test data of the worst Channel in this report.

Antenna polarity: Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		159.9900	20.54	15.04	35.58	43.50	-7.92	QP			
2		165.0038	22.84	14.56	37.40	43.50	-6.10	QP			
3		254.9964	26.69	12.87	39.56	46.00	-6.44	QP			
4		527.9989	22.06	18.81	40.87	46.00	-5.13	QP			
5		720.0406	18.82	22.02	40.84	46.00	-5.16	QP			
6	*	816.0632	17.99	23.11	41.10	46.00	-4.90	QP			

Note:1. *:Maximum data; x:Over limit; !:over margin.
2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Antenna polarity: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		164.9846	22.89	14.56	37.45	43.50	-6.05	peak			
2		254.9965	23.30	12.87	36.17	46.00	-9.83	peak			
3		404.9978	18.20	16.36	34.56	46.00	-11.44	peak			
4		527.9989	19.74	18.81	38.55	46.00	-7.45	QP			
5		640.0123	18.54	20.97	39.51	46.00	-6.49	peak			
6	*	795.0670	17.26	22.87	40.13	46.00	-5.87	QP			

Note:1. *:Maximum data; x:Over limit; !:over margin.
2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Notes: Above is below 1GHz test data. This report only shall the worst case mode for TX 2402MHz.

From 1G-25GHz

Test Mode: TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	47.69	V	33.95	10.18	34.26	57.56	74	-16.44	PK
4804	39.13	V	33.95	10.18	34.26	49.00	54	-5.00	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	43.34	H	33.95	10.18	34.26	53.21	74	-20.79	PK
4804	36.60	H	33.95	10.18	34.26	46.47	54	-7.53	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: TX Mid									
4880	41.57	V	33.93	10.2	34.29	51.41	74	-22.59	PK
4880	36.40	V	33.93	10.2	34.29	46.24	54	-7.76	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
4880	44.13	H	33.93	10.2	34.29	53.97	74	-20.03	PK
4880	34.90	H	33.93	10.2	34.29	44.74	54	-9.26	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
Test Mode: TX High									
4960	42.97	V	33.98	10.22	34.25	52.92	74	-21.08	PK
4960	36.18	V	33.98	10.22	34.25	46.13	54	-7.87	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	43.85	H	33.98	10.22	34.25	53.80	74	-20.20	PK
4960	34.72	H	33.98	10.22	34.25	44.67	54	-9.33	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:
1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Conducted RF Spurious Emission

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Date: 7.JUL.2023 11:47:41

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.397 GHz	-4.71 dBm		
M2		1	5.8534 GHz	-33.57 dBm		
M3		1	4.6887 GHz	-34.72 dBm		
M4		1	7.2034 GHz	-36.94 dBm		
M5		1	9.718 GHz	-36.39 dBm		

Date: 7.JUL.2023 11:47:59

Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



Date: 7.JUL.2023 11:51:19

Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	-5.45 dBm		
M2		1	6.9916 GHz	-32.69 dBm		
M3		1	4.7946 GHz	-34.54 dBm		
M4		1	7.2034 GHz	-36.40 dBm		
M5		1	9.8239 GHz	-35.46 dBm		

Date: 7.JUL.2023 11:51:37

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref

Date: 7.JUL.2023 11:52:53

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476 GHz	-6.53 dBm		
M2		1	6.9651 GHz	-33.18 dBm		
M3		1	4.9269 GHz	-35.67 dBm		
M4		1	7.5475 GHz	-37.00 dBm		
M5		1	9.8504 GHz	-36.46 dBm		

Date: 7.JUL.2023 11:53:11

Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref

Date: 7.JUL.2023 11:56:44

Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.397 GHz	-6.35 dBm		
M2		1	19.9354 GHz	-38.02 dBm		
M3		1	4.9799 GHz	-41.15 dBm		
M4		1	7.0446 GHz	-41.65 dBm		
M5		1	9.7974 GHz	-41.33 dBm		

Date: 7.JUL.2023 11:57:02

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref

Date: 7.JUL.2023 12:00:11

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	-7.37 dBm		
M2		1	18.3208 GHz	-37.66 dBm		
M3		1	5.0593 GHz	-40.76 dBm		
M4		1	7.1504 GHz	-42.05 dBm		
M5		1	9.8768 GHz	-40.19 dBm		

Date: 7.JUL.2023 12:00:29

Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref

Date: 7.JUL.2023 12:02:33

Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476 GHz	-9.11 dBm		
M2		1	15.8591 GHz	-36.43 dBm		
M3		1	5.0328 GHz	-40.62 dBm		
M4		1	7.5475 GHz	-41.99 dBm		
M5		1	9.8504 GHz	-40.75 dBm		

Date: 7.JUL.2023 12:02:51

4. POWER LINE CONDUCTED EMISSION

4.1. Test Limits

Frequency	Limits dB(μV)	
MHz	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.
3. The limit decreases in line with the logarithm of the frequency in rang of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.
The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup



4.4. Test Results

Pass

Polarity: L



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4680	31.66	9.83	41.49	56.55	-15.06	peak	
2	*	0.5010	36.29	9.83	46.12	56.00	-9.88	peak	
3		0.9750	26.69	9.84	36.53	56.00	-19.47	peak	
4		2.0310	26.99	9.76	36.75	56.00	-19.25	peak	
5		3.2010	26.61	9.81	36.42	56.00	-19.58	peak	
6		18.3210	21.35	10.09	31.44	60.00	-28.56	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Polarity: N



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4650	30.09	9.83	39.92	56.60	-16.68	peak	
2	*	0.5039	34.15	9.83	43.98	56.00	-12.02	peak	
3		1.0170	25.06	9.84	34.90	56.00	-21.10	peak	
4		2.0940	26.25	9.76	36.01	56.00	-19.99	peak	
5		5.4000	24.05	9.90	33.95	60.00	-26.05	peak	
6		17.8530	25.36	10.09	35.45	60.00	-24.55	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Note: All modes and channels have been tested and only the BLE 2402MHz(1Mbps) mode with the worst data is listed.

5. CONDUCTED MAXIMUM OUTPUT POWER

5.1. Test limits

Please refer section RSS-247 & 15.247.

5.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.3. Test Setup



5.4. Test Results

GFSK(1M)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-4.839	0	-4.839	30	Pass
NVNT	BLE 1M	2440	Ant1	-4.778	0	-4.778	30	Pass
NVNT	BLE 1M	2480	Ant1	-5.711	0	-5.711	30	Pass

GFSK(2M)

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 2M	2402	Ant1	-4.265	0	-4.265	30	Pass
NVNT	BLE 2M	2440	Ant1	-4.371	0	-4.371	30	Pass
NVNT	BLE 2M	2480	Ant1	-5.086	0	-5.086	30	Pass

6. PEAK POWER SPECTRAL DENSITY

6.1. Test limits

6.1.1 Please refer section RSS-247 & 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

6.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.

6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as RBW = 3kHz(Set the RBW to: 3 kHz≤RBW≤100 kHz.), VBW = 10kHz(Set the VBW≥3×RBW), span=1.5×DTS bandwidth., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

6.3. Test Setup



6.4. Test Results

Pass

The test results are listed in next pages.

GFSK (1M)

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-19.418	8	Pass
NVNT	BLE 1M	2440	Ant1	-19.175	8	Pass
NVNT	BLE 1M	2480	Ant1	-20.183	8	Pass

PSD NVNT BLE 1M 2402MHz Ant1



Date: 7.JUL.2023 11:47:22

PSD NVNT BLE 1M 2440MHz Ant1



Date: 7.JUL.2023 11:51:12

PSD NVNT BLE 1M 2480MHz Ant1



Date: 7.JUL.2023 11:52:32

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 2M	2402	Ant1	-21.298	8	Pass
NVNT	BLE 2M	2440	Ant1	-21.121	8	Pass
NVNT	BLE 2M	2480	Ant1	-21.862	8	Pass

PSD NVNT BLE 2M 2402MHz Ant1



Date: 7.JUL.2023 11:56:25

PSD NVNT BLE 2M 2440MHz Ant1



Date: 7.JUL.2023 12:00:04

PSD NVNT BLE 2M 2480MHz Ant1



Date: 7.JUL.2023 12:02:12

7. BANDWIDTH

7.1. Test limits

Please refer section RSS-247 & 15.247

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

b) The test receiver set RBW = 100kHz, VBW≥3*RBW =300kHz, sweep time set auto, detail see the test plot.

7.3. Test Setup



7.4. Test Results

GFSK(1M)

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant 1	1.028	0.72	0.5	Pass
NVNT	BLE	2440	Ant 1	1.028	0.673	0.5	Pass
NVNT	BLE	2480	Ant 1	1.034	0.687	0.5	Pass

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



Date: 7.JUL.2023 11:47:15

-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



Date: 7.JUL.2023 11:51:03

-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



OBW NVNT BLE 1M 2402MHz Ant1



OBW NVNT BLE 1M 2440MHz Ant1



Date: 7.JUL.2023 11:50:53

OBW NVNT BLE 1M 2480MHz Ant1



Date: 7.JUL.2023 11:52:14

GFSK(2M)

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant 1	2.046	1.146	0.5	Pass
NVNT	BLE	2440	Ant 1	2.034	1.371	0.5	Pass
NVNT	BLE	2480	Ant 1	2.042	1.101	0.5	Pass

-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



Date: 7.JUL.2023 11:59:56

-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1



Date: 7.JUL.2023 12:02:02

OBW NVNT BLE 2M 2402MHz Ant1



Date: 7.JUL.2023 11:56:10

OBW NVNT BLE 2M 2440MHz Ant1



Date: 7.JUL.2023 11:59:46

OBW NVNT BLE 2M 2480MHz Ant1

8. BAND EDGE CHECK

8.1. Test limits

Please refer section RSS-GEN&15.247.

8.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

8.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

8.2.2 Check the spurious emissions out of band.

8.2.3 RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 3MHz, RMS detector for AV value.

8.3. Test Setup

Same as 5.2.2.

8.4. Test Results

Pass
The test results are listed in next pages.

GFSK (1M)

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Date: 7.JUL.2023 11:47:29

Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40195 GHz	-5.55 dBm		
M2		1	2.4 GHz	-49.02 dBm		
M3		1	2.39 GHz	-50.30 dBm		
M4		1	2.3778 GHz	-46.27 dBm		

Date: 7.JUL.2023 11:47:34

Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Date: 7.JUL.2023 11:52:40

Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48005 GHz	-6.56 dBm		
M2		1	2.4835 GHz	-48.25 dBm		
M3		1	2.5 GHz	-49.35 dBm		
M4		1	2.4977 GHz	-45.67 dBm		

Date: 7.JUL.2023 11:52:45

GFSK (2M)

Band Edge NVNT BLE 2M 2402MHz Ant1 Ref

Date: 7.JUL.2023 11:56:32

Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40205 GHz	-5.64 dBm		
M2		1	2.4 GHz	-38.09 dBm		
M3		1	2.39 GHz	-54.12 dBm		
M4		1	2.3875 GHz	-51.33 dBm		

Date: 7.JUL.2023 11:56:37

Band Edge NVNT BLE 2M 2480MHz Ant1 Ref

Date: 7.JUL.2023 12:02:20

Band Edge NVNT BLE 2M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47945 GHz	-5.57 dBm		
M2		1	2.4835 GHz	-54.05 dBm		
M3		1	2.5 GHz	-54.42 dBm		
M4		1	2.4843 GHz	-51.41 dBm		

Date: 7.JUL.2023 12:02:25

Radiated Method: GFSK(1M)

Test Mode: CH-L



Test Mode: CH-H



Radiated Method: GFSK(2M)

Test Mode: CH-L



Test Mode: CH-H



9. ANTENNA REQUIREMENT

9.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2. Antenna Connected Construction

The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.

9.3. Results

The EUT antenna is Internal Antenna. It complies with the standard requirement.

10. TEST SETUP PHOTO

10.1.Photo of Radiated Emission test





10.2.Photo of Conducted Emission test



------END OF REPORT-------