



规格承认书

SPECIFICATION FOR APPROVAL

日期
Date 2026/03/13

编号
File No 26031301

版本
Revision 1.0

客户
CUSTOMER:

视声智能

客户料号
CUSTOMER NO:

品名
PART NAME:

WIFI双频 Antenna L=45mm MHF

供方料号
SUPPLIER NO:

YJL01.098.005.302A

送样日期Date:

送样数量Q'TY:

客户确认CUSTOMER APPROVED BY

APPROVAL

CHIEF

SUPERVISOR

供方确认 SUPPLIER SIGNATURE

APPROVAL

CHECK

DESIGN

ChenGuoqiang

ZhangLiqun

LiaoGuangxi

YJ-RD-F04-A





承认书项目表


NO.	内 容 (Contents)	页 数 (Number of Page)	页 码 (Page Code)
1	承认书封面 (Spec Cover)	1	1
2	承认书项目表 (Spec Item)	1	2
3	工程成品图 (Drawing)	1	3
4	天线规格 (Antenna Specification)	1	4
5	S参数测试 (S Parameter)	1	5
6	无源测试 (Passive Test)	3	6 ~ 8
7	方向图 (Radiation Pattern)	3	9 ~ 11
8	有源测试 (Active Test)	1	12
9	天线装配图 (Antenna Profile)	2	13 ~ 14
10	材质证明 (Material Certificate)	30	15 ~ 44
11	RoHS报告 (RoHS Test Report)	**	**
12	N/A	N/A	N/A
13	-	-	-



RoHS
Compatible

CUSTOMER	
PART NO	

REV.	DESCRIPTION	DATE
△	首次发行	2026-03-10



PART NAME: WIFI双频 Antenna L=45mm MHF

PART NO.: YJL01.098.005.302A

DATE: 2026-03-10

APPROVED BY

CHECKED BY

DESIGNED BY



Tolerance
X.X ±0.50
X.XX±0.15
X° ±3°

何清军

林斌

廖光喜

UNITS: mm

SCALE: 1/1

REVISION: A

3	FPC	40.0*10.4mm	FPC	1
2	Coaxial Cable	O.D.1.13 Black	O.D.1.13	1
1	Mini Connector	Au Plated 1代	Cu	1
NO	PART NAME	DESCRIPTION	Material	Q.TY



天线规格 Antenna Specification

Electrical Properties

Frequency	2.4-2.5GHz 5.15-5.85GHz
Impedance	50 Ohm Nominal
V.S.W.R	2.0 Max@2.4-2.5GHz 2.5 Max@5.15-5.85GHz
Gain	4.3 dBi@2.4-2.5GHz 4.5 dBi@5.15-5.85GHz
Radiation	Omni-directional
Polarization	Linear

Physical Properties


Connector	IPEX-1
Cable Type	O.D.1.13mm
Cable Length	45mm
Cable Color	Black
Operating Temp.	-40 ~ +85 °C
Storage Temp / Humidity	25±5°C / <70%







Antenna Performance Test

*Agilent
E5071C
S
Parameter
Test //
WiFi
Antenna*





Antenna Passive Test





Passive Test For WiFi Antenna

Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	58.2	-2.4	3.8
2410	54.5	-2.6	3.5
2420	59.2	-2.3	4.0
2430	57.7	-2.4	4.0
2440	56.9	-2.5	3.8
2450	63.4	-2.0	4.3
2460	57.3	-2.4	3.9
2470	57.4	-2.4	3.9
2480	59.2	-2.3	3.9
2490	55.1	-2.6	3.6
2500	58.8	-2.3	3.8






Passive Test For WiFi Antenna

Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
5150	47.9	-3.2	3.0
5200	46.5	-3.3	3.2
5250	50.1	-3.0	3.0
5300	48.2	-3.2	3.1
5350	54.2	-2.7	3.4
5400	51.8	-2.9	3.8
5450	56.0	-2.5	4.0
5500	51.4	-2.9	3.4
5550	64.1	-1.9	4.4
5600	56.8	-2.5	3.9
5650	51.8	-2.9	4.0
5700	52.2	-2.8	3.8
5750	59.7	-2.2	4.5
5800	55.1	-2.6	4.3
5850	57.4	-2.4	4.4






Radiation Pattern For WiFi Antenna






Radiation Pattern For WiFi Antenna






Radiation Pattern For WiFi Antenna


Phi 0°



Phi 90°



Theta 90°





Antenna Active Test

Active Test For WIFI

Band	Channel	Data Rate	TRP	EIRP	Data Rate	TIS	EIS
WIFI 2.4G 802.11b	1	11Mbps	13.4	18.6	11Mbps	-58.7	-63.7
	6		13.9	18.7		-59.2	-64.0
	11		13.3	18.3		-58.8	-63.8
WIFI 5G 802.11a	36	54Mbps	13.0	16.5	54Mbps	-75.1	-78.8
	149		6.3	11.0		-74.3	-78.7
	165		7.5	13.0		-75.0	-78.6

*红色部分数据异常，排查后为模组传导问题导致。





东莞市一佳电子通讯科技有限公司
DONGGUAN YIJIA ELECTRONICS COMMUNICATION TECHNOLOGY CO., LTD

Device




*WiFi
Antenna*



东莞市长安镇沙头社区木鱼路59号 Tel:0769-82586086 Fax:0769-82586086



WiFi Antenna



物质安全资料表

MSDS C5100,C5191,C5210,C5240

物质安全资料表编号：MCL001	改版日期：02-15-2015
版次：4	前次改版：02-20-2008

1. 物质供应商资料

物品中(英)文名称：	磷青铜(PHOSPHOR BRONZE ALLOYS)		
物品代码：	JIS C5100,C5191,C5210,C5240		
化学名称：	铜(Cu)-锡(Sn) 金属合金		
类别：	铜金属合金		
制造商或供应商名称：	福建紫金铜业有限公司		
制造商或供应商地址：	福建省龙岩市上杭县南岗开发区		
制造商或供应商电话：	0597-3960633	传真：	0597-3833128
制造商或供应商网址：	www.fjzjty.com		
紧急联络电话：	0597-3960600		

2. 成品成分

C5100	CAS编号	化学名称	重量比例%
	7440-50-8	铜(Cu)	>93.65
	7440-31-5	锡(Sn)	4.5~5.5
	7723-14-0	磷(P)	0.03~0.35

C5191	CAS编号	化学名称	重量比例%
	7440-50-8	铜(Cu)	>92.15
	7440-31-5	锡(Sn)	5.5~7.0
	7723-14-0	磷(P)	0.03~0.35

C5210	CAS编号	化学名称	重量比例%
	7440-50-8	铜(Cu)	>90.0
	7440-31-5	锡(Sn)	7.0~9.0
	7723-14-0	磷(P)	0.03~0.35
	7440-66-6	锌(Zn)	<0.20
	7439-92-1	铅(Pb)	<0.05
	7439-89-6	铁(Fe)	<0.10

C5240	CAS编号	化学名称	重量比例%
	7440-50-8	铜(Cu)	>90.15
	7440-31-5	锡(Sn)	9~11
	7723-14-0	磷(P)	0.03~0.35

OSHA 管理状态：在固体时不具危害性。其粉尘及烟对肺脏、血液、肾脏具有致癌、刺激性。反复产生之毒性及神经性毒素

OHSA：本合金产品在固体时不具危害性。其粉尘及烟具有危害性。

(美国) 职业安全卫生署 OSHA

3. 危害辨识资料

警告！ 暴露于粉尘及烟的工作环境下，对于眼睛、呼吸系统、皮肤会造成刺激伤害。其含有金属可能对血液、肾脏产生反复性及神经性之影响，也可能致癌。必须保持足够且良好之通风。避免直接接触眼睛、皮肤及衣物。佩戴保护器具，包括护目镜、适当衣物，必须要保证全部身体。身体及衣物被接触之部位，必须彻底清洗干净。	
种类的名称：	铜、锡之金属混合物。
危险标识类别：	金属粉尘或烟将对皮肤、眼睛造成刺激性且对肺具有毒性，但金属合金本身不具危害性。
HMIS 危害级数（粉尘及烟）：	健康：2；可燃性：0（0=低、4=极高）； 物性危害：无
IDLH 对生命或健康有立即性危害浓度值	IDLH(3/1/95)无本金属立即性危险浓度数值。 铜(Cu)粉尘或烟、铅(Pb)、锡(Sn)：100 mg / m ³ 磷(P)：5 mg/m ³ 氧化铁(Fe)粉尘或烟：2500 mg / m ³ 氧化锌：500 mg / m ³

Hazardous Materials Identification System (HMIS)

严重症状：

眼睛：其粉尘或烟皆具刺激性，会引起红肿及疼痛。经常暴露于此环境时，可能导致结膜炎。

皮肤：此物质不会经由皮肤渗入体内被吸收。但接触其粉尘时，皮肤有可能会引起轻微刺激而出现红肿现象。

吸入：吸入人体是有害的。吸入高浓度粉尘或烟可能会导致剧烈呼吸、鼻刺激、咳嗽、呼吸困难。吸入高浓度铜金属粉尘或烟也可能出现呕心、呕吐及胃痛现象。金属烟可能引起类似流行性感（flu-like）症状之金属烟热；其症状包括喉咙不适、呼吸困难、咳嗽、哮喘、呕吐、头痛、发冷、发热、肌痛、虚弱、昏睡、流汗、关节痛。这些症状通常会在24小时后消失，但也有可能更长时间。

食入：大量食入粉尘时，可能引起呕心、腹泻及胃痛现象。

慢性影响：皮肤长期或者重复性接触其粉尘时可能引起剧烈刺激或皮肤炎。长期或者重复性吸入其粉尘或烟会导致更剧烈刺激。慢性暴露于铅中会引起人体肾脏损害、贫血症、复发性及成长性影响、永久性神经系统损害。

4. 急救措施

对于粉尘及烟危害：

眼睛接触：	以大量清净水冲洗上下眼睛内部（至少15分钟），若眼睛被刺激不适者，立即送医院检查
皮肤接触：	以清水清洗干净。衣物被接触之部位，必须彻底清洗干净后才能再穿戴。若仍有皮肤发生刺激、出疹现象或情况持续、复发时送至医院诊疗。
吸入时：	送至通风良好较阴凉处休息，以毛巾保暖，严重者迅速送医院检查诊断。
食入时：	大量喝水并催吐，迅速送医院检查

医疗提示：对于本产品组成之元素物质并无特殊解毒剂可供使用。必须视不同症状给予适当治疗。

5. 火灾及爆炸危害资料

燃烧性资料：

爆炸性：	无
可燃性：	无
燃烧性：	无
闪火点：	不适用
自燃性：	不适用

灭火剂：

小区域之材料粉末起火时，可适用干沙、干石灰粉、食盐或苏打粉给予关熄。其他周边处起火时需以适当灭火器灭火。

意外及爆炸危害：

注意粉尘可能导致爆炸或产生可燃性气体。

6. 泄露的处置

本产品在加工中产生粉尘时，有可能产生爆炸危害，必须将火源移除。也惟有粉尘型态时才可能产生泄露，所以必须装设通风设备及集尘装置过滤空气中之粉尘，以降低其粉尘浓度。

7. 取用及储运方式

取用注意事项：

板带产品之端面易割伤皮肤应小心取用。
切削加工时会产生粉尘应小心眼睛、皮肤及呼吸应佩戴保护器具。
小心粉尘不可泄露至空气中。
需注意产品有翻到之危险性易造成压伤，吊运时要十分注意。
打包带切除时，小心其末端会弹起，对人员之身体、皮肤及眼睛造成割伤。
衣物或器具上之粉尘以水洗或HEPA吸入器清淘，不可用拍打或其他方式处理。

储存条件：

食储最高容许温度：无
避免放置于潮湿或酸/碱性物质或酸/碱性气体之场所

8. 人员暴露防设措施

CAS 编号	暴露标准：	OSHA(PEL)	ACGIH(TLV)
铜(Cu) 7440-50-8	烟烟	0.1 mg/m ³	0.2 mg/m ³
	粉尘及雾状	1 mg/m ³	1 mg/m ³
锡(Sn) 7440-31-5	粉状	2 mg/m ³	2 mg/m ³
磷(P) 7723-14-0	-	0.1 mg/m ³	0.1 mg/m ³
锌(Zn) 7440-66-6	-	无资料	无资料
铅(Pb) 7439-92-1	粉尘及烟烟	0.05 mg/m ³	0.05 mg/m ³
铁(Fe) 7439-89-6	-	无资料	无资料

本产品材料若经加热会产生烟烟，氧化锌烟烟可能形成。

OSHA(PEL)以及 ACGIH(TLV)对氧化锌烟烟之限制值为 5 mg/m³

呼吸防设：	一般情况下不需佩戴口罩。但当超过上述PEL/TLV标准值时必须佩戴NIOSH认证之全罩或半罩式HEPA滤心防口罩。
通风防设：	工作场所中，若是会产生烟烟及粉尘时，必须要有通风设备装置及集尘装置，且工作中不可饮食及抽烟
眼睛及脸部防设：	需要佩戴护目镜。
皮肤防设：	作业时应穿着适当之工作服，安全鞋及防护手套，以避免皮肤与材料直接接触并防止割伤。

(美国) 职业安全卫生署OSHA(Occupational Safety and Health Administration)

(美国) 国家职业安全卫生研究所NIOSH(National Institute for Occupational Safety and Health)

立即对生命或健康有危险 IDLH(Immediately Dangerous to Life or Health)

时量平均浓度TWA(Time Weighted Average)：

容许暴露浓度值 PEL(Permissible Exposure Limit)

9. 物理及化学性质

外观：	浅红色光泽的固态金属
熔点：	C5100(950~1060℃), C5191(900~1045℃), C5210(870~1030℃), C5240(840~1020℃)
沸点：	无资料
比重：	C5100(8.86), C5191(8.83), C5210(8.80), C5240(8.7)
蒸气压：	不适用
溶解度：	不适用
PH 值 25℃：	不适用

10. 稳定性及活性资料

稳定性	在正常一般室温及大气下为稳定性物质，非活性物质。
应避免之状况	遭受机械撞击或通电时并不会产生化性反应。
应避免之材料	氯：与金属黄铜、铜细分应形成剧烈或爆炸性反应。 乙炔：与黄铜形成爆炸性化合物。
危害之分解物	当加热至分解温度时，会产生金属氧化物和金属烟。有可能引起类似流行性感冒（flu-like）症状之金属烟热。
危害之聚合反应	无。

11. 毒性资料

潜在之暴露途径：

粉尘：食入、皮肤接触、吸入、眼睛接触。

烟：吸入、眼睛接触。

本合金产品不具毒性。

动物急毒性资料：动物半致死剂量 (LD₅₀)及浓度(LC₅₀)

针对本合金产品之粉尘或烟	铜 (Cu)	锡 (Sn)	磷 (P)	锌 (Zn)	铅 (Pb)	铁 (Fe)
口服 (LD ₅₀)	3.5mg/Kg(鼠，腹腔内)	无资料	无资料	无资料	无资料	30mg/Kg(鼠)
皮肤 (LD ₅₀)	375mg/Kg(兔，皮下注射)	无资料	无资料	无资料	无资料	无资料
吸入 (LC ₅₀)	无资料	无资料	无资料	无资料	无资料	无资料

亚慢性及慢性毒性：本合金产品不具毒性。铅对实验室中动物之血液、肾脏及神经系统会造成损害。

致癌性：本合金产品尚未被报告具致癌性。铅被 IARC(International Agency for Research on Cancer) 列入对人头可能致癌，属2B类

致基因突变型：本合金产品尚未被报告具致基因突变性。铅则在数项细胞体外试验中显示有致基因突变性。

复发性及成长性影响：本合金产品不具复发性及成长性影响。铅会导致实验室中动物之脱臼发育，包括天生畸形缺陷及影响雄性生殖能力。

神经性影响：本合金产品尚未被报告具有神经性影响。铅会导致实验室中动物之中枢、末梢神经系统损伤及行为影响。

12. 生态资料

本合金产品对生态之毒性：无资料

其单一成分之毒性说明如下：

生态毒性 ecotoxicity：水中的溶解度，在 0.1~1.0mg/l 范围内已被许多研究者证实对大多数鱼类不具有毒性。但浓度在 0.015-3.0mg/l 时，尤其在软水中，会有报告会对许多种类的鱼、甲头类的动物及软体动物、浮游生物具有毒性。
铅对大翻车鱼(Bluegill)/蓝思鱼(Lepomis macrochirus)LC₅₀(48Hrs)资料为 2~5mg/l。铅对水鸟类皆具毒性。

流动性：分解的铅会对转移入土壤内。

持续性/可分解性：铅在环境中会持续且累积。

生态累积性 (Bioaccumulation):无资料。

13. 废弃处理

本合金产品不属于危害性废弃物：须丢弃时可以委托当地回收商予以回收再生利用。

14. 运输资料

USA DOT：未被列入。

运输时本产品不要直接与水接触，并且要注意会滑落、翻落得危险发生

15. 法规资料

通常无特定法令规定，但是在会产生粉尘的场所必须遵守劳工安全卫生法劳工作业环境空气中有害物质容许浓度标准

USA/OHSA：Occupational Safety & Health Administration

USA/ACGIH Guide to protective Clothing. Cincinnati, OH:American Conference of Government Industrial Hygienists,1987

USA/SARA313

16. 其他资料

初版：04-28-2008

制表单位：福建紫金铜业有限公司

注意：本MSDS内容资料应被所有使用、运送、储存或暴露于本合金产品之公司/人员

充分了解并接受并将其应用于使用、加工、制造或管理与本合金产品有关之相关作业规定上；使用者请依应用需求，自行判断其可用性。本MSDS资料内容在编订时已经可能将最新之资料纳入，但对所有内容并不予以任何保证。

物质安全资料表 Material Safety Data Sheet (MSDS)

电镀金层

Gold Plating

一、 外观：表面金黄色，无污染物。

Appearance: Golden surface & no contaminants.

二、 标 示：参照欧盟 ROHS无铅规格之规范提示。

Symbol: Refer to EU ROHS Lead-free Specification

三、 特性：光亮均匀 。

Characteristic: bright & uniform.

四、 用途：提高基材焊接性能、防护性、耐磨性，降低接触阻抗。

Purpose: Improve the weldability, protection and wear resistance of the base metal, and reduce the contact impedance.

五、 规 格：符合欧盟ROHS要求。

SPEC: Conform to EU ROHS requirements

六、 物理性质PHYSICAL PROPERTIES:

(1) 液相温度：约1064℃。

LIQUIDUS TEMPERATURE: About 1064℃

(2) 比重：17.6 g/cm³(25℃)。

SPECIFIC GRAVITY: 17.6 g/cm³(25℃)

物质安全资料表 Material Safety Data Sheet (MSDS)

七、 物品与厂商资料 Items and Manufacturer information

物品名称：无铅电镀金层 Item Name: Lead-free gold plating			
物品编号：KSYTAu-001 Item No:			
制造厂商： 翊腾电子科技（昆山）有限公司 Manufacturer: YTOP Electronic Technology (Kunshan) Co.,Ltd.			
制作部门：PBU工程部 Prepared Dept.: Engineering Dept PBU	制作日期：2013.05.14 Prepared Date:	版本 Revision No.	V1.4
文件编号：YT-MSDS-AU File No.:	修改日期：2022-6-8 Revised Date:	有效期 Validity period	3年 3 years
联络电话： Tel: +86-512-55101900 Fax: +86-512-55101905			

八、 主要成份资料 Main Composition:

中（英）文名称 Chinese (English) Name	化学式 Chemical formula	含量(WT%) Content(WT%)	化学文摘社登记号码 (CAS NO)
金 (Gold)	Au	>99.7	7440-57-5
钴 (Cobalt)	Co	0.15-0.3	7440-48-4

九、 危害性资料 Harmfulness Information:

本产品是根据在欧盟立法之WEEE及ROHS要求、美国环保局（ENA）禁止使用铅和镉（及其衍生物）之相关规定而开发之环保产品，电镀层合金成份中含铅量（其产品关键之两个参数之一,Wt%）≤90PPM。此项要求能保证不对人体及环保产生直接性危害，故其危害性并无更深入之资料。

This green product is developed in accordance with the requirements of WEEE and ROHS in EU legislation and the relevant regulations of ENA prohibiting the use of lead and cadmium (and its derivatives). Lead content (Wt%) of electroplated alloy composition, one of two key

物质安全资料表 Material Safety Data Sheet (MSDS)

parameters of this product, is $\leq 90\text{PPM}$. This requirement can ensure that there is no direct harm to human and environmental protection. Therefore, there is no more in-depth information on its harmfulness..

十、 急救措施 First-aid Measures

使用过程中如遇下列情况, 请根据相应之指引进行处理:

If you encounter the following situations in the course of use, please deal with them according to the corresponding guidelines:

*吸入: 将患者移至有清新空气处; 如果患者已停止呼吸, 则施以人工呼吸, 送急诊。

Inhalation: Move the patient to a place with fresh air. If the patient has stopped breathing, apply artificial breathing and send to the emergency department.

*皮肤接触: /

Skin Contact

*眼睛接触: 以大量的清水冲洗15 分钟或者直到刺激感消失。如果刺激感仍存在, 则去医院救治。

Eye Contact: Rinse with plenty of water for 15 minutes or until irritation disappears. If irritation still exists, go to the hospital for treatment.

*食入: 不催吐(除非医疗人员指示); 如果患者仍有意识且清醒, 立即送诊。

Ingestion: Do not use emetic method (unless directed by a medical worker). If the patient is still conscious and awake, see the doctor immediately.

最重要症状及急害效应: 人体吸入金属粉末而超标导致神志不清。

Most Important Symptoms and Emergency Effects: Excessive inhalation of metal powder leads to unconsciousness.

对急救人员之防护: 无

Protection for First-Aid Personal: No

对医师之提示: 无

Tips to Doctors : No

十一、 灭火措施 Fire Extinguishing Measures

适用灭火剂: 水、泡沫、干粉及二氧化碳灭火剂。

Suitable extinguishing agent: Water, foam, dry powder and carbon dioxide fire extinguishing agent

灭火时可能遇到之特殊危害: 无相关资料可看。

Special hazards that may be encountered when extinguishing fire: No relevant information available.

特殊灭火程序: 不适用。

Special Fire Fighting Procedures: N/A

消防人员之特殊防护设备: 氧气筒及防护衣。

Special protective equipment for firefighters: Oxygen cylinder and protective clothing

十二、 泄露处理方法 Leakage Disposal Method

物质安全资料表 Material Safety Data Sheet (MSDS)

个人应注意事项：佩戴口罩并按规范要求进行作业（注意高温且有腐蚀性）。 Personal Attentions: Wear masks and work according to specifications (pay attention to high temperature and corrosiveness).
环境注意事项：勿使泄露面积扩大。 Environmental considerations: Do not widen the leak area.
清理方法：通风并清扫 Cleaning method: Ventilating and cleaning

十三、安全处置与储存方法 Safe disposal and storage methods

处置 Disposal: *阅读所有的容器标示。 Read all container labels. *工作场所内禁吃东西、喝饮料、抽烟及化妆。 No eating, drinking, smoking and makeup is allowed in the workplace. *使用完毕，操作者应用肥皂清洁双手。 After use, the operator needs to clean hands with soap.
储存： 避免高温及接触氧化剂、酸与过氧化氢等化学品。 Storage: Avoid high temperature and avoid contact with chemicals such as oxidants, acids and hydrogen peroxide.

十四、暴露预防措施 Exposure preventive measures

工程控制： 提供足够的机械式排气装置。 Engineering Controls: Provide enough mechanical exhaust devices.				
容许浓度Permissible concentration			生物指标Biological indicators	
时量平均容许浓度 (TWA)	短时间时量平均容许浓度 (STEL)	最高容许浓度 (Ceiling)	LD50 (测试动物、吸收途径)	LC50 (测试动物、吸收途径)
/	/	/	/.	/
个人防护设备Personal protective equipment: / 呼吸防护Respiratory protection: *一般使用：配戴口罩。 General use: Wear a mask. *紧急状态防护：粉尘或烟雾超过容许浓度时，应穿戴防粉尘、防烟雾的防毒面具。 Emergency protection : When dust or smoke exceeds the allowable concentration, gas masks should be worn to prevent dust and smoke. *眼睛防护：配戴安全眼镜及/或面罩（当有粉尘飘散或金属飞溅时）。 Eye protection: Wear safety glasses and/or masks (when dust or metal splashes are present).				

物质安全资料表 Material Safety Data Sheet (MSDS)

十五、 物理及化学资料 Physical and chemical data

物质状态：固体 Material state: Solid	PH 值：不适用 PH Value: N/A
形状：/ Shape: /	颜色：金黄色 Color: Golden
分子量：不适用 Molecular weight: N/A	熔点：1064 °C Melting point: 1064 °C
沸点：不适用 Boiling point: N/A	闪火点：不适用 Flash point: N/A
分解温度：/ Decomposition temperature: /	爆炸界限：不适用 Explosion boundaries: N/A
自然温度：不适用 Natural temperature: N/A	气味：无气味 Smell: Odorless
蒸气比重：（空气=1）：不适用 Vapor density: N/A	蒸汽压：不适用 Vapor pressure: N/A
密度：17.6 g/cm ³ Density: 17.6 g/cm ³	水中溶解度：不溶于水 Solubility in water: Insoluble in water

十六、 安定性及反应性 Stability and reactivity

安定性 Stability	安定Stable	适用 Applicable	特殊状况下可能之危害反应 Possible Harmful Reactions under Special Conditions	无 No
	不安定Unstable	不适用N/A		
危害分解物：无 Hazardous decomposition: None				
应避免之状况：高温。 Conditions to avoid: High temperature.				
应避免之物质：与酸、过氧化氢（H ₂ O ₂ ）等强酸性及强氧化性物质接触。 Substances that should be avoided: Contact with strong acidic and oxidizing substances such as acid and hydrogen peroxide（H ₂ O ₂ ）.				

十七、 毒性资料TOXICOLOGICAL INFORMATION:

（本项无法取得相关资料）--NIF（No Information Found）

急毒性Acute toxicity:
局部效应Partial effect:
致敏效应Sensitization effect:
慢毒性或长期毒性Chronic or long-term toxicity:

物质安全资料表 Material Safety Data Sheet (MSDS)

特殊效应Special effect:

12.运送资料 Transport Information

国际运送规定International Transport Regulations:

INTERNATIONAL MATERIAL DANGEROUS GOODS CODE LABEL

USA DOT SHIPPING LABEL:

DOT SHIPPING NAME:NON-HAZARDOUS MATERIAL

联合国编号：不适用

United Nations Number: N/A

国内运送规定：除依据操作及保管上应注意事项外，亦遵照有关铅中毒预防规则之注意事项。

Domestic transport regulations: In addition to matters needing attention in operation and storage, attention should also be paid to the regulations for the prevention of lead poisoning.

特殊运送方法及注意事项：无

Special transportation methods and matters needing attention: No

13. 法规资料 Regulation Data

劳动安全卫生法、废弃物清理法相关无铅环保法规

Labor Safety and Health Law, Waste Cleaning Law and Lead-free Environmental Protection Regulations

14、生态资料 Ecological data

可能之环境影响/环境分布：不需特别注意。

Possible environmental impact/distribution: No special attention is required.

15、废弃处置方法 Waste Disposal methods

废弃处置方法：属无害事业废弃物，在掩埋前先行固化

Waste disposal methods: It belongs to harmless industrial waste and solidifies before burying.

16、其它资料 Other data :

无 No

江阴凯博通信科技有限公司

环境有关物质材质证明书

Certification of the Raw Material of Environment Substance

公司名称 Company Name	江阴凯博通信科技有限公司	制造商名称 Manufacturer	江阴凯博通信科技有限公司	产品重量 Product Weight	3.1 g/m	
产品料号 Part No.	KB113/50-001D	产品名称 Product Name	RF1.13 银锡线 黑色	客户料号 P/N.		
填写人姓名/部门 Name / Dept.	徐琳/工程部	联络电话 Telephone	(0510-86070002)	E-Mail	kaibo@kaibocable.com	


兹证明向贵公司销售的产品和半成品中，使用之原材料，包装材料以及生产过程中，不含有贵公司规定的相关禁止使用物质。

另，向贵公司报告成品、半成品中使用的原材料、包装材料以及生产工程中的添加剂成分如下所述：

RoHS 及其它环保物质填写

项次 Item	零件 名称 Material Name	原料厂 Vendor	材质 Substance	重量(g) Weight	组成成份 Substance Composition	含百分比 (%)Substance Amount	化验报告 NO. Test Report No.	限用物质含量 (单位: PPM)											
								铅 (Pb)	镉 (Cd)	汞 (Hg)	六价铬 (Cr+6)	PBB	PBDE	SONY	PFOS	PFOA	PVC	卤素 (Cl、Br)	其它项目 Other substance
1.	导体	恒丰	镀银铜线	0.33	铜	10.46%	SHAEC25028332819	ND	ND	ND	ND	ND	ND	N/A	ND	N/A	N/A	N/A	
					银	0.19%													
2.	绝缘	巨化	FEP	0.75	FEP	24.19%	NGBPC26000015815 NGBPC26000015821	ND	ND	ND	ND	ND	ND	N/A	N/A	N/A	N/A	ND	
3.	编织	震雄	镀锡铜线	1.2	铜	38.32%	A2250642229101001	ND	ND	ND	ND	ND	ND	N/A	N/A	N/A	N/A	N/A	
					锡	0.39%													
4.	护套	巨化	FEP	0.82	FEP	21.16%	NGBPC26000015815 NGBPC26000015821	ND	ND	ND	ND	ND	ND	N/A	N/A	N/A	N/A	ND	
		见龙	FEP黑色		FEP	5.29%	A2250269592101001E	ND	ND	ND	ND	ND	ND	N/A	ND	ND	N/A	ND	

使用材料请贴图示于此栏，并标项次：



SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

- 1.1 Material Name: Flexible Copper-Clad Polyimide Laminates
1.2 Part Number: LPI-HF
1.3 Use of Material: Printed Circuit Boards
1.4 Date of Prepared: April 22nd, 2021
1.5 Company Identification: Jiu Jiang Flex Co., Ltd.
1210Qianjin Road (E) Jiujiang, Jiangxi, China 332006
1.6 Emergency Telephone Number: 86-792-8358899
1.7 Telephone Number for Information: 86-792-8358899, 8355813

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

Composition / substance		CAS#	%
PI	polyimide	25038-81-7	2.93~28.11
Adhesive	Epoxy resin	25036-25-3	2.42~6.81
	Flame Retardant (additive type)	225789-38-8	0.49~1.36
	Rubber	9003-18-3	1.45~3.99
Copper foil	Copper	7440-50-8	92.66~59.72

SECTION 3 HAZARDOUS IDENTIFICATION

Dust, soot, combustion gases produced when burning, of inhaled, ingested or absorbed through skin it will be harmful or irritating to the eyes, skin, mucous membrane, respiratory system, allergies can be caused to skin, flammable irritating and sensitive.

SECTION 4 FIRST-AID MEASURES (on Dust)**Inhalation:**

Remove to fresh air. Obtain medical attention if symptoms persist.

Eye Contact:

Flush immediately with large amounts of water. Do not rub eyes. Obtain medical attention if symptoms persist.

Skin Contact:

Wash area of contact thoroughly with soap and water. Do not rub or scratch. Obtain medical attention if symptoms persist.

Ingestion: Drinking water as much as possible, emetic, and see doctor.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Agents

Following extinguishing media can be used:

Carbon dioxide extinguisher

Dry powder fire extinguisher

Water Pump

Foam fire extinguisher

Hazards of Unusual burning and Explosion:

The material produces carbon monoxide, carbon dioxide, nitrogen, oxides of nitrogen, smoke and dust when extremely high temperature or burning.

Personal Protective Equipment

As in any burning, wear self-contained breathing apparatus and full protective gear.

Upper limit of Flammability: not ascertained

SECTION 6 EMERGENCY HANDLING OF LEAKAGE

Emergency handling:

Block the leakage area to avoid dust flying and wear protective equipment, use vacuum cleaner to clean the leakage.

SECTION 7 HANDLING AND STORAGE

Handling: Wear cotton gloves to protect product damage and hand lacerated.

Storage conditions

The material should be stored in dry, ambient temperature wrapped with PE film.

Environment: Keep away from heat, ignition sources, and direct sunlight.

Other conditions: Keep cartons tightly closed when not in use.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection:

No general requirements. If the occurrence of dust, gas or smoke processing or processing, is stimulating to employees, to use NIOSH/MSHA approved respiratory protection measures. Engineering control should be excluded from the need for respiratory support.

Ventilation:

Once air exhaust exposure exceeds limits, or visible smoke, dust, exhaust gas, the ventilation at site should be accompanied by all the heat process at the same time.

Mechanical operations:

Optimize and follow good industrial operation as possible as you can.

Eye Contact:

With eye-glasses on during all process

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	PI film Copper-Clad Laminate with adhesive
Physical State:	solid
PH:	Not Applicable
Melting point:	no data
Relative density (water =1):	more than 1
Boiling point:	no data
The relative vapor density (air =1):	more than 1
Saturated vapor pressure (kPa):	Not Applicable
Heat of combustion (kJ/mol):	no data
The critical temperature (c):	Not Applicable
The critical pressure (MPa):	Not Applicable
The octanol / water partition coefficient of numerical:	Not Applicable
Flash point (°C):	Not Applicable
Upper explosive limit% (V/V):	Not Applicable
Ignition temperature (c):	no data
The lower limit of explosion% (V/V):	Not Applicable
Solubility:	insoluble
Application:	used for making printed circuit board

SECTION 10 STABILITY AND REACTIVITY

Stability:

Storage for one year at 5°C to 30°C and RH less than 75%

Conditions to Avoid:

High Humidity, direct sunlight,

The copper side may have violent reaction with followings:

Acetylene, ammonium nitrate, bromide, chlorate, iodic acid, chlorine, ClF_3 , $\text{Pb}(\text{N}_3)_2$, $(\text{Cl}_2+\text{OF}_2)$, ethylene oxide, fluoride, hydrogen peroxide, nitric acid hydrazide, hydrazoic acid, H_2S , K_2O_2 , NaN_3 , Na_2O_2 .

SECTION 11 TOXICOLOGICAL INFORMATION

Sensitization: Long time skin contact may cause dermatitis

Acute Poisoning: Inhalation of dust may cause thirst, fever, headache, weakness, symptom of respiratory disorders.

SECTION 12 ECOLOGICAL INFORMATION

Normal condition: No big influence may caused to ecology.

Waste Disposal Method

To dispose based on local, state or national laws.

Tank treatment: Not applicable.

SECTION 13 DISPOSAL CONSIDERATION

Hazardous wastage: NO.

Waste Disposal Method

To bury or burn at specified place based on national laws.

SECTION 14 TRANSPORTATION INFORMATION

No special regulation on this product for domestic or international transportation.

SECTION 15 REGULATORY INFORMATION

Must be complied with domestic or local regulation

SECTION 16 REGULATORY INFORMATION

14.1 INTERNATIONAL REGULATIONS:

EU Directive 2011/65/EU (RoHS): Compliant

SECTION 17 OTHER INFORMATION

Issued by: QC Department of Jiu Jiang Flex Co., Ltd

Disclaimer:

The data sheet information is true and accurate, but all statements and recommendations do not contain any guarantee. The consequence of the material shall be from practice. This report does not include all the circumstances that the user may encounter during operation. Each aspect of the operation may be increased or decreased during operation. All health and safety information contained in this report shall be submitted to you employees and customers. Users are responsible to take appropriate measures in practical operations.

Material Safety Data Sheet

ITEM : PSM-800@ /SMH-800

Identity (Trade Name As Used On Label)

SECTION 1 IDENTIFICATION

Manufacturer

UNIRES CHEMICAL INDUSTRIAL CO.,LTD.

Address

22CHING CHIAN 4thRD.KUANYIN INDUSTRIAL

DISTRICT TAOYUAN HSIEN TAIWAN

Phone Number (For Information)

886-3-4836651 (fax)886-3-4837487

Emergency Phone Number

Telex * **886-3-4836651**

MSDS Number* **20110701AAA**

CAS Number*

07/01/2011

Data Prepared

HUANG CHIN HUAI

Prepared By*

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS No.	CONTENTS(%)	OSHA (PEL)	ACGIH (TLV)
Heavy aromtic naphtha(petroleum)	64742-94-5	<12%	N.D.	N.D.
Epoxy-Acrylic derivative	Trade secret	<48%	N.D.	N.D.
Barium sulfate	7727-43-7	<20%	dust 15mg/m3	10mg/m3
Silica, amorphous, fused	7631-86-9	<8%	N.D.	dustTLV10mg/m3
Dipropylene glycol methyl ether	34590-94-8	<12%	100ppm	200ppm

SECTION 3 HAZARDS IDENTIFICATION

INHALATION : Highly concentrated vapor irritates nose, throat ant and lungs. May cause headache and dizziness.

EYE CONTACT : Slight irritation

SKIN CONTACT : Slight irritation

INGESTION : Harmful, if swallowed.

SECTION 4 FIRST AID MEASURES

SKIN CONTACT : Wash with plenty of water using a soap. Do not use organic solvents.

EYE CONTACT : Rinse immediately with clean water for at least 15 minutes. If irritation persists, seek medical attention

INHALATION : Immediately carry the victim to a place where fresh air is available. If irritation persists, treat with oxygen and seek medical attention.

INGESTION :obtain medical advice immediately. It is not recommended that vomiting be induced except on medical advice

SECTION 5	FIRE-FIGHTING MEASURES
------------------	-------------------------------

SUITABLE EXTINGUISHING MEDIA	: Carbon dioxide, foam, powder.
UNSUITABLE EXTINGUISHING MEDIA	: water spray and water jet.
EXPOSURE HAZARDS	: Burning may release oxides of carbon, nitrogen, sulfur and other toxic gases or vapors. Do not release chemically contaminated water into drains or surface waters, and soil according to local regulations.
PROTECTIVE EQUIPMENT	: Use full protective clothing and self-contained breathing apparatus.
FIR FIREFIGHTERS MEASURES	: promptly move transferable containers to another safety area .Check the speed of fire. Extinguish the fire with suitable extinguisher from the windward side

SECTION 6	ACCTDENTAL RELEASE MEASURES
------------------	------------------------------------

PERSONAL PRECAUTION	: Avoid ignition sources. Avoid contact with skin, eyes and clothing. Avoid inhaling vapor.
ENVIRINMENTAL PRECAUTIONS	: Prevent contamination of soil, drains and surface waters
METHODS FOR CLEANING	: Scoop up or absorb into combustible material, wipe out a stain in use organic solvents. Dispose in accordance with local regulations.

SECTION 7	HANDLING AND STORAGE
------------------	-----------------------------

HANDLTNG	: Handle with care. Avoid ignition sources. Ensure good ventilation and local exhaust. Do not smoke at the workplace
STORAGE	: Store in the original sealed container at less than 20°C.Avoid direct exposure to UV and sunlights.

SECTION 8	EXPOSURE CONTROLS/PERSINAL PROTECTION
------------------	--

People who know they are chemically sensitive, should avoid contact with this product.

TECHNICAL PROTECTIVE MEASURES	: No special safety measures required.
EXPOSURE CONTROL LIMITS	: (see PEL and TLV values shown in shown in section 2)
RESPIRATORY PROTECTION	: Wear suitable mask to avoid inhalation of vapor.
HAND PROTECTION	: wear chemical resistant gloves.
EYE PROTECTION	: wear safety glasses.
SKIN PROTECTION	: wear suitable protective working cloths.

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

BOILING	: *156°C(760mmHg)	COLOR	: black
FLASH	: 75.0°C	FORM	: Paste
VAPOR PRESSURE	: * 2.00mmHg(40°C)	VAPOR DENSITY	: *6.08(Air=1)
SOLUBILITY IN WATER	: * <10.7wt%	ODOR	: Mild odor
		SPECIFIC GRAVITY	: 1.18

*Data of the organic solvents or monomers contained in this product is product is quoted.

SECTION 10	STABILITY AND REACTIVITY
-------------------	---------------------------------

STABILITY : Stable
CONDITIONS TO AVOID : Heat and sunlight.
MATERIALS TO AVOID : Strong acids, strong bases, peroxides and strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS : Burning may release oxides of carbon, nitrogen, sulfur and other toxic gases or vapors.

SECTION 11	TOXICOLGICAL INFORMATION
-------------------	---------------------------------

PRIMARY ROUTE(S) OF ENTRY
☒ DERMAL ☒ INHALATION ☐ INGESTION

TOXICITY STUDIES : Toxicity studies have not been carried out in this product. Toxicity information available for the ingredients listed in section 2 is given below.

HEALTH HAZARDS
ACUTE INGESTION TOXICITY : N.E.
ACUTE SKIN IRRITATION : Slightly irritant
MUTAGENICITY : NONE

CARCINOGENICITY
☐ NTP ☐ IARC ☐ OSHA ☒ NOT LISTED

SYMPTOMS OF OVER EXPOSURE
INHALATION : Slight irritation to respiratory tract. Highly concentrated vapor may cause headaches, and nausea.
EYES : Slight irritation
SKIN : Slight irritation
INGESTION : Expected to have a low order of toxicity.

SEVTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

ACUTE FISH TOXICITY : Ecological data are not available
BIODEGRADABILTY : No data available.

SEVTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

Incineration or landfill in accordance with local regulations.

SEVTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

ADR : Inflammable liquid
IMDG-CODE : Free
IATA : Free
US DOT : Combustible liquid

UN : Free
FLASH POINT : 75.0°C

SECTION 15	REGULATORY INFORMATION
-------------------	-------------------------------

EEC LABELING : Harmful

RISK PHRASES : Harmful : may cause lung damage if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES : Avoid contact with skin.
: Do not breathe vapor.
: If swallowed, do not induce vomiting :seek medical advice immediately and show this container or label.
: Avoid release to the environment. Refer to special instructions/Safety data sheets.

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of view of safety requirements. It should not therefore be construed as guaranteeing specific properties.

It may not be valid for this material, if used in combination with any other materials.

Material safety data sheet

Article and manufacturer informatio

Item name :KTM-150F WM
Ohter name: NONE
Recommended use: heat hardening printing ink
Name of manufacturer or supplier: supplier - keyway Technology Co., Ltd Manufacturer - kaiyao Technology Co., Ltd
Address of manufacturer or supplier: supplier - No.18, Lane 646, Boai street, Zhubei City, Xinzhu County Factory - No.18, Lane 646, Boai street, Zhubei City, Xinzhu County
Emergency contact: (03) 555-1822 Fax: (03) 553-1338

Hazard identification data

Hazard classification: flammable liquid, fire hazard Category 3, acute toxicity category 5.
Label content: flammable mixed solvent 
Symbols: warning:
Hazard warning message: flammable substances, may be harmful if inhaled.
Hazard prevention measures: tightly cover the container; keep away from the ignition source - no smoking; place the container in a well ventilated place; take off the clothes as soon as they are polluted; wear eye mask / face shield; do not eat or drink when using, and avoid release to the environment
Other hazards:

Component identification data

INGREDIENTS	% by Wt	CAS No.
Polyester resin (polymer)	20~25%	28064-14-4
Mixed solvent	20~25 %	106-65-0 ; 1119-40-0 ; 627-93-0
Titanium dioxide	30~35%	13463-67-7
Filler	10~15 %	14807-96-6
Hexamethylene diisocyanate refers to oligomer	5~10 %	21093-51-6
Butyl acetate	1~5 %	627-93-0

First aid measures

First aid methods of different exposure routes:
Inhalation:1. remove the patient to fresh air immediately. It can only cause nose irritation and may be harmful to people. Skin contact: 1. Immediately wash with water.
Eye contact: 1. Immediately open the eyelids and wash them with mild water.
Ingestion:
Most important symptoms:
Protection for first aid personnel: wear protective gloves to avoid contact with pollutants.
Tips for doctors:.

Fire fighting measures

Suitable extinguishing agent: dry powder

Special hazards that may be encountered during fire fighting:

Special fire fighting procedures: 1. Remove the container from the fire site and put out the fire in the upwind.

2. Stop leakage without endangering personnel safety.

3. If the leakage cannot be stopped and the surrounding area is empty, the fire will burn out.

Special protective equipment for firefighters: Firefighters must wear air breathing apparatus, fire clothing and protective gloves.

Leakage treatment method

Personal precautions: 1. Restrict personnel access until the overflow area is completely clean.

2. It is determined that the trained personnel are responsible for the cleaning work.

3. Wear appropriate personal protective equipment.

Environmental precautions:

1. Ventilate the area.

2. Extinguish or remove all sources of ignition.

3. Report to relevant units of safety, health and environmental protection of the government.

Cleaning method: 1. Do not touch the leakage. 2. Avoid discharging into sewer or other confined space. 3. Try to prevent or reduce the leakage under the condition of safety permission. 4. Use sand, soil or other absorbing substances that do not react with leakage substances to enclose the leakage. 5. In case of a small amount of leakage, absorb it with absorbent that will not react with the leakage. Contaminated absorbents and spills are equally hazardous and should be placed in properly capped and labeled containers. Flush the spill area with water. 6. In case of a large number of spills, contact the fire department, emergency treatment unit and supplier for assistance.

Safe handling and storage methods:

Without special measures, it is not inflammable and explosive.

Storage: no corrosive container, no reactivity, low flammability, non flammable.

Exposure precautions

Engineering control: local exhaust device or integral air exchange device.

Control parameters: eight hour daily average allowable concentration / short time

average allowable concentration / maximum allowable concentration:

Personal protective equipment: respiratory protection:

Hand protection: impervious gloves, butyl rubber recommended, Teflon, 4h, barricale, chemrel

Eye protection: 1. Goggles (minimum 8 inches). 2. splash proof safety goggles. 3. Do not wear contact lenses. Skin and body protection: chemical protective clothing.

Physical and chemical properties

Material state: viscous paste liquid shape: paste liquid

Color: smell: Fragrance

PH value: slightly acidic boiling point / melting point range: OC /---

Decomposition temperature: flash point not measured:

Test method: open cup and close cup

Autoignition temperature: explosion limit: LEL: uel:

Vapor pressure: vapor density: > 1 (air 1)/

Specific gravity: 1.2 ~ 1.4 (25 / 25 °C) for water solubility:

Stability and reactivity

Stability: under normal conditions
Possible hazardous reactions under special conditions:
Conditions to avoid:
Substances to be avoided: acids.
Hazardous decomposition:

Toxicity data

Exposure route: skin contact, eye contact, ingestion
Symptoms: eye damage
Acute toxicity: inhalation:
Skin: causes mild irritation. Eyes: cause mild irritation. Ingestion:
LD50 (test animal, absorption pathway) local effect:---
Sensitization:---
Chronic toxicity or long-term toxicity:
Special effect:.

Ecological data

Ecotoxicity:
Durability and degradability:
Bioaccumulation:
Mobility in soil:
Other adverse effects:

Waste disposal method

Waste disposal method:
1. Handle according to the current laws and regulations.
Consider sanitary burying or burning in a qualified solvent burning tower.

Delivery information

UN No:
UN transport Name:
Transportation hazard classification:
Packing category:
Marine pollutants (yes / no):
Special delivery methods and precautions:-

Other information

References: None
Prepared by: kaiyao Technology Co., Ltd. / No.18, Lane 646, Boai street, Zhubei City, Xinzhu County/ Tel:03-5551822 / Fax:03-5531338
Prepared by: Xie Jinquan
Prepared on: August 15, 2014
Note: the above information and data are for reference only. The user shall determine the feasibility of the application according to the application requirements.

MATERIAL SAFETY DATA SHEET

产 品 安 全 资 料

Section1 Preparation Identification and Company 样品标公司

Preparation Identification 标记: 防氧化原液DX-808HT

Manufacturers Name 公司名称: 深圳市东方星化工科技有限公司

Manufacturers Address 地址: 东莞市虎门镇大宁村大板地工业区

Emergency Telephone Number 联系电话: 0769-85015502

Emergency Tex Number 传真: 0769-85015500

Postal code 邮政编码: 523900

Section 2 Composition information on Ingredients

成份组成

学名

化学文摘社登记号码

浓度(%)

(Chemical Name)

(CASNO)

(Concentration)

苯并咪唑 Benzimidazole

95-14-7

1%

甲酸 Formic acid

64-18-6

3%

添加剂 Additives

0.05%

DI 水DI water

7732-18-5

95.95%

Section 3 Hazards Identification

危险性概述

Safety and Risk 安全和危险性: DX-808HT contain formic acid which may cause severe burns. 含有甲酸可能导致灼伤

Section 4 First Aid Measures

急救措施

Eyes 眼睛: flush with plenty of clean, cool water for 15 minutes and get immediate medical attention 大量清水冲洗并尽快就医

Skin 皮肤: flush with plenty of clean, cool water for 15 minutes 大量清水冲洗15 分钟

Ingestion 食入: get immediate medical attention 尽快就医

Section 5 Fire Fighting Measures

消防措施

不可燃

Section 6 Accidental Release Measures

泄漏应急措施

Personal Precautions 个人防护: wears protective clothing, chemical safety goggles, respirator, face shield and rubber gloves 穿戴耐酸防护服, 护目镜、面罩和橡胶手套

Clean-up Procedure 清洗: flush with plenty of clean, cool water 用大量清水冲洗

Section 7 Handling and Storage

操作与储存

Ventilation 通风: Store indoors in a cool dry area

阴凉干燥处

Temperature 温度: Store indoors in a cool dry area

阴凉干燥处

Containers 容器: Keep containers tightly closed. Loosen closure cautiously when opening. 保持容器密封, 打开时慎重

Incompatible Materials 不相容物质: alkalis and oxidizers 碱性和氧化物

Pot Life 有效期: six months 6 个月

Section8 Exposure Controls /Personal Protection 接触控制与个人防护

Ventilation 通风: Exhaust ventilation is recommended 推荐抽出式通风

Respiration 呼吸: respirator。Avoid breathing vapors or mist。防毒面具
避免吸入蒸汽或烟雾

Eyes and Face 眼睛和脸: chemical safety goggles and face shield 护目镜
和脸罩

Hands and Skin 手和皮肤: rubber gloves 橡胶手套

Clothing : protective clothing 耐酸防护服

Section 9 Physical and Chemical Properties 物理和化学特性

Appearance 外观: 浅蓝色液体

Odour 气味: 淡醋酸味

PH: 2.7±0.3

Section 10: Stability and Reactivity 稳定性和反应活性

Chemical Stability 化学稳定性: 弱的反应能力

Incompatible Materials 不相容物质: alkalis and oxidizers 碱性和氧化物

Section 11 Toxicological Information 毒性资料

NDA 无毒

Section 12 Disposal Consideration 废弃处理

Dispose of material in approved sites 中和后过滤排放，过滤物交当地合法
批准单位。

Section 13 生态资料

生态毒性: 无

生物降解性: 无

非生物降解性: 无

其它有害作用: 无

Section 14 法规信息

通用法规:

劳工安全卫生规则

特定化学物预防标准

Section 15 运送资料

国内运输规定: 依道路交通安全规则第84 条

Section 16 其他资料

制表单位: 深圳市东方星化工科技有限公司

制表地址: 东莞市虎门镇大宁村大板地工业区

制表部门: 品质部

制表日期: 2017 年 1 月



Article Information Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This product is defined as an article based on the definition of an Article under China New Chemical Environmental Management Method MEP Decree No. 7, and does not require a Safety Data Sheet under Dangerous Chemical Safety Management Regulatory China State Council Decree No. 591 and China GB/T16483-2008 Safety Data Sheet for Chemical Products Content and Order of Sections. This article information sheet (AIS) is provided as a courtesy in response to a customer request. When used as recommended or under ordinary conditions, the product should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

Document Group: 07-7168-3
Issue Date: 2015/05/19

Version Number: 1.00
Supersedes Date: Initial Issue

SECTION 1: Identification

1.1. Product identifier

3M™ 300LSE Adhesive Transfer Tapes: 8132LE, 8153LE, 9453FL, 9453LE, 9471FL, 9471LE, 9472FL, 9472LE, 9472LEU, 9653LE, 9671LE, 9672LE and 9698LE

Other means of identification

1.2. Recommended use and restrictions on use

Recommended use

Bonding & Attachment, Industrial use

1.3. Supplier's details

Company: 3M Company
Division: Industrial Adhesives and Tapes Division
ADDRESS: 3M Center, St. Paul, MN 55144, USA
Phone: 021-22105335
FAX: 021-22105036
E Mail: Tox.cn@mmm.com
Website: www.3m.com.cn

1.4. Emergency telephone number

021-22105335

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

This product is considered to be an article and is exempt from GHS classification.

3M™ 300LSE Adhesive Transfer Tapes: 8132LE, 8153LE, 9453FL, 9453LE, 9471FL, 9471LE, 9472FL, 9472LE, 9472LEU, 9653LE, 9671LE, 9672LE and 9698LE

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Paper or Film Liner	Mixture	Not Applicable
Acrylic Polymer Adhesive	Trade Secret	100

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

No need for first aid is anticipated.

SECTION 5: Fire-fighting measures

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical

under normal use conditions. No engineering controls or personal protective equipment (PPE) are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Roll of Tape
Appearance/Odor	Translucent adhesive, slight acrylate odor, paper or film quick release liner
Odor threshold	<i>Not Applicable</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	<i>Not Applicable</i>
Flash Point	<i>Not Applicable</i>
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Density	<i>Not Applicable</i>
Relative Density	<i>Not Applicable</i>
Water solubility	Nil
Solubility- non-water	<i>Not Applicable</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>Not Applicable</i>
Viscosity	<i>Not Applicable</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>

SECTION 10: Stability and reactivity

This material is considered to be non reactive under normal use conditions.

SECTION 11: Toxicological information

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

No health effects are expected

Eye Contact:

No health effects are expected

Ingestion:

No health effects are expected

Additional Information:

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use

3M™ 300LSE Adhesive Transfer Tapes: 8132LE, 8153LE, 9453FL, 9453LE, 9471FL, 9471LE, 9472FL, 9472LE, 9472LEU, 9653LE, 9671LE, 9672LE and 9698LE

may affect the performance of the product and may present potential health and safety hazards.

SECTION 12: Ecological information

This article is expected to present a low environmental risk either because use and disposal are unlikely to result in a significant release of components to the environment or because those components that may be released are expected to have insignificant environmental impact.

SECTION 13: Disposal considerations

Dispose of contents/container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

Not hazardous for transportation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This product is an article and is exempted from Measures on Environmental Management of New Chemical Substances and from IECSC inventory listing requirements.

SECTION 16: Other information

References

United Nations 'Recommendations on the Transport of Dangerous Goods - Model Regulations '

United Nations 'Globally Harmonized System of Classification and Labelling of Chemicals (GHS)'.

Revision information:

Conversion to AIS.

DISCLAIMER: The information on this Article Information Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Information Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M People's Republic of China AISs are available at www.3m.com.cn