FCC TEST REPORT

FCC ID: 2AVCO-ADTV

Report No.	:	SSP24010100-1E
Applicant	:	LONGVISION MEDIA SDN BHD
Product Name	:	ADTV
Model Name	:	ADTV
Test Standard	:	FCC Part 15.247
Date of Issue	:	2024-04-08

Shenzhen CCUT Quality Technology Co., Ltd.
1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant.....:	LONGVISION MEDIA SDN BHD
Address of Applicant.....:	17.01, LEVEL 17, CENTREPOINT SOUTH, MID VALLEY CITY, LINGKARAN SYED PUTRA, KL KUALA LUMPUR, W.P KUALA LUMPUR, 59200 Malaysia
Manufacturer.....:	GOSPELL Digital Technology Co., Ltd.
Address of Manufacturer.....:	Gospell Industrial Park, Guanshandong Street, Suxian District, Chenzhou City, Hunan Province,423000 China
Product Name.....:	ADTV
Brand Name.....:	LONGTV
Main Model.....:	ADTV
Series Models.....:	ADTV-1, ADTV-2, ADTV-3, ADTV-4
Test Standard.....:	FCC Part 15 Subpart C ANSI C63.4-2014 ANSI C63.10-2013
Date of Test .....:	2024-01-16 to 2024-03-25
Test Result.....:	Passed
Tested By .....:	Lorzix Luo (Lorzix Luo)
Reviewed By.....:	Lieber Ouyang (Lieber Ouyang)
Authorized Signatory.....:	Lahm Peng (Lahm Peng)

Shenzhen CCUT Quality Technology Co., Ltd. APPROVED

Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

CONTENTS

1. General Information **5**
1.1 Product Information 5
1.2 Test Setup Information 6
1.3 Compliance Standards 7
1.4 Test Facilities 7
1.5 List of Measurement Instruments 8
1.6 Measurement Uncertainty 8
2. Summary of Test Results **9**
3. Antenna Requirement **10**
3.1 Standard and Limit 10
3.2 Test Result 10
4. Conducted Emissions **11**
4.1 Standard and Limit 11
4.2 Test Procedure 11
4.3 Test Data and Results 12
5. Radiated Emissions **15**
5.1 Standard and Limit 15
5.2 Test Procedure 15
5.3 Test Data and Results 17
6. Band-edge Emissions(Radiated) **21**
6.1 Standard and Limit 21
6.2 Test Procedure 21
6.3 Test Data and Results 21
7. Maximum Peak Conducted Output Power **23**
7.1 Standard and Limit 23
7.2 Test Procedure 23
7.3 Test Data and Results 23
8. Occupied Bandwidth(-6dB) **25**
8.1 Standard and Limit 25
8.2 Test Procedure 25
8.3 Test Data and Results 25
9. Maximum Power Spectral Density **27**
9.1 Standard and Limit 27
9.2 Test Procedure 27
9.3 Test Data and Results 27
10. Band-edge Emission(Conducted) **29**
10.1 Standard and Limit 29
10.2 Test Procedure 29
10.3 Test Data and Results 29
11. Conducted RF Spurious Emissions **31**
11.1 Standard and Limit 31
11.2 Test Procedure 31
11.3 Test Data and Results 31

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-04-08	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	ADTV
Trade Name:	LONGTV
Main Model:	ADTV
Series Models:	ADTV-1, ADTV-2, ADTV-3, ADTV-4
Rated Voltage:	DC 12V from adapter
Power Adaptor:	Input: AC 100-240V/50-60Hz 0.6A, Output: DC 12V/1A
Hardware Version:	6104A-00-2346-V1.2
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer. Note 2: The model name and memory configuration of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BLE
Operating Frequency:	2402MHz ~ 2480MHz
RF Output Power:	0.67dBm (Conducted)
Number of Channel:	40
Channel Separation:	2MHz
Modulation:	GFSK
Antenna Gain:	2.86dBi
Type of Antenna:	FPCB Antenna
Type of Device:	☐ Portable Device ☒ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes		
Test Mode	Description	Remark
TM1	Lowest Channel	2402MHz
TM2	Middle Channel	2440MHz
TM3	Highest Channel	2480MHz

List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-

List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
-	-	-	-
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	11	2422	21	2442	31	2462
02	2404	12	2424	22	2444	32	2464
03	2406	13	2426	23	2446	33	2466
04	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	**Shenzhen CCUT Quality Technology Co., Ltd.** 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2023-07-31	2024-07-30
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2023-07-31	2024-07-30
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2023-07-31	2024-07-30
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2023-07-31	2024-07-30
Amplifier	SCHWARZBECK	BBV 9743B	00251	2023-07-31	2024-07-30
Amplifier	HUABO	YXL0518-2.5-45	--	2023-07-31	2024-07-30
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2023-07-31	2024-07-30
Loop Antenna	DAZE	ZN30900C	21104	2023-08-07	2024-08-06
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2023-08-07	2024-08-06
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2023-08-07	2024-08-06
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2023-08-07	2024-08-06
Conducted RF Testing					
RF Test System	MWRFTest	MW100-RFCB	220418SQS-37	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2023-07-31	2024-07-30

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB
Power Spectrum Density	9kHz ~ 26GHz	±0.62 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(b)(3)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.247(a)(2)	Occupied Bandwidth(-6dB)	Passed
FCC Part 15.247(e)	Maximum Power Spectral Density	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an FPCB antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit

According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50
Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz Note 2: The lower limit applies at the band edges		

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver
Attenuation: 10dB
Start Frequency: 0.15MHz
Stop Frequency: 30MHz
IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:
Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions	
Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3075	25.03	9.64	34.67	60.04	-25.37	QP	P	
2	0.3075	15.50	9.64	25.14	50.04	-24.90	AVG	P	
3	0.4515	39.46	9.95	49.41	56.85	-7.44	QP	P	
4 *	0.4515	33.09	9.95	43.04	46.85	-3.81	AVG	P	
5	0.4875	36.43	9.95	46.38	56.21	-9.83	QP	P	
6	0.4875	29.11	9.95	39.06	46.21	-7.15	AVG	P	
7	1.3065	25.99	10.02	36.01	56.00	-19.99	QP	P	
8	1.3065	16.29	10.02	26.31	46.00	-19.69	AVG	P	
9	1.8105	24.91	10.04	34.95	56.00	-21.05	QP	P	
10	1.8105	16.01	10.04	26.05	46.00	-19.95	AVG	P	
11	28.4640	14.69	10.28	24.97	60.00	-35.03	QP	P	
12	28.4640	3.51	10.28	13.79	50.00	-36.21	AVG	P	

Test Plots and Data of Conducted Emissions	
Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Power Line:	Live
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1860	28.82	9.01	37.83	64.21	-26.38	QP	P	
2	0.1860	17.21	9.01	26.22	54.21	-27.99	AVG	P	
3	0.4560	37.68	9.94	47.62	56.77	-9.15	QP	P	
4 *	0.4560	29.45	9.94	39.39	46.77	-7.38	AVG	P	
5	0.4830	34.45	9.93	44.38	56.29	-11.91	QP	P	
6	0.4830	27.34	9.93	37.27	46.29	-9.02	AVG	P	
7	0.5820	25.68	9.94	35.62	56.00	-20.38	QP	P	
8	0.5820	14.63	9.94	24.57	46.00	-21.43	AVG	P	
9	1.8194	23.99	10.05	34.04	56.00	-21.96	QP	P	
10	1.8194	12.05	10.05	22.10	46.00	-23.90	AVG	P	
11	28.3920	18.23	10.23	28.46	60.00	-31.54	QP	P	
12	28.3920	3.29	10.23	13.52	50.00	-36.48	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range blew 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.

b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.

c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1GHz, 100 kHz for f < 1 GHz, 10kHz for f < 30MHz
VBW ≥ RBW, Sweep = auto
Detector function = peak
Trace = max hold

d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.

f) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)	
Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Antenna Polarization:	Horizontal
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	178.7584	36.71	-10.54	26.17	43.50	-17.33	QP	100	348	P	
2	333.6867	34.94	-7.90	27.04	46.00	-18.96	QP	100	3	P	
3	400.4319	35.02	-5.84	29.18	46.00	-16.82	QP	100	319	P	
4	601.4265	39.23	-1.03	38.20	46.00	-7.80	QP	100	36	P	
5	801.7863	33.19	2.35	35.54	46.00	-10.46	QP	100	45	P	
6 *	878.3214	36.49	2.92	39.41	46.00	-6.59	QP	100	207	P	

Radiated Emission Test Data (30MHz to 1GHz)	
Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Antenna Polarization:	Vertical
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	45.6948	39.89	-9.23	30.66	40.00	-9.34	QP	100	274	P	
2	78.6888	41.97	-13.02	28.95	40.00	-11.05	QP	100	102	P	
3	199.9856	42.62	-11.99	30.63	43.50	-12.87	QP	100	360	P	
4	400.4319	33.36	-5.85	27.51	46.00	-18.49	QP	100	61	P	
5 *	601.4265	41.22	-1.03	40.19	46.00	-5.81	QP	100	173	P	
6	801.7863	35.48	2.35	37.83	46.00	-8.17	QP	100	182	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK 2402MHz)							
4804	77.5	-14.72	62.78	74	-11.22	H	PK
4804	60.44	-14.72	45.72	54	-8.28	H	AV
7206	64.5	-8.41	56.09	74	-17.91	H	PK
7206	50.38	-8.41	41.97	54	-12.03	H	AV
4804	74.44	-14.72	59.72	74	-14.28	V	PK
4804	59.28	-14.72	44.56	54	-9.44	V	AV
7206	65.72	-8.41	57.31	74	-16.69	V	PK
7206	49.54	-8.41	41.13	54	-12.87	V	AV
Middle Channel (GFSK 2440MHz)							
4880	75.11	-14.64	60.47	74	-13.53	H	PK
4880	60.25	-14.64	45.61	54	-8.39	H	AV
7320	64.14	-8.28	55.86	74	-18.14	H	PK
7320	47.25	-8.28	38.97	54	-15.03	H	AV
4880	76.57	-14.64	61.93	74	-12.07	V	PK
4880	59.84	-14.64	45.2	54	-8.8	V	AV
7320	65.19	-8.28	56.91	74	-17.09	V	PK
7320	47.7	-8.28	39.42	54	-14.58	V	AV
Highest Channel (GFSK 2480MHz)							
4960	76.04	-14.53	61.51	74	-12.49	H	PK
4960	60.16	-14.53	45.63	54	-8.37	H	AV
7440	62.46	-8.13	54.33	74	-19.67	H	PK
7440	47.89	-8.13	39.76	54	-14.24	H	AV
4960	73.81	-14.53	59.28	74	-14.72	V	PK
4960	60.24	-14.53	45.71	54	-8.29	V	AV
7440	65.06	-8.13	56.93	74	-17.07	V	PK
7440	45.78	-8.13	37.65	54	-16.35	V	AV

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK 2402MHz)							
2310	69.65	-21.34	48.31	74	-25.69	H	PK
2310	50.52	-21.34	29.18	54	-24.82	H	AV
2390	65.05	-20.96	44.09	74	-29.91	H	PK
2390	51.32	-20.96	30.36	54	-23.64	H	AV
2400	70.94	-20.91	50.03	74	-23.97	H	PK
2400	55.66	-20.91	34.75	54	-19.25	H	AV
2310	69.11	-21.34	47.77	74	-26.23	V	PK
2310	51.25	-21.34	29.91	54	-24.09	V	AV
2390	69.29	-20.96	48.33	74	-25.67	V	PK
2390	51.07	-20.96	30.11	54	-23.89	V	AV
2400	72.49	-20.91	51.58	74	-22.42	V	PK
2400	56.23	-20.91	35.32	54	-18.68	V	AV
Highest Channel (GFSK 2480MHz)							
2483.50	66.86	-20.51	46.35	74	-27.65	H	PK
2483.50	49.38	-20.51	28.87	54	-25.13	H	AV
2500	65.73	-20.43	45.3	74	-28.7	H	PK
2500	52.24	-20.43	31.81	54	-22.19	H	AV
2483.50	69.04	-20.51	48.53	74	-25.47	V	PK
2483.50	50.24	-20.51	29.73	54	-24.27	V	AV
2500	66.63	-20.43	46.2	74	-27.8	V	PK
2500	51.98	-20.43	31.55	54	-22.45	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

7. Maximum Peak Conducted Output Power

7.1 Standard and Limit

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

7.2 Test Procedure

1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 2MHz, VBW = 6MHz, Sweep = Auto, Detector = RMS.
4) Measure the highest amplitude appearing on spectral display and mark the value.
5) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

7.3 Test Data and Results

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
BLE_GFSK	2402	-1.27	30	Pass
	2440	-0.48	30	Pass
	2480	0.67	30	Pass

BLE_GFSK
2402MHz 
2440MHz 
2480MHz 

8. Occupied Bandwidth(-6dB)

8.1 Standard and Limit

According to 15.247(a)(2), Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.
1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto.
4) Set a reference level on the measuring instrument equal to the highest peak value.
5) Measure the frequency difference of two frequencies that were attenuated 6dB from the reference level. Record the frequency difference as the emission bandwidth.
6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

8.3 Test Data and Results

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit 6 dB Bandwidth (MHz)	Test Result
BLE_GFSK	2402	0.66	1.041	0.5	Pass
	2440	0.65	1.048	0.5	Pass
	2480	0.645	1.055	0.5	Pass

BLE_GFSK	
6dB bandwidth	99% bandwidth
2402MHz	2402MHz
	
2440MHz	2440MHz
	
2480MHz	2480MHz
	

9. Maximum Power Spectral Density

9.1 Standard and Limit

According to FCC 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.2 Test Procedure

1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 3kHz, VBW = 10kHz, Sweep = Auto, Detector = RMS.
4) Measure the highest amplitude appearing on spectral display and mark the value.
5) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

9.3 Test Data and Results

Test Mode	Test Channel MHz	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Test Result
BLE-GFSK	2402	-15.7	8	Pass
	2440	-14.87	8	Pass
	2480	-13.72	8	Pass

BLE_GFSK
2402MHz 
2440MHz 
2480MHz 

10. Band-edge Emission(Conducted)

10.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

10.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.
1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = RMS.
4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
6) Measure the emission and marking the edge frequency.
7) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

10.3 Test Data and Results

Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
GFSK	Lowest	2402	-51.2	-20	Pass
	Highest	2480	-51.23	-20	Pass

BLE_GFSK Lowest	
Reference Power	Band-edge Emission
	

BLE_GFSK Highest	
Reference Power	Band-edge Emission
	

11. Conducted RF Spurious Emissions

11.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

11.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.7.

1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
2) Set the spectrum analyzer to any one measured frequency within its operating range.
3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = RMS.
4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
5) Measure the spurious emissions with frequency range from 9kHz to 26.5GHz.
6) Repeat above procedures until all measured frequencies were complete.

Test Setup Block Diagram

11.3 Test Data and Results

Note: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions measurement data.

BLE_GFSK Lowest

Reference Power



Spurious Emissions



BLE_GFSK Middle

Reference Power



Spurious Emissions



BLE_GFSK Highest

Reference Power



Spurious Emissions



******* END OF REPORT *******