

Model No.: MG25004



AGR2




QUICK START GUIDE

Please read this Quick Start Guide carefully and retain it for future reference.

Charging

Before using the device for the first time, fully charge the smart glasses using the Type-C charging cable. Connect the cable to a power adapter. red indicator light remains on while charging. the blue light stays on continuously when fully charged



Function Introduction



Type-C port

Multi-function button (MFB)

Indicator light

Power On/Off

Power On: When the device is off, press and hold the "MFB" button for 4 seconds. The blue light will flash 3 times and the glasses will power on
Power Off: When the device is powered on, press and hold the "MFB" button for 5 seconds. The red light will flash 3 times and then go out. The glasses will shut down

Pairing

To pair with a new device, long press "MFB" button for 4 seconds. The glasses will turn on automatically. Enable Bluetooth on your device and search for " **Monster AGR2** ". The red and blue indicator lights will flash alternately. Once paired, a voice prompt will confirm the connection and the indicator will turn off

Voice Assistant

Connected phone status, long press "MFB" button for 2 seconds to activate the voice assistant

Music

Play/Pause: Click "MFB" button
Previous Track: Connected mobile phone status, three strikes "MFB" button
Next Track: Connected mobile phone status, Double-click "MFB" button

Call

Answer/End Call: Double-click "MFB" button
Reject Call: Long press "MFB" button for 2 seconds

Clear pairing

When the smart glasses are powered on, press the "MFB" button 8 times in quick succession, and the smart glasses will automatically shut down

Auto Shutdown

when no device is connected, the speaker will be switched off automatically in 5 minutes

Attention

*Private replacement of batteries without permission is not recommended.
*Batteries [battery packs or battery combinations] should not be exposed to lighting, baking or similar overheating environments.
*External power supply, input voltage and current standard ≤5V/0.5A;

FCC STATEMENT

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.
Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.
This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received. Including interference that may cause undesired operation.
The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.
FCC ID: 2AVD2-G02A

IC Caution

Radio Standards Specification RSS-Gen, Issue 5
- English:
This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:
This device may not cause interference.
This device must accept any interference, including interference that may cause undesired operation of the device.

RF exposure statement:
The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

- French:
Cet appareil contient des émetteurs / récepteurs exemptés de licence conformes aux RSS (RSS) d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est soumis aux deux conditions suivantes:
Cet appareil ne doit pas causer d'interférences.
Cet appareil doit accepter toutes les interférences, y compris celles susceptibles de provoquer un fonctionnement indésirable de l'appareil.

Déclaration d'exposition RF:
L'appareil a été évalué pour répondre aux exigences générales d'exposition aux RF. L'appareil peut être utilisé dans des conditions d'exposition portable sans restriction.
IC: 28087-G02A

Model No.: MG25004



AGR2



快速指南

请仔细阅读本快速指南并妥善保存以备将来使用。
本产品由中国平安保险公司承保

充电

请在使用此设备前先给眼镜充满电，此设备可以通过Type-C接口进行充电，充电时红灯长亮，充满电时蓝灯长亮



功能介绍



Type-C充电接口

多功能按键（MFB）

指示灯

电源开/关

关机状态下，长按“MFB”键4秒，蓝色指示灯闪烁3次，眼镜开机
开机状态下，长按“MFB”键5秒，红色指示灯闪烁3次熄灭，眼镜关机

配对

长按“MFB”键4秒，智能眼镜将自动开机。对于新设备连接，请打开蓝牙设备并搜索“ **Monster AGR2** ”进行连接，红灯指示灯会交替闪烁，配对成功后，您会听到系统提示音，指示灯熄灭

语音助手

已连接手机状态，长按2秒“MFB”键唤醒语音助手

音乐

播放/暂停:单击“MFB”键
上一曲:已连接手机状态，三击“MFB”键
下一曲:已连接手机状态，双击“MFB”键

通话

接听/挂断:双击“MFB”键
拒接来电:长按2秒“MFB”键

清除配对

在开机状态下,连续快速按8次“MFB”键,智能眼镜自动关机

自动关机

如果没有连接到蓝牙设备,大约在5分钟后自动关机

注意

*不建议未经许可私下更换电池。
*电池[电池组或电池组合]不得暴露在照明,烘烤或类似过热的环境中。
*外接电源,输入电压电流标准≤5V/0.5A;

产品有毒有害物质或元素表

有害物质		六价铬		镉		汞		铅		多溴联苯		多溴联苯醚	
		(Cr(VI))	(Cd)	(Hg)	(Pb)	(Hq)	(Pb)	(Pb)	(Pb)	(PBBs)	(PBBs)	(PBDEs)	(PBDEs)
部件名称	外壳												
线材													
喇叭													
主板													
电池													

0:表示该有害物质在规定的材料中的含量均在GB/T26572规定的限量要求以下。
X:表示该有害物质至少在该部件的某一均质材料中的含量超出GB/T26572规定的限量要求。

保修信息卡

信息填写

产品名称:

产品型号:

产品SN号:

购机日期:

用户信息

用户姓名:

联系电话:

地址:

封面

60X80MM 105G双胶+K+186C印刷+风琴折