FCC RF Test Report

APPLICANT	:	VinSmart Research and Manufacture Joint Stock Company
EQUIPMENT	:	SMARTPHONE
BRAND NAME	:	Vsmart
MODEL NAME	:	V340S
FCC ID	:	2AVD3V340S
STANDARD	:	47 CFR Part 2, 27(D)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Apr. 24, 2020 and completely tested on May 29, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Maximum Conducted power, Frequency Tolerance and Emission Designator 6
1.7 Testing Site 6
1.8 Test Software 6
1.9 Applied Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 10
3 CONDUCTED TEST ITEMS **11**
3.1 Measuring Instruments 11
3.2 Test Setup 11
3.3 Test Result of Conducted Test 11
3.4 Conducted Output Power Measurement 12
3.5 Peak-to-Average Ratio 13
3.6 EIRP Power Density 14
3.7 Occupied Bandwidth 15
3.8 Conducted Band Edge Measurement 16
3.9 Conducted Spurious Emission Measurement 17
3.10 Frequency Stability Measurement 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 19
4.4 Radiated Spurious Emission Measurement 20
5 LIST OF MEASURING EQUIPMENT **21**
6 UNCERTAINTY OF EVALUATION **22**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG042410-05D	Rev. 01	Initial issue of report	Dec. 25, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	-	Peak-to-Average Ratio	<13dB	N/A	Reporting only
3.6	§27.50 (a)(3)	EIRP Power Density	EIRP < 250mW/5MHz	PASS	-
3.7	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.8	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.9	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	Under limit 13.71 dB at 11530.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

VinSmart Research and Manufacture Joint Stock Company
Lot CN1-06B-1&2, Hi-tech Industrial Park 1, Hoa Lac Hi-tech Park, Ha Bang, Thach That, Hanoi, Vietnam

1.2 Manufacturer

VinSmart Research and Manufacture Joint Stock Company
Lot CN1-06B-1&2, Hi-tech Industrial Park 1, Hoa Lac Hi-tech Park, Ha Bang, Thach That, Hanoi, Vietnam

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	SMARTPHONE
Brand Name	Vsmart
Model Name	V340S
FCC ID	2AVD3V340S
EUT supports Radios application	GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE FM Receiver and GNSS
IMEI Code	Conducted: 355175110009264 Radiation: 355175110008910
HW Version	REV 1.0
SW Version	V340S_USA_U_A1_201221
EUT Stage	Identical Prototype

Remark : This is a report for change in FCC ID, there is no difference on the product design, all the test results are leveraged from original FCC ID: 2AVD3V340U, report number FG042410D.

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx Frequency	LTE Band 30 : 2307.5 MHz ~ 2312.5 MHz
Rx Frequency	LTE Band 30 : 2352.5 MHz ~ 2357.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	LTE Band 30 : 24.04 dBm
Antenna Gain	LTE Band 30 : -2.2 dBi
Type of Modulation	QPSK / 16QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted power, Frequency Tolerance and Emission Designator

LTE Band 30		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted power(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted power(W)
5	2307.5 ~ 2312.5	4M50G7D	-	0.2483	4M51W7D	-	0.1897
10	2310.0	9M05G7D	0.0041	0.2535	8M99W7D	-	0.2094

1.7 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 27(D)
- ANSI C63.26-2015
- FCC KDB 971168 Power Meas License Digital Systems D01 v03r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	V		-	-	V	V	-	V	V	V	V	V	V
		-	-		V	-	-	V	V	-	V	V	V		V	
Peak-to-Average Ratio	30	-	-		V	-	-	V	V	-	V		V		V	
E.I.R.P PSD	30	-	-	V		-	-	V	V	-	V			V	V	V
		-	-		V	-	-	V	V	-	V				V	
26dB and 99% Bandwidth	30	-	-	V		-	-	V	V	-			V	V	V	V
		-	-		V	-	-	V	V	-			V		V	
Conducted Band Edge	30	-	-	V		-	-	V	V	-	V		V	V		V
		-	-		V	-	-	V	V	-	V		V		V	
Conducted Spurious Emission	30	-	-	V		-	-	V	V	-	V			V	V	V
		-	-		V	-	-	V	V	-	V				V	
Frequency Stability	30	-	-		V	-	-	V		-			V		V	
Radiated Spurious Emission	30	Worst case													V	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	DC Power Supply	Topward	3303DR	N/A	N/A	Unshielded, 1.8m
3.	Earphone	Lenovo	SH100	N/A	Unshielded,1.2m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6.0 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 6.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth, Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP Power Density

3.6.1 Description of EIRP Power Density

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.4.5
2. Set instrument center frequency to OBW center frequency.
3. Set span to at least 1.5 times the OBW.
4. Set the RBW to the specified reference bandwidth (5MHz).
5. Set VBW ≥ 3 × RBW.
6. Detector = RMS (power averaging).
7. Ensure that the number of measurement points in the sweep ≥ 2 × span/RBW.
8. Sweep time = auto couple.
9. Employ trace averaging (RMS) mode over a minimum of 100 traces.
10. Use the peak marker function to determine the maximum amplitude level within the reference bandwidth (PSD).

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

27.53 (a)(4)

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300 MHz, 61 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz;

(iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2019	May 20, 2020~ May 29, 2020	Aug. 06, 2020	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Nov. 18, 2019	May 20, 2020~ May 29, 2020	Nov. 17, 2020	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2020	May 21, 2020	Apr. 14, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May 30, 2019	May 21, 2020	May 29, 2020	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 20, 2020	May 21, 2020	Apr. 19, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	May 21, 2020	Nov. 09, 2020	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2019	May 21, 2020	Aug. 05, 2020	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 08, 2020	May 21, 2020	Jan. 07, 2021	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Aug. 16, 2019	May 21, 2020	Aug. 15, 2020	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 15, 2019	May 21, 2020	Oct. 14, 2020	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 21, 2020	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 21, 2020	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 21, 2020	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 30 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.94	23.80	23.92
5	1	12		23.95	23.88	23.85
5	1	24		23.87	23.92	23.72
5	12	0		23.02	23.11	22.98
5	12	7		23.00	23.03	22.98
5	12	13		23.08	23.05	23.05
5	25	0		22.96	23.09	23.05
5	1	0	16-QAM	22.40	22.59	22.78
5	1	12		22.73	22.69	22.72
5	1	24		22.35	22.34	22.78
5	12	0		21.87	21.93	21.97
5	12	7		21.81	21.75	21.87
5	12	13		21.90	21.97	21.95
5	25	0		21.91	22.12	22.00
10	1	0	QPSK	-	24.04	-
10	1	25			23.95	
10	1	49			23.88	
10	25	0			23.11	
10	25	12			23.06	
10	25	25			23.10	
10	50	0			23.08	
10	1	0	16-QAM		23.21	
10	1	25			22.76	
10	1	49			22.97	
10	25	0			22.08	
10	25	12			22.11	
10	25	25			22.14	
10	50	0			22.11	

Peak-to-Average Ratio

Mode	LTE Band 30 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	2.67	4.12	3.88	5.10	
Highest CH	-	-	-	-	

LTE Band 30 / 10MHz / QPSK

Middle Channel / 1RB



Middle Channel / Full RB



LTE Band 30 / 10MHz / 16QAM

Middle Channel / 1RB



Middle Channel / Full RB



EIRP Power Density

Mode	LTE Band 30 : Conducted Power Density (dBm/5MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	25.54	24.49	-	-	-	-	-	-
Middle CH	-	-	-	-	25.55	24.43	25.81	24.49	-	-	-	-
Highest CH	-	-	-	-	25.71	24.44	-	-	-	-	-	-

Mode	LTE Band 30 : EIRP Power Density (dBm/5MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	23.34	22.29			-	-	-	-
Middle CH	-	-	-	-	23.35	22.23	23.61	22.29	-	-	-	-
Highest CH	-	-	-	-	23.51	22.24			-	-	-	-
Antenna Gain	-2.2 dBi											
Limit	250mW / 5MHz = 24dBm / 5MHz											
Result	Pass											

LTE Band 30 / 5MHz

Lowest Channel / 5MHz / 1RB12 / QPSK



Lowest Channel / 5MHz / 1RB12 / 16QAM



Middle Channel / 5MHz / 1RB24 / QPSK



Middle Channel / 5MHz / 1RB12 / 16QAM



Highest Channel / 5MHz / 1RB0 / QPSK



Highest Channel / 5MHz / 1RB0 / 16QAM



LTE Band 30 / 10MHz	
Lowest Channel / 10MHz / 1RB0 / QPSK	**Lowest Channel / 10MHz / 1RB0 / 16QAM**
	

26dB Bandwidth

Mode	LTE Band 30 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.97	4.97	-	-	-	-	-	-
Middle CH	-	-	-	-	4.95	4.84	9.99	9.87	-	-	-	-
Highest CH	-	-	-	-	4.87	5.01	-	-	-	-	-	-

LTE Band 30

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 30	
Middle Channel / 10MHz / QPSK	Middle Channel / 10MHz / 16QAM





Occupied Bandwidth

Mode	LTE Band 30 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.50	4.48	-	-	-	-	-	-
Middle CH	-	-	-	-	4.49	4.51	9.05	8.99	-	-	-	-
Highest CH	-	-	-	-	4.49	4.48	-	-	-	-	-	-

LTE Band 30

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 30	
Middle Channel / 10MHz / QPSK	Middle Channel / 10MHz / 16QAM





Conducted Band Edge

LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-45.21 dBm	-14.21 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29669 GHz	-39.68 dBm	-14.68 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30103 GHz	-29.28 dBm	-16.28 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30499 GHz	-20.62 dBm	-7.62 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30532 GHz	21.24 dBm	-8.76 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31002 GHz	-56.21 dBm	-43.21 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31382 GHz	-27.21 dBm	-14.21 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32051 GHz	-53.08 dBm	-28.08 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32612 GHz	-53.33 dBm	-22.33 dB

Date: 20.MAY.2020 07:58:52

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29451 GHz	-53.23 dBm	-22.23 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29824 GHz	-53.01 dBm	-28.01 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30581 GHz	-22.24 dBm	-9.24 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30998 GHz	-56.19 dBm	-43.19 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31467 GHz	21.63 dBm	-8.37 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-20.16 dBm	-7.16 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31686 GHz	-30.72 dBm	-17.72 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32317 GHz	-34.26 dBm	-9.26 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32404 GHz	-41.38 dBm	-10.38 dB

Date: 20.MAY.2020 08:15:21

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29592 GHz	-44.07 dBm	-13.07 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29989 GHz	-28.23 dBm	-3.23 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30377 GHz	-19.73 dBm	-6.73 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-27.45 dBm	-14.45 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30741 GHz	7.94 dBm	-22.06 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31000 GHz	-27.54 dBm	-14.54 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31154 GHz	-20.13 dBm	-7.13 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32009 GHz	-44.54 dBm	-19.54 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32419 GHz	-52.07 dBm	-21.07 dB

Date: 20.MAY.2020 08:05:29

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29580 GHz	-52.08 dBm	-21.08 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29995 GHz	-44.64 dBm	-19.64 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30890 GHz	-17.74 dBm	-4.74 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.31000 GHz	-25.77 dBm	-12.77 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31233 GHz	7.62 dBm	-22.38 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-25.96 dBm	-12.96 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31605 GHz	-17.13 dBm	-4.13 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32000 GHz	-27.87 dBm	-2.87 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32411 GHz	-42.43 dBm	-11.43 dB

Date: 20.MAY.2020 08:16:13

LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29596 GHz	-47.81 dBm	-16.81 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29657 GHz	-43.15 dBm	-18.15 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30130 GHz	-33.31 dBm	-20.31 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-21.92 dBm	-8.92 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30534 GHz	20.12 dBm	-9.88 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31000 GHz	-57.26 dBm	-44.26 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31408 GHz	-29.32 dBm	-16.32 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32060 GHz	-53.21 dBm	-28.21 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32510 GHz	-53.39 dBm	-22.39 dB

Date: 20.MAY.2020 07:59:26

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29569 GHz	-53.33 dBm	-22.33 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29813 GHz	-53.09 dBm	-28.09 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30592 GHz	-24.92 dBm	-11.92 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30999 GHz	-56.58 dBm	-43.58 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31465 GHz	20.25 dBm	-9.75 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-21.34 dBm	-8.34 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31673 GHz	-32.46 dBm	-19.46 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32314 GHz	-40.45 dBm	-15.45 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32400 GHz	-47.35 dBm	-16.35 dB

Date: 20.MAY.2020 08:14:35

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29592 GHz	-46.40 dBm	-15.40 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29999 GHz	-28.94 dBm	-3.94 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30384 GHz	-20.77 dBm	-7.77 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-28.77 dBm	-15.77 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30611 GHz	6.95 dBm	-23.05 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31001 GHz	-29.29 dBm	-16.29 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31122 GHz	-21.00 dBm	-8.00 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32034 GHz	-46.15 dBm	-21.15 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32416 GHz	-52.83 dBm	-21.83 dB

Date: 20.MAY.2020 08:04:37

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29586 GHz	-52.83 dBm	-21.83 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29994 GHz	-45.42 dBm	-20.42 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30875 GHz	-19.89 dBm	-6.89 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30999 GHz	-27.84 dBm	-14.84 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31437 GHz	6.74 dBm	-23.26 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-28.37 dBm	-15.37 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31613 GHz	-19.50 dBm	-6.50 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32000 GHz	-27.63 dBm	-2.63 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32401 GHz	-44.42 dBm	-13.42 dB

Date: 20.MAY.2020 08:17:12

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-38.05 dBm	-7.05 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29663 GHz	-30.44 dBm	-5.44 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30146 GHz	-32.87 dBm	-19.87 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-29.86 dBm	-16.86 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30560 GHz	21.84 dBm	-8.16 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31504 GHz	-52.47 dBm	-39.47 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31886 GHz	-45.55 dBm	-32.55 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32335 GHz	-26.46 dBm	-1.46 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32403 GHz	-33.01 dBm	-2.01 dB

Date: 20.MAY.2020 08:29:25

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-32.90 dBm	-1.90 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29669 GHz	-26.17 dBm	-1.17 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30138 GHz	-41.02 dBm	-28.02 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-50.57 dBm	-37.57 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31445 GHz	21.03 dBm	-8.97 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-29.76 dBm	-16.76 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31871 GHz	-32.07 dBm	-19.07 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32327 GHz	-40.01 dBm	-15.01 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32403 GHz	-45.13 dBm	-14.13 dB

Date: 20.MAY.2020 08:36:30

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-40.42 dBm	-9.42 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29989 GHz	-29.58 dBm	-4.58 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30399 GHz	-23.98 dBm	-10.98 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30493 GHz	-32.09 dBm	-19.09 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30847 GHz	1.90 dBm	-28.10 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31502 GHz	-32.45 dBm	-19.45 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31616 GHz	-24.43 dBm	-11.43 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32003 GHz	-29.56 dBm	-4.56 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32402 GHz	-40.01 dBm	-9.01 dB

Date: 29.MAY.2020 22:51:50

LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29593 GHz	-41.07 dBm	-10.07 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29692 GHz	-33.34 dBm	-8.34 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30096 GHz	-34.99 dBm	-21.99 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-30.48 dBm	-17.48 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30562 GHz	20.13 dBm	-9.87 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31503 GHz	-51.98 dBm	-38.98 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31901 GHz	-46.94 dBm	-33.94 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32334 GHz	-28.17 dBm	-3.17 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32401 GHz	-35.52 dBm	-4.52 dB

Date: 20.MAY.2020 08:30:48

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-34.89 dBm	-3.89 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29681 GHz	-28.10 dBm	-3.10 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30095 GHz	-41.91 dBm	-28.91 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-51.44 dBm	-38.44 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31441 GHz	20.24 dBm	-9.76 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-31.85 dBm	-18.85 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31866 GHz	-34.78 dBm	-21.78 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32317 GHz	-42.55 dBm	-17.55 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32407 GHz	-48.19 dBm	-17.19 dB

Date: 20.MAY.2020 08:35:58

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29600 GHz	-32.74 dBm	-1.74 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29999 GHz	-26.31 dBm	-1.31 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30375 GHz	-22.18 dBm	-9.18 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30498 GHz	-29.61 dBm	-16.61 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31151 GHz	4.04 dBm	-25.96 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-29.52 dBm	-16.52 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31639 GHz	-21.60 dBm	-8.60 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32000 GHz	-26.04 dBm	-1.04 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32401 GHz	-32.71 dBm	-1.71 dB

Date: 20.MAY.2020 08:21:58

Conducted Spurious Emission

LTE Band 30 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	926.55922 MHz	-53.45 dBm	-13.45 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.26079 GHz	-53.73 dBm	-13.73 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.65829 GHz	-52.75 dBm	-12.75 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61105 GHz	-43.63 dBm	-3.63 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.87827 GHz	-50.01 dBm	-10.01 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.94801 GHz	-48.13 dBm	-8.13 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.91651 GHz	-45.92 dBm	-5.92 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.82860 GHz	-45.37 dBm	-5.37 dB

Date: 20.MAY.2020 07:55:51

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	923.65067 MHz	-53.53 dBm	-13.53 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29178 GHz	-53.92 dBm	-13.92 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.85106 GHz	-52.75 dBm	-12.75 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61105 GHz	-44.70 dBm	-4.70 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.91826 GHz	-50.20 dBm	-10.20 dB
10.000 GHz	14.000 GHz	1.000 MHz	12.40995 GHz	-48.07 dBm	-8.07 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.04837 GHz	-45.76 dBm	-5.76 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.86709 GHz	-45.53 dBm	-5.53 dB

Date: 20.MAY.2020 08:00:32

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	871.78161 MHz	-53.46 dBm	-13.46 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.27758 GHz	-53.24 dBm	-13.24 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.64889 GHz	-52.97 dBm	-12.97 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61605 GHz	-43.23 dBm	-3.23 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.87027 GHz	-50.24 dBm	-10.24 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.94051 GHz	-47.96 dBm	-7.96 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.03837 GHz	-46.01 dBm	-6.01 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.82760 GHz	-45.48 dBm	-5.48 dB

Date: 20.MAY.2020 08:09:31

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	963.88556 MHz	-53.55 dBm	-13.55 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.28834 GHz	-53.69 dBm	-13.69 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.83259 GHz	-52.85 dBm	-12.85 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61605 GHz	-45.23 dBm	-5.23 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.16389 GHz	-50.05 dBm	-10.05 dB
10.000 GHz	14.000 GHz	1.000 MHz	12.83090 GHz	-48.04 dBm	-8.04 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.04937 GHz	-45.87 dBm	-5.87 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.85910 GHz	-45.46 dBm	-5.46 dB

Date: 20.MAY.2020 08:08:33

LTE Band 30 / 5MHz

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	856.75412 MHz	-53.37 dBm	-13.37 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.28490 GHz	-53.79 dBm	-13.79 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.66467 GHz	-52.98 dBm	-12.98 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.62105 GHz	-43.23 dBm	-3.23 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.86527 GHz	-50.19 dBm	-10.19 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.95551 GHz	-48.00 dBm	-8.00 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.04037 GHz	-45.95 dBm	-5.95 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.86759 GHz	-45.42 dBm	-5.42 dB

Date: 20.MAY.2020 08:10:41

Highest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	916.37931 MHz	-53.19 dBm	-13.19 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29049 GHz	-53.74 dBm	-13.74 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.68146 GHz	-52.95 dBm	-12.95 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.62105 GHz	-45.21 dBm	-5.21 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.15789 GHz	-50.12 dBm	-10.12 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.93501 GHz	-48.19 dBm	-8.19 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.05487 GHz	-46.10 dBm	-6.10 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.83910 GHz	-45.41 dBm	-5.41 dB

Date: 20.MAY.2020 08:11:38

LTE Band 30 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	864.02549 MHz	-53.45 dBm	-13.45 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.28791 GHz	-51.38 dBm	-11.38 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.64889 GHz	-52.84 dBm	-12.84 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61155 GHz	-43.15 dBm	-3.15 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.37485 GHz	-50.11 dBm	-10.11 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.95301 GHz	-48.18 dBm	-8.18 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.04937 GHz	-45.94 dBm	-5.94 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.84460 GHz	-45.51 dBm	-5.51 dB

Date: 20.MAY.2020 08:30:12

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	949.34283 MHz	-53.49 dBm	-13.49 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.28791 GHz	-53.19 dBm	-13.19 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.65560 GHz	-52.76 dBm	-12.76 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61155 GHz	-44.96 dBm	-4.96 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.86877 GHz	-50.20 dBm	-10.20 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.89851 GHz	-48.19 dBm	-8.19 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.91301 GHz	-45.89 dBm	-5.89 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.87359 GHz	-45.34 dBm	-5.34 dB

Date: 20.MAY.2020 08:32:10

Frequency Stability

Test Conditions		LTE Band 30 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0021	PASS
40	Normal Voltage	0.0035	
30	Normal Voltage	0.0008	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0014	
-10	Normal Voltage	0.0023	
-20	Normal Voltage	0.0029	
-30	Normal Voltage	0.0013	
20	Maximum Voltage	0.0007	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0041	

Note:

1. Normal Voltage =4.0 V.；Battery End Point (BEP) =3.6 V.；Maximum Voltage =4.4 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

LTE Band 30 / 10MHz / QPSK / RB Size 1 Offset 0								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4612	-58.25	-40	-18.25	-66.43	2.12	10.30	H
	6916	-55.64	-40	-15.64	-64.88	2.47	11.71	H
	9220	-58.43	-40	-18.43	-68.53	2.81	12.91	H
	11530	-53.71	-40	-13.71	-63.75	3.60	13.64	H
	4612	-63.73	-40	-23.73	-71.91	2.12	10.30	V
	6916	-58.74	-40	-18.74	-67.98	2.47	11.71	V
	9222.36	-57.79	-40	-17.79	-67.89	2.81	12.91	V
	11530	-53.99	-40	-13.99	-64.03	3.60	13.64	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.