FCC RF Test Report

APPLICANT	:	VinSmart Research and Manufacture Joint Stock Company
EQUIPMENT	:	SMARTPHONE
BRAND NAME	:	AT&T
MODEL NAME	:	V350C
FCC ID	:	2AVD3V350C
STANDARD	:	47 CFR Part 2, 90(R)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on May 15, 2020 and completely tested on Aug. 18, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Maximum ERP Power, Frequency Tolerance, and Emission Designator 6
1.5 Testing Site 6
1.6 Test Software 6
1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 10

3 CONDUCTED TEST ITEMS **11**

3.1 Measuring Instruments 11
3.2 Conducted Output Power and ERP 12
3.3 Peak-to-Average Ratio 13
3.4 Occupied Bandwidth 14
3.5 Conducted Band Edge Measurement 15
3.6 Emission Mask 16
3.7 Conducted Spurious Emission Measurement 17
3.8 Frequency Stability Measurement 18

4 RADIATED TEST ITEMS **19**

4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 19
4.4 Radiated Spurious Emission Measurement 20

5 LIST OF MEASURING EQUIPMENT **21**

6 UNCERTAINTY OF EVALUATION **22**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG051501-01C	Rev. 01	Initial issue of report	Sep. 15, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	PASS	-
	§90.542 (a)(7)	Effective Radiated Power	ERP < 3Watt	PASS	-
3.3	-	Peak-to-Average Ratio	Reporting only	-	-
3.4	§2.1049	Occupied Bandwidth	Reporting only	PASS	-
3.5	§2.1053 §90.543 (e)(2)(3)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.6	§2.1051 §90.210(n)	Emission Mask	Mask B	PASS	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	< ±1.25 ppm	PASS	-
4.4	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 25.86 dB at 1578.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

VinSmart Research and Manufacture Joint Stock Company
Lot CN1-06B-1&2, Hi-tech Industrial Park 1, Hoa Lac Hi-tech Park, Ha Bang, Thach That, Hanoi, Vietnam

1.2 Manufacturer

VinSmart Research and Manufacture Joint Stock Company
Lot CN1-06B-1&2, Hi-tech Industrial Park 1, Hoa Lac Hi-tech Park, Ha Bang, Thach That, Hanoi, Vietnam

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	SMARTPHONE
Brand Name	AT&T
Model Name	V350C
FCC ID	2AVD3V350C
Tx Frequency	LTE Band 14: 790.5 MHz ~ 795.5 MHz
Rx Frequency	LTE Band 14: 760.5 MHz ~ 765.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	23.11 dBm
Antenna Gain	-0.73 dBi
Type of Modulation	QPSK / 16QAM / 16QAM
IMEI Code	Conducted: 353795160003958 Radiation: 353795160011787
HW Version	REV 1.0
SW Version	V350C_A1_200903
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a test report for change in FCC ID, there is no difference on the product design between FCC ID: 2AVD3V350C and original FCC ID: 2AVD3V350U, all the test results are leveraged from original FCC ID: 2AVD3V350U, report number FG051501C.

1.4 Maximum ERP Power, Frequency Tolerance, and Emission Designator

LTE Band 14		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	**790.5~795.5**	4M50G7D	-	0.1028	4M51W7D	-	0.0875
10	**793**	8M95G7D	0.0044	0.1054	9M01W7D	-	0.0893

LTE Band 14		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	**790.5~795.5**	4M51W7D	-	0.0698
10	**793**	8M99W7D	-	0.0690

1.5 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 90(R)
- ANSI C63.26-2015
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	V	-	-	-	V	V	V	V	V	V	V	V	V
	14	-	-		V	-	-	V	V	V	V	V	V		V	
Peak-to-Average Ratio	14	-	-		V	-	-	V	V	V	V		V		V	
26dB and 99% Bandwidth	14	-	-	V		-	-	V	V	V			V	V	V	V
	14	-	-		V	-	-	V	V	V			V		V	
Conducted Band Edge	14	-	-	V		-	-	V	V	V	V		V	V		V
	14	-	-		V	-	-	V	V	V	V		V		V	
Emission Mask	14	-	-	V		-	-	V	V	V	V		V	V	V	V
	14	-	-		V	-	-	V	V	V	V		V		V	
Conducted Spurious Emission	14	-	-	V		-	-	V	V	V	V			V	V	V
	14	-	-		V	-	-	V	V	V	V				V	
Frequency Stability	14	-	-		V	-	-	V					V		V	
E.R.P	14	-	-	V		-	-	V	V	V	V			V	V	V
	14	-	-		V	-	-	V	V	V	V				V	
Radiated Spurious Emission	14	Worst case													V	
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Earphone	Moto	N/A	N/A	Unshielded,1.2m	N/A
3.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.8 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 4.8 (dB)

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.6 Emission Mask

3.6.1 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The power of the modulated signal was measured on a spectrum analyzer using an RMS and 10 second sweep time in order to maximize the level.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.6.2 Test Setup



3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

4. The testing follows ANSI C63.26 section 5.7
5. The EUT was connected to spectrum analyzer and base station via power divider.
6. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
7. The middle channel for the highest RF power within the transmitting frequency was measured.
8. The conducted spurious emission for the whole frequency range was taken.
9. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
10. Set spectrum analyzer with RMS detector.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
12. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±1.25 ppm of the center frequency.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 02, 2019	Aug. 06, 2020~ Aug. 18, 2020	Nov. 01, 2020	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 28, 2019	Aug. 06, 2020~ Aug. 18, 2020	Oct. 27, 2020	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2020	Aug. 17, 2020	Apr. 14, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jan. 02, 2020	Aug. 17, 2020	Jan. 01, 2021	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 20, 2020	Aug. 17, 2020	Apr. 19, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Aug. 17, 2020	Nov. 09, 2020	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 02, 2020	Aug. 17, 2020	Jan. 01, 2021	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 08, 2020	Aug. 17, 2020	Jan. 07, 2021	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 02, 2020	Aug. 17, 2020	Jan. 01, 2021	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 15, 2019	Aug. 17, 2020	Oct. 14, 2020	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 17, 2020	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 17, 2020	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 17, 2020	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.75	22.85	22.81
5	1	12		22.90	22.74	23.00
5	1	24		22.80	22.79	22.81
5	12	0		22.06	21.93	21.96
5	12	7		22.01	21.86	21.88
5	12	13		21.97	21.81	21.83
5	25	0		21.95	21.89	21.81
5	1	0	16-QAM	22.24	22.23	22.23
5	1	12		22.10	22.30	22.10
5	1	24		22.00	22.05	22.01
5	12	0		21.08	20.98	20.89
5	12	7		21.02	20.95	20.92
5	12	13		20.87	20.83	20.86
5	25	0		20.93	20.91	20.93
5	1	0	64QAM	21.20	21.24	21.10
5	1	12		21.32	21.23	20.97
5	1	24		20.98	21.00	20.99
5	12	0		20.08	19.89	19.87
5	12	7		19.95	19.88	19.88
5	12	13		20.00	19.85	19.86
5	25	0		20.02	19.90	19.82

LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	-	23.11	-
10	1	25			22.91	
10	1	49			22.93	
10	25	0			22.05	
10	25	12			21.89	
10	25	25			21.86	
10	50	0			21.92	
10	1	0	16-QAM		22.39	
10	1	25			22.07	
10	1	49			22.23	
10	25	0			20.98	
10	25	12			20.90	
10	25	25			20.70	
10	50	0			20.95	
10	1	0	64QAM		21.23	
10	1	25			20.96	
10	1	49			21.27	
10	25	0			20.17	
10	25	12			20.05	
10	25	25			19.89	
10	50	0			20.03	

ERP

LTE Band 14 (G_T - L_C = -0.73 dBi) QPSK						
Bandwidth	5M			10M		
Channel	23305	23330	23355		23330	
	(Low)	(Mid)	(High)		(Mid)	
Frequency (MHz)	790.5	793	795.5		793	
Conducted Power (dBm)	22.90	22.74	23.00		23.11	
Conducted Power (Watts)	0.1950	0.1879	0.1995		0.2046	
ERP(dBm)	20.02	19.86	20.12		20.23	
ERP(Watts)	0.1005	0.0968	0.1028		0.1054	

LTE Band 14 (G_T - L_C = -0.73 dBi) 16QAM						
Bandwidth	5M			10M		
Channel	23305	23330	23355		23330	
	(Low)	(Mid)	(High)		(Mid)	
Frequency (MHz)	790.5	793	795.5		793	
Conducted Power (dBm)	22.10	22.30	22.10		22.39	
Conducted Power (Watts)	0.1622	0.1698	0.1622		0.1734	
ERP(dBm)	19.22	19.42	19.22		19.51	
ERP(Watts)	0.0836	0.0875	0.0836		0.0893	

LTE Band 14 (G_T - L_C = -0.73 dBi) 64QAM						
Bandwidth	**5M**			**10M**		
Channel	**23305**	**23330**	**23355**		**23330**	
	(Low)	**(Mid)**	**(High)**		**(Mid)**	
Frequency (MHz)	**790.5**	**793**	**795.5**		**793**	
Conducted Power (dBm)	21.32	21.23	20.97		21.27	
Conducted Power (Watts)	0.1355	0.1327	0.1250		0.1340	
ERP(dBm)	18.44	18.35	18.09		18.39	
ERP(Watts)	0.0698	0.0684	0.0644		0.0690	

Peak-to-Average Ratio

Mode	LTE Band 14 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.94	4.67	4.49	5.83	
Highest CH	-	-	-	-	
Mode	LTE Band 14 / 10MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	-	-	-	-	PASS
Middle CH	5.54	6.20	-	-	
Highest CH	-	-	-	-	

LTE Band 14 / 10MHz / QPSK

Middle Channel/ 1RB



Middle Channel / Full RB



LTE Band 14 / 10MHz / 16QAM

Middle Channel/ 1RB



Middle Channel / Full RB



LTE Band 14 / 10MHz / 64QAM	
Middle Channel/ 1RB	**Middle Channel / Full RB**
	

26dB Bandwidth

Mode	LTE Band 14 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.96	4.90	-	-	-	-	-	-
Middle CH	-	-	-	-	4.92	4.93	10.05	9.83	-	-	-	-
Highest CH	-	-	-	-	4.94	4.89	-	-	-	-	-	-
Mode	LTE Band 14 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.88	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.85	-	9.85	-	-	-	-	-
Highest CH	-	-	-	-	4.94	-	-	-	-	-	-	-

LTE Band 14

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 14	
Middle Channel / 10MHz / QPSK	**Middle Channel / 10MHz / 16QAM**





LTE Band 14

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



Occupied Bandwidth

Mode	LTE Band 14 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.48	4.51	-	-	-	-	-	-
Middle CH	-	-	-	-	4.48	4.50	8.95	9.01	-	-	-	-
Highest CH	-	-	-	-	4.50	4.47	-	-	-	-	-	-
Mode	LTE Band 14 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.51	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.50	-	8.99	-	-	-	-	-
Highest CH	-	-	-	-	4.49	-	-	-	-	-	-	-

LTE Band 14

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 14	
Middle Channel / 10MHz / QPSK	**Middle Channel / 10MHz / 16QAM**





LTE Band 14

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	754.00799 MHz	-65.50 dBm	-52.50 dB
758.000 MHz	769.000 MHz	100.000 kHz	758.56593 MHz	-64.13 dBm	-94.13 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.71828 MHz	-76.40 dBm	-41.40 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-20.56 dBm	-7.56 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.35714 MHz	19.91 dBm	-10.09 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.70430 MHz	-71.60 dBm	-36.60 dB
805.000 MHz	810.000 MHz	100.000 kHz	807.55495 MHz	-63.61 dBm	-50.61 dB

Date: 6.AUG.2020 22:03:37

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.97802 MHz	-61.99 dBm	-48.99 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.73077 MHz	-64.41 dBm	-94.41 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.33367 MHz	-76.50 dBm	-41.50 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.29221 MHz	-61.71 dBm	-48.71 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.67582 MHz	20.62 dBm	-9.38 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.83616 MHz	-48.16 dBm	-13.16 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.19131 MHz	-60.98 dBm	-47.98 dB

Date: 6.AUG.2020 22:10:45

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	754.60739 MHz	-65.57 dBm	-52.57 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.54396 MHz	-64.07 dBm	-94.07 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.62937 MHz	-76.72 dBm	-41.72 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-27.61 dBm	-14.61 dB
788.000 MHz	799.000 MHz	100.000 kHz	790.46703 MHz	6.74 dBm	-23.26 dB
799.000 MHz	805.000 MHz	6.250 kHz	800.49550 MHz	-55.73 dBm	-20.73 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.08741 MHz	-53.94 dBm	-40.94 dB

Date: 6.AUG.2020 22:00:29

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	752.96104 MHz	-65.52 dBm	-52.52 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.76374 MHz	-64.45 dBm	-94.45 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.37862 MHz	-76.51 dBm	-41.51 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.90260 MHz	-44.26 dBm	-31.26 dB
788.000 MHz	799.000 MHz	100.000 kHz	794.50000 MHz	6.21 dBm	-23.79 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.05894 MHz	-52.76 dBm	-17.76 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.11738 MHz	-45.47 dBm	-32.47 dB

Date: 6.AUG.2020 22:07:37

LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge /1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	753.13686 MHz	-65.54 dBm	-52.54 dB
758.000 MHz	769.000 MHz	100.000 kHz	767.06044 MHz	-64.36 dBm	-94.36 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.36464 MHz	-76.54 dBm	-41.54 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-20.30 dBm	-7.30 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.33516 MHz	19.56 dBm	-10.44 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.74625 MHz	-72.21 dBm	-37.21 dB
805.000 MHz	810.000 MHz	100.000 kHz	809.77772 MHz	-63.64 dBm	-50.64 dB

Date: 6.AUG.2020 22:02:34

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.97802 MHz	-62.75 dBm	-49.75 dB
758.000 MHz	769.000 MHz	100.000 kHz	767.45604 MHz	-64.27 dBm	-94.27 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.20480 MHz	-76.53 dBm	-41.53 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.30519 MHz	-61.87 dBm	-48.87 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.67582 MHz	19.37 dBm	-10.63 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.83616 MHz	-52.48 dBm	-17.48 dB
805.000 MHz	810.000 MHz	100.000 kHz	809.00849 MHz	-61.60 dBm	-48.60 dB

Date: 6.AUG.2020 22:09:42

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.49451 MHz	-65.50 dBm	-52.50 dB
758.000 MHz	769.000 MHz	100.000 kHz	759.10440 MHz	-64.49 dBm	-94.49 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.46354 MHz	-76.44 dBm	-41.44 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-29.07 dBm	-16.07 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.39011 MHz	5.54 dBm	-24.46 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.29670 MHz	-57.20 dBm	-22.20 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.26723 MHz	-57.11 dBm	-44.11 dB

Date: 6.AUG.2020 22:01:31

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.15784 MHz	-65.55 dBm	-52.55 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.35714 MHz	-64.43 dBm	-94.43 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.76324 MHz	-76.67 dBm	-41.67 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.87662 MHz	-44.63 dBm	-31.63 dB
788.000 MHz	799.000 MHz	100.000 kHz	796.43407 MHz	5.42 dBm	-24.58 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.72228 MHz	-51.46 dBm	-16.46 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.00250 MHz	-47.03 dBm	-34.03 dB

Date: 6.AUG.2020 22:08:39

LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.82218 MHz	-65.53 dBm	-52.53 dB
758.000 MHz	769.000 MHz	100.000 kHz	764.33516 MHz	-64.51 dBm	-94.51 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.47552 MHz	-76.69 dBm	-41.69 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-21.63 dBm	-8.63 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.35714 MHz	19.90 dBm	-10.10 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.75225 MHz	-72.61 dBm	-37.61 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.71678 MHz	-63.62 dBm	-50.62 dB

Date: 6.AUG.2020 22:13:57

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.96204 MHz	-62.90 dBm	-49.90 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.37912 MHz	-63.97 dBm	-93.97 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.38462 MHz	-76.42 dBm	-41.42 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.30519 MHz	-62.55 dBm	-49.55 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.65385 MHz	19.57 dBm	-10.43 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.83616 MHz	-51.91 dBm	-16.91 dB
805.000 MHz	810.000 MHz	100.000 kHz	809.04845 MHz	-61.32 dBm	-48.32 dB

Date: 6.AUG.2020 22:17:31

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	752.32967 MHz	-65.53 dBm	-52.53 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.77473 MHz	-64.15 dBm	-94.15 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.87712 MHz	-76.60 dBm	-41.60 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-29.26 dBm	-16.26 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.43407 MHz	5.87 dBm	-24.13 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.11688 MHz	-56.56 dBm	-21.56 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.09241 MHz	-56.96 dBm	-43.96 dB

Date: 6.AUG.2020 22:12:54

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.22178 MHz	-65.56 dBm	-52.56 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.10440 MHz	-64.27 dBm	-94.27 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.20579 MHz	-76.49 dBm	-41.49 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.88961 MHz	-44.74 dBm	-31.74 dB
788.000 MHz	799.000 MHz	100.000 kHz	796.50000 MHz	5.29 dBm	-24.71 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.24276 MHz	-52.00 dBm	-17.00 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.02248 MHz	-47.68 dBm	-34.68 dB

Date: 6.AUG.2020 22:16:28

LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	767.02747 MHz	-65.36 dBm	-30.36 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.57742 MHz	-76.14 dBm	-63.14 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-33.18 dBm	-20.18 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.60989 MHz	21.36 dBm	-8.64 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.80220 MHz	-59.86 dBm	-24.86 dB

Date: 6.AUG.2020 23:17:25

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.72228 MHz	-61.81 dBm	-48.81 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.64286 MHz	-64.20 dBm	-94.20 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.12188 MHz	-76.56 dBm	-41.56 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.16234 MHz	-51.80 dBm	-38.80 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.40110 MHz	20.26 dBm	-9.74 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.83816 MHz	-54.40 dBm	-19.40 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.11638 MHz	-48.94 dBm	-35.94 dB

Date: 6.AUG.2020 22:23:51

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.11489 MHz	-65.54 dBm	-52.54 dB
758.000 MHz	769.000 MHz	100.000 kHz	759.01648 MHz	-64.30 dBm	-94.30 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.61239 MHz	-76.57 dBm	-41.57 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.96753 MHz	-32.89 dBm	-19.89 dB
788.000 MHz	799.000 MHz	100.000 kHz	794.51099 MHz	3.79 dBm	-26.21 dB
799.000 MHz	805.000 MHz	6.250 kHz	802.50350 MHz	-54.49 dBm	-19.49 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.12238 MHz	-44.17 dBm	-31.17 dB

Date: 6.AUG.2020 22:19:40

LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.04595 MHz	-65.55 dBm	-52.55 dB
758.000 MHz	769.000 MHz	100.000 kHz	766.39011 MHz	-64.08 dBm	-94.08 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.24176 MHz	-76.63 dBm	-41.63 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-33.66 dBm	-20.66 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.59890 MHz	19.07 dBm	-10.93 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.82018 MHz	-65.20 dBm	-30.20 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.24126 MHz	-57.88 dBm	-44.88 dB

Date: 6.AUG.2020 22:21:46

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.73826 MHz	-62.50 dBm	-49.50 dB
758.000 MHz	769.000 MHz	100.000 kHz	766.42308 MHz	-64.41 dBm	-94.41 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.80719 MHz	-76.67 dBm	-41.67 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.17532 MHz	-53.11 dBm	-40.11 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.41209 MHz	19.38 dBm	-10.62 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.82018 MHz	-56.48 dBm	-21.48 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.20629 MHz	-49.39 dBm	-36.39 dB

Date: 6.AUG.2020 22:24:54

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.87013 MHz	-65.55 dBm	-52.55 dB
758.000 MHz	769.000 MHz	100.000 kHz	764.30220 MHz	-64.33 dBm	-94.33 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.32767 MHz	-76.47 dBm	-41.47 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-34.53 dBm	-21.53 dB
788.000 MHz	799.000 MHz	100.000 kHz	795.00549 MHz	2.97 dBm	-27.03 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.23077 MHz	-53.85 dBm	-18.85 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.05744 MHz	-45.65 dBm	-32.65 dB

Date: 6.AUG.2020 22:20:43

LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.59740 MHz	-65.53 dBm	-52.53 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.65385 MHz	-64.47 dBm	-94.47 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.08392 MHz	-76.49 dBm	-41.49 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-34.88 dBm	-21.88 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.59890 MHz	19.77 dBm	-10.23 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.83217 MHz	-65.59 dBm	-30.59 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.21129 MHz	-58.13 dBm	-45.13 dB

Date: 6.AUG.2020 22:28:06

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.73027 MHz	-62.68 dBm	-49.68 dB
758.000 MHz	769.000 MHz	100.000 kHz	759.81868 MHz	-64.39 dBm	-94.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.11688 MHz	-76.55 dBm	-41.55 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.16234 MHz	-53.40 dBm	-40.40 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.40110 MHz	19.61 dBm	-10.39 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.88012 MHz	-56.13 dBm	-21.13 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.24126 MHz	-50.45 dBm	-37.45 dB

Date: 6.AUG.2020 22:29:09

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.86913 MHz	-65.58 dBm	-52.58 dB
758.000 MHz	769.000 MHz	100.000 kHz	761.74176 MHz	-64.09 dBm	-94.09 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.08092 MHz	-76.32 dBm	-41.32 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-34.31 dBm	-21.31 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.23626 MHz	2.92 dBm	-27.08 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.27872 MHz	-54.00 dBm	-19.00 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.32717 MHz	-46.27 dBm	-33.27 dB

Date: 6.AUG.2020 22:27:03

Conducted Spurious Emission

LTE Band 14 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	743.26537 MHz	-64.50 dBm	-51.50 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.24363 MHz	-63.69 dBm	-50.69 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-45.07 dBm	-32.07 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.99835 GHz	-49.90 dBm	-36.90 dB

Date: 7.AUG.2020 01:51:18

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	734.89755 MHz	-64.58 dBm	-51.58 dB
805.000 MHz	1.000 GHz	100.000 kHz	807.48501 MHz	-63.91 dBm	-50.91 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-46.30 dBm	-33.30 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.99485 GHz	-50.05 dBm	-37.05 dB

Date: 6.AUG.2020 22:04:20

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	745.81209 MHz	-64.40 dBm	-51.40 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.04873 MHz	-63.46 dBm	-50.46 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-44.98 dBm	-31.98 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.97335 GHz	-49.92 dBm	-36.92 dB

Date: 6.AUG.2020 22:05:04

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	745.81209 MHz	-64.58 dBm	-51.58 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.24363 MHz	-63.83 dBm	-50.83 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-46.92 dBm	-33.92 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.99185 GHz	-49.91 dBm	-36.91 dB

Date: 6.AUG.2020 22:04:42

LTE Band 14 / 5MHz

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	613.74613 MHz	-64.66 dBm	-51.66 dB
805.000 MHz	1.000 GHz	100.000 kHz	807.19265 MHz	-63.16 dBm	-50.16 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-45.58 dBm	-32.58 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.98935 GHz	-50.00 dBm	-37.00 dB

Date: 6.AUG.2020 22:11:06

Highest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	748.35882 MHz	-64.45 dBm	-51.45 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.04873 MHz	-63.00 dBm	-50.00 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-46.38 dBm	-33.38 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.99485 GHz	-49.87 dBm	-36.87 dB

Date: 6.AUG.2020 22:11:28

LTE Band 14 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	743.62919 MHz	-63.81 dBm	-50.81 dB
805.000 MHz	1.000 GHz	100.000 kHz	806.21814 MHz	-58.17 dBm	-45.17 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57761 GHz	-44.79 dBm	-31.79 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.95735 GHz	-49.96 dBm	-36.96 dB

Date: 6.AUG.2020 22:25:37

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	724.71064 MHz	-64.63 dBm	-51.63 dB
805.000 MHz	1.000 GHz	100.000 kHz	806.31559 MHz	-58.84 dBm	-45.84 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57761 GHz	-44.76 dBm	-31.76 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.97035 GHz	-49.83 dBm	-36.83 dB

Date: 6.AUG.2020 22:25:15

LTE Band 14 / 5MHz

Lowest Channel / 64QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	753.81609 MHz	-64.78 dBm	-51.78 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.43853 MHz	-63.57 dBm	-50.57 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-45.98 dBm	-32.98 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.98185 GHz	-49.91 dBm	-36.91 dB

Date: 6.AUG.2020 22:14:18

Middle Channel / 64QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	755.63518 MHz	-64.84 dBm	-51.84 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.14618 MHz	-63.52 dBm	-50.52 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-46.36 dBm	-33.36 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.97535 GHz	-49.90 dBm	-36.90 dB

Date: 6.AUG.2020 22:14:40

Highest Channel / 64QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	746.53973 MHz	-64.78 dBm	-51.78 dB
805.000 MHz	1.000 GHz	100.000 kHz	806.41304 MHz	-63.52 dBm	-50.52 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-46.75 dBm	-33.75 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.92286 GHz	-49.49 dBm	-36.49 dB

Date: 6.AUG.2020 22:17:52

LTE Band 14 / 10MHz	
Middle Channel / 64QAM	



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	743.62919 MHz	-64.60 dBm	-51.60 dB
805.000 MHz	1.000 GHz	100.000 kHz	806.21814 MHz	-57.77 dBm	-44.77 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57761 GHz	-46.98 dBm	-33.98 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.98935 GHz	-49.84 dBm	-36.84 dB

Mask

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / 64QAM

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / QPSK

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / 64QAM

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / QPSK

Highest Channel / 1RB





Highest Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Highest Channel / 1RB





Highest Channel / Full RB



LTE Band 14 / 5MHz / 64QAM

Highest Channel / 1RB





Highest Channel / Full RB



LTE Band 14 / 10MHz / QPSK

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 10MHz / 16QAM

Middle Channel / 1RB





Middle Channel / Full RB