



TEST REPORT

Applicant Name : Guangzhou Chixiang Car Accessories Co., Ltd
Address : Room 408, Building 2, No. 87, Jiangxia East 1st Road,
Huangshi Street, Baiyun District, GuangZhou,Guangdong,
China
Report Number : RA230511-25549E-RF-00
FCC ID: 2AVDT-EWSM50K1

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Monitor Display
Model No.: EW-SM50K1
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2023/05/11
Report Date: 2023/06/09

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Dave Liang

Dave Liang
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- MPE-BASED EXEMPTION	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	14
TEST PROCEDURE	14
FACTOR & MARGIN CALCULATION	14
TEST DATA	14
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(E) - POWER SPECTRAL DENSITY	26

APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
APPENDIX	27
APPENDIX A: DTS BANDWIDTH	27
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	34
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	41
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	42
APPENDIX E: BAND EDGE MEASUREMENTS.....	49
APPENDIX F: DUTY CYCLE	53

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230511-25549E-RF-00	Original Report	2023/06/09

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	Wi-Fi: 2412-2462MHz/2422-2452MHz
Maximum Conducted Average Output Power	15.28dBm
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification*	2.39dBi (provided by the applicant)
Voltage Range	DC 12V
Sample serial number	25OD-1 for Radiated Emissions Test 25OC-1 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Audio Frequency Response		0.1dB
Low Pass Filter Response		1.2dB
Modulation Limiting		1%
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

802.11 b/g/n20 modes were tested with Channel 1, 6 and 11. 802.11n40 mode was tested with Channel 3, 6 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“MT7601USB”* software was used to test and power level as below table. The software and power level was provided by applicant.

The device was tested with the worst case was performed as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	01	01	01
802.11g	6Mbps	01	01	01
802.11n-HT20	MCS0	01	01	01
802.11n-HT40	MCS0	01	01	01

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
UNI-T	Programmable DC power supply	UTP8305M	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable DC Cable	1.0	Programmable DC power supply	EUT

Block Diagram of Test Setup

For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Not Applicable: The device is powered by the vehicle.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2022/11/30	2025/11/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18G-10SS	5	2022/11/25	2023/11/24
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101495	2022/11/25	2023/11/24
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
Agilent	USB wideband power sensor	U2021XA	MY54250003	2022/6/27	2023/6/26
WEINSCHHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	Each time

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
Wi-Fi	2412-2462	16.00	2.39	0.24	16.24	42.07	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.

2. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an integral antenna arrangement, which was permanently attached and the antenna gain is 2.39dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247, RSS-247, RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a overlimit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Corrected Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23~25.6 °C
Relative Humidity:	52%
ATM Pressure:	101.0 kPa


The testing was performed by Jason Liu on 2023-05-24 for below 1GHz and Jason Liu on 2023-05-23 for above 1GHz.

EUT operation mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz: (Worst case is 802.11b mode, low Channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA230511-25549E-RF
Test Mode: 2.4G WIFI Transmitting

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	96.605	-12.29	49.79	37.50	43.50	-6.00	Peak
2	152.731	-15.10	43.65	28.55	43.50	-14.95	Peak
3	287.990	-9.36	45.94	36.58	46.00	-9.42	Peak
4	312.043	-8.82	51.10	42.28	46.00	-3.72	QP
5	593.050	-2.71	40.33	37.62	46.00	-8.38	Peak
6	842.868	0.36	39.36	39.72	46.00	-6.28	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA230511-25549E-RF
Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	41.531	-10.10	40.15	30.05	40.00	-9.95	Peak
2	75.380	-16.31	48.53	32.22	40.00	-7.78	QP
3	152.798	-15.10	54.09	38.99	43.50	-4.51	QP
4	287.990	-9.36	52.20	42.84	46.00	-3.16	QP
5	312.043	-8.82	50.70	41.88	46.00	-4.12	QP
6	561.923	-3.98	41.91	37.93	46.00	-8.07	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11b									
Low Channel(2412MHz)									
2389.92	66.49	PK	113	1.5	H	-10.62	55.87	74	-18.13
2389.92	53.05	AV	113	1.5	H	-10.62	42.43	54	-11.57
2389.21	65.02	PK	321	2.1	V	-10.62	54.40	74	-19.60
2389.21	52.61	AV	321	2.1	V	-10.62	41.99	54	-12.01
2390	65.37	PK	220	2.4	H	-10.62	54.75	74	-19.25
2390	52.36	AV	220	2.4	H	-10.62	41.74	54	-12.26
2390	63.72	PK	164	1.3	V	-10.62	53.10	74	-20.90
2390	51.14	AV	164	1.3	V	-10.62	40.52	54	-13.48
4824	59.90	PK	303	1.7	H	-5.55	54.35	74	-19.65
4824	47.38	AV	303	1.7	H	-5.55	41.83	54	-12.17
4824	60.42	PK	209	1.8	V	-5.55	54.87	74	-19.13
4824	47.87	AV	209	1.8	V	-5.55	42.32	54	-11.68
Middle Channel(2437MHz)									
4874	60.28	PK	194	2.1	H	-5.29	54.99	74	-19.01
4874	47.87	AV	194	2.1	H	-5.29	42.58	54	-11.42
4874	60.60	PK	305	2.3	V	-5.29	55.31	74	-18.69
4874	48.49	AV	305	2.3	V	-5.29	43.2	54	-10.80
High Channel(2462MHz)									
2483.5	64.44	PK	78	1.8	H	-10.46	53.98	74	-20.02
2483.5	52.15	AV	78	1.8	H	-10.46	41.69	54	-12.31
2483.5	64.26	PK	182	1.9	V	-10.46	53.8	74	-20.20
2483.5	52.00	AV	182	1.9	V	-10.46	41.54	54	-12.46
2484.6	65.07	PK	114	1.9	H	-10.45	54.62	74	-19.38
2484.6	52.66	AV	114	1.9	H	-10.45	42.21	54	-11.79
2484.12	64.94	PK	357	2.4	V	-10.46	54.48	74	-19.52
2484.12	52.16	AV	357	2.4	V	-10.46	41.7	54	-12.30
4924	60.42	PK	245	1.3	H	-5.03	55.39	74	-18.61
4924	48.55	AV	245	1.3	H	-5.03	43.52	54	-10.48
4924	60.67	PK	3	2.2	V	-5.03	55.64	74	-18.36
4924	48.66	AV	3	2.2	V	-5.03	43.63	54	-10.37

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11g									
Low Channel(2412MHz)									
2389.83	67.04	PK	21	2.1	H	-10.62	56.42	74	-17.58
2389.83	54.12	AV	21	2.1	H	-10.62	43.50	54	-10.50
2382.47	65.92	PK	172	2.4	V	-10.64	55.28	74	-18.72
2382.47	53.85	AV	172	2.4	V	-10.64	43.21	54	-10.79
2390	66.25	PK	185	2.4	H	-10.62	55.63	74	-18.37
2390	53.16	AV	185	2.4	H	-10.62	42.54	54	-11.46
2390	65.14	PK	144	1.2	V	-10.62	54.52	74	-19.48
2390	52.71	AV	144	1.2	V	-10.62	42.09	54	-11.91
4824	60.63	PK	171	2	H	-5.55	55.08	74	-18.92
4824	49.41	AV	171	2	H	-5.55	43.86	54	-10.14
4824	61.02	PK	339	1.7	V	-5.55	55.47	74	-18.53
4824	49.94	AV	339	1.7	V	-5.55	44.39	54	-9.61
Middle Channel(2437MHz)									
4874	60.87	PK	43	2.5	H	-5.29	55.58	74	-18.42
4874	49.71	AV	43	2.5	H	-5.29	44.42	54	-9.58
4874	61.28	PK	346	2.3	V	-5.29	55.99	74	-18.01
4874	50.20	AV	346	2.3	V	-5.29	44.91	54	-9.09
High Channel(2462MHz)									
2483.5	66.62	PK	223	1.5	H	-10.46	56.16	74	-17.84
2483.5	53.68	AV	223	1.5	H	-10.46	43.22	54	-10.78
2483.5	65.24	PK	274	1.5	V	-10.46	54.78	74	-19.22
2483.5	52.28	AV	274	1.5	V	-10.46	41.82	54	-12.18
2484.63	66.98	PK	143	1.9	H	-10.45	56.53	74	-17.47
2484.63	53.82	AV	143	1.9	H	-10.45	43.37	54	-10.63
2485.16	66.55	PK	167	2	V	-10.45	56.1	74	-17.90
2485.16	53.69	AV	167	2	V	-10.45	43.24	54	-10.76
4924	60.91	PK	263	2	H	-5.03	55.88	74	-18.12
4924	49.80	AV	263	2	H	-5.03	44.77	54	-9.23
4924	61.42	PK	221	2.3	V	-5.03	56.39	74	-17.61
4924	50.25	AV	221	2.3	V	-5.03	45.22	54	-8.78

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11n20									
Low Channel(2412MHz)									
2375.13	66.53	PK	126	2.5	H	-10.67	55.86	74	-18.14
2375.13	54.35	AV	126	2.5	H	-10.67	43.68	54	-10.32
2382.94	65.85	PK	88	1.3	V	-10.64	55.21	74	-18.79
2382.94	53.73	AV	88	1.3	V	-10.64	43.09	54	-10.91
2390	66.23	PK	134	1.5	H	-10.62	55.61	74	-18.39
2390	53.28	AV	134	1.5	H	-10.62	42.66	54	-11.34
2390	64.70	PK	94	1.9	V	-10.62	54.08	74	-19.92
2390	53.05	AV	94	1.9	V	-10.62	42.43	54	-11.57
4824	60.66	PK	258	1.9	H	-5.55	55.11	74	-18.89
4824	45.41	AV	258	1.9	H	-5.55	39.86	54	-14.14
4824	61.13	PK	185	1.6	V	-5.55	55.58	74	-18.42
4824	45.92	AV	185	1.6	V	-5.55	40.37	54	-13.63
Middle Channel(2437MHz)									
4874	60.87	PK	233	2	H	-5.29	55.58	74	-18.42
4874	45.72	AV	233	2	H	-5.29	40.43	54	-13.57
4874	61.38	PK	350	1.8	V	-5.29	56.09	74	-17.91
4874	46.11	AV	350	1.8	V	-5.29	40.82	54	-13.18
High Channel(2462MHz)									
2483.5	65.49	PK	3	1.5	H	-10.46	55.03	74	-18.97
2483.5	53.23	AV	3	1.5	H	-10.46	42.77	54	-11.23
2483.5	64.23	PK	67	2	V	-10.46	53.77	74	-20.23
2483.5	52.13	AV	67	2	V	-10.46	41.67	54	-12.33
2486.06	66.18	PK	252	1.7	H	-10.44	55.74	74	-18.26
2486.06	54.03	AV	252	1.7	H	-10.44	43.59	54	-10.41
2485.32	65.66	PK	354	1.9	V	-10.45	55.21	74	-18.79
2485.32	53.71	AV	354	1.9	V	-10.45	43.26	54	-10.74
4924	60.90	PK	126	2	H	-5.03	55.87	74	-18.13
4924	45.85	AV	126	2	H	-5.03	40.82	54	-13.18
4924	61.44	PK	346	2.4	V	-5.03	56.41	74	-17.59
4924	46.11	AV	346	2.4	V	-5.03	41.08	54	-12.92

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11n40									
Low Channel(2422MHz)									
2379.35	65.66	PK	99	1.3	H	-10.65	55.01	74	-18.99
2379.35	54.33	AV	99	1.3	H	-10.65	43.68	54	-10.32
2380.61	65.05	PK	18	1.1	V	-10.65	54.40	74	-19.60
2380.61	53.77	AV	18	1.1	V	-10.65	43.12	54	-10.88
2390	64.17	PK	201	2.1	H	-10.62	53.55	74	-20.45
2390	53.48	AV	201	2.1	H	-10.62	42.86	54	-11.14
2390	63.87	PK	251	1	V	-10.62	53.25	74	-20.75
2390	53.12	AV	251	1	V	-10.62	42.50	54	-11.50
4844	58.75	PK	337	2.4	H	-5.52	53.23	74	-20.77
4844	45.52	AV	337	2.4	H	-5.52	40.00	54	-14.00
4844	59.28	PK	63	1.5	V	-5.52	53.76	74	-20.24
4844	46.09	AV	63	1.5	V	-5.52	40.57	54	-13.43
Middle Channel(2437MHz)									
4874	58.97	PK	53	1.2	H	-5.29	53.68	74	-20.32
4874	45.70	AV	53	1.2	H	-5.29	40.41	54	-13.59
4874	59.51	PK	76	2.1	V	-5.29	54.22	74	-19.78
4874	46.32	AV	76	2.1	V	-5.29	41.03	54	-12.97
High Channel(2452MHz)									
2483.5	65.62	PK	314	2.1	H	-10.46	55.16	74	-18.84
2483.5	53.64	AV	314	2.1	H	-10.46	43.18	54	-10.82
2483.5	63.99	PK	319	2.3	V	-10.46	53.53	74	-20.47
2483.5	53.08	AV	319	2.3	V	-10.46	42.62	54	-11.38
2487.15	65.84	PK	137	2.2	H	-10.43	55.41	74	-18.59
2487.15	54.50	AV	137	2.2	H	-10.43	44.07	54	-9.93
2486.09	65.62	PK	177	1.8	V	-10.44	55.18	74	-18.82
2486.09	53.94	AV	177	1.8	V	-10.44	43.5	54	-10.50
4904	59.08	PK	122	2.3	H	-5.06	54.02	74	-19.98
4904	45.87	AV	122	2.3	H	-5.06	40.81	54	-13.19
4904	59.45	PK	230	2.5	V	-5.06	54.39	74	-19.61
4904	46.29	AV	230	2.5	V	-5.06	41.23	54	-12.77

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading


Margin = Absolute Level - Limit

The other spurious emission which is 20dB below to the limit was not recorded.


1-18 GHz:

Pre-scan Plots:

802.11 g High Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 g High Channel
Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2023-05-19.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.2.3.2.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2023-05-19.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2023-05-19.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.5.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling on 2023-06-09.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix.

APPENDIX


Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.04	2406.96	2417.00	0.5	PASS
		2437	10.04	2431.96	2442.00	0.5	PASS
		2462	10.04	2456.96	2467.00	0.5	PASS
11G	Ant1	2412	16.36	2403.80	2420.16	0.5	PASS
		2437	16.36	2428.80	2445.16	0.5	PASS
		2462	16.36	2453.80	2470.16	0.5	PASS
11N20SISO	Ant1	2412	17.08	2403.44	2420.52	0.5	PASS
		2437	17.08	2428.44	2445.52	0.5	PASS
		2462	17.08	2453.44	2470.52	0.5	PASS
11N40SISO	Ant1	2422	35.20	2404.40	2439.60	0.5	PASS
		2437	35.20	2419.40	2454.60	0.5	PASS
		2452	35.12	2434.48	2469.60	0.5	PASS


Test Graphs




11B Ant1 2462




11G Ant1 2412




11G Ant1_2437




11G Ant1_2462





11N20SISO Ant1 2412



11N20SISO Ant1 2437








**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.308	2405.846	2418.154	---	---
		2437	12.308	2430.846	2443.154	---	---
		2462	12.308	2455.846	2468.154	---	---
11G	Ant1	2412	17.263	2403.329	2420.591	---	---
		2437	17.263	2428.329	2445.591	---	---
		2462	17.223	2453.329	2470.551	---	---
11N20SISO	Ant1	2412	17.862	2403.049	2420.911	---	---
		2437	17.862	2428.049	2445.911	---	---
		2462	17.862	2453.049	2470.911	---	---
11N40SISO	Ant1	2422	36.284	2403.858	2440.142	---	---
		2437	36.124	2418.938	2455.062	---	---
		2452	36.124	2433.938	2470.062	---	---


Test Graphs




11B Ant1 2462




11G Ant1 2412




11G Ant1_2437




11G Ant1_2462





11N20SISO Ant1 2412



11N20SISO Ant1 2437







Appendix C: Maximum conducted output power**Test Result**


Test Mode	Antenna	Frequency [MHz]	Average Power [dBm]	Conducted Limit [dBm]	Verdict
11B	Ant1	2412	14.60	≤30.00	PASS
		2437	13.92	≤30.00	PASS
		2462	13.94	≤30.00	PASS
11G	Ant1	2412	15.28	≤30.00	PASS
		2437	14.68	≤30.00	PASS
		2462	14.66	≤30.00	PASS
11N20SISO	Ant1	2412	15.18	≤30.00	PASS
		2437	14.62	≤30.00	PASS
		2462	14.52	≤30.00	PASS
11N40SISO	Ant1	2422	14.27	≤30.00	PASS
		2437	13.92	≤30.00	PASS
		2452	14.13	≤30.00	PASS

Appendix D: Maximum power spectral density**Test Result**


TestMode	Antenna	Frequency[MHz]	Result[dBm/10kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-10.72	≤8.00	PASS
		2437	-11.34	≤8.00	PASS
		2462	-11.15	≤8.00	PASS
11G	Ant1	2412	-8.83	≤8.00	PASS
		2437	-9.29	≤8.00	PASS
		2462	-9.03	≤8.00	PASS
11N20SISO	Ant1	2412	-9.04	≤8.00	PASS
		2437	-9.1	≤8.00	PASS
		2462	-9.25	≤8.00	PASS
11N40SISO	Ant1	2422	-9.34	≤8.00	PASS
		2437	-9.26	≤8.00	PASS
		2452	-8.85	≤8.00	PASS

Note: the duty cycle factor has added into the plot.


Test Graphs




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437



11G_Ant1_2462




11N20SISO Ant1 2412




Date: 9 JUN 2023 18:42:46

11N20SISO Ant1 2437




Date: 9 JUN 2023 18:43:14

11N20SISO Ant1 2462




Date: 9 JUN 2023 18:44:10


11N40SISO Ant1 2422




Date: 9 JUN 2023 18:45:02




Appendix E: Band edge measurements Test Graphs





11G Ant1 Low 2412



11G Ant1 High 2462







Appendix F: Duty Cycle**Test Result**

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Duty cycle Correction Factor (dB)	1/T (kHz)
11B	Ant1	2437	8.69	8.90	97.64	0.10	0.12
11G	Ant1	2437	1.44	1.64	87.80	0.57	0.69
11N20SISO	Ant1	2437	1.35	1.55	87.10	0.60	0.74
11N40SISO	Ant1	2437	0.66	0.87	75.86	1.20	1.52

Test Graphs





***** END OF REPORT *****