FCC TEST REPORT

Test report
On Behalf of
EIS GmbH
For
Partner Vibrator
Model No.: 4002408, 4001708, 4002392, 4001692, 4002453, 4002460, 4001722, 4001715, 4002446
FCC ID: 2AVEP-2408

Prepared for :	**EIS GmbH** **Am Lenkwerk 3, 33609 Bielefeld Germany**
Prepared By :	**Shenzhen HUAK Testing Technology Co., Ltd.** **1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China**

Date of Test:	**Dec. 15, 2019 ~ Dec. 23, 2019**
Date of Report:	**Dec. 23, 2019**
Report Number:	**HK1912113192-E**

TEST RESULT CERTIFICATION

Applicant's name ..... : EIS GmbH

Address ..... : Am Lenkwerk 3, 33609 Bielefeld Germany

Manufacture's Name..... : Ninghai County Jimeite Electronics Co., Ltd

Address ..... : No. 18, 8th Jinshan Road, Ninghai County, Ningbo City, China, 315600

Product description

Trade Mark: N/A

Product name ..... : Partner Vibrator

Model and/or type reference : 4002408, 4001708, 4002392, 4001692, 4002453, 4002460, 4001722, 4001715, 4002446

Standards ..... : FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test.....:

Date (s) of performance of tests .....: **Dec. 15, 2019 ~ Dec. 23, 2019**

Date of Issue.....: **Dec. 23, 2019**

Test Result .....: **Pass**

Testing Engineer : Gary Qian

(Gary Qian)

Technical Manager : Eden Hu

(Eden Hu)

Authorized Signatory : Jason Zhou

(Jason Zhou)

Table of Contents **Page**

1 . TEST SUMMARY 4

2 . GENERAL INFORMATION 5

2.1 GENERAL DESCRIPTION OF EUT 5

2.2 Carrier Frequency of Channels 6

2.3 Operation of EUT during testing 6

2.4 DESCRIPTION OF TEST SETUP 6

2.5 MEASUREMENT INSTRUMENTS LIST 7

3 . CONDUCTED EMISSIONS TEST 8

3.1 Conducted Power Line Emission Limit 8

3.2 Test Setup 8

3.3 Test Procedure 8

3.4 Test Result 8

4 RADIATED EMISSION TEST 11

4.1 Radiation Limit 11

4.2 Test Setup 11

4.3 Test Procedure 12

4.4 Test Result 12

5 BAND EDGE 18

5.1 Limits 18

5.2 Test Procedure 18

5.3 Test Result 19

6 OCCUPIED BANDWIDTH MEASUREMENT 21

6.1 Test Setup 21

6.2 Test Procedure 21

6.3 Measurement Equipment Used 21

6.4 Test Result 21

7 ANTENNA REQUIREMENT 23

8 PHOTOGRAPH OF TEST 24

8.1 Radiated Emission 24

8.2 Conducted Emission 25

9 PHOTOS OF THE EUT 26

1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST		RESULT
CONDUCTED EMISSIONS TEST	15.207	COMPLIANT
RADIATED EMISSION TEST	15.249(a) /15.209	COMPLIANT
BAND EDGE	15.249(d)/15.205	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	15.215（c）	COMPLIANT
ANTENNA REQUIREMENT	15.203	COMPLIANT

1.2 TEST FACILITY

Test Firm : Shenzhen HUAK Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	=	4.06dB, k=2

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Partner Vibrator
Model Name	4002408
Serial Model	4001708, 4002392, 4001692, 4002453, 4002460, 4001722, 4001715, 4002446
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: 4002408
FCC ID	2AVEP-2408
Antenna Type	Internal Antenna
Antenna Gain	2 dBi
Equipment	Partner Vibrator
Operation frequency	2402-2480MHz
Number of Channels	40CH
Modulation Type	GFSK
Power Source	DC 5V from USB or DC 3.7V from battery
Power Rating	DC 5V from USB or DC 3.7V from battery

2.2 Carrier Frequency of Channels

Channel List							
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
01	2402	11	2422	21	2442	31	2462
02	2404	12	2424	22	2444	32	2464
03	2406	13	2426	23	2446	33	2466
04	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

2.3 Operation of EUT during testing

Operating Mode
The mode is used: **Transmitting mode**
Low Channel: 2402MHz
Middle Channel: 2440MHz
High Channel: 2480MHz

2.4 DESCRIPTION OF TEST SETUP

Operation of EUT during conducted testing and Radiation testing:



Operation of EUT Above1GHz Radiation testing:

- Adapter information

  Model: HW-059200CHQ

  Input: 100-240V, 50/60Hz, 0.5A

  Output: 5VDC, 2A

The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working,
investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations.The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.

2.5 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 27, 2018	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2018	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Dec. 27, 2018	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 27, 2018	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 27, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 27, 2018	1 Year
10.	Horn Antenna	Schewarzbeck	9120D	HKE-013	Dec. 27, 2018	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2018	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 27, 2018	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JY3120-B Version	HKE-083	Dec. 27, 2018	N/A
14.	Power Sensor	Agilent	E9300A	HKE-086	Dec. 27, 2018	1 Year
15.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Dec. 27, 2018	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Dec. 27, 2018	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 27, 2018	3 Year
19.	Hight gain antenna	Schwarzbeck	LB-180400K F	HKE-054	Dec. 27, 2018	1 Year

3. CONDUCTED EMISSIONS TEST

3.1 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure

1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
2, Support equipment, if needed, was placed as per ANSI C63.10.
3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5, All support equipments received AC power from a second LISN, if any.
6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

3.4 Test Result

PASS

All the test modes completed for test. only the worst result of of AC240V/60Hz (High Channel) was reported as below:

Test Specification: Line



Suspected List								
NO.	Freq. [MHz]	Level [dBµV]	Factor [dB]	Limit [dBµV]	Margin [dB]	Reading [dBµV]	Detector	Type
1	0.5145	42.62	10.04	56.00	13.38	32.58	PK	L
2	0.5145	31.72	10.04	46.00	14.28	21.68	AV	L
3	0.6810	31.20	10.05	46.00	14.80	21.15	AV	L
4	0.6900	43.51	10.05	56.00	12.49	33.46	PK	L
5	0.8880	30.67	10.06	46.00	15.33	20.61	AV	L
6	0.9870	42.18	10.06	56.00	13.82	32.12	PK	L
7	1.1760	29.45	10.09	46.00	16.55	19.36	AV	L
8	1.2120	41.13	10.09	56.00	14.87	31.04	PK	L
9	2.0265	27.21	10.15	46.00	18.79	17.06	AV	L
10	2.1210	38.28	10.16	56.00	17.72	28.12	PK	L
11	2.7870	26.53	10.21	46.00	19.47	16.32	AV	L
12	2.8860	37.44	10.21	56.00	18.56	27.23	PK	L

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

Test Specification: Neutral



Suspected List								
NO.	Freq. [MHz]	Level [dBµV]	Factor [dB]	Limit [dBµV]	Margin [dB]	Reading [dBµV]	Detector	Type
1	0.4695	31.13	10.04	46.52	15.39	21.09	AV	N
2	0.5145	41.94	10.04	56.00	14.06	31.90	PK	N
3	0.7080	30.51	10.05	46.00	15.49	20.46	AV	N
4	0.7125	41.45	10.05	56.00	14.55	31.40	PK	N
5	1.1625	29.08	10.09	46.00	16.92	18.99	AV	N
6	1.2975	40.74	10.10	56.00	15.26	30.64	PK	N
7	2.3955	26.70	10.18	46.00	19.30	16.52	AV	N
8	2.7285	36.74	10.21	56.00	19.26	26.53	PK	N
9	10.9905	36.09	10.01	60.00	23.91	26.08	PK	N
10	13.5870	24.98	9.96	50.00	25.02	15.02	AV	N
11	21.3765	34.41	10.14	60.00	25.59	24.27	PK	N
12	25.2780	23.58	10.25	50.00	26.42	13.33	AV	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

4 RADIATED EMISSION TEST

4.1 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.490	300	20log 2400/F (kHz)	2400/F (kHz)
0.490-1.705	30	20log 24000/F (kHz)	24000/F (kHz)
1.705-30	30	20log 30	30
30-88	3	40	100
88-216	3	43.5	150
216-960	3	46	200
Above 960	3	54	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2 Test Setup

（1）Radiated Emission Test-Up Frequency Below 30MHz



（2）Radiated Emission Test-Up Frequency 30MHz~1GHz



（3）Radiated Emission Test-Up Frequency Above 1GHz



4.3 Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:
For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4 Test Result

PASS
All the test modes completed for test. The worst case of Radiated Emission is CH 01; the test data of this mode was reported.

Below 1GHz Test Results:

Antenna polarity: H



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	39.7000	-14.64	40.08	25.44	40.00	14.56	100	54	Horizontal
2	49.4000	-13.65	41.39	27.74	40.00	12.26	100	249	Horizontal
3	56.1900	-14.58	43.34	28.76	40.00	11.24	100	119	Horizontal
4	167.7400	-17.51	39.61	22.10	43.50	21.40	100	54	Horizontal
5	279.2900	-13.28	43.48	30.20	46.00	15.80	100	278	Horizontal
6	440.3100	-9.41	38.05	28.64	46.00	17.36	100	190	Horizontal

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Antenna polarity: V



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBµV/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	39.7000	-14.64	40.93	26.29	40.00	13.71	100	309	Vertical
2	50.3700	-13.71	41.06	27.35	40.00	12.65	100	25	Vertical
3	56.1900	-14.58	43.54	28.96	40.00	11.04	100	116	Vertical
4	166.7700	-17.60	44.83	27.23	43.50	16.27	100	180	Vertical
5	199.7500	-15.08	39.80	24.72	43.50	18.78	100	90	Vertical
6	519.8500	-7.73	43.41	35.68	46.00	10.32	100	193	Vertical

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Harmonics and Spurious Emissions

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dBµV/m)	Limit@3m (dBµV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: *1. Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor*

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Above 1 GHz Test Results:

CH Low (2402MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2402	108.65	-5.84	102.81	114	-11.19	peak
2402	87.46	-5.84	81.62	94	-12.38	AVG
4804	59.62	-3.64	55.98	74	-18.02	peak
4804	47.18	-3.64	43.54	54	-10.46	AVG
7206	55.30	-0.95	54.35	74	-19.65	peak
7206	43.19	-0.95	42.24	54	-11.76	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2402	111.3	-5.84	105.46	114	-8.54	peak
2402	83.99	-5.84	78.15	94	-15.85	AVG
4804	57.46	-3.64	53.82	74	-20.18	peak
4804	46.19	-3.64	42.55	54	-11.45	AVG
7206	55.25	-0.95	54.3	74	-19.7	peak
7206	42.81	-0.95	41.86	54	-12.14	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

CH Middle (2440MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2440	108.65	-5.71	102.94	114	-11.06	peak
2440	80.34	-5.71	74.63	94	-19.37	AVG
4880	56.49	-3.51	52.98	74	-21.02	peak
4880	46.87	-3.51	43.36	54	-10.64	AVG
7320	57.15	-0.82	56.33	74	-17.67	peak
7320	42.66	-0.82	41.84	54	-12.16	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2440	104.36	-5.71	98.65	114	-15.35	peak
2440	84.25	-5.71	78.54	94	-15.46	AVG
4880	56.97	-3.51	53.46	74	-20.54	peak
4880	47.12	-3.51	43.61	54	-10.39	AVG
7320	55.34	-0.82	54.52	74	-19.48	peak
7320	42.88	-0.82	42.06	54	-11.94	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

CH High (2480MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2480	105.62	-5.65	99.97	114	-14.03	peak
2480	82.49	-5.65	76.84	94	-17.16	AVG
4960	55.38	-3.43	51.95	74	-22.05	peak
4960	45.79	-3.43	42.36	54	-11.64	AVG
7440	56.00	-0.75	55.25	74	-18.75	peak
7440	41.68	-0.75	40.93	54	-13.07	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2480	106.02	-5.65	100.37	114	-13.63	peak
2480	82.36	-5.65	76.71	94	-17.29	AVG
4960	56.30	-3.43	52.87	74	-21.13	peak
4960	45.78	-3.43	42.35	54	-11.65	AVG
7440	55.99	-0.75	55.24	74	-18.76	peak
7440	39.45	-0.75	38.7	54	-15.3	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Remark：
(1) Measuring frequencies from 1 GHz to the 25 GHz。
(2) “F” denotes fundamental frequency; “H” denotes spurious frequency. “E” denotes band edge frequency.
(3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
(4)The emissions are attenuated more than 20dB below the permissible limits are not record in the report.
(5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak
detection at frequency above 1GHz.
(6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
(7)All modes of operation were investigated and the worst-case emissions are reported.

5 BAND EDGE

5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.

5.3 Test Result

PASS

Radiated Band Edge Test:

Operation Mode: TX CH Low (2402MHz)

Horizontal (Worst case)

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2310	58.03	-5.81	52.22	74	-21.78	peak
2310	/	-5.81	/	54	/	AVG
2390	52.67	-5.84	46.83	74	-27.17	peak
2390	/	-5.84	/	54	/	AVG
2400	51.49	-5.84	45.65	74	-28.35	peak
2400	/	-5.84	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2310	55.62	-5.81	49.81	74	-24.19	peak
2310	/	-5.81	/	54	/	AVG
2390	52.79	-5.84	46.95	74	-27.05	peak
2390	/	-5.84	/	54	/	AVG
2400	55.31	-5.84	49.47	74	-24.53	peak
2400	/	-5.84	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Operation Mode: TX CH High (2480MHz)

Horizontal (Worst case)

Frequency (MHz)	Reading Result (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.50	56.38	-5.65	50.73	74	-23.27	peak
2483.50	/	-5.65	/	54	/	AVG
2500.00	53.24	-5.65	47.59	74	-26.41	peak
2500.00	/	-5.65	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Reading Result (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.50	56.84	-5.65	51.19	74	-22.81	peak
2483.50	/	-5.65	/	54	/	AVG
2500.00	52.68	-5.65	47.03	74	-26.97	peak
2500.00	/	-5.65	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						
Remark: All the other emissions not reported were too low to read and deemed to comply with FCC limit.						

6 OCCUPIED BANDWIDTH MEASUREMENT

6.1 Test Setup

Same as Radiated Emission Measurement

6.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on ANSI C63.10 section 6.9.2: RBW= 30KHz. VBW= 100 KHz, Span=4MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3 Measurement Equipment Used

Same as Radiated Emission Measurement

6.4 Test Result

PASS

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.052	**PASS**
2440 MHz	1.051	**PASS**
2480 MHz	1.052	**PASS**

CH: 2402MHz



CH: 2440MHz



CH: 2480MHz



7 ANTENNA REQUIREMENT

Standard Applicable
For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Connected Construction
The antenna used in this product is a internal Antenna, The directional gains of antenna used for transmitting is 2dBi.

ANTENNA



8 PHOTOGRAPH OF TEST

8.1 Radiated Emission





8.2 Conducted Emission



9 PHOTOS OF THE EUT

Reference to the reporter : ANNEX A of external photos and ANNEX B of internal photos

---------End of test report---------