TEST REPORT

Report No. ..... :	**CHTEW1912017402** Report Verification:
Project No.....:	**SHT1912016905EW**
FCC ID ..... :	**2AVFS-GEO10**
Applicant's name ..... :	**Geotechvision Enterprises Limited**
Address.....:	44 Cowper Drive, Kingston 20, Jamaica W.I. JMK0020
Manufacturer.....:	DBETTER INTERNATIONAL LIMITED
Address.....:	Room803 6F., Chevalier House, 45-51 Chatham Road South, Tsim Sha Tsui, Kowloon
Test item description ..... :	**Tablet**
Trade Mark .....:	Geo
Model/Type reference.....:	GEO10
Listed Model(s) .....:	Geo10X
Standard ..... :	**FCC CFR Title 47 Part 15 Subpart C Section 15.247**
Date of receipt of test sample.....:	Dec.12,2019
Date of testing.....:	Dec.12,2019 ~ Dec.24,2019
Date of issue.....:	Dec.25,2019
Result.....:	**PASS**

Compiled by (Position+Printed name+Signature):	File administrator Yueming Li	Yueming.Li
Supervised by (Position+Printed name+Signature):	Project Engineer Kiki Kong	Kiki Kong
Approved by (Position+Printed name+Signature):	RF Manager Hans Hu	Hans Hu

Testing Laboratory Name ..... :	**Shenzhen Huatongwei International Inspection Co., Ltd.**
Address.....:	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1. TEST STANDARDS AND REPORT VERSION 3

1.1. Test Standards 3
1.2. Report version 3

2. TEST DESCRIPTION 4

3. SUMMARY 5

3.1. Client Information 5
3.2. Product Description 5
3.3. Radio Specification Description 5
3.4. Testing Laboratory Information 6

4. TEST CONFIGURATION 7

4.1. Test frequency list 7
4.2. Descriptions of Test mode 7
4.3. Test mode 7
4.4. Support unit used in test configuration and system 8
4.5. Testing environmental condition 8
4.6. Measurement uncertainty 8
4.7. Equipment Used during the Test 9

5. TEST CONDITIONS AND RESULTS 11

5.1. Antenna Requirement 11
5.2. AC Conducted Emission 12
5.3. Peak Output Power 15
5.4. Power Spectral Density 16
5.5. 6dB bandwidth 17
5.6. 99% Occupied Bandwidth 18
5.7. Duty Cycle 19
5.8. Conducted Band edge and Spurious Emission 20
5.9. Radiated Band edge Emission 22
5.10. Radiated Spurious Emission 27

6. TEST SETUP PHOTOS 35

7. EXTERANAL AND INTERNAL PHOTOS 37

8. APPENDIX REPORT 37

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

– FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

– ANSI C63.10:2013: American National Standard for Testing Unlicensed Wireless Devices

– KDB 558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-12-25	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247(c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Peak Output Power	15.247(b)(3)	PASS
5.4	Power Spectral Density	15.247(e)	PASS
5.5	6dB Bandwidth	15.247(a)(2)	PASS
5.6	99% Occupied Bandwidth	-	PASS*1
5.7	Duty cycle	-	PASS*1
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.9	Radiated Band Edge Emission	15.205/15.209	PASS
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

– The measurement uncertainty is not included in the test result.

– *1: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	Geotechvision Enterprises Limited
Address:	44 Cowper Drive, Kingston 20, Jamaica W.I. JMK0020
Manufacturer:	DBETTER INTERNATIONAL LIMITED
Address:	Room803 6F., Chevalier House, 45-51 Chatham Road South, Tsim Sha Tsui, Kowloon

3.2. Product Description

Name of EUT:	Tablet
Trade Mark:	Geo
Model No.:	GEO10
Listed Model(s):	Geo10X
Power supply:	DC 3.7V
Adapter information:	Model:BSY-F18Q Input:100-240Va.c.50/60Hz,0.5A Max Output:DC 5V/3A,7V,9V/2A,12V/1.5A,18W Max
Hardware version:	PC62_H_IPD
Software version:	andriid version 9

3.3. Radio Specification Description

Support type*2:	802.11b, 802.11g, 802.11n(HT20), 802.11n(H4T0)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 9 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	FPCB Antenna
Antenna gain:	1.97dBi

Note:

*2: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Qualifications	Type	Accreditation Number
	CNAS	L1225
	A2LA	3902.01
	FCC	762235
	Canada	5377A

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

802.11b/802.11g/802.11n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	**2412**	**03**	**2422**
02	2417	04	2427
· :	· :	· :	· :
06	**2437**	**06**	**2437**
· :	· :	· :	· :
10	2457	08	2447
11	**2462**	**09**	**2452**

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0

4.3. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
✓ No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.7. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX_142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifer	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/08/21	2020/08/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX 104	501184/4	2019/05/27	2020/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2017/04/01	2020/03/31
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2017/03/27	2020/03/26
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/10
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

●	RF Conducted Method					
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25
●	Power Meter	Anritsu	ML249A	N/A	2019/10/26	2020/10/25
○	Radio communication tester	R&S	CMW500	137688-Lv	2019/10/26	2020/10/25

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a FPCB antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. AC Conducted Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Test Line:	L



MEASUREMENT RESULT: "GM191218544_fin"

12/18/2019 7:39PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.186000	47.40	10.1	64	16.8	QP	L1	GND
0.231000	47.80	10.2	62	14.6	QP	L1	GND
0.343500	43.90	10.1	59	15.2	QP	L1	GND
0.348000	39.70	10.1	59	19.3	QP	L1	GND
0.352500	37.20	10.1	59	21.7	QP	L1	GND
0.433500	37.30	10.1	57	19.9	QP	L1	GND

MEASUREMENT RESULT: "GM191218544_fin2"

12/18/2019 7:39PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.186000	30.60	10.1	54	23.6	AV	L1	GND
0.492000	35.50	10.0	46	10.6	AV	L1	GND
1.086000	25.50	10.0	46	20.5	AV	L1	GND
2.481000	24.90	10.0	46	21.1	AV	L1	GND
7.539000	23.30	10.1	50	26.7	AV	L1	GND
13.609500	21.10	10.2	50	28.9	AV	L1	GND

Test Line:	N



MEASUREMENT RESULT: "GM191218539_fin"

12/18/2019 7:11PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.204000	47.80	10.2	63	15.6	QP	N	GND
0.325500	38.40	10.1	60	21.2	QP	N	GND
0.415500	39.80	10.1	58	17.7	QP	N	GND
0.474000	43.20	10.1	56	13.2	QP	N	GND
10.068000	39.70	10.2	60	20.3	QP	N	GND
17.551500	29.60	10.3	60	30.4	QP	N	GND

MEASUREMENT RESULT: "GM191218539_fin2"

12/18/2019 7:11PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	37.00	10.1	56	19.0	AV	N	GND
0.465000	36.00	10.1	47	10.6	AV	N	GND
0.906000	21.00	9.9	46	25.0	AV	N	GND
4.938000	19.10	10.0	46	26.9	AV	N	GND
12.363000	29.00	10.2	50	21.0	AV	N	GND
12.444000	29.30	10.2	50	20.7	AV	N	GND

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix A on the appendix report

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
   Center frequency=DTS channel center frequency
   Span =1.5 times the DTS bandwidth
   RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW
   Sweep time = auto couple
   Detector = peak
   Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix B on the appendix report

5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).

   Center Frequency =DTS channel center frequency

   Span=2 x DTS bandwidth

   RBW = 100 kHz, VBW ≥ 3 × RBW

   Sweep time= auto couple

   Detector = Peak

   Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix C on the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output andthe spectrum analyzer).
   Center Frequency =channel center frequency
   Span≥1.5 x OBW
   RBW = 1%~5%OBW
   VBW ≥ 3 × RBW
   Sweep time= auto couple
   Detector = Peak
   Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix D on the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW ≥ RBW
   Sweep=as necessary to capture the entire dwell time,
   Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST Data

Please refer to appendix E on the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
   Center frequency=DTS channel center frequency
   The span = 1.5 times the DTS bandwidth.
   RBW = 100 kHz, VBW ≥ 3 x RBW
   Detector = peak, Sweep time = auto couple, Trace mode = max hold
   Allow trace to fully stabilize
   Use the peak marker function to determine the maximum PSD level

   Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement
   Set the center frequency and span to encompass frequency range to be measured
   RBW = 100 kHz, VBW ≥ 3 x RBW
   Detector = peak, Sweep time = auto couple, Trace mode = max hold
   Allow trace to fully stabilize
   Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix F on the appendix report

5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. Thisis repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
   a) Span shall wide enough to fully capture the emission being measured
   b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
   c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

      For average measurement:
      – VBW=10Hz, When duty cycle is no less than 98 percent
      – VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clasue 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Note:

1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
2) Margin = Limit – Level
3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Type	802.11b	Test channel	CH01	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	23.89	35.78	59.67	74.00	14.33	Horizontal	PK
2	2390.009	23.70	35.50	59.20	74.00	14.80	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.63	35.78	49.41	54.00	4.59	Horizontal	AV
2	2390.009	13.76	35.50	49.26	54.00	4.74	Horizontal	AV

Type	802.11b	Test channel	CH01	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	25.03	35.78	60.81	74.00	13.19	Vertical	PK
2	2390.009	24.05	35.50	59.55	74.00	14.45	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.36	35.78	49.14	54.00	4.86	Vertical	AV
2	2390.009	13.61	35.50	49.11	54.00	4.89	Vertical	AV

Type	802.11b	Test channel	CH11	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	24.00	35.31	59.31	74.00	14.69	Horizontal	PK
2	2500.000	24.59	35.28	59.87	74.00	14.13	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	13.79	35.31	49.10	54.00	4.90	Horizontal	AV
2	2500.000	13.59	35.28	48.87	54.00	5.13	Horizontal	AV

Type	802.11b	Test channel	CH11	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	24.62	35.31	59.93	74.00	14.07	Vertical	PK
2	2500.000	23.60	35.28	58.88	74.00	15.12	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	13.60	35.31	48.91	54.00	5.09	Vertical	AV
2	2500.000	13.73	35.28	49.01	54.00	4.99	Vertical	AV

Type	802.11g	Test channel	CH01	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	24.09	35.78	59.87	74.00	14.13	Horizontal	PK
2	2390.009	24.11	35.50	59.61	74.00	14.39	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.67	35.78	49.45	54.00	4.55	Horizontal	AV
2	2390.009	13.53	35.50	49.03	54.00	4.97	Horizontal	AV

Type	802.11g	Test channel	CH01	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	23.34	35.78	59.12	74.00	14.88	Vertical	PK
2	2390.009	24.48	35.50	59.98	74.00	14.02	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.71	35.78	49.49	54.00	4.51	Vertical	AV
2	2390.009	13.72	35.50	49.22	54.00	4.78	Vertical	AV

Type	802.11g	Test channel	CH11	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	24.36	35.31	59.67	74.00	14.33	Horizontal	PK
2	2500.000	23.03	35.28	58.31	74.00	15.69	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	13.78	35.31	49.09	54.00	4.91	Horizontal	AV
2	2500.000	13.68	35.28	48.96	54.00	5.04	Horizontal	AV

Type	802.11g	Test channel	CH11	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	23.74	35.31	59.05	74.00	14.95	Vertical	PK
2	2500.000	24.51	35.28	59.79	74.00	14.21	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	13.81	35.31	49.12	54.00	4.88	Vertical	AV
2	2500.000	14.01	35.28	49.29	54.00	4.71	Vertical	AV

Type	802.11n(HT20)	Test channel	CH01	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	23.93	35.78	59.71	74.00	14.29	Horizontal	PK
2	2390.116	24.11	35.50	59.61	74.00	14.39	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.74	35.78	49.52	54.00	4.48	Horizontal	AV
2	2390.116	13.69	35.50	49.19	54.00	4.81	Horizontal	AV

Type	802.11n(HT20)	Test channel	CH01	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	24.38	35.78	60.16	74.00	13.84	Vertical	PK
2	2390.116	24.53	35.50	60.03	74.00	13.97	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.31	35.78	49.09	54.00	4.91	Vertical	AV
2	2390.116	13.99	35.50	49.49	54.00	4.51	Vertical	AV

Type	802.11n(HT20)	Test channel	CH11	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	24.12	35.31	59.43	74.00	14.57	Horizontal	PK
2	2500.000	23.35	35.28	58.63	74.00	15.37	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	13.75	35.31	49.06	54.00	4.94	Horizontal	AV
2	2500.000	13.63	35.28	48.91	54.00	5.09	Horizontal	AV

Type	802.11n(HT20)	Test channel	CH11	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	24.03	35.31	59.34	74.00	14.66	Vertical	PK
2	2500.000	26.20	35.28	61.48	74.00	12.52	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	13.71	35.31	49.02	54.00	4.98	Vertical	AV
2	2500.000	13.61	35.28	48.89	54.00	5.11	Vertical	AV

Type	802.11n(HT40)	Test channel	CH03	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	24.96	35.78	60.74	74.00	13.26	Horizontal	PK
2	2390.108	25.11	35.50	60.61	74.00	13.39	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.35	35.78	49.13	54.00	4.87	Horizontal	AV
2	2390.108	15.63	35.50	50.87	54.00	3.13	Horizontal	AV

Type	802.11n(HT40)	Test channel	CH03	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	24.19	35.78	59.97	74.00	14.03	Vertical	PK
2	2390.108	26.47	35.50	61.97	74.00	12.03	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	13.53	35.78	49.31	54.00	4.69	Vertical	AV
2	2390.108	16.08	35.50	50.88	54.00	3.12	Vertical	AV

Type	802.11n(HT40)	Test channel	CH09	Polarity	Horizontal

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.517	24.18	35.31	59.49	74.00	14.51	Horizontal	PK
2	2500.000	22.85	35.28	58.13	74.00	15.87	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.553	15.65	35.31	50.96	54.00	3.04	Horizontal	AV
2	2500.000	13.80	35.28	49.08	54.00	4.92	Horizontal	AV

Type	802.11n(HT40)	Test channel	CH09	Polarity	Vertical

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.517	30.14	35.31	65.45	74.00	8.55	Vertical	PK
2	2500.000	23.06	35.28	58.34	74.00	15.66	Vertical	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.553	14.97	35.31	50.28	54.00	3.72	Vertical	AV
2	2500.000	13.75	35.28	49.03	54.00	4.97	Vertical	AV

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak

Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.

Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
   a) Span shall wide enough to fully capture the emission being measured;
   b) Below 1 GHz:
      RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
      If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
   c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
      For average measurement:
      – VBW=10Hz, When duty cycle is no less than 98 percent
      – VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clasue 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Note:

1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
2) Margin = Limit – Level
3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

TEST DATA FOR 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH06 of 802.11B which it was worst case, so only show the worst case's data on this report.

Polarization:	Horizontal



MEASUREMENT RESULT: "GM1912186102_red"

12/18/2019 10:57PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	19.60	-8.4	40.0	20.4	QP	100.0	33.00	HORIZONTAL
59.100000	19.40	-9.1	40.0	20.6	QP	300.0	172.00	HORIZONTAL
125.060000	22.80	-12.3	43.5	20.7	QP	300.0	239.00	HORIZONTAL
185.200000	19.90	-11.2	43.5	23.6	QP	300.0	21.00	HORIZONTAL
553.800000	27.50	0.2	46.0	18.5	QP	300.0	304.00	HORIZONTAL
957.320000	36.50	8.3	46.0	9.5	QP	300.0	132.00	HORIZONTAL

Polarization:	Vertical



MEASUREMENT RESULT: "GM1912186101_red"

12/18/2019 10:48PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	24.20	-12.1	40.0	15.8	QP	100.0	335.00	VERTICAL
59.100000	20.80	-9.1	40.0	19.2	QP	100.0	117.00	VERTICAL
125.060000	31.40	-12.3	43.5	12.1	QP	100.0	193.00	VERTICAL
295.780000	21.90	-6.5	46.0	24.1	QP	100.0	295.00	VERTICAL
546.040000	26.60	0.1	46.0	19.4	QP	100.0	358.00	VERTICAL
959.260000	35.20	8.4	46.0	10.8	QP	100.0	106.00	VERTICAL

TEST DATA FOR 1 GHz ~ 25 GHz

Type	802.11b	Test channel	CH01

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1182.125	35.39	-6.02	29.37	74.00	44.63	Horizontal	PK
2	3176.687	33.40	0.72	34.12	74.00	39.88	Horizontal	PK
3	4823.156	39.11	7.08	46.19	74.00	27.81	Horizontal	PK
4	6732.531	31.93	13.38	45.31	74.00	28.69	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1180.656	35.88	-6.04	29.84	74.00	44.16	Vertical	PK
2	3176.687	33.93	0.72	34.65	74.00	39.35	Vertical	PK
3	4823.156	38.57	7.08	45.65	74.00	28.35	Vertical	PK
4	7079.156	31.06	14.38	45.44	74.00	28.56	Vertical	PK

Type	802.11b	Test channel	CH06

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1192.406	35.49	-5.91	29.58	74.00	44.42	Horizontal	PK
2	3139.968	33.82	0.53	34.35	74.00	39.65	Horizontal	PK
3	4873.093	38.74	7.15	45.89	74.00	28.11	Horizontal	PK
4	6585.656	31.35	13.06	44.41	74.00	29.59	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1220.312	36.47	-5.78	30.69	74.00	43.31	Vertical	PK
2	3138.500	34.54	0.52	35.06	74.00	38.94	Vertical	PK
3	4873.093	36.93	7.15	44.08	74.00	29.92	Vertical	PK
4	6719.312	30.83	13.42	44.25	74.00	29.75	Vertical	PK

Type	802.11b	Test channel	CH11

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1188.000	36.60	-5.96	30.64	74.00	43.36	Horizontal	PK
2	3148.781	34.56	0.57	35.13	74.00	38.87	Horizontal	PK
3	4924.500	32.81	7.34	40.15	74.00	33.85	Horizontal	PK
4	6720.781	32.18	13.41	45.59	74.00	28.41	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1202.687	35.20	-5.82	29.38	74.00	44.62	Vertical	PK
2	3116.468	34.81	0.41	35.22	74.00	38.78	Vertical	PK
3	4923.031	31.68	7.33	39.01	74.00	34.99	Vertical	PK
4	6648.812	30.66	13.31	43.97	74.00	30.03	Vertical	PK

Type	802.11g	Test channel	CH01

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1207.093	35.57	-5.81	29.76	74.00	44.24	Horizontal	PK
2	3151.718	33.37	0.59	33.96	74.00	40.04	Horizontal	PK
3	4826.093	33.55	7.08	40.63	74.00	33.37	Horizontal	PK
4	7184.906	32.11	14.91	47.02	74.00	26.98	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1180.656	35.65	-6.04	29.61	74.00	44.39	Vertical	PK
2	3173.750	33.78	0.70	34.48	74.00	39.52	Vertical	PK
3	4823.156	32.06	7.08	39.14	74.00	34.86	Vertical	PK
4	7137.906	31.54	14.64	46.18	74.00	27.82	Vertical	PK

Type	802.11g	Test channel	CH06

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1227.656	35.19	-5.76	29.43	74.00	44.57	Horizontal	PK
2	3228.093	33.70	0.51	34.21	74.00	39.79	Horizontal	PK
3	4880.437	32.89	7.15	40.04	74.00	33.96	Horizontal	PK
4	6914.656	30.86	14.11	44.97	74.00	29.03	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1168.906	35.69	-6.16	29.53	74.00	44.47	Vertical	PK
2	3170.812	33.39	0.69	34.08	74.00	39.92	Vertical	PK
3	4674.812	31.99	6.23	38.22	74.00	35.78	Vertical	PK
4	6739.875	30.84	13.36	44.20	74.00	29.80	Vertical	PK

Type	802.11g	Test channel	CH11

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1242.343	35.41	-5.72	29.69	74.00	44.31	Horizontal	PK
2	3063.593	33.98	0.16	34.14	74.00	39.86	Horizontal	PK
3	4870.156	31.76	7.14	38.90	74.00	35.10	Horizontal	PK
4	6670.843	31.26	13.38	44.64	74.00	29.36	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1124.843	36.02	-6.63	29.39	74.00	44.61	Vertical	PK
2	3186.968	33.06	0.77	33.83	74.00	40.17	Vertical	PK
3	4657.187	31.78	6.12	37.90	74.00	36.10	Vertical	PK
4	6725.187	30.92	13.40	44.32	74.00	29.68	Vertical	PK

Type	802.11n(HT20)	Test channel	CH01

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1193.875	35.05	-5.89	29.16	74.00	44.84	Horizontal	PK
2	3206.062	33.17	0.77	33.94	74.00	40.06	Horizontal	PK
3	4823.156	33.81	7.08	40.89	74.00	33.11	Horizontal	PK
4	6839.750	31.13	13.56	44.69	74.00	29.31	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1249.687	35.04	-5.70	29.34	74.00	44.66	Vertical	PK
2	3172.281	33.57	0.70	34.27	74.00	39.73	Vertical	PK
3	4821.687	32.27	7.08	39.35	74.00	34.65	Vertical	PK
4	7234.843	31.35	15.01	46.36	74.00	27.64	Vertical	PK

Type	802.11n(HT20)	Test channel	CH06

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1202.687	35.42	-5.82	29.60	74.00	44.40	Horizontal	PK
2	3203.125	33.22	0.80	34.02	74.00	39.98	Horizontal	PK
3	4874.562	33.71	7.15	40.86	74.00	33.14	Horizontal	PK
4	6736.937	31.26	13.37	44.63	74.00	29.37	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1276.125	35.47	-5.63	29.84	74.00	44.16	Vertical	PK
2	3041.562	33.37	0.06	33.43	74.00	40.57	Vertical	PK
3	4876.031	33.02	7.15	40.17	74.00	33.83	Vertical	PK
4	6679.656	30.93	13.40	44.33	74.00	29.67	Vertical	PK

Type	802.11n(HT20)	Test channel	CH11

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1220.312	35.51	-5.78	29.73	74.00	44.27	Horizontal	PK
2	3176.687	33.13	0.72	33.85	74.00	40.15	Horizontal	PK
3	4657.187	32.06	6.12	38.18	74.00	35.82	Horizontal	PK
4	6841.218	31.13	13.57	44.70	74.00	29.30	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1188.000	35.48	-5.96	29.52	74.00	44.48	Vertical	PK
2	3134.093	33.48	0.50	33.98	74.00	40.02	Vertical	PK
3	5165.375	31.25	8.92	40.17	74.00	33.83	Vertical	PK
4	7243.656	32.29	15.02	47.31	74.00	26.69	Vertical	PK

Type	802.11n(HT40)	Test channel	CH03

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1221.781	35.65	-5.77	29.88	74.00	44.12	Horizontal	PK
2	3175.218	33.45	0.71	34.16	74.00	39.84	Horizontal	PK
3	4663.062	31.70	6.15	37.85	74.00	36.15	Horizontal	PK
4	7478.656	32.73	15.40	48.13	74.00	25.87	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1242.343	35.18	-5.72	29.46	74.00	44.54	Vertical	PK
2	3137.031	34.03	0.51	34.54	74.00	39.46	Vertical	PK
3	4883.375	30.84	7.16	38.00	74.00	36.00	Vertical	PK
4	7380.250	31.23	15.31	46.54	74.00	27.46	Vertical	PK

Type	802.11n(HT40)	Test channel	CH06

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1239.406	35.95	-5.73	30.22	74.00	43.78	Horizontal	PK
2	3073.875	33.68	0.21	33.89	74.00	40.11	Horizontal	PK
3	4854.000	31.32	7.12	38.44	74.00	35.56	Horizontal	PK
4	6640.000	31.06	13.28	44.34	74.00	29.66	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1179.187	35.40	-6.05	29.35	74.00	44.65	Vertical	PK
2	3164.937	33.48	0.66	34.14	74.00	39.86	Vertical	PK
3	4641.031	32.93	6.02	38.95	74.00	35.05	Vertical	PK
4	6851.500	31.01	13.66	44.67	74.00	29.33	Vertical	PK

Type	802.11n(HT40)	Test channel	CH09

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1198.281	34.78	-5.85	28.93	74.00	45.07	Horizontal	PK
2	3198.718	33.60	0.83	34.43	74.00	39.57	Horizontal	PK
3	4670.406	32.33	6.20	38.53	74.00	35.47	Horizontal	PK
4	6676.718	31.38	13.40	44.78	74.00	29.22	Horizontal	PK

Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1229.125	35.14	-5.75	29.39	74.00	44.61	Vertical	PK
2	3150.250	33.12	0.58	33.70	74.00	40.30	Vertical	PK
3	4739.437	30.84	6.64	37.48	74.00	36.52	Vertical	PK
4	6685.531	31.12	13.42	44.54	74.00	29.46	Vertical	PK

6. TEST SETUP PHOTOS

Radiated Emission







AC Conducted Emission



7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No. : CHTEW1912017401.

8 . APPENDIX REPORT

APPENDIX REPORT

Project No.	SHT1912016905EW	Radio Specification	WIFI 2.4G
Test sample No.	YPHT19120169004	Model No.	GEO10
Start test date	2019/12/24	Finish date	2019/12/24
Temperature	25°C	Humidity	50%
Test Engineer	Ximing Huang	Auditor	William wang

Appendix clause	Test item	Result
A	Conducted Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty Cycle	PASS
E	Band edge and Spurious Emissions (conducted)	PASS

Appendix A: Conducted Peak Output Power

Type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
802.11b	01	16.86	15.18	≤30.00	Pass
	06	16.96	15.43		
	11	17.24	15.63		
802.11g	01	16.24	14.56	≤30.00	Pass
	06	16.09	14.33		
	11	16.68	14.94		
802.11n(HT20)	01	16.34	14.48	≤30.00	Pass
	06	16.28	14.36		
	11	16.79	14.95		
802.11n(HT40)	03	15.51	13.73	≤30.00	Pass
	06	15.47	13.68		
	09	15.85	13.11		

Appendix B：Power Spectral Density

Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-1.55	≤8.00	Pass
	06	-1.53		
	11	-0.94		
802.11g	01	-8.61	≤8.00	Pass
	06	-8.96		
	11	-8.08		
802.11n(HT20)	01	-8.89	≤8.00	Pass
	06	-9.28		
	11	-7.81		
802.11n(HT40)	03	-12.41	≤8.00	Pass
	06	-11.70		
	09	-11.06		

Type:	802.11 b
CH01	
CH06	
CH11	

Type:	**802.11 g**
CH01	
CH06	
CH11	

Type:	802.11n(HT20)
CH01	
CH06	
CH11	

Type:	802.11n(HT40)
CH03	
CH06	
CH09	

Appendix C：6dB bandwidth

Type	Channel	6dB Bandwidth (MHz)	Limit (MHz)	Result
802.11b	01	9.12	≥0.5	Pass
	06	9.18		
	11	8.61		
802.11g	01	16.47	≥0.5	Pass
	06	16.65		
	11	16.50		
802.11n(HT20)	01	17.67	≥0.5	Pass
	06	17.88		
	11	17.40		
802.11n(HT40)	03	36.42	≥0.5	Pass
	06	36.72		
	09	36.06		

Type:	802.11 b
CH01	
CH06	
CH11	

Type:	802.11 g
CH01	
CH06	
CH11	

Type:	802.11n(HT20)
CH01	
CH06	
CH11	

Type:	802.11n(HT40)
CH03	
CH06	
CH09	

Appendix D：99% Occupied Bandwidth

Type	Channel	99% Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	12.02	-	Pass
	06	12.53		
	11	12.17		
802.11g	01	16.78	-	Pass
	06	17.14		
	11	16.75		
802.11n(HT20)	01	17.62	-	Pass
	06	17.89		
	11	17.62		
802.11n(HT40)	03	36.02	-	Pass
	06	36.74		
	09	35.90		

Type:	802.11 b
CH01	
CH06	
CH11	

Type:	802.11 g
CH01	
CH06	
CH11	

Type:	802.11n(HT20)
CH01	
CH06	
CH11	

Type:	802.11n(HT40)
CH03	
CH06	
CH09	

Appendix E：Duty Cycle

Modulation Type	Test Frequency（MHz）	$T_{on\ time}$ for single burst (ms)	T_{period} (ms)	Duty cycle	$1/T_{on\ time}$ (kHz)
11b	2437	---	---	100%	1.0
11g	2437	---	---	100%	1.0
11n20	2437	---	---	100%	1.0
11n40	2437	---	---	100%	1.0

11b	
11g	

11n20	 Spectrum Ref Level 30.00 dBm RBW 1 MHz Att 40 dB SWT 10 ms VBW 1 MHz SGL TRG:VID 1 Zero Span 1Pk Clrw CF 2.437 GHz 8000 pts 1.0 ms/ Date: 24.DEC.2019 09:49:30
11n40	 Spectrum Ref Level 30.00 dBm RBW 1 MHz Att 40 dB SWT 10 ms VBW 1 MHz SGL TRG:VID 1 Zero Span 1Pk Clrw CF 2.437 GHz 8000 pts 1.0 ms/ Date: 24.DEC.2019 09:48:29

Appendix F：Band edge and Spurious Emissions (conducted)

Test Item:	Bandedge	Type:	802.11 b
CH01			
CH11			

Test Item:	Bandedge	Type:	802.11 g
CH01			
CH11			

Test Item:	Bandedge	Type:	802.11 n(HT20)
CH01			
CH11			

Test Item:	Bandedge	Type:	802.11 n(HT40)
CH03			
CH09			

Test Item:	SE	Type:	802.11b
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			

CH06 Reference level	
CH06 30MHz~1000MHz	
CH06 1GHz~26GHz	

CH11 Reference level	
CH11 30MHz~1000MHz	
CH11 1GHz~26GHz	

Test Item:	SE	Type:	802.11g
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			

CH06 Reference level	
CH06 30MHz~1000MHz	
CH06 1GHz~26GHz	

CH11 Reference level	
CH11 30MHz~1000MHz	
CH11 1GHz~26GHz	

Test Item:	SE	Type:	802.11n(HT20)
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			

CH06 Reference level	
CH06 30MHz~1000MHz	
CH06 1GHz~26GHz	

CH11 Reference level	
CH11 30MHz~1000MHz	
CH11 1GHz~26GHz	

Test Item:	SE	Type:	802.11n(HT40)
CH03 Reference level			
CH03 30MHz~1000MHz			
CH03 1GHz~26GHz			

CH06 Reference level	
CH06 30MHz~1000MHz	
CH06 1GHz~26GHz	

CH09 Reference level	
CH09 30MHz~1000MHz	
CH09 1GHz~26GHz	

--------End of Report--------