
Difference Description

We Hisense Visual Technology Co., Ltd. state:

Product name: Remote Controller


New Model: ERF6E66H, ERF6xy66pqrstuvw,x: A-Z; y: A-Z, Blank; p: A-Z, Blank; q: A-Z, Blank; r: (, Blank; s: 0-9, Blank; t: 0-9, Blank; u: 0-9, Blank; v: 0-9, Blank; w:), Blank

Compared to the original model(ERF6K66H, ERF6xy66pqrstuvw,x: A-Z; y: A-Z, Blank; p: A-Z, Blank; q: A-Z, Blank; r: (, Blank; s: 0-9, Blank; t: 0-9, Blank; u: 0-9, Blank; v: 0-9, Blank; w:), Blank)

There is no difference except:

1, the new model ERF6E66H, ERF6xy66pqrstuvw,x: A-Z; y: A-Z, Blank; p: A-Z, Blank; q: A-Z, Blank; r: (, Blank; s: 0-9, Blank; t: 0-9, Blank; u: 0-9, Blank; v: 0-9, Blank; w:), Blank changes the power management
Other factors remain unchanged and do not affect the RF performance.

Signature:



Signature: _____ **Date:** 2026-04-15

Name: Yansong Li

Title: Certification Engineer

Company: Hisense Visual Technology Co., Ltd.