

3911 盛和工厂控制号5015752, 柬埔寨工厂控制号5018316

产品标签: 110*80mm

字高
2.4mm


KIND LED GROW LIGHTS

**COMMERCIAL
HORTICULTURE
FIXTURE**

READ MANUAL BEFORE INSTALLATION
KINDLEDGROWLIGHTS.COM



Intertek
5015752

CONFORMS TO UL STD. 1598
CERT. TO CSA STD. CSA C 22.2 #250.0
CONFORMS TO ANSI/CAN/UL STD. 8800
CAN ICES-005-(B)/NMB-005-(B)
FCC ID : 2AVIPK-X2-V2

MODEL..... K-X2-V2
WATTAGE..... 780 W
VOLTAGE..... 120-277 Vac
AMPERAGE..... 6.66 A
FREQUENCY..... 50/60 Hz

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
SUITABLE FOR OPERATION IN AMBIENT NOT
EXCEEDING 45°C
PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE AMBIANTE
N'EXCÉDANT PAS 45°C
CAUTION – RISK OF FIRE
ATTENTION – RISQUE D'INCENDIE
Not Suitable for Intracanopy Applications
Non applicable aux applications intracavitaires

This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference,
and
(2) this device must accept any interference
received, including interference that may
cause undesired operation.

 CAUTION: Possibly hazardous
optical radiation emitted from
this product. Do not stare at
operation lamp. May be harmful
to the eyes.

外箱标签: 120*60mm 字高: 2.4mm

CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT
CONDUCTOR
CONSULTER UN ÉLECTRICIEN QUALIFIÉ POUR VOUS ASSURER QUE LES CONDUCTEURS
DE LA DÉRIVATION SONT ADÉQUATS
THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE
INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION
OF THE PRODUCT AND THE HAZARDS INVOLVED
CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE
PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES
RISQUES INHÉRENTS

字高
2.4mm


KIND LED GROW LIGHTS

**COMMERCIAL
HORTICULTURE
FIXTURE**

READ MANUAL BEFORE INSTALLATION
KINDLEDGROWLIGHTS.COM



Intertek
5018316

CONFORMS TO UL STD. 1598
CERT. TO CSA STD. CSA C 22.2 #250.0
CONFORMS TO ANSI/CAN/UL STD. 8800
CAN ICES-005-(B)/NMB-005-(B)
FCC ID : 2AVIPK-X2-V2

MODEL..... K-X2-V2
WATTAGE..... 780 W
VOLTAGE..... 120-277 Vac
AMPERAGE..... 6.66 A
FREQUENCY..... 50/60 Hz

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
SUITABLE FOR OPERATION IN AMBIENT NOT
EXCEEDING 45°C
PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE AMBIANTE
N'EXCÉDANT PAS 45°C
CAUTION – RISK OF FIRE
ATTENTION – RISQUE D'INCENDIE
Not Suitable for Intracanopy Applications
Non applicable aux applications intracavitaires

This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference,
and
(2) this device must accept any interference
received, including interference that may
cause undesired operation.

 CAUTION: Possibly hazardous
optical radiation emitted from
this product. Do not stare at
operation lamp. May be harmful
to the eyes.