FCC TEST REPORT

For

Strong Current Enterprises Limited

SoloForce Solar Wireless Charge Power Bank

Test Model: 30412

Prepared for	:	Strong Current Enterprises Limited
Address	:	Suite 2201, 22/F, Chinachem Century Tower, 178 Gloucester Road, Wan Chai, Hong Kong
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	June 28, 2020
Number of tested samples	:	1
Serial number	:	Prototype
Date of Test	:	June 28, 2020 ~ July 01, 2020
Date of Report	:	July 02, 2020

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

FCC TEST REPORT
FCC CFR 47 PART 18

Report Reference No.	**:**	**LCS200615139AEA**
Date Of Issue	:	July 02, 2020
Testing Laboratory Name.....	**:**	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Testing Location/ Procedure.....	:	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name	**:**	**Strong Current Enterprises Limited**
Address	:	Suite 2201, 22/F, Chinachem Century Tower, 178 Gloucester Road, Wan Chai, Hong Kong
Test Specification		
Standard.....	:	FCC CFR 47 PART 18
Test Report Form No.	:	LCSEMC-1.0
TRF Originator.....	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	:	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.....	**:**	**SoloForce Solar Wireless Charge Power Bank**
Trade Mark.....	:	SoloForce
Test Model.....	:	30412
Power Supply	:	Please Refer To Page 6
Result	**:**	**Positive**

Compiled by:	**Supervised by:**	**Approved by:**
Vera Deng/ File administrators	Jin Wang/ Technique principal	Gavin Liang/ Manager

FCC TEST REPORT

Test Report No. : **LCS200615139AEA**	July 02, 2020 Date of issue

Test Model.....	: 30412
EUT.....	: SoloForce Solar Wireless Charge Power Bank
Applicant.....	**: Strong Current Enterprises Limited**
Address.....	: Suite 2201, 22/F, Chinachem Century Tower, 178 Gloucester Road, Wan Chai, Hong Kong
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: Shenzhen Intention Interactive Technology Co., Ltd**
Address.....	: 4th Floor, Building 2, No. 4, West District, Shangxue Science and Technology Park, Bantian Street, Longgang District, Shenzhen, Guangdong 518000
Telephone.....	: /
Fax.....	: /
Factory.....	: /
Address.....	: /
Telephone.....	: /
Fax.....	: /

Test Result	**Positive**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	July 02, 2020	Initial Issue	Gavin Liang

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION 6
1.1 Description of Device (EUT) 6
1.2 Support equipment List 6
1.3 External I/O Cable 6
1.4 Description of Test Facility 7
1.5 Statement of the Measurement Uncertainty 7
1.6 Measurement Uncertainty 7
1.7 Description of Test Modes 8
2. TEST METHODOLOGY 9
2.1 EUT Configuration 9
2.2 EUT Exercise 9
2.3 General Test Procedures 9
2.3.1 Conducted Emissions 9
2.3.2 Radiated Emissions 9
3. SYSTEM TEST CONFIGURATION 10
3.1 Justification 10
3.2 EUT Exercise Software 10
3.3 Special Accessories 10
3.4 Block Diagram/Schematics 10
3.5 Equipment Modifications 10
3.6 Test Setup 10
4. SUMMARY OF TEST EQUIPMENT 11
5. SUMMARY OF TEST RESULT 12
6. POWER LINE CONDUCTED MEASUREMENT 13
7. RADIATED EMISSION MEASUREMENT 16
7.1. Block Diagram of Test Setup 16
7.2. Radiated Emission Limit 17
7.3. EUT Configuration on Measurement 17
7.4. Operating Condition of EUT 17
7.5. Measuring Setting 17
7.6. Test Procedure 18
7.7. Test Results 19
8. PHOTOGRAPHS OF TEST SETUP 23
9. EXTERNAL PHOTOGRAPHS OF THE EUT 23
10. INTERNAL PHOTOGRAPHS OF THE EUT 23

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT	:	SoloForce Solar Wireless Charge Power Bank
Test Model	:	30412
Power Supply	:	Input :Micro USB: 5V⎓2A, 9V⎓2A USB-C: 5V⎓3A, 9V⎓2A Output: USB-A1:5V⎓3A USB-A2: 5V⎓2.4A, 9V⎓2A, 12V⎓1.5A USB-C: 5V⎓3A, 9V⎓2A, 12V⎓1.5A USB Total Output:18W Wireless Output:10W Battery: 3.7V⎓, 20000mAh
Hardware Version	:	V3.0
Software Version	:	V1.04
Wireless Charging	:	
Operating Frequency	:	110.0~205.0KHz
Modulation Type	:	Continuous Wave
Antenna Type	:	Coil Antenna

1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Huawei	Mobile phone	FRD-AL10	FRD-AL10C00B373	SDOC
Dongguan BestGK Smart Technology Co,.Ltd	ADAPTER	K-T50501000U1	--	SDOC

Note: The support equipment are only used test, not shipped

1.3 External I/O Cable

I/O Port Description	Quantity	Cable
USB Port	2	N/A
Micro USB Port	1	N/A
Type-C Port	1	USB Cable: 0.2m, unshielded

1.4 Description of Test Facility

FCC Registration Number is 254912.

Industry Canada Registration Number is 9642A.

EMSD Registration Number is ARCB0108.

UL Registration Number is 100571-492.

TUV SUD Registration Number is SCN1081.

TUV RH Registration Number is UA 50296516-001.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier: CN0071

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	3.10dB	(1)
		30MHz~200MHz	2.96dB	(1)
		200MHz~1000MHz	3.10dB	(1)
		1GHz~26.5GHz	3.80dB	(1)
		26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	1.63dB	(1)
Power disturbance	:	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7 Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

☒ Charging and communication mode

Modulation Type: CW (Continuous Wave)

Test Modes		
Mode 1	EUT + Mobile Phone (Battery Status: <1%)	Pre-tested
Mode 2	EUT + Mobile Phone (Battery Status: <50%)	Pre-tested
Mode 3	EUT + Mobile Phone (Battery Status: 100%)	Pre-tested
Mode 4	Charge from PC + EUT + Mobile Phone (Battery Status: <1%)	Pre-tested
Mode 5	Charge from PC + EUT + Mobile Phone (Battery Status: <50%)	Pre-tested
Mode 6	Charge from PC + EUT + Mobile Phone (Battery Status: 100%)	Record
Mode 7	AC/DC Adapter (5V/2A) + EUT+ Mobile Phone (Battery Status: <1%)	Pre-tested
Mode 8	AC/DC Adapter (5V/2A) + EUT+ Mobile Phone (Battery Status: <50%)	Pre-tested
Mode 9	AC/DC Adapter (5V/2A) + EUT+ Mobile Phone (Battery Status: 100%)	Pre-tested
Mode 10	AC/DC Adapter (9V/2A) + EUT+ Mobile Phone (Battery Status: <1%)	Pre-tested
Mode 11	AC/DC Adapter (9V/2A) + EUT+ Mobile Phone (Battery Status: <50%)	Pre-tested
Mode 12	AC/DC Adapter (9V/2A) + EUT+ Mobile Phone (Battery Status: 100%)	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		

For AC conducted emission, pre-test at both AC 120V/60Hz and AC 240V/50Hz, recorded worst case;

For AC conducted emission, pre-test at both AC charge from power adapter and PC modes, recorded worst case.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with MP-5, and FCC CFR PART 18.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the charging and compunction mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 18.305 and 18.307 under the FCC Rules Part 18.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in FCC MP-5 for Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in FCC MP-5 for radiated emission.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a normal condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

N/A.

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

4. SUMMARY OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100040	2020-06-10	2021-06-09
2	SPECTRUM ANALYZER	R&S	FSP40	100503	2019-11-14	2020-11-13
3	3m Full Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2020-06-11	2021-06-10
4	Positioning Controller	MF	MF-7082	/	2020-06-11	2021-06-10
5	EMI Test Software	AUDIX	E3	/	N/A	N/A
6	EMI Test Receiver	R&S	ESR 7	101181	2020-06-11	2021-06-10
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2018-07-26	2021-07-25
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2018-07-26	2021-07-25
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2018-07-02	2021-07-01
10	RF Cable-R03m	Jye Bao	RG142	CB021	2020-06-11	2021-06-10
11	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2020-06-11	2021-06-10
12	EMI Test Receiver	R&S	ESPI	101840	2020-06-10	2021-06-09
13	Artificial Mains	R&S	ENV216	101288	2020-06-11	2021-06-10
14	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2020-06-10	2021-06-09
Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.						

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

5. SUMMARY OF TEST RESULT

Test Item	FCC Rule No.	Temperature conditions	Power source conditions	C	NC	NA	NP	Remark
Radiated Emission	§18.305 (b)	Nominal	Nominal	☒	☐	☐	☐	**-/-**
AC conducted emission	§18.307 (a)	Nominal	Nominal	☒	☐	☐	☐	**-/-**

Remark: The measurement uncertainty is not included in the test result.
N/A – Not Applicable.

6. POWER LINE CONDUCTED MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. Standard Applicable

According to §18.307 (b): For all other part 18 consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

6.3 Test Results

PASS

The test data please refer to following page.

Temperature	23.3℃	Humidity	53.7%
Test Engineer	Qu Xin	Configurations	Transmit

AC Power Line Conducted Emission (Power input to Adapter @ AC 120V/60Hz (Worst Case))

Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	37.86	15.15	53.01	65.52	-12.51	QP
2	0.1590	19.59	15.15	34.74	55.52	-20.78	AVG
3	0.2940	33.12	15.27	48.39	60.41	-12.02	QP
4	0.2987	17.52	15.27	32.79	50.28	-17.49	AVG
5	0.5955	36.04	15.28	51.32	56.00	-4.68	QP
6	0.6945	22.07	15.27	37.34	46.00	-8.66	AVG
7	2.1929	32.85	15.41	48.26	56.00	-7.74	QP
8	2.2200	16.69	15.41	32.10	46.00	-13.90	AVG
9	2.8770	31.45	15.45	46.90	56.00	-9.10	QP
10	2.9085	15.12	15.46	30.58	46.00	-15.42	AVG
11	15.7110	23.81	16.18	39.99	60.00	-20.01	QP
12	15.8370	8.99	16.18	25.17	50.00	-24.83	AVG

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

Neutral



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1500	42.57	15.14	57.71	66.00	-8.29	QP
2	0.1516	20.02	15.14	35.16	55.91	-20.75	AVG
3	0.2085	35.99	15.19	51.18	63.26	-12.08	QP
4	0.2085	14.88	15.19	30.07	53.26	-23.19	AVG
5	0.6270	29.03	15.25	44.28	56.00	-11.72	QP
6	0.6809	16.24	15.25	31.49	46.00	-14.51	AVG
7	1.2210	28.99	15.28	44.27	56.00	-11.73	QP
8	1.2210	14.74	15.28	30.02	46.00	-15.98	AVG
9	3.0615	27.12	15.46	42.58	56.00	-13.42	QP
10	3.0750	11.18	15.46	26.64	46.00	-19.36	AVG
11	12.6780	20.72	15.93	36.65	60.00	-23.35	QP
12	14.0460	5.88	16.03	21.91	50.00	-28.09	AVG

****Note: Pre-scan all modes and recorded the worst case results in this report.*

7. RADIATED EMISSION MEASUREMENT

7.1. Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Above 1GHz

7.2. Radiated Emission Limit

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following table:

Frequency MHz	Distance Meters	Field Strengths Limit	
		dBμV/m	Remark
0.009~30MHz	3	103.5	Quasi-peak

Remark:
(1) Emission level dBμV/m for 0.009~30MHz = 20log (15) + 40log (300/3) dBμV/m;
(2) Calculated according FCC 18.305.
(3) The smaller limit shall apply at the cross point between two frequency bands.
(4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

7.3. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

(1) Setup the EUT as shown in Section 4.1.

(2) Let the EUT work in worst test mode (Mode 1) and measure it.

7.5. Measuring Setting

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/Average
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/Average
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

7.6. Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 0.8 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

7.7. Test Results

PASS.

Only report the worst test data (Mode 1) in test report;

The test data please refer to following page:

Temperature	24.3℃	Humidity	54.3%
Test Engineer	Qu Xin	Configurations	Transmit

0.009 MHz – 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0117	54.90	20.58	75.48	103.50	-28.02	QP
2 *	0.1526	68.36	20.68	89.04	103.50	-14.46	QP
3	0.3786	51.53	20.56	72.09	103.50	-31.41	QP
4	0.4382	50.10	20.56	70.66	103.50	-32.84	QP
5	1.0105	37.07	20.51	57.58	103.50	-45.92	QP
6	9.2534	35.47	20.33	55.80	103.50	-47.70	QP

Remark: Measured at antenna position 0 degree and 90 degree, recorded worst case at 0 degree.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

Temperature	24.6℃	Humidity	54.1%
Test Engineer	Qu Xin	Configurations	Transmit

Below 1GHz

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	58.6126	27.71	-16.64	11.07	40.00	-28.93	QP
2	112.5244	29.26	-18.24	11.02	43.50	-32.48	QP
3	180.6488	35.48	-19.55	15.93	43.50	-27.57	QP
4	381.2487	30.85	-12.65	18.20	46.00	-27.80	QP
5	658.8362	29.47	-8.43	21.04	46.00	-24.96	QP
6 *	872.1832	29.73	-6.29	23.44	46.00	-22.56	QP

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	47.3255	27.97	-15.60	12.37	40.00	-27.63	QP
2	96.7749	28.53	-17.92	10.61	43.50	-32.89	QP
3 *	183.8440	38.13	-19.16	18.97	43.50	-24.53	QP
4	259.2338	30.85	-15.42	15.43	46.00	-30.57	QP
5	428.0193	28.99	-11.86	17.13	46.00	-28.87	QP
6	642.8613	29.42	-8.39	21.03	46.00	-24.97	QP

Note: Level = Reading + Factor .
Margin = Level – Limit.

8. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files for Test Setup Photos of the EUT.

9. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

10. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

----------THE END OF REPORT----------

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.