

MPE Calculation

Regulation(s): Part 1.1310, Part 2.1091

Method: KDB447498 D01v06

RF feature(Mode)	Frequency range (MHz)			Separation distance(cm)	Max. tune-up EIRP (dBm) ^{Note1}	Maximum EIRP (mW)	Maximum power density(mW/cm ²)	Requirement (mW/cm ²)
FMCW Radar	61 000.0	~	61 500.0	20.00	13.00	19.953 0	0.004 0	1.000
		~						
		~						
		~						
		~						
		~						
		~						
		~						

Note1: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 19.953 / (4 \times 20^2 \times \pi) \\
 &= 0.0040 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20cm)

Part 1.1310

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC