

Test Report

Electromagnetic Compatibility (EMC)

HELEM2204000190-1



TESTS ACCORDING TO FCC PART 15 B AND ISED CANADA REQUIREMENTS

Equipment Under Test:	Acoustic camera
Model:	AC13
Trademark:	NL Camera
Customer:	Noiseless Acoustics Oy Sitratie 7 A FI-00420, Helsinki Finland
FCC Rule Part:	FCC CFR 47 Part 15 Subpart B, Class A
IC Rule Part:	ICES-003 Issue 7, Class A

Date: 13 May 2022

Issued by:

A blue ink signature of Pekka Kälviäinen.

Pekka Kälviäinen
Testing Engineer

Date: 13 May 2022

Checked by:

A blue ink signature of Rauno Repo.

Rauno Repo
Senior EMC Specialist

TABLE OF CONTENTS

TABLE OF CONTENTS	2
GENERAL REMARKS	3
Disclaimer	3
RELEASE HISTORY	4
PRODUCT DESCRIPTION	5
Equipment Under Test (EUT)	5
General description	5
Samples and modifications.....	5
Ports and cables	5
Peripherals	5
TEST CONDITION.....	6
EUT Test Conditions During EMC-Testing.....	6
Operation modes	6
Emission Measurement Uncertainty	6
SUMMARY OF TESTING	7
EMISSION TESTS.....	8
Radiated Emissions In The Frequency Range 30 MHz - 1000 MHz.	8
TEST EQUIPMENT	10

GENERAL REMARKS

Disclaimer

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

RELEASE HISTORY

Version	Changes	Issued
1.0	Initial release	13 May 2022

PRODUCT DESCRIPTION

Equipment Under Test (EUT)

EUT information	
General Product Description	Acoustic camera
Trademark	NL Camera
Model	AC13
Type	-
Serial number	AC130655
Power input port type	DC (battery)
Rated voltage	12 V
Rated current	1 A
Rated frequency	-
Rated power	-
EUT Highest operation freq.	5 GHz WLAN
Hardware Version (if any)	-
Software Version (if any)	-
Mechanical size of the EUT	Height: 28 cm Width: 18 cm Length: 12 cm Weight: 1 kg
Parallel models	LF10

The EUT was tested as a tabletop unit.

General description

The equipment under test is a battery powered handheld acoustic camera. It measures the direction of a sound source and converts it to visual form for the display. The equipment includes 2.4 and 5 GHz WLAN radios.

Samples and modifications

No.	Name	Description
1	Sample 1	Test sample supplied by the customer

Ports and cables

none

Peripherals

none

TEST CONDITION

EUT Test Conditions During EMC-Testing

Configuration of the EUT was made to correspond to the actual assembling conditions as far as possible. The EUT was powered on and the sound source measurement was enabled. During testing the EUT was powered by the internal battery. Radios were set to stand-by mode during the tests.

The test conditions and the performance criteria were proposed (supplied) by the customer.




Figure 1: Test setup block diagram

Operation modes

During the tests the EUT was in the following operation modes:

Mode	Description
1	Power on, sound source measurement enabled

Emission Measurement Uncertainty

The uncertainties comply with CISPR 16-4-2 ed.2 requirements ($U_{lab} < U_{cispr}$).

Summary of Testing

SUMMARY OF TESTING

Test Specification	Description of Test	Result
FCC CFR 47 15/B §15.107, ICES-003 3.2.1	Conducted emissions, Class A/B	Not Applicable
FCC CFR 47 15/B §15.109, ICES 003 3.2.2	Radiated Emissions, Class A	PASS

Decision rule used for the emission tests are defined in standard CISPR 16-4-2 / EN 55016-4-2 clause 4.2

Test Facility

Testing Laboratory / address: FCC designation number: FI0002 ISED CAB identifier: T004	SGS Fimko Ltd Takomotie 8 FI-00380, HELSINKI FINLAND
Test Site:	☐ K10LAB, ISED Canada registration number: 8708A-1 ☒ K5LAB, ISED Canada registration number: 8708A-2 ☐ T10LAB

Radiated Emissions In The Frequency Range 30 MHz - 1000 MHz.

EMISSION TESTS**Radiated Emissions In The Frequency Range 30 MHz - 1000 MHz.**

Standard:	ANSI C63.4 (2014)	
Tested by:	PKA	
Date:	13 May 2022	
Humidity:	30 – 60 %	
Temperature:	22 ± 3 °C	
Barometric pressure:	860 – 1 060 mbar	
Measurement uncertainty:	± 4.9 dB (30 – 200 MHz)	Level of confidence 95 % (k = 2).
	± 4.1 dB (200 – 1 000 MHz)	

FCC Rule: 15.109(a)
ICES-003: 3.2.2

Test plan

The radiated emission measurements were done within a semi anechoic screened chamber. The EUT was placed on a table 0.8 m above the reflecting ground plane. The measurement distance was 3 meters. The worst interferences were determined during measurements by rotating the turntable and adjusting the antenna height. The measurements were done in horizontal and vertical antenna polarizations. The supply voltage to the turntable was fed through the filter.

The EUT was working as described in the section “EUT Test Conditions During EMC-Testing”.

Field strength results at the distance of 3 m were converted (by -10.46 dB) so that they can be directly compared with Class A 10 m limits.

Radiated measurement settings**Preliminary testing:**

Turntable movement:	30 ° step
Turntable position:	0 ° to 330°
Antenna movement:	1.5 m step
Antenna height:	1.0 m to 4.0 m
Antenna polarization:	Vertical and horizontal

Final testing:

Turntable movement:	Continuous
Turntable position:	± 15 °
Antenna movement:	Continuous
Antenna height:	± 0.75 m
Antenna polarization:	Vertical and horizontal

Radiated Emissions In The Frequency Range 30 MHz - 1000 MHz.

Measured Quasi-Peak Values In The Frequency Range 30 MHz - 1000 MHz.




Figure 2: Measured results

Final measurements from the worst frequencies

Table 1: Final quasi-peak results

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
384.620000	30.40	46.40	16.00	1000.0	120.000	229.0	H	28.0	11.2
400.000000	31.08	46.40	15.32	1000.0	120.000	214.0	H	199.0	11.4
442.500000	37.08	46.40	9.32	1000.0	120.000	187.0	H	196.0	13.0
676.820000	32.32	46.40	14.08	1000.0	120.000	100.0	H	255.0	17.4
704.800000	18.24	46.40	28.16	1000.0	120.000	108.0	H	335.0	17.8
752.140000	19.26	46.40	27.14	1000.0	120.000	108.0	H	173.0	18.8
761.490000	23.88	46.40	22.52	1000.0	120.000	100.0	H	251.0	19.0
774.590000	22.03	46.40	24.37	1000.0	120.000	172.0	V	356.0	19.2
902.400000	33.47	46.40	12.93	1000.0	120.000	108.0	V	24.0	20.9

Correction factor (dB) in the final result tables contains the sum of the transducers (antenna + cables).

QuasiPeak values are measured values corrected with the correction factor.

TEST EQUIPMENT

Equipment	Manufacturer	Type	Inv or serial	Prev Calib	Next Calib
TEMPERATURE/ HUMIDITY SENSOR	EDS	OW-ENV-TH, K5 SAC	inv:10517	2021-10-22	2022-10-22
TURNTABLE	MATURO	DS430 UPGRADED	inv:10182	NCR	NCR
MAST & TURNTABLE CONTROLLER	MATURO	NCD	inv:10183	NCR	NCR
ANTENNA MAST	MATURO	TAM 4.0E	inv:10181	NCR	NCR
ATTENUATOR	PASTERNAK	PE 7004-4 (4dB)	inv:10126	2021-03-30	2023-03-30
TEST SOFTWARE	ROHDE & SCHWARZ	EMC-32	-	NCR	NCR
EMI TEST RECEIVER	ROHDE & SCHWARZ	ESW26	inv:10679	2021-06-21	2022-06-21
ANTENNA	SCHWARZBECK	VULB 9168	inv:8911	2020-11-04	2022-11-04

NCR = No calibration required

END OF REPORT