

RF EXPOSURE EVALUATION**1.1 Limit**

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2 \pi)$ $S = (0.57 * 0.30) / (4 * 20^2 * \pi)$ $S = 0.00003 \text{ mW/cm}^2$	Where, S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
--	--

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 0 dBm $\pm$ 0.5dB)

3-1. 2.4 GHz Mode

Max Peak output Power at antenna input terminal	-2.46	dBm
Max Peak output Power at antenna input terminal	0.57	mW
Prediction distance	5	mm
Prediction frequency	2,405	MHz
Antenna Gain(typical)	-5.27	dBi
Antenna Gain(numeric)	0.30	-

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$$

$$\cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$[(0.57)/(5)] \cdot [\sqrt{2.412}] = 0.177 \leq 3.0$$

Thus, SAR for this device is not required.