

Test Report

Report No. : MTi250604016-0106E2

Date of Issue : 2025-06-13

Applicant : Shenzhen Mgctech Co., Ltd.

Product : Wireless Charger

Model(s) : CBT-40Q, XX-1, TWINS-40Q, KR-CBT-40Q-BK,
KR-CBT-40Q-WT, BTLO40, PEI-WS28

FCC ID : 2AVSB-CBT-40Q

Shenzhen Microtest Co., Ltd.

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	5
1.3	Description of support units	6
2	Measurement uncertainty	6
3	Test facilities and accreditations	7
3.1	Test laboratory	7
4	List of test equipment	8
5	Test result	9
5.2	Test setup	10
5.3	Test Procedures	10
5.4	Information of test equipment	11
5.5	Test results	12
	Photographs of the Test Setup	15
	Photographs of the EUT	15

Test Result Certification		
Applicant	Shenzhen Mgctech Co.,Ltd.	
Applicant Address	401, Bldg.14, No. 48-12, Fuchengao Rd, Pinghu Street, Longgang District. Shenzhen, China.	
Manufacturer	Shenzhen Mgctech Co., Ltd.	
Manufacturer Address	201, Bldg.C, No.12, Fusheng Road Pinghu Fuchengao Street, Longgang District, Shenzhen, China.	
Product description		
Product name	Wireless Charger	
Trademark	N/A	
Model name	CBT-40Q	
Series Model(s)	XX-1, TWINS-40Q, KR-CBT-40Q-BK, KR-CBT-40Q-WT, BTLO40, PEI-WS28	
Standards	47 CFR PART 1, § 1.1310 part2.1091	
Test method	KDB 680106 D01 Wireless Power Transfer v04	
Testing Information		
Date of test	2025-06-07 to 2025-06-12	
Test Result	Pass	
Prepared by:	Letter Lan	<i>Letter. Lan.</i>
Reviewed by:	David Lee	<i>David. Lee</i>
Approved by:	Lewis Lian	<i>Lewis Lian</i>

1 General Description

1.1 Description of the EUT

Product name:	Wireless Charger
Model name:	Wireless Charger
Series Model(s):	CBT-40Q
Model difference:	XX-1, TWINS-40Q, KR-CBT-40Q-BK, KR-CBT-40Q-WT, BTLO40, PEI-WS28
Electrical rating:	All the models are the same circuit and module, except the model name.
Accessories:	Input: 9V/3A, 12V/3A Wireless Output: Phone: 5W, 10W, 15W Max Earphone: 5W Watch: 2.5W
Hardware version:	Cable: Type-C to Type-C cable 1.2m
Software version:	V1.0
Test sample(s) number:	V1.0
RF specification	
Operating frequency range:	Coil 1 (Phone 5W, 10W): 115-205kHz Coil 1 (Phone 15W): 360kHz Coil 2 (Earphone): 115-205kHz Coil 3 (Apple Watch): 300-350kHz Coil 3 (Samsung Watch): 115-205kHz
Modulation type:	ASK
Antenna(s) type:	Coil

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless Output(PHONE(5W)+Earphone(5W)+Apple Watch(2.5W))
Mode2	Wireless Output(PHONE(10W)+Earphone(5W)+Apple Watch(2.5W))
Mode3	Wireless Output(PHONE(15W) + Earphone(5W)+Apple Watch(2.5W))
Mode4	Wireless Output(PHONE(5W)+Earphone(5W)+Samsung Watch(2.5W))
Mode5	Wireless Output(PHONE(10W)+Earphone(5W)+ Samsung Watch(2.5W))
Mode6	Wireless Output(PHONE(15W)+ Earphone(5W)+Samsung Watch(2.5W))
Mode7	Wireless output phone(5W)+earphone(5W)
Mode8	Wireless output phone(10W)+earphone(5W)
Mode9	Wireless output phone(15W)+earphone(5W)
Mode10	Wireless output phone(5W)+Apple Watch(2.5W))
Mode11	Wireless output phone(10W)+Apple Watch(2.5W))
Mode12	Wireless output phone(15W)+Apple Watch(2.5W))
Mode13	Wireless Output(PHONE(5W)+Samsung Watch(2.5W))
Mode14	Wireless Output(PHONE(10W)+Samsung Watch(2.5W))
Mode15	Wireless Output(PHONE(15W)+ Samsung Watch(2.5W))
Mode16	Wireless output earphone(5W)+Apple Watch(2.5W))
Mode17	Wireless output earphone(5W)+Samsung Watch(2.5W))
Mode18	Wireless output phone(5W)
Mode19	Wireless output phone(10W)
Mode20	Wireless output phone(15W)
Mode21	Wireless output Samsung Watch(2.5W)
Mode22	Wireless output Apple Watch(2.5W)
Mode23	Wireless output earphone(5W)
Mode24	Stand by

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list

Description	Model	Serial No.	Manufacturer
Mobile phone	iPhone 12	/	Apple
Phone	S9	/	Samsung
watch	Apple watch S7	M0JVGQG1VP	Apple
Watch	Galaxy Watch 5	R32T5467890	Samsung
Air Pods	MQD83CH/A	/	Apple

Support cable list

Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 14.8\%$
Electric field measurements(3kHz~10MHz)	$\pm 17.5\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3 Test facilities and accreditations**3.1 Test laboratory**

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+ED3	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.6	2.6	/	/

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Test setup**5.3 Test Procedures**

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+ED3	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

5.5 Test results

Test condition 1: Mode 3 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	2.15	614	0.35%	0.08	1.63	4.19%
Left	1.62			0.06		
Right	1.97			0.04		
Front	1.86			0.07		
Rear	1.88			0.06		
Bottom	1.45			0.05		

Test condition 2: Mode 3 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	2.13	614	0.35%	0.07	1.63	4.29%
Left	1.61			0.05		
Right	1.92			0.04		
Front	1.85			0.06		
Rear	1.84			0.06		
Bottom	1.41			0.04		

TEST REPORT

Report No.: MTi250604016-0106E2

Test condition 3: Mode 3 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	2.11	614	0.34%	0.05	1.63	3.07%
Left	1.61			0.04		
Right	1.90			0.04		
Front	1.85			0.05		
Rear	1.82			0.05		
Bottom	1.41			0.04		

Test condition 1: Mode 5 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	2.25	614	0.37%	0.11	1.63	6.75%
Left	1.98			0.07		
Right	1.87			0.04		
Front	1.59			0.05		
Rear	1.68			0.07		
Bottom	1.73			0.06		

Test condition 2: Mode 5 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	2.18	614	0.36%	0.10	1.63	6.13%
Left	1.95			0.07		
Right	1.84			0.03		
Front	1.59			0.05		
Rear	1.61			0.05		
Bottom	1.66			0.06		

Test condition 3: Mode 5 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	2.11	614	0.34%	0.08	1.63	4.91%
Left	1.90			0.06		
Right	1.84			0.03		
Front	1.54			0.05		
Rear	1.61			0.05		
Bottom	1.60			0.04		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****