

RF Exposure Evaluation

FCC ID: 2AVSW-QM02C

Product Name:	Quick Launch Mount (Rechargeable) Series
Trade Mark:	N/A
Model Number:	QM02C, QMC01, QMC02, QMC03, QM01C, QM04C, QM05C, QM09C, QM10C, QM11C, QM12C, QM13C, QM14C, QM15C, QM16C
Test Model:	QM02C
Model Difference:	All models are same as the samples except model name, appearance and appearance color ,they have the same structure and circuit.
Transmitting mode	Keep the EUT in continuously wireless charging mode
Power supply:	Input: DC 12.5V-16V 3A
Date of Receipt:	May. 11, 2026
Test Date:	May. 11, 2026 - Jun. 10, 2026
Date of Report:	Jun. 10, 2026

Mode1. Wireless Output Mode

1 Measuring Standard

According to Part 2.1091 RF exposure is calculated. According KDB 680106 D01 WirelessPower Transfer v04.

2 Requirements

- ①According to the item 5 of KDB680106 D01v04:
- ②Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

3 Limits


The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
* =Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

4 Test Setup



5 Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20 cm from all sides and 20 cm from the top) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB680106 D01v04.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

6 Description of Support Units

N/A

7 Test Instruments list

Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Exposure Level Tester	Narda	ELT-400	N-0231	Oct. 25, 2025	Oct. 24, 2026
Magnetic field probe 100cm ²	Narda	ELT probe 100cm ²	M0675	Oct. 25, 2025	Oct. 24, 2026
Field Probe	ETS	HI-6105	/	Oct. 25, 2025	Oct. 24, 2026
Laser Data Interface	ETS	HI-6113	/	Oct. 25, 2025	Oct. 24, 2026

8 Test Uncertainty

E-Filed Strength(1Hz-400kHz) : ±0.08V/m

H-Filed Strength(1Hz-400kHz) : ±0.02A/m

uT : ±0.01

Note: The field intensity value A/m in the report is converted from uT, and the formula is as follows:

uT to A/m

$$A/m = \frac{\mu T}{1.25}$$

9 Test Result

E-Filed Strength at 20 cm from the edges surrounding the EUT

Frequency Range (MHz)	Test Position A (V/m)	Test Position B (V/m)	Test Position C (V/m)	Test Position D (V/m)	Test Position E (V/m)	Limits (V/m)
0.115-0.205	0.13	0.21	0.15	0.23	0.31	614

H-Filed Strength at 20 cm from the edges surrounding the EUT (uT)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E
0.115-0.205	0.419	0.708	0.715	0.631	0.738

H-Filed Strength at 20 cm from the edges surrounding the EUT

Frequency Range (MHz)	Test Position A (A/m)	Test Position B (A/m)	Test Position C (A/m)	Test Position D (A/m)	Test Position E (A/m)	Limits (A/m)
0.115-0.205	0.331	0.569	0.577	0.504	0.589	1.63

10 Test Set-up Photo

