

Nemko Korea Co., Ltd.

165-51, Yurim-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 17042, Republic of Korea

TEL: +82 31 330-1700

FAX: +82 31 322 2332

FCC EVALUATION REPORT FOR CERTIFICATION

Project No. : NK-26-R-251**Dates of receipt :** July 6, 2026**Applicant :** QUDELIX, Inc.**Dates of Issue :** September 18, 2026B-1316, 190 Soha-ro, Gwangmyeong-si,
Gyeonggi-do, 14322, Korea (the Republic of)**Test Site :**

Nemko Korea Co., Ltd.

FCC ID :

2AVUO-5KP

Applicant :

QUDELIC, Inc.

Brand Name :**Model:**

Quidelix-5K Plus

Additional Model(s):

-

EUT Type:

BLUETOOTH DAX/AMP

Classification:

FCC Part 15 Digital Transmission System (DTS)

Date of Test:

August 10, 2026 ~ August 28, 2026

Applied Standard:

FCC 47 CFR Part 15.247

The device bearing the brand name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.
This test report is prepared according to the requirements of ISO / IEC 17025.



Tested by : Jaehyong Lee

Test Engineer



Reviewed by : Hoonpyo Lee

Technical Manager

Revision History

Rev.	Issue Date	Revisions	Revised By
00	September 18, 2026	Initial issue	Jaehyong Lee

TABLE OF CONTENTS

1. INTRODUCTION	4
1.1 Test facility	4
1.2 Accreditation and listing	4
2. EUT INFORMATION & TEST CONDITIONS	5
2.1 EUT Information	5
2.2 Operation During Test	6
2.3 Support Equipment	9
2.4 Setup Drawing	9
3. ANTENNA REQUIREMENTS	10
4. SUMMARY OF TEST RESULTS	11
5. TEST METHODOLOGY	11
6. DESCRIPTION OF TESTS	12
6.1 6 dB Bandwidth / Occupied Bandwidth	12
6.2 Peak Output Power	13
6.3 Power Spectral Density	14
6.4 Band Edge / Conducted Spurious Emissions	15
6.5 Radiated Emissions	16
6.6 AC Line Conducted Emissions	17
7. TEST DATA	18
7.1 Duty Cycle	18
7.2 6 dB Bandwidth	19
7.3 Peak Output Power	21
7.4 Power Spectral Density	23
7.5 Band Edge / Conducted Spurious Emissions	25
7.6 Radiated Spurious Emissions	28
7.7 Radiated Band Edge	32
7.8 Radiated Emissions_Below 1GHz	36
7.9 AC Line Conducted	38
8. TEST EQUIPMENT	40
9. ACCURACY OF MEASUREMENT & DECISION RULE	41
9.1 Uncertainty Calculation	41
9.2 Decision rule	41

1. INTRODUCTION

1.1 Test facility

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014), the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2020) was used in determining radiated and conducted emissions emanating.

These measurement tests were conducted at **Nemko Korea Co., Ltd.**

The site address 165-51, Yurim-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 17042, Rep. of Korea.

1.2 Accreditation and listing

Accreditation type		Accreditation number
	CAB Accreditation for DOC	Designation No. KR0026
	KOLAS Accredited Lab. (Korea Laboratory Accreditation Scheme)	Registration No. KT155
	Canada IC Registered site	Site No. 29506
	VCCI registration site(RE/CE/Telecom CE)	Member No. 2118
	EMC CBTL	TL124
	KCC(RRL)Designated Lab.	Registration No. KR0026

2. EUT INFORMATION & TEST CONDITIONS

2.1 EUT Information

2.1.1 Specifications

EUT Type	BLUETOOTH DAC/AMP
Model Name	Qudelix-5K Plus
Frequency of Operation	2 402 MHz ~ 2 480 MHz
Peak Output Power (Conducted)	11.59 dBm
Number of Channels	40 CH
Modulations	GFSK
Antenna Gain (peak)	2.87 dBi
Antenna Setup	1TX / 1RX
EUT Test Voltage	DC 3.7 V
Temperature Range	-10 °C ~ 50 °C
Hardware Version	4.0
Software Version	1.0
Remarks	-

2.2 Operation During Test

The EUT is a transceiver supporting Bluetooth v5.4 with Bluetooth BR/EDR, LE 1M, and LE 2M modes. The EUT was controlled by the BlueTest Tool running on a laptop PC to continuously transmit on the desired TX channel (duty cycle < 98%).

During testing, the EUT was powered by its internal 3.7 Vdc battery and connected to a laptop PC via a USB Type-C charging cable.

The EUT was tested on the lowest, middle, and highest channels at the maximum output power in accordance with the manufacturer's specifications. The worst-case data were recorded in this report.

2.2.1 Table of Test power setting

Frequency	Mode	Modulation	Power setting Level
2 402 MHz ~ 2 480 MHz	BLE 1Mbps	GFSK	Table 7, Mag AF
	BLE 2Mbps	GFSK	Table 6, Mag 89

2.2.2 Table of Test frequency

Frequency band	Modulation	Mode	Test Channel (CH)	Frequency (MHz)
2.4 GHz	GFSK	BLE 1Mbps, 2Mbps	0	2 402
			19	2 440
			39	2 480

2.2.3 Antenna Information

Frequency band	Modulation	Antenna TX mode	Support CDD	Support MIMO
2.4 GHz	GFSK	☒ 1TX, ☐ 2TX	☐ Yes, ☒ No	☐ Yes, ☒ No

2.2.4 Additional Information Related to Testing

The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for all conducted testing.

2.2.5 Worst-case Configuration and Mode

Radiated emission below 1GHz was performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The emissions (Band-edge & spurious emissions) were investigated in three orthogonal orientations X, Y and Z.

Accordingly, the orientation was determined and tested as shown in the table below:

Test Items	X	Y	Z
Band-edge	O	-	-
Spurious emissions	O	-	-

The average output power of 37 pkt data rate and 255 pkt data rate was investigated. The 255 pkt data rate exhibited the worst-case results. Therefore, the conducted emission and radiated emission test plots are based on these modes to demonstrate compliance.

Mode	Channel	Frequency	Average Output Power (dBm)
BLE 1Mbps (37 pkt)	0	2 402	10.54
	19	2 440	10.49
	39	2 480	10.41
BLE 1Mbps (255 pkt)	0	2 402	10.55
	19	2 440	10.48
	39	2 480	10.41
BLE 2Mbps (37 pkt)	0	2 402	9.35
	19	2 440	9.28
	39	2 480	9.22
BLE 2Mbps (255 pkt)	0	2 402	9.38
	19	2 440	9.31
	39	2 480	9.24

2.2.6 Maximum Output Power

The maximum peak and average conducted output powers of the transmitter are as follows:

Frequency (MHz)	Mode	Power Type	Output Power (dBm)	Output Power (mW)
2 402 ~ 2 480	BLE 1Mbps	Peak	10.64	11.59
		Average	10.55	11.35
	BLE 2Mbps	Peak	9.63	9.18
		Average	9.38	8.67


2.2.7 Additional model covered by this report

- N/A

2.3 Support Equipment

EUT	QUDELIX, Inc. Model : Qudelix-5k Plus	S/N: N/A
Laptop Computer	DELL MODEL : P56F	FCC DOC S/N : 17ZYNQ2
AC/DC Adapter	DELTA ELECTRONICS(JIANGSU) MODEL : DA130PM130	FCC DOC S/N : 09TXK7
Laptop Computer	LG MODEL : 15U47	FCC DOC S/N : 709QCTB565737
AC/DC Adapter	Chicony Power Technology MODEL : A13-040N3A	FCC DOC S/N : A040R066C

2.4 Setup Drawing



3. ANTENNA REQUIREMENTS

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15.

§15.203 of the FCC Rules part 15 Subpart C

: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna of the EUT and there are no provisions for connection to an external antenna. It complies with the requirement of §15.203.

The transmitter has a permanently attached LDS antenna inside the EUT enclosure.

Used Antenna	
Model name	2 402 MHz ~ 2 480 MHz
	Max. peak gain (dBi)
Qudelix 5K PRO	2.87

4. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

Name of Test	FCC Paragraph No.	Test Limit	Test Condition	Result	Remark
6dB Bandwidth	15.247(a)(2)	> 500 kHz	Conducted	Complies	-
Peak Output Power	15.247(b)(3)	< 1 Watt < 4 Watt(e.i.r.p.)		Complies	-
Power Spectral Density	15.247(e)	< 8 dBm/3 kHz		Complies	-
Band Edge / Conducted Spurious Emission	15.247(d)	≥ 20 dBc		Complies	-
Radiated Spurious Emission	15.205, 15.209	< 74 dBμV/m (PK) < 54 dBμV/m (AV) Radiated limits detailed in 15.209	Radiated	Complies	-
AC Line Conducted Emission	15.207	FCC 15.207 Limits	Line Conducted	Complies	-

5. TEST METHODOLOGY

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2020.

6. DESCRIPTION OF TESTS

6.1 6 dB Bandwidth / Occupied Bandwidth

Test Setup



Test Measurement Method

ANSI C63.10-2020, Section 11.8.2 Option 2

Test Procedure

- 6 dB Bandwidth (DTS Chanel Bandwidth)

EUTs 6 dB bandwidth is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

RBW = 100 kHz

VBW > 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow trace to fully stabilize.

The bandwidth measurement function on the spectrum analyzer is used to measure the 6 dB bandwidth.

6.2 Peak Output Power

Test Setup



Test Measurement Method

ANSI C63.10-2020, Section 11.9.1.1

Test Procedure

EUTs Maximum Peak Conducted Output Power is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

RBW $\geq$ DTS bandwidth

VBW $\geq$ 3 x RBW

Span $\geq$ 3 x RBW

Sweep time = auto couple

Detector = peak

Trace mode = max hold

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

6.3 Power Spectral Density

Test Setup



Test Measurement Method

ANSI C63.10-2020, Section 11.10.2 Method PKPSD

Test Procedure

EUTs Power Spectral Density is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

Center frequency = DTS channel center frequency

Span > 1.5 times the DTS channel bandwidth

RBW to $\geq 3 \text{ kHz}$ $\leq$ RBW $\leq 100 \text{ kHz}$

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow the trace to stabilize.

The peak search function on the spectrum analyzer is used to determine the maximum amplitude level within the RBW.

6.4 Band Edge / Conducted Spurious Emissions

Test Setup



Test Measurement Method

ANSI C63.10-2020, Section 11.11

Test Procedure

EUTs Conducted spurious emissions are measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

1) Reference Level

Center frequency = DTS channel center frequency

Span $\geq 1.5 \times$ DTS bandwidth

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

2) Unwanted Emissions

Set the center frequency and span to encompass frequency range to be measured.

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

6.5 Radiated Emissions

Test Measurement Method

ANSI C63.10-2020, Section 6.6.4.3, Section 11.11, Section 11.12

Test Procedure

The measurement was performed at the test site that is specified in accordance with ANSI C63.10-2020. The spurious emission was scanned from 9 kHz to 30 MHz using Loop Antenna and 30 to 1000 MHz using Trilog broadband test antenna. Above 1 GHz, Horn antenna was used. For emissions testing at below 1GHz, The test equipment was placed on turntable with 0.8 m above ground. For emission measurements above 1 GHz, The test equipment was placed on turntable with 1.5 m above ground. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The EUT, cable, wire arrangement and mode of operation that has the highest amplitude relative to the limit was selected. Then, the turn table was rotated from 0° to 360° and an antenna mast was moved from 1 m to 4 m height to maximize the suspected highest amplitude signal. The final maximized level was recorded.

At frequencies below 1000 MHz, measurements performed using the CISPR quasi-peak detection. At frequencies above 1000 MHz, measurements performed using the peak and average measurement procedures described in ANSI 63.10-2020 section 11.12. Peak emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Trace mode = max hold. Average emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 10 kHz, Detector = Peak, Trace mode = max hold. Allow max hold to run for at least 50 times (1/duty cycle) traces.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100	3
88–216	150	3
216–960	200	3
Above 960	500	3

Radiated Emissions Limits per 47 CFR 15.209(a)

6.6 AC Line Conducted Emissions

Test Measurement Method

ANSI C63.10-2020, Section 6.2

Test Procedure

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure. It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6. A 1 m x 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room. Rohde & Schwarz (ENV216) of the 50 ohm/50 μ H Line Impedance Stabilization Network (LISN) are bonded to the shielded room. The EUT is powered from the Rohde & Schwarz LISN. Power to the LISNs are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ". If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs, All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1 meter length. Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with 200 msec sweep time. The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCI). The detector functions were set to CISPR quasi-peak mode & average mode. The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

7. TEST DATA


7.1 Duty Cycle

For reporting purposes only.

Result

Mode	On time [msec]	Period [msec]	Duty Cycle [%]	1/T Minimum VBW [kHz]
BLE 1Mbps (37 pkt)	0.392	0.626	62.70	2.55
BLE 1Mbps (255 pkt)	2.135	2.503	85.30	0.47
BLE 2Mbps (37 pkt)	0.208	0.626	33.31	4.80
BLE 2Mbps (255 pkt)	1.080	1.877	57.51	0.93

PLOTS OF EMISSIONS



7.2 6 dB Bandwidth

FCC §15.247(a)(2)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

Mode	Channel No.	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Bandwidth Limit (kHz)
BLE 1Mbps (255 pkt)	0	2 402	0.779	500
	19	2 440	0.789	500
	39	2 480	0.759	500
BLE 2Mbps (255 pkt)	0	2 402	1.389	500
	19	2 440	1.459	500
	39	2 480	1.244	500

PLOTS OF EMISSIONS


BLE 1Mbps (255 pkt)

Lowest Channel




BLE 2Mbps (255 pkt)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel



Highest Channel



7.3 Peak Output Power

FCC §15.247(b)(3)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Margin (dB)
BLE 1Mbps (255 pkt)	Lowest	2 402	10.64	30.00	19.36
	Middle	2 440	10.57	30.00	19.43
	Highest	2 480	10.50	30.00	19.50
BLE 2Mbps (255 pkt)	Lowest	2 402	9.63	30.00	20.37
	Middle	2 440	9.54	30.00	20.46
	Highest	2 480	9.49	30.00	20.51

Notes:

1. The following equation was used for spectrum offset:

$$\text{Spectrum offset (dB)} = \text{Attenuator (dB)} + \text{Cable Loss (dB)} + \text{SMA Type Connector Loss (dB)}$$

PLOTS OF EMISSIONS



7.4 Power Spectral Density

FCC §15.247(e)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result


Mode	Channel No.	Frequency (MHz)	Measured PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Margin (dB)
BLE 1Mbps (255 pkt)	0	2 402	-6.21	8.00	14.21
	19	2 440	-6.25	8.00	14.25
	39	2 480	-6.28	8.00	14.28
BLE 2Mbps (255 pkt)	1	2 404	-9.76	8.00	17.76
	19	2 440	-9.81	8.00	17.81
	38	2 478	-9.87	8.00	17.87

Notes:

1. The following equation was used for spectrum offset:

$$\text{Spectrum offset (dB)} = \text{Attenuator (dB)} + \text{Cable Loss (dB)} + \text{SMA Type Connector Loss (dB)}$$

PLOTS OF EMISSIONS



7.5 Band Edge / Conducted Spurious Emissions

FCC §15.247(d)

Test Mode : Set to Lowest channel, Middle channel and Highest channel


Result

Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
BLE 1Mbps (255 pkt)	0	2 402	More than 20 dBc	20
	19	2 440	More than 20 dBc	20
	39	2 480	More than 20 dBc	20
BLE 2Mbps (255 pkt)	0	2 402	More than 20 dBc	20
	19	2 440	More than 20 dBc	20
	39	2 480	More than 20 dBc	20


Notes:

The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for the spurious emissions test.

PLOTS OF EMISSIONS (Band Edge)



PLOTS OF EMISSIONS (Conducted Spurious Emissions)



7.6 Radiated Spurious Emissions

FCC §15.205, §15.209, §15.247(d)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

BLE 1Mbps (255 pkt)_Lowest channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
3 603.33	41.38	V	PK	-0.3	41.08	74.00	32.92
3 603.03	37.33	H	AV	-0.3	37.03	54.00	16.97
4 804.03	39.62	H	PK	4.0	43.62	74.00	30.38
4 803.70	33.20	H	AV	4.0	37.20	54.00	16.80
9 606.83	37.60	H	PK	16.0	53.60	74.00	20.40

BLE 1Mbps (255 pkt)_Middle channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
3 659.50	41.61	H	PK	-0.1	41.51	74.00	32.49
3 659.87	37.38	H	AV	-0.1	37.28	54.00	16.72
4 880.40	39.47	H	PK	4.3	43.77	74.00	30.23
4 879.83	34.87	H	AV	4.3	39.17	54.00	14.83
9 759.03	37.96	V	PK	16.5	54.46	74.00	19.54

BLE 1Mbps (255 pkt)_Highest channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
3 720.07	41.96	H	PK	0.1	42.06	74.00	31.94
3 720.43	36.16	H	AV	0.1	36.26	54.00	17.74
4 947.30	39.12	H	PK	4.3	43.42	74.00	30.58
4 959.93	35.06	H	AV	4.4	39.46	54.00	14.54
9 920.03	38.53	V	PK	16.6	55.13	74.00	18.87

BLE 2Mbps (255 pkt) _Lowest channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
3 987.63	47.40	V	PK	1.3	48.70	74.00	25.30
3 985.07	34.84	V	AV	1.3	36.14	54.00	17.86
4 803.77	39.54	V	PK	4.0	43.54	74.00	30.46
4 803.00	32.60	H	AV	4.0	36.60	54.00	17.40
9 605.63	37.92	H	PK	16.0	53.92	74.00	20.08

BLE 2Mbps (255 pkt) _Middle channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
3 996.77	48.53	V	PK	1.2	49.73	74.00	24.27
3 985.97	34.17	V	AV	1.3	35.47	54.00	18.53
4 879.70	39.74	V	PK	4.3	44.04	74.00	29.96
4 880.33	33.17	H	AV	4.3	37.47	54.00	16.53
9 761.10	36.95	H	PK	16.5	53.45	74.00	20.55

BLE 2Mbps (255 pkt) _Highest channel


Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
3 719.83	41.72	H	PK	0.1	41.82	74.00	32.18
3 719.30	36.06	H	AV	0.1	36.16	54.00	17.84
4 960.93	39.73	H	PK	4.4	44.13	74.00	29.87
4 958.63	33.20	H	AV	4.3	37.50	54.00	16.50
9 917.58	37.43	V	PK	16.6	54.03	74.00	19.97

Notes:


- *Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, AV = Average
- **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
- Average measurement was not performed when peak-detected emission complies with the average limit.
- Other spurious was under 20 dB below Fundamental.
- Bluetooth LE 125kbps, Lowest channel (2 402 MHz) was the worst condition.
- The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
- Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
- Average emissions were measured using RBW = 1 MHz, VBW = 10 kHz, Detector = Peak.
- The spectrum was measured from 1 GHz to 10th harmonic and the worst-case emissions were reported.

PLOTS OF EMISSIONS (Worst Case)


BLE 1Mbps (255 pkt), Highest Channel, Full Scan




BLE 1Mbps (255 pkt), Highest Channel, Zoom scan, 4 960 MHz, Peak




BLE 1Mbps (255 pkt), Highest Channel, Zoom scan, 4 960 MHz, Average




BLE 2Mbps (255 pkt), Highest Channel, Full Scan



BLE 2Mbps (255 pkt), Highest Channel, Zoom scan, 4 960 MHz, Peak



BLE 2Mbps (255 pkt), Highest Channel, Zoom scan, 4 960 MHz, Average



7.7 Radiated Band Edge

FCC §15.205, §15.209

Test Mode : Set to Lowest channel and Highest channel

Result

BLE 1Mbps (255 pkt)_Lowest Channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 388.67	53.09	H	PK	-5.1	47.99	74.00	26.01
2 388.67	38.74	H	AV	-5.1	33.64	54.00	20.36
2 389.99	53.04	H	PK	-5.1	47.94	74.00	26.06
2 389.99	39.17	H	AV	-5.1	34.07	54.00	19.93

BLE 1Mbps (255 pkt)_Highest Channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.50	58.53	H	PK	-5.0	53.53	74.00	20.47
2 483.50	47.67	H	AV	-5.0	42.67	54.00	11.33
2 486.49	63.44	H	PK	-5.0	58.44	74.00	15.56
2 486.49	44.69	H	AV	-5.0	39.69	54.00	14.31

BLE 2Mbps (255 pkt)_Lowest Channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 370.61	48.31	H	PK	-5.0	43.31	74.00	30.69
2 370.61	37.13	H	AV	-5.0	32.13	54.00	21.87
2 389.99	52.06	H	PK	-5.1	46.96	74.00	27.04
2 389.99	40.05	H	AV	-5.1	34.95	54.00	19.05

BLE 2Mbps (255 pkt)_Highest Channel


Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.50	67.57	H	PK	-5.0	62.57	74.00	11.43
2 483.50	56.32	H	AV	-5.0	51.32	54.00	2.68
2 484.10	69.08	H	PK	-5.0	64.08	74.00	9.92
2 484.10	50.51	H	AV	-5.0	45.51	54.00	8.49

Notes:


- *Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, AV = Average
- **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
- Other spurious was under 20 dB below Fundamental.
- The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
- Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
- Average emissions were measured using RBW = 1 MHz, VBW = 10 kHz, Detector = Peak.

PLOTS OF EMISSIONS (Worst Case)


BLE 1Mbps (255 pkt), Highest Channel, Peak




BLE 2Mbps (255 pkt), Highest Channel, Average



BLE 2Mbps (255 pkt), Highest Channel, Peak



BLE 2Mbps (255 pkt), Highest Channel, Average



7.8 Radiated Emissions_Below 1GHz

FCC §15.209

Result

BLE 1Mbps (255 pkt), Lowest Channel


Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.59	33.88	V	QP	-9.7	24.20	40.00	15.80
54.30	37.95	V	QP	-5.7	32.29	40.00	7.71
141.98	42.20	V	QP	-10.7	31.46	43.50	12.04
168.01	44.76	H	QP	-9.7	35.08	43.50	8.42
323.80	41.34	H	QP	-3.6	37.72	46.00	8.28
360.02	41.79	H	QP	-3.3	38.51	46.00	7.49

Radiated Measurements at 3meters

Notes:

1. The worst-case emission was reported.
2. *Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, QP = Quasi-Peak
3. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
4. Measurements using CISPR quasi-peak mode below 1 GHz.
5. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
6. No emission found between lowest internal used/generated frequency to 30 MHz (9 kHz~30 MHz).
Per FCC part 15.31(o), test results were not reported.
Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.
7. The limit is on the FCC §15.209.

PLOTS OF EMISSIONS (Worst Case)



7.9 AC Line Conducted

FCC §15.207

Result

BLE 1Mbps (255 pkt), Lowest Channel


Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.214675	48.25	---	62.64	14.40	N	ON	9.8
0.214675	---	38.86	52.64	13.78	N	ON	9.8
0.234575	46.81	---	61.95	15.14	N	ON	9.7
0.234575	---	35.13	51.95	16.81	N	ON	9.7
0.247013	46.45	---	61.54	15.09	L1	ON	9.6
0.247013	---	32.68	51.54	18.86	L1	ON	9.6
0.324125	42.07	---	59.41	17.34	N	ON	9.6
0.324125	---	29.96	49.41	19.44	N	ON	9.6
0.413675	---	25.64	47.49	21.85	L1	ON	9.7
0.413675	42.48	---	57.49	15.01	L1	ON	9.7
0.809188	---	25.09	46.00	20.91	N	ON	9.7
0.809188	39.74	---	56.00	16.26	N	ON	9.7

Notes:

1. Measurement using CISPR quasi-peak mode & average mode.
2. The worst channel was investigated and the worst-case emission are reported. See attached Plots.
3. *) Factor = LISN + Cable loss
4. **) LINE : L = Line, N = Neutral
5. QP = Qusi-Peak CAV = CISPR Average
6. The limit is on the FCC §15.207.

PLOTS OF EMISSIONS (Worst Case)



8. TEST EQUIPMENT

No.	Instrument	Manufacture	Model	Serial No.	Calibration Date	Next Calibration Date
3	Signal & Spectrum Analyzer	R&S	FSW67	101362	2026-03-30	2027-03-30
2	10 dB Attenuator	API technologies corp	40A2W-10	1914	2026-07-01	2027-07-01
3	Signal Generator	R&S	SMB100A	175861	2026-03-27	2027-03-27
4	Vector Signal Generator	R&S	SMBV100A	257152	2025-10-01	2026-10-01
5	Environment Detecor	YOWEXA	YEM-20AL-E	25061007	2026-07-09	2027-07-09
6	DIGITAL MULTIMETER	EZ DIGITAL	DM-334	2111395	2025-10-02	2026-10-02
7	Signal & Spectrum Analyzer	R&S	FSW43	104084	2026-03-26	2027-03-26
8	OPEN SWITCH AND CONTROL UNIT	R&S	OSP120	100081	N/A	N/A
9	Environment Detecor	YOWEXA	YEM-20AL-E	25081030	2025-11-06	2026-11-06
10	SWITCH AND EXTENSION UNIT CAN-BUS	R&S	OSP150	100922	N/A	N/A
11	BROADBAND LOW NOISE AMPLIFIER	EXYNOD	ELNA03-40D	631516	2026-07-02	2027-07-02
12	WiFi Filter Bank	R&S	U083	U083-001	N/A	N/A
13	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-508	2026-07-07	2027-07-07
14	Horn Antenna	Q-par Angus	QMS-00208	17636	2025-08-26	2026-08-26
15	Horn Antenna	Q-par Angus	QSH20S20	8179	2026-07-06	2027-07-06
16	Signal Conditioning Unit	R&S	SCU-18F	180025	2026-03-26	2027-03-26
17	Signal Conditioning Unit	R&S	SCU-26	10011	2026-07-06	2027-07-06
18	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESW44	103318	2026-01-07	2027-01-07
19	Open Switch and Control Unit	ROHDE & SCHWARZ	OSP220	102977	N/A	N/A
20	Humidity Temperature	DRETEC	O-230	NK-B-E-0157	2026-01-19	2027-01-19
21	AMPLIFIER	HP	8447F	2805A03406	2026-01-07	2027-01-07
22	TRILOG Broadband Test Antenna	Schwarzbeck	VULB 9163	01431	2024-11-11	2026-11-11
23	Active Loop Antenna	R&S	HFH2-Z2E	101190	2026-01-15	2027-01-15
24	BIAS UNIT	R&S	IN 600	101621	N/A	N/A
25	EMI TEST RECEIVER	R&S	ESR3	102930	2026-07-02	2027-07-02
26	TWO-LINE V-NETWORK	R&S	ENV216	102829	2026-07-02	2027-07-02
Test Software Version						
No.	Instrument	Manufacture	Model	Version		
1	AC Line Conducted Emissions	R&S	EMC32	11.50.00		
2	Radiated Emissions (Below 1GHz)	R&S	ELEKTRA	5.20.1		
3	Radiated Emissions (Above 1GHz)	R&S	EMC32	10.60.20		

9. ACCURACY OF MEASUREMENT & DECISION RULE

9.1 Uncertainty Calculation

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

PARAMETER	UNCERTAINTY
Radiated Disturbance, Below 30 MHz	4.6 dB
Radiated Disturbance, 30 MHz to 1 GHz	5.6 dB
Radiated Disturbance, 1 GHz to 18 GHz	3.5 dB
Radiated Disturbance, 18 GHz to 26.5 GHz	4.9 dB
AC Line Conducted Emission	1.82 dB

9.2 Decision rule

The choice of whether or not to include the measurement uncertainty of the measuring system used in the test in the conformance determination.:

- ☐ Application of internal procedures used in type testing where traceability of measurement uncertainty is established.
- ☒ Applying the decision that the standard used for type testing does not require it.

END REPORT