




Test Report

Report No. : MTi260603021-0101E2
Date of Issue : 2026-09-22
Applicant : Liquipel Protection, LLC
Product : 3-in-1 Wireles 15W Foldable Charge Station
Model(s) : 827369, PT87369
FCC ID : 2AVV6-827369

Shenzhen Microtest Co., Ltd.

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	5
1.3	Description of support units	6
2	Measurement uncertainty	6
2.1	Test laboratory	7
3	Test facilities and accreditations	8
4	List of test equipment	8
5	Test result	9
5.2	Test setup	10
5.3	Test Procedures	10
5.4	Information of test equipment	11
5.5	Test results	12
	Photographs of the Test Setup	14
	Photographs of the EUT	15

Test Result Certification		
Applicant	Liquipel Protection, LLC	
Applicant Address	19800 MacArthur Blvd. Suite 300, Irvine CA 92612	
Manufacturer	Liquipel Protection, LLC	
Manufacturer Address	19800 MacArthur Blvd. Suite 300, Irvine CA 92612	
Factory	Versogo Tech (shenzhen) Co., Ltd	
Factory Address	1-4F,No.3,Xialing Pai New Industrial Zone,Dalang Community,Dalang Street,Longhua District,Shenzhen	
Product description		
Product name	3-in-1 Wireles 15W Foldable Charge Station	
Trademark	Powertek	
Model name	827369	
Series Model(s)	PT87369	
Standards	FCC CFR 47 PART 1, § 1.1310 FCC CFR 47 Part 2.1091	
Test Method	KDB 680106 D01 Wireless Power Transfer v04	
Testing Information		
Date of test	2026-08-19 to 2026-09-18	
Test result	Pass	
Prepared by:	Yanice Xie	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

1 General Description

1.1 Description of the EUT

Product name:	3-in-1 Wireles 15W Foldable Charge Station
Model name:	827369
Series Model(s):	PT87369
Model difference:	All the models are the same circuit and module, except the model name.
Electrical rating:	Input: DC 9V/3A Qi2 Smartphone Output:5W/7.5W/10W/15W Max Earbuds Output:5W Max Apple Watch Output:2.5W Max
Accessories:	Cable: USB-C to USB-C 0.9m
Hardware version:	USD-212-QI2-V2.0
Software version:	IP6802B_MPP_212_V2_2
Test sample(s) number:	MTi260603021-01-R001
RF specification:	
Operating frequency range:	Coil 1 (Phone): 115-205kHz(5W-10W)&360kHz(15W) Coil 2 (Earbuds): 115-205kHz Coil 3 (Watch): 300-350kHz
Modulation type:	ASK
Antenna type:	Coil

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless output(PHONE(5W)+Earbuds(5W)+Watch(2.5W))
Mode2	Wireless output(PHONE(7.5W)+Earbuds(5W)+Watch(2.5W))
Mode3	Wireless output(PHONE(5W)+Earbuds(5W))
Mode4	Wireless output(PHONE(7.5W)+Earbuds(5W))
Mode5	Wireless output(PHONE(10W)+Earbuds(5W))
Mode6	Wireless output(PHONE(5W)+Watch(2.5W))
Mode7	Wireless output(PHONE(7.5W)+Watch(2.5W))
Mode8	Wireless output(PHONE(10W)+Watch(2.5W))
Mode9	Wireless Output(Earbuds(5W)+Watch(2.5W))
Mode10	Wireless output(PHONE(5W))
Mode11	Wireless output(PHONE(7.5W))
Mode12	Wireless output(PHONE(10W))
Mode13	Wireless output(PHONE(15W))
Mode14	Wireless Output(Earbuds(5W))
Mode15	Wireless Output(Watch(2.5W))
Mode16	Standby
Notes: The maximum output of the three-in-one device is only Wireless output (PHONE: 7.5W + Earbuds: 5W + Watch: 2.5W), The maximum output of the two-in-one device is only Wireless output (PHONE: 10W + Earbuds: 5W)	

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list

Description	Model	Serial No.	Manufacturer
Mobile phone	iPhone 16 pro max	/	Apple
Mobile phone	S9+	/	Samsung
Adapter	PT827369	/	Powertek
Earbuds	Air Pods	MQD83CH/A	Apple
Apple Watch	Apple Watch SE	FH7PP6BAG91J6	Apple

Support cable list

Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 0.7\text{dB}$
Electric field measurements(3kHz~10MHz)	$\pm 1.06\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

3 Test facilities and accreditations**4 List of test equipment**

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+E3D	3101	2025/9/25	2026/9/24

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.8	2.8	/	/

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Test setup

Note: tips mode of the test probe is used for 0cm measurement.

5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+E3D	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

Item	Specification
Test frequency range:	3kHz ~ 10MHz
Probe sensitivity	E-field: 0.08-2000 V/m H-field: 0.1-3200 A/m
Probe level response	E-field: ±1dB H-field: ±1dB
linearity error	E-field: ±0.3dB H-field: ±0.3dB
Isotropy	E-field: ±0.8dB H-field: ±0.6dB

5.5 Test results

Test condition 1: Mode 2 operating mode with client device (1 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	4.23	614	0.69%	0.12	1.63	7.36%
Bottom	1.05			0.04		
Left	1.64			0.05		
Right	1.90			0.06		
Front	1.41			0.04		
Back	0.84			0.03		

Test condition 2: Mode 2 operating mode with client device (50 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	5.29	614	0.86%	0.14	1.63	8.83%
Bottom	1.31			0.06		
Left	2.05			0.06		
Right	2.37			0.08		
Front	1.76			0.05		
Back	1.05			0.03		

Test condition 3: Mode 2 operating mode with client device (99 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	3.44	614	0.56%	0.09	1.63	5.52%
Bottom	0.85			0.04		
Left	1.33			0.04		
Right	1.54			0.05		
Front	1.14			0.03		
Back	0.68			0.02		

Test condition 1: Mode 13 operating mode with client device (1 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	2.01	614	0.33%	0.07	1.63	4.29%
Bottom	0.57			0.02		
Left	0.98			0.03		
Right	1.09			0.03		
Front	0.82			0.02		
Back	0.73			0.01		

Test condition 2: Mode 13 operating mode with client device (50 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	2.51	614	0.41%	0.08	1.63	4.91%
Bottom	0.71			0.02		
Left	1.22			0.04		
Right	1.36			0.04		
Front	1.02			0.03		
Back	0.91			0.01		

Test condition 3: Mode 13 operating mode with client device (99 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	1.63	614	0.27%	0.06	1.63	3.68%
Bottom	0.46			0.01		
Left	0.79			0.03		
Right	0.88			0.03		
Front	0.66			0.02		
Back	0.59			0.01		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****