

承 認 書



SPECIFICATION FOR APPROVAL

客 戶：
CUSTOMER: 惠州市奥嘉达科技有限公司 (Huizhou Aojiada
Technology Co., Ltd.)

客 戶 料 號：
CUST P/N:

料 號：
FINE P/N:

G42.5-6.5UH Single coil 0.08*24P*2-10TS

產 品 型 號：
DESC:

Φ 42.5MMX5.0MMX0.8MM

日 期：
DATE:

2026/6/26

版 本：
Version:

A.0



擬制 PREPARED BY	審核 CHECKED BY	批准 APPROVED BY	客戶承認 CUSTOMER APPROVE
黃燕銘	寧元安	黃錦華	

东莞市西联干城科技有限公司

Dongguan Xilian Gancheng Technology Co., Ltd

工廠地址：东莞市东坑镇骏发路 123 号三甲高新技术产业园 2 栋 8 楼

8th Floor, Building 2, Sanjia High-tech Industrial Park, No. 123 Junfa Road, Dongkeng Town, Dongguan City

TEL: 0769-82989159

FAX: 0769-82989159

E-mail: aming198204@163.com

版本變更履歷


Version Change History

[illegible]

SPECIFICATION

產品型號: DESC	Φ 20.5x39-6.5uH-0.08x24PX2P-30mm	版本 Rev: A.0	客戶 CUST:	XXX
			客戶料号 CUST P/N:	

一、尺寸 DIMENSION:(mm)



A	42.0+0.5
B	39±1
C	30+2
D	3±2
E	1.6±0.2
F	0.8±0.1
G	20.5±0.5


Note

1. Cross out of line;

2. Wrap 8mm(ref) width high-temperature adhesive tape 1-2Ts around the lead-out position;

3. The coil is attached with a circular hard magnetic sheet with grooves. The size of the magnetic sheet is 43.5±0.5mm, the inner hole is 5.0mm, and the thickness is 0.8±0.1mm.

二、原理图 SCHEMATIC DIAGRAM:



三、绕线参数 Winding Specification:

序号 NO.	端子 TERMINAL		线径 WIRE	圈数 Turns	绕线方向 Winding Direction
1	S	F	0.08*24PX2	10Ts	CCW

四、电气特性 ELECTRICAL CHARACTERISTICS:

温度 TEMPERATURE:25±10℃, 湿度 RELATIVE HUMIDITY:65±20%

序号 NO.	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND.	S-F	3.8uH ±20%单独线圈	100KHz/1.0V	LCZ METER 1062B
2	IND.	S-F	6.5uH +10%加磁片	100KHz/1.0V	LCZ METER 1062B
3	DCR	S-F	≤120m Ω	100KHz/1.0V	LCZ METER 502B
4	Q	S-F	≥38	100KHz/1.0V	LCZ METER 502B

擬制/日期 PREPARED BY/DATE	審核/日期 CHECKED BY/DATE
------------------------	-----------------------

黄燕铭 2026/6/26	黄锦华 2026/6/26
---------------	---------------