



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao' an District, Shenzhen, China

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No.....: CTA22061500402

FCC ID.....: 2AVVA-1200M-ZJQ-2

Compiled by
(position+printed name+signature)...: File administrators Kevin Liu

Supervised by
(position+printed name+signature)...: Project Engineer Kevin Liu

Approved by
(position+printed name+signature)...: RF Manager Eric Wang

Date of issue.....: Jun. 22, 2022

Testing Laboratory Name: Shenzhen CTA Testing Technology Co., Ltd.

Address.....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao' an District, Shenzhen, China

Applicant's name: Shenzhen Xiaoyi IOT Technology Co., Ltd

Address: 7/F, Building 4, Haoshida Industrial Zone, Yalian, Bantian, Longgang District, Shenzhen, China

Test specification

Standard: FCC Part 15 Subpart E 15.407

TRF Originator: Shenzhen Global Test Service Co.,Ltd.

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: WiFi Repeater

Trade Mark: 小艺 (xiao yi)

Manufacturer: Shenzhen Xiaoyi IOT Technology Co., Ltd

Model/Type reference.....: 1200M-ZJQ-2

Listed Models: N/A

Modulation: OFDM

Frequency.....: From 5180MHz-5240MHz, 5745MHz-5825MHz

Ratings: AC 120V 60Hz

Result.....: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TEST REPORT

Equipment under Test : WiFi Repeater

Model /Type : 1200M-ZJQ-2

Serial Models : N/A

Applicant : Shenzhen Xiaoyi IOT Technology Co., Ltd

Address : 7/F, Building 4, Haoshida Industrial Zone, Yalian, Bantian,
LonggangDistrict, Shenzhen, China

Manufacturer : Shenzhen Xiaoyi IOT Technology Co., Ltd

Address : 7/F, Building 4, Haoshida Industrial Zone, Yalian, Bantian,
LonggangDistrict, Shenzhen, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1	TEST STANDARDS	4
2	SUMMARY	5
2.1	General Remarks	5
2.2	Product Description	5
2.3	Equipment Under Test	5
2.4	Short description of the Equipment under Test (EUT)	5
2.5	EUT operation mode	6
2.6	Block Diagram of Test Setup	6
2.7	Related Submittal(s) / Grant (s)	6
2.8	Modifications	6
3	TEST ENVIRONMENT	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Environmental conditions	7
3.4	Test Description	8
3.5	Statement of the measurement uncertainty	8
3.6	Equipments Used during the Test	9
4	TEST CONDITIONS AND RESULTS.....	10
4.1	AC Power Conducted Emission	10
4.2	Radiated Emissions	13
4.3	Maximum Conducted Average Output Power	40
4.4	Power Spectral Density	44
4.5	Emission Bandwidth (26dB Bandwidth)	58
4.6	Minimum Emission Bandwidth (6dB Bandwidth)	66
4.7	Frequency Stability	74
5	TEST SETUP PHOTOS OF THE EUT	76
6	PHOTOS OF THE EUT	77

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v01r02

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Jun. 01, 2022
Testing commenced on	:	Jun. 01, 2022
Testing concluded on	:	Jun. 22, 2022

2.2 Product Description

Product Description:	WiFi Repeater			
Model:	1200M-ZJQ-2			
Power supply:	AC 120V 60Hz			
testing sample ID:	CTA220615004-1# (Engineer sample), CTA220615004-2# (Normal sample)			
Hardware version:	V1.0			
Software version:	V1.0			
WIFI				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n 802.11ac	802.11n 802.11ac	802.11ac	N/A
Operation frequency:	5180MHz-5240MHz 5745MHz-5825MHz	5190MHz-5230MHz 5755MHz-5795MHz	5210MHz 5775MHz	N/A
Modulation:	OFDM	OFDM	OFDM	N/A
Channel number:	9	4	2	N/A
Channel separation:	20MHz	40MHz	80MHz	N/A
Antenna type:	External antenna			
Antenna gain:	0.00 dBi for Ant 0 and Ant 1			

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☒ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☐ Other (specified in blank below)	

/

2.4 Short description of the Equipment under Test (EUT)

This is a WiFi Repeater.

For more details, refer to the user's manual of the EUT.

2.5 EUT operation mode


The Applicant provides communication tools software (AT command) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.
All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz		40MHz		80MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190	42	5210
	40	5200				
	44	5220	46	5230		
	48	5240				
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755	155	5775
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825	--	--	--	--

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	25 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	25 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

AC Power Conducted Emission

Temperature:	24 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS ^{Note1}
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	PASS ^{Note2}
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.407(h)	Dynamic Frequency Selection	N/A ^{Note 3}
FCC Part 15.203/15.247(b)	Antenna Requirement	PASS

Note 1: Apply to U-NII 1 band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	6 Mbps
	11n(20MHz),11ac(20MHz)/OFDM	7.2 Mbps
	11n(40MHz),11ac(40MHz)/OFDM	15.0Mbps
	11ac(80MHz)/OFDM	65.0Mbps

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen CTA Testing Technology Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd.:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	CTA-308	2021/08/06	2022/08/05
LISN	R&S	ENV216	CTA-314	2021/08/06	2022/08/05
EMI Test Receiver	R&S	ESPI	CTA-307	2021/08/06	2022/08/05
EMI Test Receiver	R&S	ESCI	CTA-306	2021/08/06	2022/08/05
Spectrum Analyzer	Agilent	N9020A	CTA-301	2021/08/06	2022/08/05
Spectrum Analyzer	R&S	FSP	CTA-337	2021/08/06	2022/08/05
Vector Signal generator	Agilent	N5182A	CTA-305	2021/08/06	2022/08/05
Analog Signal Generator	R&S	SML03	CTA-304	2021/08/06	2022/08/05
Universal Radio Communication	CMW500	R&S	CTA-302	2021/08/06	2022/08/05
Temperature and humidity meter	Chigo	ZG-7020	CTA-326	2021/08/06	2022/08/05
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	CTA-310	2021/08/07	2022/08/06
Horn Antenna	Schwarzbeck	BBHA 9120D	CTA-309	2021/08/07	2022/08/06
Loop Antenna	Zhinan	ZN30900C	CTA-311	2021/08/07	2022/08/06
Horn Antenna	Beijing Hangwei Dayang	OBH100400	CTA-336	2021/08/06	2022/08/05
Amplifier	Schwarzbeck	BBV 9745	CTA-312	2021/08/06	2022/08/05
Amplifier	Taiwan chengyi	EMC051845B	CTA-313	2021/08/06	2022/08/05
Directional coupler	NARDA	4226-10	CTA-303	2021/08/06	2022/08/05
High-Pass Filter	XingBo	XBLBQ-GTA18	CTA-402	2021/08/06	2022/08/05
High-Pass Filter	XingBo	XBLBQ-GTA27	CTA-403	2021/08/06	2022/08/05
Automated filter bank	Tonscend	JS0806-F	CTA-404	2021/08/06	2022/08/05
Power Sensor	Agilent	U2021XA	CTA-405	2021/08/06	2022/08/05
Amplifier	Schwarzbeck	BBV9719	CTA-406	2021/08/06	2022/08/05

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. All modes of 802.11a/n were tested at Low, Middle, and High channel; only the worst result of 802.11a CH36 was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Power supply: AC 120V/60Hz Polarization L


**Final Data List**

NO.	Freq. [MHz]	Factor [dB]	QP Reading [dB μV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1598	10.50	29.41	39.91	65.47	25.56	18.89	29.39	55.47	26.08	PASS
2	0.6181	10.50	23.79	34.29	56.00	21.71	15.23	25.73	46.00	20.27	PASS
3	1.6219	10.50	18.22	28.72	56.00	27.28	11.25	21.75	46.00	24.25	PASS
4	4.8721	10.50	10.88	21.38	56.00	34.62	2.43	12.93	46.00	33.07	PASS
5	10.7587	10.50	9.96	20.46	60.00	39.54	2.79	13.29	50.00	36.71	PASS
6	21.9316	10.50	17.76	28.26	60.00	31.74	11.01	21.51	50.00	28.49	PASS

Note:1). Value (dBμV)= Reading (dBμV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBμV) - Value (dBμV)



4.2 Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) Note1
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

- Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak


TEST RESULTS

Remark:

- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for below 1GHz test, only the worst case 802.11a low channel of U-NII 1 band was recorded.
- All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz

Horizontal




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	40.9125	29.23	12.21	-17.02	40.00	27.79	100	148	Horizontal
2	58.4938	27.89	10.00	-17.89	40.00	30.00	100	18	Horizontal
3	149.916	43.49	21.73	-21.76	43.50	21.77	100	100	Horizontal
4	249.947	47.43	29.45	-17.98	46.00	16.55	100	221	Horizontal
5	349.978	40.14	24.09	-16.05	46.00	21.91	100	92	Horizontal
6	583.991	52.36	39.68	-12.68	46.00	6.32	100	360	Horizontal

Note:1). Level (dBμV/m) = Reading (dBμV) + Factor (dB/m)

2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin (dB) = Limit (dBμV/m) - Level (dBμV/m)



For 1GHz to 40GHz

Note: All 802.11a / 802.11n/ac (HT20) /802.11n/ac (HT40)/ 802.11ac (HT80) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.

U-NII 1 & 802.11a Mode (above 1GHz)

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00 (5180MHz)	5150.00	56.44	PK	H	68.20	11.76	59.87	33.04	5.45	41.92	-3.43
	5150.00	47.67	AV	H	54.00	6.33	51.10	33.04	5.45	41.92	-3.43
	10360.00	51.34	PK	H	68.20	16.86	38.83	38.83	10.12	45.28	3.67
	--	--	--	--	--	--	--	--	--	--	--
40.00 (5200MHz)	10400.00	51.67	PK	H	68.20	16.53	47.99	38.85	10.13	45.3	3.68
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5240MHz)	5350.50	47.69	PK	H	68.20	20.51	50.96	32.84	5.97	42.08	-3.27
	10480.00	51.36	PK	H	68.20	16.84	47.62	38.89	10.19	45.34	3.74
	--	--	--	--	--	--	--	--	--	--	--

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00 (5180MHz)	5150.00	54.87	PK	V	68.20	13.33	58.30	33.04	5.45	41.92	-3.43
	5150.00	47.67	AV	V	54.00	6.33	51.10	33.04	5.45	41.92	-3.43
	10360.00	51.77	PK	V	68.20	16.43	48.10	38.83	10.12	45.28	3.67
	--	--	--	--	--	--	--	--	--	--	--
40.00 (5200MHz)	10400.00	51.45	PK	V	68.20	16.75	47.77	38.85	10.13	45.3	3.68
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5240MHz)	5350.50	51.45	PK	V	68.20	16.75	54.72	32.84	5.97	42.08	-3.27
	10480.00	51.59	PK	V	68.20	16.61	47.85	38.89	10.19	45.34	3.74
	--	--	--	--	--	--	--	--	--	--	--

U-NII 3 & 802.11a Mode (above 1GHz)

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
	5720.00	55.67	PK	H	68.20	12.53	58.45	33.42	6.04	42.24	-2.78
149.00 (5745MHz)	5720.00	47.89	AV	H	54.00	6.11	50.67	33.42	6.04	42.24	-2.78
	11490.00	50.12	PK	H	68.20	18.08	45.64	39.02	10.91	45.45	4.48
	--	--	--	--	--	--	--	--	--	--	--
157.00 (5785MHz)	11570.00	51.56	PK	H	68.20	16.64	47.11	38.93	10.95	45.43	4.45
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5825MHz)	5855.00	51.92	PK	H	68.20	16.28	54.11	33.91	6.17	42.27	-2.19
	11650.00	64.00	PK	H	68.20	4.20	59.42	38.83	11.16	45.41	4.58
	--	--	--	--	--	--	--	--	--	--	--

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
	5720.00	56.45	PK	V	68.20	11.75	59.23	33.42	6.04	42.24	-2.78
149.00 (5745MHz)	5720.00	47.48	AV	V	54.00	6.52	50.26	33.42	6.04	42.24	-2.78
	11490.00	49.34	PK	V	68.20	18.86	44.86	39.02	10.91	45.45	4.48
	--	--	--	--	--	--	--	--	--	--	--
157.00 (5785MHz)	11570.00	51.63	PK	V	68.20	16.57	47.18	38.93	10.95	45.43	4.45
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5825MHz)	5855.00	51.34	PK	V	68.20	16.86	53.53	33.91	6.17	42.27	-2.19
	11650.00	52.49	PK	V	68.20	15.71	47.91	38.83	11.16	45.41	4.58
	--	--	--	--	--	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

4.3 Band edge measurements

4.3.1 Test Result B1/2/3 for antenna 1


TestMode	Antenna	ChName	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
11A	Ant1	Low	5180	-39.49	≤-27	PASS
		High	5240	-40.5	≤-27	PASS
11N20SISO	Ant1	Low	5180	-39.28	≤-27	PASS
		High	5240	-40.67	≤-27	PASS
11N40SISO	Ant1	Low	5190	-37.96	≤-27	PASS
		High	5230	-41.4	≤-27	PASS
11AC20SISO	Ant1	Low	5180	-39.22	≤-27	PASS
		High	5240	-40.72	≤-27	PASS
11AC40SISO	Ant1	Low	5190	-39.75	≤-27	PASS
		High	5230	-41.13	≤-27	PASS
11AC80SISO	Ant1	Low	5210	-40.06	≤-27	PASS
		High	5210	-40.87	≤-27	PASS


4.3.2 Test Result B4


TestMode	Antenna	ChName	Frequency[MHz]	FreqRange [MHz]	Result [dBm]	Limit [dBm]	Verdict
11A	Ant1	Low	5745	5650~5700	-41.01	≤-21.17	PASS
				5700~5720	-41.35	≤12.44	PASS
				5720~5725	-41.47	≤26.83	PASS
				5760~5650	-41.77	≤-27	PASS
		High	5825	5850~5855	-40.74	≤23.18	PASS
				5855~5875	-39.89	≤13.46	PASS
				5875~5925	-39.96	≤0.82	PASS
				5925~5935	-39.2	≤-27	PASS
11N20SISO	Ant1	Low	5745	5650~5700	-40.26	≤-8.74	PASS
				5700~5720	-40.94	≤15.11	PASS
				5720~5725	-40.69	≤19.75	PASS
				5760~5650	-41.23	≤-27	PASS
		High	5825	5850~5855	-40.48	≤24.10	PASS
				5855~5875	-39.78	≤10.93	PASS
				5875~5925	-38.8	≤-21.56	PASS
				5925~5935	-37.63	≤-27	PASS
11N40SISO	Ant1	Low	5755	5650~5700	-41.29	≤-5.23	PASS
				5700~5720	-40.93	≤13.54	PASS
				5720~5725	-41.51	≤20.35	PASS
				5780~5650	-42.34	≤-27	PASS
		High	5795	5850~5855	-40.48	≤20.55	PASS
				5855~5875	-40.23	≤14.34	PASS
				5875~5925	-39.33	≤-6.65	PASS
				5925~5935	-40.31	≤-27	PASS
11AC20SISO	Ant1	Low	5745	5650~5700	-40.79	≤-19.30	PASS
				5700~5720	-40.66	≤13.95	PASS
				5720~5725	-40.49	≤23.94	PASS
				5760~5650	-40.67	≤-27	PASS
		High	5825	5850~5855	-41.22	≤25.34	PASS
				5855~5875	-38.77	≤14.56	PASS
				5875~5925	-38.75	≤-26.66	PASS
				5925~5935	-40.01	≤-27	PASS
11AC40SISO	Ant1	Low	5755	5650~5700	-41.22	≤-9.32	PASS
				5700~5720	-40.69	≤10.02	PASS
				5720~5725	-41.18	≤26.82	PASS
				5780~5650	-41.91	≤-27	PASS
		High	5795	5850~5855	-40.58	≤17.16	PASS
				5855~5875	-40	≤11.61	PASS
				5875~5925	-40.48	≤-3.48	PASS
				5925~5935	-40.98	≤-27	PASS
11AC80SISO	Ant1	Low	5775	5650~5700	-40.58	≤-9.82	PASS
				5700~5720	-40.92	≤10.40	PASS
				5720~5725	-41.01	≤21.30	PASS
				5800~5650	-39.96	≤-27	PASS


		High	5775	5850~5855	-41.05	≤15.79	PASS
				5855~5875	-40.16	≤11.52	PASS
				5875~5925	-40.23	≤-0.12	PASS
				5925~5935	-40.4	≤-27	PASS

4.3.3 Test Graphs B1/2/3













4.3.4 Test Graphs B4









4.3.5 Test Result B1/2/3 for antenna2

TestMode	Antenna	ChName	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
11A	Ant2	Low	5180	-39.77	≤-27	PASS
		High	5240	-41.03	≤-27	PASS
11N20SISO	Ant2	Low	5180	-38.72	≤-27	PASS
		High	5240	-40.51	≤-27	PASS
11N40SISO	Ant2	Low	5190	-39.48	≤-27	PASS
		High	5230	-40.51	≤-27	PASS
11AC20SISO	Ant2	Low	5180	-39.69	≤-27	PASS
		High	5240	-41.43	≤-27	PASS
11AC40SISO	Ant2	Low	5190	-39.29	≤-27	PASS
		High	5230	-41.16	≤-27	PASS
11AC80SISO	Ant2	Low	5210	-39.55	≤-27	PASS
		High	5210	-41.08	≤-27	PASS

4.3.6 Test Result B4

TestMode	Antenna	ChName	Frequency[MHz]	FreqRange [MHz]	Result [dBm]	Limit [dBm]	Verdict
11A	Ant2	Low	5745	5650~5700	-41.52	≤-26.27	PASS
				5700~5720	-40.71	≤14.69	PASS
				5720~5725	-41.8	≤23.68	PASS
				5760~5650	-40.48	≤-27	PASS
		High	5825	5850~5855	-39.32	≤21.03	PASS
				5855~5875	-39.35	≤11.65	PASS
				5875~5925	-39.32	≤-10.97	PASS
				5925~5935	-41.41	≤-27	PASS
11N20SISO	Ant2	Low	5745	5650~5700	-40.75	≤-7.98	PASS
				5700~5720	-41.03	≤11.34	PASS
				5720~5725	-41.25	≤16.60	PASS
				5760~5650	-42.38	≤-27	PASS
		High	5825	5850~5855	-40.52	≤19.80	PASS
				5855~5875	-39.45	≤14.90	PASS
				5875~5925	-39.83	≤-10.67	PASS
				5925~5935	-40.01	≤-27	PASS
11N40SISO	Ant2	Low	5755	5650~5700	-40.69	≤-5.03	PASS
				5700~5720	-40.28	≤12.67	PASS
				5720~5725	-40.53	≤24.66	PASS
				5780~5650	-41.47	≤-27	PASS
		High	5795	5850~5855	-41.23	≤24.31	PASS
				5855~5875	-39.63	≤12.12	PASS
				5875~5925	-40.31	≤-7.87	PASS
				5925~5935	-40.91	≤-27	PASS
11AC20SISO	Ant2	Low	5745	5650~5700	-40.67	≤-15.38	PASS
				5700~5720	-40.87	≤12.41	PASS
				5720~5725	-41.39	≤25.26	PASS
				5760~5650	-41.29	≤-27	PASS
		High	5825	5850~5855	-41.42	≤15.79	PASS
				5855~5875	-39.92	≤10.10	PASS
				5875~5925	-39.97	≤1.42	PASS
				5925~5935	-40.29	≤-27	PASS
11AC40SISO	Ant2	Low	5755	5650~5700	-40.86	≤-26.00	PASS
				5700~5720	-41.28	≤14.90	PASS
				5720~5725	-40.58	≤26.20	PASS
				5780~5650	-42.01	≤-27	PASS
		High	5795	5850~5855	-41.36	≤17.91	PASS
				5855~5875	-40.22	≤11.84	PASS
				5875~5925	-39.59	≤-13.86	PASS
				5925~5935	-39.89	≤-27	PASS
11AC80SISO	Ant2	Low	5775	5650~5700	-40.52	≤8.87	PASS
				5700~5720	-40.68	≤10.57	PASS
				5720~5725	-40.88	≤21.30	PASS
				5800~5650	-40.6	≤-27	PASS
		High	5775	5850~5855	-40.93	≤22.12	PASS

				5855~5875	-40.22	≤14.63	PASS
				5875~5925	-39.95	≤-26.13	PASS
				5925~5935	-39.97	≤-27	PASS