



Pod 2.3 Specification

Product: Pod 2.3

Model: 22-134

File Number: 20220503001

Date: May. 3, 2022

Pod 2.3 Specification

Version 2.21

Version History

Version #	Author	Revision Date	Approval	Approval Date	Reason
2.21	Carolyn Bi	05/03/2022	Chen Wei	05/03/2022	



Pod 2.3 Specification

Product: Pod 2.3

Model: 22-134

File Number: 20220503001

Date: May. 3, 2022

Table of Contents

1. Product Description	Page 3
2. Scope	Page 3
3. Materials	Page 3
4. Part Numbers	Page 3
5. Pod Electronics Characteristics	Page 3
6. Battery Specification & Features	Page 4
7. WiFi Specification	Page 4
8. Pod Operation & Features	Page 4
9. LED Functions	Page 5



Pod 2.3 Specification

Product: Pod 2.3

File Number: 20220503001

Model: 22-134

Date: May. 3, 2022

1. Product Description

- 1.1 This product can collect and store human motion and posture, positioning information and environmental data.
- 1.2 Pod electronics include: 6-Axis Motion Tracking IMU, 3D magnetometer, barometric pressure / humidity and temperature sensors, WiFi 5G/2.4G & BLE 5.0 combo module, Flash memory, high stability and low power consumption RTC chip that can work for up to 3 months when the battery is out of power.
- 1.3 Pod contains 2 lithium rechargeable batteries.
- 1.4 Pod can connect to AWS IoT to upload data.
- 1.5 RGB LED displays different work states.
- 1.6 Pod supports OTA firmware.

2. Scope

This document contains general requirements for the electrical and mechanical elements.

3. Materials

- 3.1 Pod housing: 65% ABS+35% PC (black)

4. Part Numbers

Pod V2.3	22-134
----------	--------

5. Pod Electronics Characteristics

Working Voltage	Max 5V $\pm$ 5%
Working Current	Avg. 13mA
WIFI Channel Frequency	2.4G & 5.0G
Power off Current	<20 μ A
Charging Current	80mA
Battery Charging Time	<2.5 hours
Battery Life (continuous working time)	10 hours
Temperature Accuracy	$\pm$ 1°C
Humidity Accuracy	3%
Pressure Accuracy	$\pm$ 1.5pa/k
Gyroscope Specifications	$\pm$ 2000°/s, 1% sensitivity
Accelerometer Specifications	$\pm$ 16g, 1% Sensitivity



Pod 2.3 Specification

Product: Pod 2.3

File Number: 20220503001

Model: 22-134

Date: May. 3, 2022

Magnetic Sensor Specifications	±1000uT dynamic range, <0.1%FS Ultra -low hysteresis
ESD Protect	5kv
WiFi Communication Distance	>15m
Working Temperature	-20°C ~ 60°C

6. Battery Specifications & Features

Mechanical Form Factor	30 x 21 x 3mm
Battery Type	Lithium polymer rechargeable battery
Battery Capacity	3.7V DC, 150mAh
Protection	Over current and short
Working Environment	-20°C ~ 60°C

Mechanical Form Factor	Φ4.8 x 2.5mm
Battery Type	Lithium rechargeable battery
Battery Capacity	3V, 2.3mAh

7. WiFi Specification

7.1 Work Frequency: 2412 - 2462MHz & 5180 - 5850MHz

7.2 Transmit Power: 13 dBm transmit output power

7.3 Supported Data Rates: 6, 9, 12, 18, 24, 36, 48, 54Mbps

7.4 Working Temperature: -20°C ~ 60°C

7.5 Storage Temperature: -40°C ~ 85°C

7.6 Receive Current: 20mA (with ideal DC-DC converter)

7.7 Transmit Current: 230mA peak current in TX (13dBm)

8. Pod Operation & Features

8.1 POWER OFF State

8.1.1 The Pod default state is POWER OFF. Under this state, all the peripherals and functions for the system micro power consumption are closed.

8.1.2 Under NORMAL State, press and hold the button for 12s to power it off.

8.2 NORMAL State

8.2.1 From POWER OFF State, press and hold the button for 3s to enter into NORMAL State.



Pod 2.3 Specification

Product: Pod 2.3

File Number: 20220503001

Model: 22-134

Date: May. 3, 2022

8.2.2 Once powered on, the Pod automatically collects motion posture and environmental data, and stores them in Flash.

8.2.3 Wi-Fi hotspot device (MiFi) with WPA-2 personal network broadcast. The credentials must be defined as follows:

SSID: modjoul1 PW: BW489A600365

The broadcast SSID should NOT be a hidden network.

8.2.4 When the Pod is plugged into the Charger, the Pod will automatically connect to AWS IoT core and update data.

8.3 CHARGING State

8.3.1 The Pod will enter into CHARGING State when it is plugged into Docking Station that is connected to a Power Supply.

8.3.2 In CHARGING State, the Pod can upload data via WiFi.

8.4 ERASE DATA State

8.4.1 In NORMAL State or CHARGING State, press and hold the button for 6s and then release the button, then press the button for 3 times to start erase data.

8.5 HW RESET

8.5.1 When MCU hang-up, press and hold the button for 16s to reset the system.

9. LED Functions

Pod System State	LED Status
Power Off	Off
Normal	Blue LED on
Send Data	Green LED on
Send Data Completed	White LED on
Charging	Purple LED on
Erase Data	LED turns Red --> Green --> Red --> Blue --> Purple in order
Warning (Low Battery <10%)	Red LED on
HW Reset	Off



Pod 2.3 Specification

Product: Pod 2.3

File Number: 20220503001

Model: 22-134

Date: May. 3, 2022

FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Specific absorption rate (SAR):

This Pod meets the government's requirements for exposure to radio waves. The guidelines are based on standards developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a margin of safety designed to ensure the safety of all people regardless of their age or health.

The FCC Statement of Exposure to RF and the SAR limit for the United States (FCC) is 1.6 W/kg average for each gram of tissue. This device was tested for typical operations of use on the body, with the back of the tablet at 0mm from the body. To maintain compliance with FCC RF exposure requirements, use accessories that maintain a distance of 0mm between the user's body and the back of the tablet. The use of belt clips, covers and similar accessories must not contain metallic components in their assembly. The use of accessories that do not meet these requirements may not meet FCC RF exposure requirements and should be avoided.

Functioning in the body

This device was tested for typical operations of use in the body. To comply with RF exposure requirements, a minimum separation distance of 0mm must be maintained between the user's body and the telephone, including the antenna. Third-party accessories such as belt clips, covers and similar accessories used with this device should not contain metallic components, accessories that do not meet these RF exposure requirements and should be avoided from use on the body. Use only the supplied antenna or an approved antenna.

The maximum results of Specific Absorption Rate (SAR) found during testing for 22-134 are 0.531W/kg