

TEST REPORT

of

FCC Part 15 Subpart C

Product: **IPQ4019 SOM module**
Brand: **EMBUX**
Main Model: **SOM4019**
Series Model: **N/A**
Model Difference: **N/A**
FCC ID: **2AVW3-SOM4019**
FCC Rule Part: **§15.247, Cat: DTS**
Reference: **ANSI C63.10: 2013**
KDB 558074 D01 v05r02
Applicant: **EMBUX Technology Co. Ltd.**
Address: **13F, No. 920, Chung-Cheng Rd. Zhonghe Dist., New Taipei City 23586 Taiwan**

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: **ISL-23LR0098FCDTS**

Issue Date : **September 01, 2023**



FCC Registration Number: 487532

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. The uncertainty of the measurement does not include in consideration of the test result unless the customer required the determination of uncertainty via the agreement, regulation or standard document specification. This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

VERIFICATION OF COMPLIANCE

Applicant: EMBUX Technology Co. Ltd.
Equipment Under Test: IPQ4019 SOM module
Brand: EMBUX
Main Model: SOM4019
Series Model: N/A
Model Difference: N/A
FCC ID: 2AVW3-SOM4019
Date of Test: August 2, 2023 ~ August 31, 2023
Date of EUT Received: August 2, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC Part 15.247	Complied

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:

Kevin Yao

Date:

September 01, 2023

Kevin Yao / Senior Engineer

Prepared By:

Gigi Yeh

Date:

September 01, 2023

Gigi Yeh / Senior Engineer

Approved By:

Jerry Liu

Date:

September 01, 2023

Jerry Liu / Manager

Version

Version No.	Date	Description
00	September 01, 2023	Initial creation of document

TABLE OF CONTENTS

1. General.....	6
1.1 DESCRIPTION OF EUT	6
1.2 SPECIAL ACCESSORIES	7
1.3 EQUIPMENT MODIFICATIONS	7
2. System Test Configuration.....	8
2.1 EUT CONFIGURATION.....	8
2.2 EUT EXERCISE	8
2.3 TEST PROCEDURE.....	8
2.4 CONFIGURATION OF TESTED SYSTEM.....	8
2.5 DUTY FACTOR	9
3. Summary of Test Results.....	12
4. Description of Test Modes.....	12
5. AC Line Conduced Emission Test.....	13
5.1 STANDARD APPLICABLE	13
5.2 MEASUREMENT PROCEDURE.....	13
5.3 MEASUREMENT RESULT.....	14
6. Peak Output Power Measurement	16
6.1 STANDARD APPLICABLE	16
6.2 MEASUREMENT PROCEDURE.....	16
6.3 MEASUREMENT RESULT.....	17
7. Radiated Spurious Emission Test.....	18
7.1 STANDARD APPLICABLE	18
7.2 MEASUREMENT PROCEDURE.....	18
7.3 FIELD STRENGTH CALCULATION	19
7.4 MEASUREMENT RESULT.....	20
8. 100kHz Bandwidth of Band Edges Measurement	68
8.1 STANDARD APPLICABLE	68
8.2 MEASUREMENT PROCEDURE.....	68
8.3 FIELD STRENGTH CALCULATION	68
8.4 MEASUREMENT RESULT.....	69
9. 6dB Bandwidth.....	93
9.1 STANDARD APPLICABLE	93
9.2 MEASUREMENT PROCEDURE.....	93
9.3 MEASUREMENT RESULT.....	93
10. Peak Power Spectral Density	100
10.1 STANDARD APPLICABLE	100
10.2 MEASUREMENT PROCEDURE.....	100
10.3 MEASUREMENT RESULT.....	100
11. Appendix.....	113
11.1 APPENDIX A: EQUIPMENT LIST	113
11.2 APPENDIX B: UNCERTAINTY OF MEASUREMENT.....	115

11.3	APPENDIX C: TEST SETUP	116
11.4	APPENDIX D: PHOTOGRAPHS OF SETUP	119
11.5	APPENDIX E: PHOTOGRAPHS OF EUT	124

1. General

1.1 Description of EUT

General Information		
Product Name:	IPQ4019 SOM module	
Brand Name:	EMBUX	
Model Name:	SOM4019	
Model Difference:	N/A	
Temperature Range	-40°C to +75°C	
Power Supply:	12Vdc For Adapter	Model: ATS018T-W120U; Supplier: I.T.E
WiFi Information		
WLAN Modular	IPQ4019	
Frequency Range:	WLAN 2.4GHz Band 802.11b/g : 2412MHz~2462MHz 802.11n(HT20) : 2412MHz~2462MHz 802.11n(HT40) : 2422MHz~2452MHz	
Max Output Power:	2412MHz ~ 2462MHz : 24.73dBm(PK)	
Channel number:	WLAN 2.4GHz Band 802.11b/g : 11 802.11n(HT20) : 11 802.11n(HT40) : 9	
Product HW Version:	Ver. A	
Product SW Version:	N/A	
Product FW Version:	Ver 1.0.9	
Test SW Version:	V5.0.0-00188	
Worst Case:	WLAN 2.4G: 802.11n HT20	

	Antenna Type	Brand	Model	Peak Gain	Frequency Range	Connector Type
1	Dipole Antenna	ARISTOTLE	RFA-25-T42-U-M70	2.6dBi 5dBi	2400-2500 MHz 5150-5875 MHz	SMA

According to KDB 662911 D01 MU-MIMO signals could be considered completely uncorrelated for purposes of directional gain computation in case.

Directional gain = G_{ANT}

1.2 Special Accessories

Not available for this EUT intended for grant.

1.3 Equipment Modifications

Not available for this EUT intended for grant.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 AC Line Conducted Emissions


The EUT is placed on a turn table which is 0.8 m above ground plane. According to ANSI C63.10 and RSS-Gen. AC Line Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m/1.5m (Frequency above 1GHz) above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to ANSI C63.10.

2.4 Configuration of Tested System

Configuration of Tested System (Fixed channel)



Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	Notebook	HP	Probook	N/A	150cm	100cm
2	Adapter	I.T.E	ATS018T-W120U	N/A	N/A	100cm

2.5 Duty factor

Mode	ON time (ms)	Total time (ms)	Duty Cycle	Duty Factor	1/Ton	VBW (kHz)
b	12.21	12.3	99.268%	0	0.0819	0.01
g	1.68	1.77	94.894%	0.228	0.595	1
HT20	1.68	1.77	94.894%	0.228	0.595	1
HT40	0.825	0.915	90.164%	0.45	1.212	2


If duty cycle of test signal is $\geq 98\%$, duty factor is not required.

If duty cycle of test signal is $< 98\%$, duty factor shall be considered.


The output power = measured power + duty factor

For frequency above 1GHz, the video bandwidth setting for average detector: $VBW \geq 1/Ton$


Test Data: b mode Duty




Test Data: g mode Duty



Test Data: 2.4G HT20 mode Duty



Test Data: 2.4G HT40 mode Duty



3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207(a)	AC Power Line Conducted Emission	Compliant
§15.247(b) (3), (4)	Peak Output Power/ EIRP	Compliant
§15.247(a)(2)	6dB & 99% Power Bandwidth	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edges	Compliant
§15.247(d)	Spurious Emission	Compliant
§15.247(e)	Peak Power Density	Compliant
§15.203	Antenna Requirement	Compliant

4. Description of Test Modes

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

802.11 b mode: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 1Mbps lowest data rate are chosen for full testing.

802.11 g mode: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6Mbps lowest data rate are chosen for full testing.

802.11 n HT20: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

802.11 n HT40: Channel low (2422MHz), mid (2437MHz), high (2452MHz) with 13.5Mbps lowest data rate are chosen for full testing.

5. AC Line Conducted Emission Test

5.1 Standard Applicable

According to §15.207, frequency range within 150kHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note


- 1.The lower limit shall apply at the transition frequencies
- 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.2 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.
4. Both 120V & 240V have been verified, and 120V/60Hz was defined as the worst-case and record in the report.

5.3 Measurement Result

AC POWER LINE CONDUCTED EMISSION TEST DATA



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.152	38.84	19.56	9.64	48.48	65.88	-17.40	29.20	55.88	-26.68
2	0.164	35.89	14.58	9.64	45.53	65.28	-19.75	24.22	55.28	-31.06
3	0.452	20.72	14.77	9.65	30.37	56.85	-26.48	24.42	46.85	-22.43
4*	0.562	32.29	25.44	9.65	41.94	56.00	-14.06	35.09	46.00	-10.91
5	0.987	19.19	13.10	9.68	28.87	56.00	-27.13	22.78	46.00	-23.22
6	1.372	18.98	12.37	9.69	28.67	56.00	-27.33	22.06	46.00	-23.94



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638868


Conducted Emission Measurement

Date: 2023/8/28

operator: Jeff Chou

Temperature: 24 °C

Humidity: 62 %



Site: Conduction 02

Phase: **N**

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.152	38.81	20.98	9.63	48.44	65.88	-17.44	30.61	55.88	-25.27
2	0.164	35.91	16.20	9.63	45.54	65.28	-19.74	25.83	55.28	-29.45
3	0.224	31.90	19.86	9.64	41.54	62.66	-21.12	29.50	52.66	-23.16
4	0.449	22.90	17.16	9.65	32.55	56.89	-24.34	26.81	46.89	-20.08
5*	0.562	33.74	26.89	9.65	43.39	56.00	-12.61	36.54	46.00	-9.46
6	0.987	18.86	12.80	9.68	28.54	56.00	-27.46	22.48	46.00	-23.52

6. Peak Output Power Measurement

6.1 Standard Applicable

According to §15.247

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

6.2 Measurement Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum analyzer with proper instrument's parameters.
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.3 Measurement Result

Mode	Freq. (MHz)	Output Power (dBm)		Duty Factor (dB)	Total Output Power (dBm)	Output Power Limit (dBm)	Total Output Power (W)	Output Power Limit (W)
		Chain 0	Chain 1					
802.11b	2412	18.210	17.430	0.00	20.85	30.00	0.12	1.00
	2437	18.440	16.990	0.00	20.79	30.00	0.12	1.00
	2462	18.150	17.140	0.00	20.68	30.00	0.12	1.00
802.11g	2412	21.370	21.460	0.00	24.43	30.00	0.28	1.00
	2437	21.590	21.690	0.00	24.65	30.00	0.29	1.00
	2462	21.930	20.840	0.00	24.43	30.00	0.28	1.00
802.11n HT20	2412	21.730	21.480	0.00	24.62	30.00	0.29	1.00
	2437	21.970	21.460	0.00	24.73	30.00	0.30	1.00
	2462	22.550	20.630	0.00	24.71	30.00	0.30	1.00
802.11n HT40	2422	18.040	17.910	0.00	20.99	30.00	0.13	1.00
	2437	18.570	16.490	0.00	20.66	30.00	0.12	1.00
	2452	19.240	17.370	0.00	21.42	30.00	0.14	1.00

7. Radiated Spurious Emission Test

7.1 Standard Applicable

According to §15.247(d), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

7.2 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m/1.5m above ground plane in 966 chamber.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

Test receiver setting	: Blew 1GHz
Detector	: Average (9kHz – 90kHz, 110kHz – 90kHz), Quasi-Peak
Bandwidth	: 200Hz, 120kHz
Test spectrum setting	: Above 1GHz
Peak	: RBW=1MHz, VBW $\geq$ 3*RBW, Sweep=auto
Average	: RBW=1MHz, VBW $\geq$ 1/T _{on} , Sweep=auto

7.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

Remark:

<1GHz

1. No further spurious emissions detected from the lowest internal frequency and 30MHz.
2. Measuring frequencies from the lowest internal frequency to the 1GHz.
3. Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
4. Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

>1GHz


- 5 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 6 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 7 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

7.4 Measurement Result

7.4.1 Radiated Spurious Emission Measurement Result (below 1GHz)

International Standard Laboratory Corp.
Company Address: No.120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	70.74	46.99	-12.52	34.47	40.00	-5.53	Peak	VERTICAL
2	141.55	44.53	-10.13	34.40	43.50	-9.10	Peak	VERTICAL
3	212.36	50.51	-12.74	37.77	43.50	-5.73	Peak	VERTICAL
4	300.63	43.50	-9.13	34.37	46.00	-11.63	Peak	VERTICAL
5	392.78	39.69	-6.52	33.17	46.00	-12.83	Peak	VERTICAL
6	803.09	31.00	1.83	32.83	46.00	-13.17	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	49.82	-13.19	36.63	40.00	-3.37	Peak	HORIZONTAL
2	129.91	43.39	-11.57	31.82	43.50	-11.68	Peak	HORIZONTAL
3	209.45	45.73	-12.77	32.96	43.50	-10.54	Peak	HORIZONTAL
4	335.55	41.53	-8.08	33.45	46.00	-12.55	Peak	HORIZONTAL
5	391.81	41.98	-6.54	35.44	46.00	-10.56	Peak	HORIZONTAL
6	802.12	36.78	1.81	38.59	46.00	-7.41	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	80.44	48.67	-14.58	34.09	40.00	-5.91	Peak	VERTICAL
2	141.55	45.56	-10.13	35.43	43.50	-8.07	Peak	VERTICAL
3	207.51	48.62	-12.82	35.80	43.50	-7.70	Peak	VERTICAL
4	302.57	44.19	-9.12	35.07	46.00	-10.93	Peak	VERTICAL
5	431.58	35.52	-5.25	30.27	46.00	-15.73	Peak	VERTICAL
6	813.76	29.81	1.94	31.75	46.00	-14.25	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	65.89	49.23	-11.69	37.54	40.00	-2.46	Peak	HORIZONTAL
2	331.67	41.44	-8.10	33.34	46.00	-12.66	Peak	HORIZONTAL
3	391.81	38.65	-6.54	32.11	46.00	-13.89	Peak	HORIZONTAL
4	531.49	32.45	-3.21	29.24	46.00	-16.76	Peak	HORIZONTAL
5	656.62	29.80	-0.52	29.28	46.00	-16.72	Peak	HORIZONTAL
6	810.85	35.43	1.87	37.30	46.00	-8.70	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	72.68	47.85	-12.91	34.94	40.00	-5.06	Peak	VERTICAL
2	80.44	49.44	-14.58	34.86	40.00	-5.14	Peak	VERTICAL
3	140.58	44.93	-10.32	34.61	43.50	-8.89	Peak	VERTICAL
4	205.57	51.23	-12.86	38.37	43.50	-5.13	Peak	VERTICAL
5	300.63	43.53	-9.13	34.40	46.00	-11.60	Peak	VERTICAL
6	406.36	39.23	-6.27	32.96	46.00	-13.04	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	65.89	48.88	-11.69	37.19	40.00	-2.81	Peak	HORIZONTAL
2	72.68	49.74	-12.91	36.83	40.00	-3.17	Peak	HORIZONTAL
3	161.92	42.35	-9.97	32.38	43.50	-11.12	Peak	HORIZONTAL
4	268.62	41.88	-10.02	31.86	46.00	-14.14	Peak	HORIZONTAL
5	389.87	43.18	-6.58	36.60	46.00	-9.40	Peak	HORIZONTAL
6	741.98	40.84	1.14	41.98	46.00	-4.02	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	80.44	49.44	-14.58	34.86	40.00	-5.14	Peak	VERTICAL
2	140.58	44.77	-10.32	34.45	43.50	-9.05	Peak	VERTICAL
3	209.45	51.08	-12.77	38.31	43.50	-5.19	Peak	VERTICAL
4	299.66	43.77	-9.14	34.63	46.00	-11.37	Peak	VERTICAL
5	399.57	39.53	-6.36	33.17	46.00	-12.83	Peak	VERTICAL
6	500.45	33.40	-3.92	29.48	46.00	-16.52	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	66.86	49.67	-11.74	37.93	40.00	-2.07	Peak	HORIZONTAL
2	164.83	42.14	-9.94	32.20	43.50	-11.30	Peak	HORIZONTAL
3	297.72	41.75	-9.19	32.56	46.00	-13.44	Peak	HORIZONTAL
4	382.11	43.01	-6.77	36.24	46.00	-9.76	Peak	HORIZONTAL
5	600.36	32.19	-1.33	30.86	46.00	-15.14	Peak	HORIZONTAL
6	729.37	38.38	0.72	39.10	46.00	-6.90	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	71.71	45.91	-12.65	33.26	40.00	-6.74	Peak	VERTICAL
2	140.58	45.89	-10.32	35.57	43.50	-7.93	Peak	VERTICAL
3	206.54	48.00	-12.84	35.16	43.50	-8.34	Peak	VERTICAL
4	302.57	44.24	-9.12	35.12	46.00	-10.88	Peak	VERTICAL
5	500.45	32.74	-3.92	28.82	46.00	-17.18	Peak	VERTICAL
6	600.36	31.60	-1.33	30.27	46.00	-15.73	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	66.86	48.32	-11.74	36.58	40.00	-3.42	Peak	HORIZONTAL
2	167.74	40.77	-9.98	30.79	43.50	-12.71	Peak	HORIZONTAL
3	294.81	42.50	-9.25	33.25	46.00	-12.75	Peak	HORIZONTAL
4	363.68	41.15	-7.72	33.43	46.00	-12.57	Peak	HORIZONTAL
5	500.45	31.36	-3.92	27.44	46.00	-18.56	Peak	HORIZONTAL
6	808.91	32.88	1.85	34.73	46.00	-11.27	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	80.44	46.95	-14.58	32.37	40.00	-7.63	Peak	VERTICAL
2	168.71	44.24	-9.95	34.29	43.50	-9.21	Peak	VERTICAL
3	226.91	45.90	-12.75	33.15	46.00	-12.85	Peak	VERTICAL
4	301.60	43.68	-9.12	34.56	46.00	-11.44	Peak	VERTICAL
5	422.85	34.85	-5.59	29.26	46.00	-16.74	Peak	VERTICAL
6	729.37	38.43	0.72	39.15	46.00	-6.85	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	66.86	48.97	-11.74	37.23	40.00	-2.77	Peak	HORIZONTAL
2	202.66	46.28	-12.90	33.38	43.50	-10.12	Peak	HORIZONTAL
3	241.46	44.17	-11.20	32.97	46.00	-13.03	Peak	HORIZONTAL
4	390.84	41.91	-6.56	35.35	46.00	-10.65	Peak	HORIZONTAL
5	729.37	36.54	0.72	37.26	46.00	-8.74	Peak	HORIZONTAL
6	817.64	32.81	2.03	34.84	46.00	-11.16	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	71.71	46.51	-12.65	33.86	40.00	-6.14	Peak	VERTICAL
2	139.61	43.95	-10.45	33.50	43.50	-10.00	Peak	VERTICAL
3	210.42	51.19	-12.75	38.44	43.50	-5.06	Peak	VERTICAL
4	301.60	43.96	-9.12	34.84	46.00	-11.16	Peak	VERTICAL
5	422.85	35.47	-5.59	29.88	46.00	-16.12	Peak	VERTICAL
6	717.73	29.03	0.46	29.49	46.00	-16.51	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	68.80	48.45	-12.20	36.25	40.00	-3.75	Peak	HORIZONTAL
2	141.55	40.63	-10.13	30.50	43.50	-13.00	Peak	HORIZONTAL
3	204.60	45.57	-12.88	32.69	43.50	-10.81	Peak	HORIZONTAL
4	390.84	44.35	-6.56	37.79	46.00	-8.21	Peak	HORIZONTAL
5	533.43	32.84	-3.20	29.64	46.00	-16.36	Peak	HORIZONTAL
6	799.21	33.20	1.79	34.99	46.00	-11.01	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwa
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	71.71	45.69	-12.65	33.04	40.00	-6.96	Peak	VERTICAL
2	183.26	46.14	-11.71	34.43	43.50	-9.07	Peak	VERTICAL
3	207.51	49.89	-12.82	37.07	43.50	-6.43	Peak	VERTICAL
4	302.57	44.58	-9.12	35.46	46.00	-10.54	Peak	VERTICAL
5	374.35	39.81	-7.06	32.75	46.00	-13.25	Peak	VERTICAL
6	777.87	29.16	1.57	30.73	46.00	-15.27	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwa
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	65.89	48.26	-11.69	36.57	40.00	-3.43	Peak	HORIZONTAL
2	159.01	40.16	-9.90	30.26	43.50	-13.24	Peak	HORIZONTAL
3	205.57	44.07	-12.86	31.21	43.50	-12.29	Peak	HORIZONTAL
4	337.49	42.71	-8.08	34.63	46.00	-11.37	Peak	HORIZONTAL
5	396.66	44.34	-6.43	37.91	46.00	-8.09	Peak	HORIZONTAL
6	818.61	31.21	2.05	33.26	46.00	-12.74	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	72.68	46.88	-12.91	33.97	40.00	-6.03	Peak	VERTICAL
2	140.58	42.10	-10.32	31.78	43.50	-11.72	Peak	VERTICAL
3	165.80	43.19	-9.88	33.31	43.50	-10.19	Peak	VERTICAL
4	211.39	48.89	-12.74	36.15	43.50	-7.35	Peak	VERTICAL
5	303.54	44.08	-9.12	34.96	46.00	-11.04	Peak	VERTICAL
6	371.44	38.96	-7.19	31.77	46.00	-14.23	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwa
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	65.89	48.49	-11.69	36.80	40.00	-3.20	Peak	HORIZONTAL
2	165.80	41.26	-9.88	31.38	43.50	-12.12	Peak	HORIZONTAL
3	308.39	41.13	-8.95	32.18	46.00	-13.82	Peak	HORIZONTAL
4	393.75	44.51	-6.50	38.01	46.00	-7.99	Peak	HORIZONTAL
5	600.36	31.74	-1.33	30.41	46.00	-15.59	Peak	HORIZONTAL
6	817.64	32.15	2.03	34.18	46.00	-11.82	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	45.69	-13.19	32.50	40.00	-7.50	Peak	VERTICAL
2	141.55	41.76	-10.13	31.63	43.50	-11.87	Peak	VERTICAL
3	167.74	43.48	-9.98	33.50	43.50	-10.00	Peak	VERTICAL
4	210.42	47.17	-12.75	34.42	43.50	-9.08	Peak	VERTICAL
5	302.57	44.31	-9.12	35.19	46.00	-10.81	Peak	VERTICAL
6	600.36	31.83	-1.33	30.50	46.00	-15.50	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	67.83	48.72	-11.73	36.99	40.00	-3.01	Peak	HORIZONTAL
2	159.98	42.90	-9.89	33.01	43.50	-10.49	Peak	HORIZONTAL
3	287.05	42.71	-9.34	33.37	46.00	-12.63	Peak	HORIZONTAL
4	389.87	43.99	-6.58	37.41	46.00	-8.59	Peak	HORIZONTAL
5	532.46	31.81	-3.20	28.61	46.00	-17.39	Peak	HORIZONTAL
6	856.44	30.27	2.32	32.59	46.00	-13.41	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	79.47	47.91	-14.21	33.70	40.00	-6.30	Peak	VERTICAL
2	167.74	44.19	-9.98	34.21	43.50	-9.29	Peak	VERTICAL
3	215.27	46.73	-12.73	34.00	43.50	-9.50	Peak	VERTICAL
4	300.63	44.07	-9.13	34.94	46.00	-11.06	Peak	VERTICAL
5	329.73	39.19	-8.12	31.07	46.00	-14.93	Peak	VERTICAL
6	729.37	34.89	0.72	35.61	46.00	-10.39	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	64.92	48.38	-11.23	37.15	40.00	-2.85	Peak	HORIZONTAL
2	163.86	41.52	-9.86	31.66	43.50	-11.84	Peak	HORIZONTAL
3	264.74	41.09	-10.19	30.90	46.00	-15.10	Peak	HORIZONTAL
4	296.75	41.27	-9.20	32.07	46.00	-13.93	Peak	HORIZONTAL
5	389.87	37.40	-6.58	30.82	46.00	-15.18	Peak	HORIZONTAL
6	652.74	29.13	-0.53	28.60	46.00	-17.40	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	79.47	46.95	-14.21	32.74	40.00	-7.26	Peak	VERTICAL
2	167.74	43.54	-9.98	33.56	43.50	-9.94	Peak	VERTICAL
3	214.30	46.83	-12.73	34.10	43.50	-9.40	Peak	VERTICAL
4	302.57	44.48	-9.12	35.36	46.00	-10.64	Peak	VERTICAL
5	435.46	34.73	-5.08	29.65	46.00	-16.35	Peak	VERTICAL
6	600.36	32.01	-1.33	30.68	46.00	-15.32	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	66.86	48.25	-11.74	36.51	40.00	-3.49	Peak	HORIZONTAL
2	164.83	43.74	-9.94	33.80	43.50	-9.70	Peak	HORIZONTAL
3	300.63	41.25	-9.13	32.12	46.00	-13.88	Peak	HORIZONTAL
4	389.87	37.58	-6.58	31.00	46.00	-15.00	Peak	HORIZONTAL
5	531.49	32.87	-3.21	29.66	46.00	-16.34	Peak	HORIZONTAL
6	704.15	29.27	0.26	29.53	46.00	-16.47	Peak	HORIZONTAL

7.4.2 Radiated Spurious Emission Measurement Result (above1GHz)

International Standard Laboratory Corp.
Company Address: No.120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3210.00	57.31	4.40	61.71	91.84	-30.13	Peak	VERTICAL
2	4824.00	33.54	7.40	40.94	74.00	-33.06	Peak	VERTICAL
3	7236.00	32.66	10.27	42.93	74.00	-31.07	Peak	VERTICAL

Remark:

The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	34.38	7.40	41.78	74.00	-32.22	Peak	HORIZONTAL
2	7236.00	33.20	10.27	43.47	74.00	-30.53	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Mid CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3244.00	54.67	4.46	59.13	91.62	-32.49	Peak	VERTICAL
2	4874.00	33.35	7.45	40.80	74.00	-33.20	Peak	VERTICAL
3	7311.00	33.09	10.43	43.52	74.00	-30.48	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	33.80	7.45	41.25	74.00	-32.75	Peak	HORIZONTAL
2	7311.00	34.22	10.43	44.65	74.00	-29.35	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3278.00	54.02	4.47	58.49	91.80	-33.31	Peak	VERTICAL
2	4924.00	33.48	7.54	41.02	74.00	-32.98	Peak	VERTICAL
3	7375.00	33.07	10.54	43.61	74.00	-30.39	Peak	VERTICAL

Remark:

The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	33.41	7.54	40.95	74.00	-33.05	Peak	HORIZONTAL
2	7386.00	33.04	10.54	43.58	74.00	-30.42	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3210.00	61.21	4.40	65.61	90.70	-25.09	Peak	VERTICAL
2	4824.00	36.51	7.40	43.91	74.00	-30.09	Peak	VERTICAL
3	7236.00	34.73	10.27	45.00	74.00	-29.00	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	33.60	7.40	41.00	74.00	-33.00	Peak	HORIZONTAL
2	7236.00	35.28	10.27	45.55	74.00	-28.45	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Mid CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3244.00	57.12	4.46	61.58	89.67	-28.09	Peak	VERTICAL
2	4874.00	36.97	7.45	44.42	74.00	-29.58	Peak	VERTICAL
3	7311.00	33.93	10.43	44.36	74.00	-29.64	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	33.47	7.45	40.92	74.00	-33.08	Peak	HORIZONTAL
2	7311.00	33.13	10.43	43.56	74.00	-30.44	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3278.00	56.19	4.47	60.66	89.82	-29.16	Peak	VERTICAL
2	4924.00	35.86	7.54	43.40	74.00	-30.60	Peak	VERTICAL
3	7386.00	33.80	10.54	44.34	74.00	-29.66	Peak	VERTICAL

Remark:

The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3278.00	44.19	4.47	48.66	74.00	-25.34	Peak	HORIZONTAL
2	4924.00	33.49	7.54	41.03	74.00	-32.97	Peak	HORIZONTAL
3	7386.00	33.17	10.54	43.71	74.00	-30.29	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3210.00	58.21	4.40	62.61	90.02	-27.41	Peak	VERTICAL
2	4824.00	33.30	7.40	40.70	74.00	-33.30	Peak	VERTICAL
3	7236.00	32.82	10.27	43.09	74.00	-30.91	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	34.47	7.40	41.87	74.00	-32.13	Peak	HORIZONTAL
2	7236.00	32.96	10.27	43.23	74.00	-30.77	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Mid CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3244.00	56.45	4.46	60.91	90.14	-29.23	Peak	VERTICAL
2	4874.00	35.83	7.45	43.28	74.00	-30.72	Peak	VERTICAL
3	7311.00	34.31	10.43	44.74	74.00	-29.26	Peak	VERTICAL

Remark:

The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	33.44	7.45	40.89	74.00	-33.11	Peak	HORIZONTAL
2	7311.00	33.17	10.43	43.60	74.00	-30.40	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3278.00	53.55	4.47	58.02	90.51	-32.49	Peak	VERTICAL
2	4924.00	36.18	7.54	43.72	74.00	-30.28	Peak	VERTICAL
3	7386.00	33.88	10.54	44.42	74.00	-29.58	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwa
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	36.14	7.54	43.68	74.00	-30.32	Peak	HORIZONTAL
2	7386.00	33.71	10.54	44.25	74.00	-29.75	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3227.00	56.12	4.43	60.55	84.30	-23.75	Peak	VERTICAL
2	4844.00	33.71	7.42	41.13	74.00	-32.87	Peak	VERTICAL
3	7266.00	34.11	10.32	44.43	74.00	-29.57	Peak	VERTICAL

Remark:

The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Low CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4844.00	33.05	7.42	40.47	74.00	-33.53	Peak	HORIZONTAL
2	7266.00	33.60	10.32	43.92	74.00	-30.08	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Mid CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3244.00	55.14	4.46	59.60	83.86	-24.26	Peak	VERTICAL
2	4874.00	33.55	7.45	41.00	74.00	-33.00	Peak	VERTICAL
3	7311.00	33.48	10.43	43.91	74.00	-30.09	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	32.95	7.45	40.40	74.00	-33.60	Peak	HORIZONTAL
2	7311.00	33.39	10.43	43.82	74.00	-30.18	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3275.00	54.50	4.47	58.97	84.02	-25.05	Peak	VERTICAL
2	4904.00	32.54	7.48	40.02	74.00	-33.98	Peak	VERTICAL
3	7356.00	33.17	10.53	43.70	74.00	-30.30	Peak	VERTICAL

Remark:
The limit of non-restricted frequency for radiated emission is 20dB below the field strength of fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 TX High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4904.00	33.78	7.48	41.26	74.00	-32.74	Peak	HORIZONTAL
2	7356.00	34.13	10.53	44.66	74.00	-29.34	Peak	HORIZONTAL

8. 100kHz Bandwidth of Band Edges Measurement

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Measurement Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW=1MHz, VBW $\geq$ 3*RBW (for Peak); VBW $\geq$ 1/T_{on} (for Average), Sweep = auto.
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

8.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$


Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.4 Measurement Result

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan

Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2367.23	51.65	2.16	53.81	74.00	-20.19	Peak	VERTICAL
2	2390.00	49.44	2.33	51.77	74.00	-22.23	Peak	VERTICAL
3	2400.00	53.42	2.41	55.83	91.84	-36.01	Peak	VERTICAL
4	2413.38	109.39	2.45	111.84	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	2340.13	50.97	1.96	52.93	74.00	-21.07	Peak	HORIZONTAL
2	2390.00	48.28	2.33	50.61	74.00	-23.39	Peak	HORIZONTAL
3	2400.00	49.16	2.41	51.57	81.93	-30.36	Peak	HORIZONTAL
4	2410.91	99.49	2.44	101.93	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2435.83	109.09	2.53	111.62	--	--	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2438.38	97.93	2.55	100.48	--	--	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2463.18	109.15	2.65	111.80	F	--	Peak	VERTICAL
2	2483.50	49.61	2.76	52.37	74.00	-21.63	Peak	VERTICAL
3	2497.22	50.42	2.84	53.26	74.00	-20.74	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G b Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2460.83	98.35	2.64	100.99	F	--	Peak	HORIZONTAL
2	2483.50	49.76	2.76	52.52	74.00	-21.48	Peak	HORIZONTAL
3	2491.55	50.49	2.81	53.30	74.00	-20.70	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-04

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2385.71	43.51	2.30	45.81	54.00	-8.19	Average	VERTICAL
2	2385.71	54.55	2.30	56.85	74.00	-17.15	Peak	VERTICAL
3	2390.00	43.62	2.33	45.95	54.00	-8.05	Average	VERTICAL
4	2390.00	54.71	2.33	57.04	74.00	-16.96	Peak	VERTICAL
5	2391.09	48.79	2.34	51.13	54.00	-2.87	Average	VERTICAL
6	2391.09	59.76	2.34	62.10	74.00	-11.90	Peak	VERTICAL
7	2400.00	83.96	2.41	86.37	90.70	-4.33	Peak	VERTICAL
8	2415.62	108.24	2.46	110.70	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan Qty 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2383.47	51.05	2.28	53.33	74.00	-20.67	Peak	HORIZONTAL
2	2390.00	49.25	2.33	51.58	74.00	-22.42	Peak	HORIZONTAL
3	2400.00	68.88	2.41	71.29	81.30	-10.01	Peak	HORIZONTAL
4	2415.73	98.84	2.46	101.30	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2442.49	107.12	2.55	109.67	--	--	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2433.61	97.37	2.53	99.90	--	--	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwa
Date: 2023-08-04

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2463.18	107.17	2.65	109.82	F	--	Peak	VERTICAL
2	2483.50	44.08	2.76	46.84	54.00	-7.16	Average	VERTICAL
3	2483.50	55.78	2.76	58.54	74.00	-15.46	Peak	VERTICAL
4	2485.60	43.23	2.77	46.00	54.00	-8.00	Average	VERTICAL
5	2485.60	54.56	2.77	57.33	74.00	-16.67	Peak	VERTICAL
6	2496.35	42.70	2.84	45.54	54.00	-8.46	Average	VERTICAL
7	2496.35	53.76	2.84	56.60	74.00	-17.40	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G g Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2463.14	96.57	2.65	99.22	F	--	Peak	HORIZONTAL
2	2483.50	48.52	2.76	51.28	74.00	-22.72	Peak	HORIZONTAL
3	2490.74	50.55	2.80	53.35	74.00	-20.65	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-04

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2387.39	43.04	2.31	45.35	54.00	-8.65	Average	VERTICAL
2	2387.39	55.35	2.31	57.66	74.00	-16.34	Peak	VERTICAL
3	2390.00	44.36	2.33	46.69	54.00	-7.31	Average	VERTICAL
4	2390.00	56.96	2.33	59.29	74.00	-14.71	Peak	VERTICAL
5	2400.00	82.69	2.41	85.10	90.02	-4.92	Peak	VERTICAL
6	2409.23	107.58	2.44	110.02	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-04

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	48.51	2.33	50.84	74.00	-23.16	Peak	HORIZONTAL
2	2400.00	70.43	2.41	72.84	82.24	-9.40	Peak	HORIZONTAL
3	2416.51	99.78	2.46	102.24	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2444.77	107.57	2.57	110.14	--	--	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2435.62	96.04	2.53	98.57	--	--	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-04

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2469.62	107.82	2.69	110.51	F	--	Peak	VERTICAL
2	2483.50	44.28	2.76	47.04	54.00	-6.96	Average	VERTICAL
3	2483.50	62.46	2.76	65.22	74.00	-8.78	Peak	VERTICAL
4	2486.70	44.13	2.78	46.91	54.00	-7.09	Average	VERTICAL
5	2486.70	62.23	2.78	65.01	74.00	-8.99	Peak	VERTICAL
6	2488.48	39.62	2.78	42.40	54.00	-11.60	Average	VERTICAL
7	2488.48	57.69	2.78	60.47	74.00	-13.53	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n20 Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2463.52	97.85	2.65	100.50	F	--	Peak	HORIZONTAL
2	2483.50	38.96	2.76	41.72	54.00	-12.28	Average	HORIZONTAL
3	2483.50	52.48	2.76	55.24	74.00	-18.76	Peak	HORIZONTAL
4	2483.68	38.02	2.76	40.78	54.00	-13.22	Average	HORIZONTAL
5	2483.68	52.07	2.76	54.83	74.00	-19.17	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2365.31	51.64	2.15	53.79	74.00	-20.21	Peak	VERTICAL
2	2390.00	49.81	2.33	52.14	74.00	-21.86	Peak	VERTICAL
3	2400.00	74.92	2.41	77.33	84.30	-6.97	Peak	VERTICAL
4	2432.10	101.78	2.52	104.30	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 Bandedge Low CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2316.34	51.00	1.79	52.79	74.00	-21.21	Peak	HORIZONTAL
2	2390.00	49.46	2.33	51.79	74.00	-22.21	Peak	HORIZONTAL
3	2400.00	61.49	2.41	63.90	72.80	-8.90	Peak	HORIZONTAL
4	2424.84	90.31	2.49	92.80	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2427.70	101.36	2.50	103.86	--	--	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24


Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 Mid CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2427.52	88.57	2.50	91.07	--	--	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-04

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 Bandedge High CH Tested by : Kevin Yao




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2444.92	101.45	2.57	104.02	F	--	Peak	VERTICAL
2	2483.50	50.82	2.76	53.58	74.00	-20.42	Peak	VERTICAL
3	2484.43	40.63	2.77	43.40	54.00	-10.60	Average	VERTICAL
4	2484.43	52.31	2.77	55.08	74.00	-18.92	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2023-08-24

Project Number. : 23LR0098 Temp.(°C)/RH(%) : 25/60
Test Mode : 2.4G n40 Bandedge High CH Tested by : Kevin Yao



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2456.41	92.55	2.62	95.17	F	--	Peak	HORIZONTAL
2	2483.50	48.86	2.76	51.62	74.00	-22.38	Peak	HORIZONTAL
3	2487.69	50.15	2.78	52.93	74.00	-21.07	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

9. 6dB Bandwidth

9.1 Standard Applicable

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.


9.2 Measurement Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as
 - RBW = 100 kHz.
 - VBW $\geq 3 \times$ RBW.
 - Detector = Peak.
 - Trace mode = max hold.
 - Sweep = auto couple.
 - Allow the trace to stabilize.
 - Use 6-dB BW measurement function
4. Repeat above procedures until all frequency measured were complete.


9.3 Measurement Result

Band	Frequency (MHz)	6dB Bandwidth (MHz)	6dB BW Limit (kHz)
802.11b	2412	8.083	> 500
	2437	8.099	> 500
	2462	8.085	> 500
802.11g	2412	17.768	> 500
	2437	17.76	> 500
	2462	17.76	> 500
802.11n HT20	2412	17.769	> 500
	2437	17.781	> 500
	2462	17.751	> 500
802.11n HT40	2422	36.528	> 500
	2437	36.532	> 500
	2452	36.5	> 500

Test Data: Ant1 b 2412MHz




Test Data: Ant1 b 2437MHz



Test Data: Ant1 b 2462MHz




Test Data: Ant1 g 2412MHz




Test Data: Ant1 g 2437MHz




Test Data: Ant1 g 2462MHz




Test Data: Ant1 HT20 2412MHz




Test Data: Ant1 HT20 2437MHz



Test Data: Ant1 HT20 2462MHz




Test Data: Ant1 HT40 2422MHz



Test Data: Ant1 HT40 2437MHz



Test Data: Ant1 HT40 2452MHz



10. Peak Power Spectral Density

10.1 Standard Applicable

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

10.2 Measurement Procedure


1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW =3kHz, VBW = 10kHz, Set the span to 1.5 DTS bandwidth., Sweep=Auto
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.

10.3 Measurement Result


CDD mode

Mode	Freq. (MHz)	PSD (dBm/3kHz)				Duty Factor (dB)	Total PSD (dBm/MHz)	PSD Limit (dBm/MHz)
		Chain 0	Chain 1	Chain 2	Chain 3			
802.11b	2412	-5.661	-7.658			0	-5.661	8
	2437	-6.647	-7.526			0	-6.647	8
	2462	-6.829	-7.443			0	-6.829	8
802.11g	2412	-13.118	-14.023			0	-13.118	8
	2437	-13.026	-13.506			0	-13.026	8
	2462	-12.764	-13.445			0	-12.764	8
802.11n HT20	2412	-12.785	-12.798			0	-9.781	8
	2437	-11.777	-13.416			0	-9.509	8
	2462	-12.531	-13.416			0	-9.941	8
802.11n HT40	2422	-20.105	-20.023			0	-17.054	8
	2437	-20.119	-19.981			0	-17.039	8
	2452	-19.415	-20.812			0	-17.047	8


Test Data: Ant1 b 2412MHz




Test Data: Ant1 b 2437MHz




Test Data: Ant1 b 2462MHz




Test Data: Ant1 g 2412MHz




Test Data: Ant1 g 2437MHz




Test Data: Ant1 g 2462MHz




Test Data: Ant1 HT20 2412MHz




Test Data: Ant1 HT20 2437MHz




Test Data: Ant1 HT20 2462MHz




Test Data: Ant1 HT40 2422MHz



Test Data: Ant1 HT40 2437MHz



Test Data: Ant1 HT40 2452MHz




Test Data: Ant2 b 2412MHz




Test Data: Ant2 b 2437MHz




Test Data: Ant2 b 2462MHz




Test Data: Ant2 g 2412MHz




Test Data: Ant2 g 2437MHz




Test Data: Ant2 g 2462MHz




Test Data: Ant2 n20 2412MHz




Test Data: Ant2 n20 2437MHz




Test Data: Ant2 n20 2462MHz




Test Data: Ant2 n40 2422MHz



Test Data: Ant2 n40 2437MHz



Test Data: Ant2 n40 2452MHz



11. Appendix

11.1 Appendix A: Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 02	EMI Receiver 19	R&S	ESR3	102460	05/08/2023	05/08/2024
Conduction 02	Conduction 02-1 Cable	WOKEN	CFD 300-NL	Conduction 02 -1	10/11/2022	10/11/2023
Conduction 02	LISN 26	R&S	ENV216	102378	12/08/2022	12/08/2023
Conduction 02	LISN 15	R&S	ENV216	101335	12/08/2022	12/08/2023
Conduction 02	ISN T8 CAT6A 02	SCHWARZBECK	NTFM 8158	NTFM 8158-00370	07/07/2023	07/07/2024
Conduction 02	ISN T4 08	TESEQ	ISN T400A	49913	08/31/2022	08/31/2023
Conduction 02	ISN T8 08	Teseq GmbH	ISN T800	36155	10/03/2022	10/03/2023
Conduction 02	CDN ISN ST08A 1	Teseq GmbH	CDN ISN ST08A	43352	10/04/2022	10/04/2023
Conduction 02	Capacitive Voltage Probe 01	SCHAFFNER	CVP 2200A	18711	02/22/2023	02/22/2024
Conduction 02	Current Probe	SCHAFFNER	SMZ 11	18030	02/22/2023	02/22/2024

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Chamber 19	Spectrum analyzer	R&S	FSV40	101919	08/16/2022	08/16/2023
Chamber 19	EMI Receiver	R&S	ESR3	102461	05/08/2023	05/08/2024
Chamber 19	Loop Antenna	EM	EM-6879	271	10/05/2022	10/05/2023
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 6dB Att.	9168-736	03/09/2023	03/09/2024
Chamber 19	Horn antenna (1GHz-18GHz)	ETS	3117	00218718	10/12/2022	10/12/2023
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/24/2022	11/24/2023
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/25/2023	03/25/2024
Chamber 19	Preamplifier (9kHz-3GHz)	EM	EM330	060822	01/05/2023	01/05/2024
Chamber 19	Preamplifier (1GHz-26GHz)	HP	8449B	3008A02471	10/26/2022	10/26/2023
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000-27-5A	818471	05/04/2023	05/04/2024
Chamber 19	RF Cable (100kHz-26.5GHz)	Huber Suhner	Sucoflex 104A	MY1394/4A & 50886/4A	09/02/2022	09/02/2023
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SUHNER	Sucoflex 102	27963/2&37421/2	11/23/2022	11/23/2023
Chamber 19	Signal Generator	Anritsu	MG3692A	20311	12/29/2022	12/29/2023
Chamber 19	Test Software	Audix	E3 Ver:6.120203b	N/A	N/A	N/A

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conducted	Power Meter	Anritsu	ML2495A	1116010	09/29/2022	09/29/2023
Conducted	Power Sensor	Anritsu	MA2411B	34NKF50	09/29/2022	09/29/2023
Conducted	Power Sensor	DARE	RPR3006W	13I00030SNO33	01/06/2023	01/06/2024
Conducted	Power Sensor	DARE	RPR3006W	13I00030SNO34	01/06/2023	01/06/2024
Conducted	Power Sensor	DARE	RPR3006W	14I00889SNO35	06/21/2023	06/21/2024
Conducted	Power Sensor	DARE	RPR3006W	14I00889SNO36	06/21/2023	06/21/2024
Conducted	Temperature Chamber	KSON	THS-B4H100	2287	05/17/2023	05/17/2024
Conducted	DC Power supply	ABM	8185D	N/A	01/04/2023	01/04/2024
Conducted	AC Power supply	EXTECH	CFC105W	NA	N/A	N/A
Conducted	Spectrum analyzer	Keysight	N9010A	MY56070257	09/28/2022	09/28/2023
Conducted	Test Software	DARE	Radiation Ver:2013.1.23	NA	NA	NA
Conducted	Test Software	R&S	CMUGO Ver:2.0.0	N/A	N/A	N/A
Conducted	Universal Radio Comm. Tester	R&S	CMU200	111968	11/19/2022	11/19/2023
Conducted	Wideband Radio Comm. Tester	R&S	CMW500	1201.002K50108793-JG	10/31/2022	10/31/2023
Conducted	BT Simulator	Agilent	N4010A	MY48100200	NA	NA
Conducted	Signal Generator	Agilent	E4438C	MY49071550	12/28/2022	12/28/2023
Conducted	Signal Generator	Keysight	N5182B	MY53052399	12/28/2022	12/28/2023
Conducted	Spectrum analyzer	Keysight	N9010A	MY56070257	09/28/2022	09/28/2023
Conducted (TS8997)	Wideband Radio Comm. Tester	R&S	CMW500	168811	09/22/2022	09/22/2023
Conducted (TS8997)	UP/DOWN converter	R&S	CMW-Z800A	100566	12/22/2022	12/22/2023
Conducted (TS8997)	Signal Generator	R&S	SMB100A	183701	01/18/2023	01/18/2024
Conducted (TS8997)	Vector Signal Generator	R&S	SMM100A	101908	11/23/2022	11/23/2023
Conducted (TS8997)	Signal analyzer 40GHz	R&S	FSV40	101884	09/22/2022	09/22/2023
Conducted (TS8997)	OSP150 extension unit CAM-BUS	R&S	OSP150	101107	09/21/2022	09/21/2023
Conducted (TS8997)	Test Software	R&S	EMC32 Ver: 11.60.00	NA	NA	NA

11.2 Appendix B: Uncertainty of Measurement


ISO/IEC 17025 requires that an estimate of measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Parameters	Uncertainty ($k=2$)
Conducted Emission (AC power line)	± 0.632 dB
Spurious emissions, radiated	± 3.46 dB
RF power, conducted	± 1.531 dB
Power Density	± 1.690 dB
RF Frequency	$\pm 0.00403\%$
Time	$\pm 0.01\%$
DC Voltage	$\pm 0.03\%$

11.3 Appendix C: Test Setup


AC Line Conducted Emission Test Setup

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10-2013.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.




Radiated Spurious Emission Test & 100kHz Bandwidth of Band Edges Measurement Test Setup

(A) Radiated Emission Test Setup for frequency below 1000MHz



(B) Radiated Emission Test Setup for frequency above 1 GHz



RF Conducted Measurement Test Setup

