



Appendix Test Data for SRD (Conducted Measurement)

Product Name: RC TOYS

Trade Mark: /

Test Model: 6088

FCC ID: 2AVY8-6088

Environmental Conditions

Temperature:	23.5°C
Relative Humidity:	58%
ATM Pressure:	100.0 kPa
Test Engineer:	Allen Lai
Supervised by:	Max Zhang
NOTE	N/A

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
SRD	Ant1	2403	0.588	2402.696	2403.284	0.5	PASS
SRD	Ant1	2440	0.600	2439.724	2440.324	0.5	PASS
SRD	Ant1	2477	0.584	2476.696	2477.280	0.5	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix B: Occupied Channel Bandwidth

Test Result


Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
SRD	Ant1	2403	0.76997	2402.6363	2403.4062	---	---
SRD	Ant1	2440	0.73045	2439.6474	2440.3778	---	---
SRD	Ant1	2477	0.73906	2476.6732	2477.4122	---	---


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix C: Maximum peak conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
SRD	Ant1	2403	-2.41	≤30	PASS
SRD	Ant1	2440	-1.97	≤30	PASS
SRD	Ant1	2477	-2.22	≤30	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs Peak







Appendix D: Maximum peak power spectral density

Test Result


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
SRD	Ant1	2403	-10.67	≤8.00	PASS
SRD	Ant1	2440	-9.45	≤8.00	PASS
SRD	Ant1	2477	-9.03	≤8.00	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix E: Band edge measurements

Test Result


Test Mode	Antenna	Ch. Name	Frequency [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
SRD	Ant1	Low	2403	-3.30	-44.72	≤ -23.3	PASS
SRD	Ant1	High	2477	-3.17	-43.01	≤ -23.17	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs





Appendix F: Conducted Spurious Emission

Test Result

Test Mode	Antenna	Frequency [MHz]	Freq. Range [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
SRD	Ant1	2403	0~Reference	-3.29	-3.29	---	PASS
SRD	Ant1	2403	30~1000	-3.29	-62.51	≤ -23.29	PASS
SRD	Ant1	2403	1000~26500	-3.29	-36.71	≤ -23.29	PASS
SRD	Ant1	2440	0~Reference	-3.91	-3.91	---	PASS
SRD	Ant1	2440	30~1000	-3.91	-59.88	≤ -23.91	PASS
SRD	Ant1	2440	1000~26500	-3.91	-36.74	≤ -23.91	PASS
SRD	Ant1	2477	0~Reference	-3.43	-3.43	---	PASS
SRD	Ant1	2477	30~1000	-3.43	-62.17	≤ -23.43	PASS
SRD	Ant1	2477	1000~26500	-3.43	-36.29	≤ -23.43	PASS

Note: offset(dB) in Reference test plots = cable loss(dB) + attenuator factor(dB); For spurious emissions plots from 30MHz to 26.5GHz, the cable loss and attenuator factors have been set in the 'Input Correction' of the Spectrum Analyzer during the test.






Test Graphs




SRD-Ant1-2403-0~Reference-PASS



SRD-Ant1-2403-30~1000-PASS






SRD-Ant1-2403-1000~26500-PASS




SRD-Ant1-2440-0~Reference-PASS





SRD-Ant1-2440-30~1000-PASS




SRD-Ant1-2440-1000~26500-PASS






SRD-Ant1-2477-0~Reference-PASS



SRD-Ant1-2477-30~1000-PASS





SRD-Ant1-2477-1000~26500-PASS





Appendix G: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
SRD	Ant1	2403	1.08	20.00	5.40	12.68
SRD	Ant1	2440	1.08	20.00	5.40	12.68
SRD	Ant1	2477	1.04	20.00	5.20	12.84

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs

