



CFR 47 FCC PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

CONSUMER CAMERA

MODEL NUMBER: IPC-F42P-D, IPC-F42P-D-0280B-imou, IPC-F42N-D-0280B-imou, IPC-F42P-D-0360B-imou, IPC-F42N-D-0360B-imou, IPC-F42P-D-0600B-imou, IPC-F42N-D-0600B-imou, IPC-F42P-D-0280B, IPC-F42N-D-0280B, IPC-F42P-D-0360B, IPC-F42N-D-0360B, IPC-F42P-D-0600B, IPC-F42N-D-0600B, IPC-F42N-D, IPC-F42P-D-imou, IPC-F42N-D-imou

FCC ID: 2AVYF-IPC-F4X-D

REPORT NUMBER: 4789973747-16

ISSUE DATE: June 12, 2021

Prepared for

**Hangzhou Huacheng Network Technology Co.,Ltd.
No.2930, Nanhuan Road, Binjiang District, Hangzhou, China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	06/12/2021	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6dB Bandwidth	FCC Part 15.247 (a) (2)	Pass
2	Conducted Output Power	FCC Part 15.247 (b) (3)	Pass
3	Power Spectral Density	FCC Part 15.247 (e)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d)	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Pass
6	Conducted Emission Test for AC Power Port	FCC Part 15.207	Pass
7	Antenna Requirement	FCC Part 15.203	Pass
Note: 1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.			

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. CHANNEL LIST	9
5.3. MAXIMUM OUTPUT POWER	10
5.4. TEST CHANNEL CONFIGURATION	10
5.5. THE WORSE CASE POWER SETTING PARAMETER	10
5.6. THE WORSE CASE CONFIGURATIONS	11
5.7. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.8. DESCRIPTION OF TEST SETUP	13
6. MEASURING INSTRUMENT AND SOFTWARE USED	14
7. ANTENNA PORT TEST RESULTS	16
7.1. ON TIME AND DUTY CYCLE	16
7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH	17
7.3. CONDUCTED OUTPUT POWER	19
7.4. POWER SPECTRAL DENSITY	20
7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS	21
8. RADIATED TEST RESULTS	23
8.1. RESTRICTED BANDEDGE	28
8.1.1. 802.11b SISO MODE	28
8.1.2. 802.11g SISO MODE	32
8.1.3. 802.11n HT20 MIMO MODE	36
8.1.4. 802.11n HT40 MIMO MODE	40
8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)	44
8.2.1. 802.11g SISO MODE	44
8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)	50
8.3.1. 802.11b SISO MODE	50
8.3.2. 802.11g SISO MODE	56
8.3.3. 802.11n HT20 MIMO MODE	62
8.3.4. 802.11n HT40 MIMO MODE	68



8.4.	SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)	74
8.4.1.	802.11n HT20 MIMO MODE	74
8.5.	SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)	76
8.5.1.	802.11n HT20 MIMO MODE	76
8.6.	SPURIOUS EMISSIONS BELOW 30 MHz	78
8.6.1.	802.11n H20 MIMO MODE	78
9.	AC POWER LINE CONDUCTED EMISSIONS	81
9.1.	802.11n HT20 MIMO MODE	83
10.	ANTENNA REQUIREMENTS	85
11.	Appendix A	86
11.1.	Appendix A: DTS Bandwidth	86
11.1.1.	Test Result	86
11.1.2.	Test Graphs	87
11.2.	Appendix B: Occupied Channel Bandwidth	95
11.2.1.	Test Result	95
11.2.2.	Test Graphs	96
11.3.	Appendix C: Maximum conducted output power	104
11.3.1.	Test Result	104
11.4.	Appendix D: Maximum power spectral density	105
11.4.1.	Test Result	105
11.4.2.	Test Graphs	106
11.5.	Appendix E: Band edge measurements	112
11.5.1.	Test Result	112
11.5.2.	Test Graphs	113
11.6.	Appendix F: Conducted Spurious Emission	117
11.6.1.	Test Result	117
11.6.2.	Test Graphs	118
11.7.	Appendix G: Duty Cycle	136
11.7.1.	Test Result	136
11.7.2.	Test Graphs	137



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hangzhou Huacheng Network Technology Co.,Ltd.
Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

Manufacturer Information

Company Name: Hangzhou Huacheng Network Technology Co.,Ltd.
Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

EUT Information

EUT Name: CONSUMER CAMERA
Model Name: IPC-F42P-D
Series Model: IPC-F42P-D-0280B-imou, IPC-F42N-D-0280B-imou,
IPC-F42P-D-0360B-imou, IPC-F42N-D-0360B-imou,
IPC-F42P-D-0600B-imou, IPC-F42N-D-0600B-imou,
IPC-F42P-D-0280B, IPC-F42N-D-0280B, IPC-F42P-D-0360B,
IPC-F42N-D-0360B, IPC-F42P-D-0600B, IPC-F42N-D-0600B,
IPC-F42N-D, IPC-F42P-D-imou, IPC-F42N-D-imou
Model difference: The difference is only the name of the models.
Sample Received Date: June 7, 2021
Sample Status: Normal
Sample ID: 3967062
Date of Tested: June 7, 2021~ June 12, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Kebo Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15 and ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	CONSUMER CAMERA
Model Name	IPC-F42P-D
Series Model	IPC-F42P-D-0280B-imou, IPC-F42N-D-0280B-imou, IPC-F42P-D-0360B-imou, IPC-F42N-D-0360B-imou, IPC-F42P-D-0600B-imou, IPC-F42N-D-0600B-imou, IPC-F42P-D-0280B, IPC-F42N-D-0280B, IPC-F42P-D-0360B, IPC-F42N-D-0360B, IPC-F42P-D-0600B, IPC-F42N-D-0600B, IPC-F42N-D, IPC-F42P-D-imou, IPC-F42N-D-imou
Model difference	The difference is only the name of the models.
Radio Technology	IEEE802.11b/g/n HT20/HT40
Operation frequency	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz
Modulation	IEEE 802.11b: DSSS(CCK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Rating	DC 12 V, 0.5 A

5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/



5.3. MAXIMUM OUTPUT POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)
b	2412 ~ 2462	1-11[11]	15.86
g	2412 ~ 2462	1-11[11]	14.69
n HT20	2412 ~ 2462	1-11[11]	16.48
n HT40	2422 ~ 2452	3-9[7]	16.06

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
WiFi TX(802.11b)	CH 1, CH 6, CH 11/ Low, Middle, High	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11g)	CH 1, CH 6, CH 11/ Low, Middle, High	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT20)	CH 1, CH 6, CH 11/ Low, Middle, High	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT40)	CH 3, CH 6, CH 9/ Low, Middle, High	2422MHz, 2437MHz, 2452MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		SecureCRT					
Modulation Mode	Transmit Antenna Number	Test Software setting value					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	2	default	default	default	/		
802.11g	2	default	default	default			
802.11n HT20	2	default	default	default			
802.11n HT40	2	/			default	default	default

Note: Antenna 1 and antenna 2 use the same power setting for both SISO and MIMO modes.



5.6. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

802.11b mode: 1 Mbps

802.11b mode: 6 Mbps

802.11n HT20 MIMO mode: MCS0

802.11n HT40 MIMO mode: MCS0

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 0 and Core 1 correspond to antenna 1 and antenna 2 respectively.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported SISO & MIMO port combinations.

Duty cycle and 6dB DTS bandwidth/occupied channel bandwidth tests, only SISO mode and one chain were tested since the duty cycle and bandwidth does not change depending on chains used.

Conducted bandedge and spurious emissions tests were performed with SISO mode, as this port was found to have the worst case in terms of power settings amongst all supported possible SISO & MIMO port combinations.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations.



5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)	Directional gain (dBi)
1	2412-2462	Monopole	1.79	4.8
2	2412-2462	Monopole	1.79	

Note: Directional gain= $G_{ANT} + 10 \log(N_{ANT})$

G_{ANT} : Average of the Antenna Gain

N_{ANT} : Antenna numbers

Note: The value of the antenna gain was declared by customer.

IEEE Std. 802.11	Transmit and Receive Mode	Description
b	1TX, 1RX	Antenna 1, 2 can be used as transmitting/receiving antenna.
g	1TX, 1RX	Antenna 1, 2 can be used as transmitting/receiving antenna.
n HT20	2TX, 2RX	Antenna 1, 2 can be used as transmitting/receiving antenna.
n HT40	2TX, 2RX	Antenna 1, 2 can be used as transmitting/receiving antenna.
Note: Only 802.11n HT20/HT40 support MIMO mode		

5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	laptop	Lenovo	TP00094A	/
2	UART	/	/	/
3	RJ45 Terminal load	/	/	/
4	micro SD card	Kingston	/	32GB

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0 m	/
2	RJ 45 Cable	/	/	1.0 m	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	Switching Power Supply	MASS	NBS05C120050VU	Input: AC100~240V,50/60Hz,0.15A Output: 12Vdc,0.5A

TEST SETUP

The EUT can work in engineering mode with a software through a laptop.

SETUP DIAGRAM FOR TESTS





6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network	R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 11, 2018	Aug. 10, 2021
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#691	Aug. 11, 2018	Aug. 11, 2021
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	TDK	PA-02-3	TRS-308-00002	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Nov. 20, 2020	Nov. 19, 2021
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Nov. 12, 2020	Nov. 11, 2021
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Nov. 12, 2020	Nov. 11, 2021



Software					
Description		Manufacturer	Name	Version	
Test Software for Radiated Emissions		Farad	EZ-EMC	Ver. UL-3A1	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Nov.20,2020	Nov.19,2021
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Nov.20,2020	Nov.19,2021
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Nov.20,2020	Nov.19,2021
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Nov.20,2020	Nov.19,2021
DC power supply	Keysight	E3642A	MY55159130	Nov.24,2020	Nov.23,2021
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	

Other Instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Dual Channel Power Meter	Keysight	N1912A	MY55416024	Nov. 20, 2020	Nov. 19, 2021
Power Sensor	Keysight	USB Wideband Power Sensor	MY5100022	Nov. 20, 2020	Nov. 19, 2021



7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.8 °C	Relative Humidity	57 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix G.



7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.8 °C	Relative Humidity	57 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix A & B.



7.3. CONDUCTED OUTPUT POWER

LIMITS


CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.8 °C	Relative Humidity	57 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix C.

7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

TEST PROCEDURE


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.8 °C	Relative Humidity	57 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix D.



7.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.8 °C	Relative Humidity	57 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix E & F.



8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT

Temperature	23.2 °C	Relative Humidity	62 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS


8.1. RESTRICTED BANDEDGE

8.1.1. 802.11b SISO MODE

ANTENNA 1 TEST RESULTS (WORST CASE)

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.850	19.14	32.91	52.05	74.00	-21.95	peak
2	2385.670	21.35	33.32	54.67	74.00	-19.33	peak
3	2390.000	19.12	33.35	52.47	74.00	-21.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.850	10.56	32.91	43.47	54.00	-10.53	AVG
2	2385.670	6.16	33.32	39.48	54.00	-14.52	AVG
3	2390.000	5.55	33.35	38.90	54.00	-15.10	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)
PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.60	33.71	53.31	74.00	-20.69	peak
2	2483.700	20.92	33.71	54.63	74.00	-19.37	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.29	33.71	41.00	54.00	-13.00	AVG
2	2483.700	7.65	33.71	41.36	54.00	-12.64	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Horizontal and Vertical have been tested, only the worst data was recorded in the report.


Note: Both antennas have been tested, only the worst data was recorded in the report.

8.1.2. 802.11g SISO MODE

ANTENNA 1 TEST RESULTS (WORST CASE)

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.850	21.42	32.91	54.33	74.00	-19.67	peak
2	2390.000	27.66	33.35	61.01	74.00	-12.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.850	11.36	32.91	44.27	54.00	-9.73	AVG
2	2390.000	10.20	33.35	43.55	54.00	-10.45	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL) **PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	24.65	33.71	58.36	74.00	-15.64	peak
2	2484.100	25.66	33.71	59.37	74.00	-14.63	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.98	33.71	43.69	54.00	-10.31	AVG
2	2484.100	9.39	33.71	43.10	54.00	-10.90	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Horizontal and Vertical have been tested, only the worst data was recorded in the report.

Note: Both antennas have been tested, only the worst data was recorded in the report.

8.1.3. 802.11n HT20 MIMO MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.850	21.09	32.91	54.00	74.00	-20.00	peak
2	2390.000	26.68	33.35	60.03	74.00	-13.97	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.850	12.32	32.91	45.23	54.00	-8.77	AVG
2	2390.000	9.99	33.35	43.34	54.00	-10.66	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)
PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	28.07	33.71	61.78	74.00	-12.22	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.98	33.71	43.69	54.00	-10.31	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 4. For the transmitting duration, please refer to clause 7.1.
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and vertical had been tested, only the worst data was recorded in the report.


8.1.4. 802.11n HT40 MIMO MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL) PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2341.995	22.19	32.99	55.18	74.00	-18.82	peak
2	2389.650	28.31	33.35	61.66	74.00	-12.34	peak
3	2390.000	27.23	33.35	60.58	74.00	-13.42	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2341.995	14.02	32.99	47.01	54.00	-6.99	AVG
2	2389.650	11.96	33.35	45.31	54.00	-8.69	AVG
3	2390.000	12.06	33.35	45.41	54.00	-8.59	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.15	33.71	59.86	74.00	-14.14	peak
2	2494.190	26.24	33.74	59.98	74.00	-14.02	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	11.05	33.71	44.76	54.00	-9.24	AVG
2	2494.190	8.82	33.74	42.56	54.00	-11.44	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
4. For the transmitting duration, please refer to clause 7.1.
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Both horizontal and vertical had been tested, only the worst data was recorded in the report.



8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

8.2.1. 802.11g SISO MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2172.000	51.71	-9.20	42.51	74.00	-31.49	peak
2	2212.000	54.82	-9.01	45.81	74.00	-28.19	peak
3	2252.000	55.47	-8.88	46.59	74.00	-27.41	peak
4	2332.000	52.87	-8.61	44.26	74.00	-29.74	peak
5	2412.000	50.66	-8.37	42.29	/	/	fundamental
6	2572.000	47.86	-7.96	39.90	74.00	-34.10	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1890.000	46.48	-10.12	36.36	74.00	-37.64	peak
2	1974.000	46.19	-10.17	36.02	74.00	-37.98	peak
3	2252.000	48.59	-8.88	39.71	74.00	-34.29	peak
4	2340.000	51.07	-8.59	42.48	74.00	-31.52	peak
5	2412.000	50.76	-8.37	42.39	/	/	fundamental
6	2750.000	43.63	-6.88	36.75	74.00	-37.25	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2118.000	49.72	-9.52	40.20	74.00	-33.80	peak
2	2198.000	49.29	-9.06	40.23	74.00	-33.77	peak
3	2278.000	51.09	-8.79	42.30	74.00	-31.70	peak
4	2318.000	49.62	-8.66	40.96	74.00	-33.04	peak
5	2437.000	49.39	-8.33	41.06	/	/	fundamental
6	2758.000	47.24	-6.82	40.42	74.00	-33.58	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1874.000	46.51	-10.10	36.41	74.00	-37.59	peak
2	2198.000	46.66	-9.06	37.60	74.00	-36.40	peak
3	2278.000	54.48	-8.79	45.69	74.00	-28.31	peak
4	2344.000	51.22	-8.58	42.64	74.00	-31.36	peak
5	2437.000	49.55	-8.33	41.22	/	/	fundamental
6	2758.000	44.51	-6.82	37.69	74.00	-36.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2142.000	51.88	-9.37	42.51	74.00	-31.49	peak
2	2222.000	54.39	-8.98	45.41	74.00	-28.59	peak
3	2302.000	51.55	-8.72	42.83	74.00	-31.17	peak
4	2462.000	47.73	-8.29	39.44	/	/	fundamental
5	2582.000	46.73	-7.92	38.81	74.00	-35.19	peak
6	2782.000	45.52	-6.67	38.85	74.00	-35.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2142.000	47.24	-9.37	37.87	74.00	-36.13	peak
2	2222.000	47.76	-8.98	38.78	74.00	-35.22	peak
3	2302.000	51.25	-8.72	42.53	74.00	-31.47	peak
4	2342.000	52.06	-8.58	43.48	74.00	-30.52	peak
5	2462.000	48.54	-8.29	40.25	/	/	fundamental
6	2782.000	44.54	-6.67	37.87	74.00	-36.13	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes and channels had been tested, but only the worst data was recorded in the report.

8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

8.3.1. 802.11b SISO MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	51.02	1.38	52.40	74.00	-21.60	peak
2	5400.000	48.42	2.89	51.31	74.00	-22.69	peak
3	7200.000	40.37	7.36	47.73	74.00	-26.27	peak
4	12600.000	34.63	15.78	50.41	74.00	-23.59	peak
5	14715.000	34.66	17.74	52.40	74.00	-21.60	peak
6	16350.000	32.10	19.65	51.75	74.00	-22.25	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	47.03	1.38	48.41	74.00	-25.59	peak
2	5400.000	44.22	2.89	47.11	74.00	-26.89	peak
3	9375.000	37.55	10.83	48.38	74.00	-25.62	peak
4	11880.000	34.47	15.46	49.93	74.00	-24.07	peak
5	13965.000	34.72	17.62	52.34	74.00	-21.66	peak
6	16950.000	30.53	21.41	51.94	74.00	-22.06	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	50.64	1.32	51.96	74.00	-22.04	peak
2	5400.000	48.15	2.89	51.04	74.00	-22.96	peak
3	11715.000	35.22	15.34	50.56	74.00	-23.44	peak
4	13965.000	33.89	17.62	51.51	74.00	-22.49	peak
5	14805.000	34.39	18.00	52.39	74.00	-21.61	peak
6	17220.000	30.15	22.12	52.27	74.00	-21.73	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	47.04	1.32	48.36	74.00	-25.64	peak
2	7845.000	38.52	9.14	47.66	74.00	-26.34	peak
3	9375.000	36.84	10.83	47.67	74.00	-26.33	peak
4	12285.000	34.79	16.08	50.87	74.00	-23.13	peak
5	13590.000	34.41	17.11	51.52	74.00	-22.48	peak
6	17220.000	30.30	22.12	52.42	74.00	-21.58	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	51.46	1.45	52.91	74.00	-21.09	peak
2	5400.000	48.18	2.89	51.07	74.00	-22.93	peak
3	9360.000	37.13	10.75	47.88	74.00	-26.12	peak
4	12285.000	35.20	16.08	51.28	74.00	-22.72	peak
5	14775.000	34.14	17.95	52.09	74.00	-21.91	peak
6	16455.000	32.75	19.68	52.43	74.00	-21.57	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	47.08	1.45	48.53	74.00	-25.47	peak
2	5400.000	44.39	2.89	47.28	74.00	-26.72	peak
3	9375.000	37.35	10.83	48.18	74.00	-25.82	peak
4	11400.000	35.77	14.76	50.53	74.00	-23.47	peak
5	14430.000	34.21	17.34	51.55	74.00	-22.45	peak
6	16920.000	30.68	21.51	52.19	74.00	-21.81	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.2. 802.11g SISO MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	46.35	1.40	47.75	74.00	-26.25	peak
2	5400.000	48.10	2.89	50.99	74.00	-23.01	peak
3	8970.000	37.29	10.70	47.99	74.00	-26.01	peak
4	12735.000	34.96	15.75	50.71	74.00	-23.29	peak
5	13560.000	34.49	17.15	51.64	74.00	-22.36	peak
6	17625.000	29.55	22.92	52.47	74.00	-21.53	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.34	1.38	44.72	74.00	-29.28	peak
2	5400.000	44.80	2.89	47.69	74.00	-26.31	peak
3	8115.000	38.12	10.13	48.25	74.00	-25.75	peak
4	12270.000	34.19	16.04	50.23	74.00	-23.77	peak
5	13440.000	34.00	17.10	51.10	74.00	-22.90	peak
6	17235.000	30.53	22.21	52.74	74.00	-21.26	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.23	1.32	47.55	74.00	-26.45	peak
2	5400.000	47.81	2.89	50.70	74.00	-23.30	peak
3	8970.000	37.30	10.70	48.00	74.00	-26.00	peak
4	12225.000	35.24	15.99	51.23	74.00	-22.77	peak
5	14715.000	34.58	17.74	52.32	74.00	-21.68	peak
6	16890.000	30.54	21.49	52.03	74.00	-21.97	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5400.000	43.78	2.89	46.67	74.00	-27.33	peak
2	8115.000	38.57	10.13	48.70	74.00	-25.30	peak
3	11910.000	34.39	15.52	49.91	74.00	-24.09	peak
4	12285.000	34.28	16.08	50.36	74.00	-23.64	peak
5	13980.000	33.63	17.64	51.27	74.00	-22.73	peak
6	17280.000	29.50	22.48	51.98	74.00	-22.02	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	47.06	1.33	48.39	74.00	-25.61	peak
2	5400.000	47.90	2.89	50.79	74.00	-23.21	peak
3	9360.000	37.70	10.75	48.45	74.00	-25.55	peak
4	11820.000	34.84	15.29	50.13	74.00	-23.87	peak
5	14835.000	33.72	17.80	51.52	74.00	-22.48	peak
6	16785.000	31.25	20.59	51.84	74.00	-22.16	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5400.000	44.14	2.89	47.03	74.00	-26.97	peak
2	8115.000	37.32	10.13	47.45	74.00	-26.55	peak
3	9390.000	36.96	10.92	47.88	74.00	-26.12	peak
4	12240.000	34.83	16.01	50.84	74.00	-23.16	peak
5	13890.000	33.89	17.53	51.42	74.00	-22.58	peak
6	17340.000	29.52	22.31	51.83	74.00	-22.17	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**8.3.3. 802.11n HT20 MIMO MODE****HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	45.10	1.38	46.48	74.00	-27.52	peak
2	5400.000	48.29	2.89	51.18	74.00	-22.82	peak
3	8985.000	36.61	10.99	47.60	74.00	-26.40	peak
4	12210.000	34.73	15.97	50.70	74.00	-23.30	peak
5	13920.000	33.70	17.55	51.25	74.00	-22.75	peak
6	16890.000	30.71	21.49	52.20	74.00	-21.80	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.77	1.38	45.15	74.00	-28.85	peak
2	5400.000	43.79	2.89	46.68	74.00	-27.32	peak
3	9390.000	37.11	10.92	48.03	74.00	-25.97	peak
4	11820.000	34.59	15.29	49.88	74.00	-24.12	peak
5	13860.000	34.67	17.55	52.22	74.00	-21.78	peak
6	16890.000	30.54	21.49	52.03	74.00	-21.97	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	49.14	1.33	50.47	74.00	-23.53	peak
2	5400.000	47.82	2.89	50.71	74.00	-23.29	peak
3	8115.000	38.29	10.13	48.42	74.00	-25.58	peak
4	11415.000	35.41	14.74	50.15	74.00	-23.85	peak
5	12540.000	35.64	15.72	51.36	74.00	-22.64	peak
6	16380.000	32.03	19.67	51.70	74.00	-22.30	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	45.66	1.32	46.98	74.00	-27.02	peak
2	5400.000	43.85	2.89	46.74	74.00	-27.26	peak
3	8865.000	38.92	9.33	48.25	74.00	-25.75	peak
4	12600.000	35.59	15.78	51.37	74.00	-22.63	peak
5	16020.000	33.17	18.41	51.58	74.00	-22.42	peak
6	16920.000	30.19	21.51	51.70	74.00	-22.30	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	47.22	1.45	48.67	74.00	-25.33	peak
2	5400.000	47.68	2.89	50.57	74.00	-23.43	peak
3	9345.000	37.25	10.66	47.91	74.00	-26.09	peak
4	11670.000	35.63	15.16	50.79	74.00	-23.21	peak
5	14760.000	32.90	17.90	50.80	74.00	-23.20	peak
6	17295.000	30.08	22.58	52.66	74.00	-21.34	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	48.39	1.45	49.84	74.00	-24.16	peak
2	5400.000	44.26	2.89	47.15	74.00	-26.85	peak
3	9390.000	37.16	10.92	48.08	74.00	-25.92	peak
4	12240.000	34.95	16.01	50.96	74.00	-23.04	peak
5	13635.000	33.76	17.28	51.04	74.00	-22.96	peak
6	16890.000	30.40	21.49	51.89	74.00	-22.11	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**8.3.4. 802.11n HT40 MIMO MODE****HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5400.000	47.56	2.89	50.45	74.00	-23.55	peak
2	8115.000	37.38	10.13	47.51	74.00	-26.49	peak
3	9360.000	36.80	10.75	47.55	74.00	-26.45	peak
4	12645.000	35.48	15.71	51.19	74.00	-22.81	peak
5	14820.000	33.58	17.91	51.49	74.00	-22.51	peak
6	17175.000	30.41	21.97	52.38	74.00	-21.62	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5400.000	44.24	2.89	47.13	74.00	-26.87	peak
2	8115.000	37.68	10.13	47.81	74.00	-26.19	peak
3	9210.000	38.02	9.95	47.97	74.00	-26.03	peak
4	12285.000	34.24	16.08	50.32	74.00	-23.68	peak
5	13605.000	34.16	17.12	51.28	74.00	-22.72	peak
6	16875.000	30.61	21.35	51.96	74.00	-22.04	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.20	1.32	44.52	74.00	-29.48	peak
2	5400.000	48.04	2.89	50.93	74.00	-23.07	peak
3	9015.000	36.87	11.10	47.97	74.00	-26.03	peak
4	11790.000	35.94	15.26	51.20	74.00	-22.80	peak
5	14820.000	33.31	17.91	51.22	74.00	-22.78	peak
6	17145.000	30.19	21.94	52.13	74.00	-21.87	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5400.000	43.50	2.89	46.39	74.00	-27.61	peak
2	7875.000	38.13	8.98	47.11	74.00	-26.89	peak
3	9645.000	36.70	10.81	47.51	74.00	-26.49	peak
4	12285.000	33.69	16.08	49.77	74.00	-24.23	peak
5	14820.000	32.94	17.91	50.85	74.00	-23.15	peak
6	17325.000	29.69	22.42	52.11	74.00	-21.89	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	47.55	1.30	48.85	74.00	-25.15	peak
2	5400.000	48.14	2.89	51.03	74.00	-22.97	peak
3	8115.000	37.45	10.13	47.58	74.00	-26.42	peak
4	12615.000	35.26	15.75	51.01	74.00	-22.99	peak
5	13950.000	33.77	17.60	51.37	74.00	-22.63	peak
6	16890.000	30.30	21.49	51.79	74.00	-22.21	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5400.000	43.72	2.89	46.61	74.00	-27.39	peak
2	7875.000	37.78	8.98	46.76	74.00	-27.24	peak
3	8985.000	36.58	10.99	47.57	74.00	-26.43	peak
4	13620.000	33.87	17.19	51.06	74.00	-22.94	peak
5	16035.000	32.89	18.41	51.30	74.00	-22.70	peak
6	16920.000	31.03	21.51	52.54	74.00	-21.46	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

8.4.1. 802.11n HT20 MIMO MODE


SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18592.000	50.25	-5.31	44.94	74.00	-29.06	peak
2	19392.000	50.62	-5.57	45.05	74.00	-28.95	peak
3	20000.000	50.81	-5.45	45.36	74.00	-28.64	peak
4	21600.000	50.02	-4.54	45.48	74.00	-28.52	peak
5	23064.000	48.99	-3.42	45.57	74.00	-28.43	peak
6	25368.000	46.73	-1.72	45.01	74.00	-28.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18256.000	50.59	-5.55	45.04	74.00	-28.96	peak
2	19784.000	50.57	-5.28	45.29	74.00	-28.71	peak
3	21544.000	49.76	-4.63	45.13	74.00	-28.87	peak
4	22792.000	48.61	-3.65	44.96	74.00	-29.04	peak
5	24864.000	47.53	-2.23	45.30	74.00	-28.70	peak
6	25728.000	46.61	-0.72	45.89	74.00	-28.11	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


Note: All the modes and channels have been tested, but only the worst data was recorded in the report.



8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

8.5.1. 802.11n HT20 MIMO MODE

SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	141.5500	46.69	-18.76	27.93	43.50	-15.57	QP
2	185.2000	42.53	-16.75	25.78	43.50	-17.72	QP
3	343.3100	42.15	-14.40	27.75	46.00	-18.25	QP
4	375.3200	38.45	-13.79	24.66	46.00	-21.34	QP
5	576.1100	34.75	-10.02	24.73	46.00	-21.27	QP
6	676.9900	37.41	-8.62	28.79	46.00	-17.21	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	52.3100	55.38	-20.71	34.67	40.00	-5.33	QP
2	61.0400	55.15	-20.50	34.65	40.00	-5.35	QP
3	87.2300	55.42	-21.80	33.62	40.00	-6.38	QP
4	141.5500	58.16	-18.76	39.40	43.50	-4.10	QP
5	576.1100	39.54	-10.02	29.52	46.00	-16.48	QP
6	676.9900	40.01	-8.62	31.39	46.00	-14.61	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes and channels have been tested, but only the worst data was recorded in the report.

8.6. SPURIOUS EMISSIONS BELOW 30 MHz

8.6.1. 802.11n H20 MIMO MODE

SPURIOUS EMISSIONS (HIGH CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	75.22	-101.40	-26.18	47.60	-73.78	peak
2	0.0145	69.55	-101.38	-31.83	44.37	-76.20	peak
3	0.0221	68.13	-101.35	-33.22	40.71	-73.93	peak
4	0.0279	66.17	-101.38	-35.21	38.69	-73.90	peak
5	0.0427	62.14	-101.45	-39.31	34.99	-74.30	peak
6	0.0675	59.64	-101.56	-41.92	31.02	-72.94	peak

Note: 1. Measurement = Reading Level + Correct Factor

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150 kHz ~ 490 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	75.27	-101.65	-26.38	23.77	-50.15	peak
2	0.1621	73.92	-101.65	-27.73	23.41	-51.14	peak
3	0.2053	66.29	-101.73	-35.44	21.35	-56.79	peak
4	0.2210	65.84	-101.75	-35.91	20.71	-56.62	peak
5	0.2782	62.29	-101.83	-39.54	18.71	-58.25	peak
6	0.3163	61.70	-101.87	-40.17	17.60	-57.77	peak

Note: 1. Measurement = Reading Level + Correct Factor

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5039	64.44	-62.07	2.37	33.56	-31.19	peak
2	0.8296	63.44	-62.17	1.27	29.23	-27.96	peak
3	1.5564	57.68	-62.02	-4.34	23.76	-28.10	peak
4	3.7100	54.20	-61.41	-7.21	29.54	-36.75	peak
5	10.7299	53.98	-60.83	-6.85	29.54	-36.39	peak
6	16.3959	53.67	-60.96	-7.29	29.54	-36.83	peak

Note: 1. Measurement = Reading Level + Correct Factor

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes and channels had been tested, but only the worst data was recorded in the report.

9. AC POWER LINE CONDUCTED EMISSIONS


LIMITS

Please refer to CFR 47 FCC §15.207 (a).

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


**TEST ENVIRONMENT**

Temperature	23.4 °C	Relative Humidity	66.2 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

9.1. 802.11n HT20 MIMO MODE

LINE L RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	31.43	9.59	41.02	65.52	-24.50	QP
2	0.1590	14.56	9.59	24.15	55.52	-31.37	AVG
3	0.3933	36.04	9.59	45.63	57.99	-12.36	QP
4	0.3933	26.75	9.59	36.34	47.99	-11.65	AVG
5	0.8045	28.19	9.60	37.79	56.00	-18.21	QP
6	0.8045	19.35	9.60	28.95	46.00	-17.05	AVG
7	10.9604	37.09	9.64	46.73	60.00	-13.27	QP
8	10.9604	20.01	9.64	29.65	50.00	-20.35	AVG
9	14.4001	33.32	9.66	42.98	60.00	-17.02	QP
10	14.4001	26.85	9.66	36.51	50.00	-13.49	AVG
11	20.7600	28.84	9.85	38.69	60.00	-21.31	QP
12	20.7600	21.50	9.85	31.35	50.00	-18.65	AVG


Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

LINE N RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3929	37.78	9.59	47.37	58.00	-10.63	QP
2	0.3929	31.68	9.59	41.27	48.00	-6.73	AVG
3	0.7855	33.30	9.60	42.90	56.00	-13.10	QP
4	0.7855	24.35	9.60	33.95	46.00	-12.05	AVG
5	1.1395	31.46	9.61	41.07	56.00	-14.93	QP
6	1.1395	24.36	9.61	33.97	46.00	-12.03	AVG
7	1.3951	28.23	9.61	37.84	56.00	-18.16	QP
8	1.3951	19.72	9.61	29.33	46.00	-16.67	AVG
9	13.3601	31.92	9.66	41.58	60.00	-18.42	QP
10	13.3601	23.21	9.66	32.87	50.00	-17.13	AVG
11	20.4401	30.31	9.74	40.05	60.00	-19.95	QP
12	20.4401	24.52	9.74	34.26	50.00	-15.74	AVG

Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes and channels have been tested, but only the worst data was recorded in the report.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies



11. Appendix A

11.1. Appendix A: DTS Bandwidth

11.1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.120	2406.960	2417.080	0.5	PASS
	Ant2	2412	10.160	2406.920	2417.080	0.5	PASS
	Ant1	2437	10.120	2431.960	2442.080	0.5	PASS
	Ant2	2437	10.160	2431.920	2442.080	0.5	PASS
	Ant1	2462	10.160	2456.920	2467.080	0.5	PASS
	Ant2	2462	9.680	2456.920	2466.600	0.5	PASS
11G	Ant1	2412	16.640	2403.680	2420.320	0.5	PASS
	Ant2	2412	16.600	2403.720	2420.320	0.5	PASS
	Ant1	2437	16.640	2428.680	2445.320	0.5	PASS
	Ant2	2437	16.560	2428.720	2445.280	0.5	PASS
	Ant1	2462	16.600	2453.720	2470.320	0.5	PASS
	Ant2	2462	16.640	2453.680	2470.320	0.5	PASS
11N20MIMO	Ant1	2412	17.760	2403.080	2420.840	0.5	PASS
	Ant2	2412	17.720	2403.160	2420.880	0.5	PASS
	Ant1	2437	17.760	2428.120	2445.880	0.5	PASS
	Ant2	2437	17.800	2428.160	2445.960	0.5	PASS
	Ant1	2462	17.840	2453.120	2470.960	0.5	PASS
	Ant2	2462	17.840	2453.120	2470.960	0.5	PASS
11N40MIMO	Ant1	2422	36.560	2403.760	2440.320	0.5	PASS
	Ant2	2422	36.560	2403.760	2440.320	0.5	PASS
	Ant1	2437	36.560	2418.760	2455.320	0.5	PASS
	Ant2	2437	36.560	2418.760	2455.320	0.5	PASS
	Ant1	2452	36.560	2433.760	2470.320	0.5	PASS
	Ant2	2452	36.560	2433.760	2470.320	0.5	PASS



11.1.2. Test Graphs




















**11.2. Appendix B: Occupied Channel Bandwidth****11.2.1. Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant1	2412	14.973	2404.492	2419.465	PASS
	Ant2	2412	14.976	2404.491	2419.467	PASS
	Ant1	2437	14.990	2429.496	2444.486	PASS
	Ant2	2437	15.025	2429.484	2444.509	PASS
	Ant1	2462	14.991	2454.471	2469.462	PASS
	Ant2	2462	15.001	2454.505	2469.506	PASS
11G	Ant1	2412	17.050	2403.420	2420.470	PASS
	Ant2	2412	17.039	2403.409	2420.448	PASS
	Ant1	2437	17.013	2428.460	2445.473	PASS
	Ant2	2437	17.090	2428.380	2445.470	PASS
	Ant1	2462	17.098	2453.361	2470.459	PASS
	Ant2	2462	17.057	2453.414	2470.471	PASS
11N20MIMO	Ant1	2412	18.081	2402.968	2421.049	PASS
	Ant2	2412	18.119	2402.945	2421.064	PASS
	Ant1	2437	18.081	2427.976	2446.057	PASS
	Ant2	2437	18.130	2427.964	2446.094	PASS
	Ant1	2462	18.083	2452.972	2471.055	PASS
	Ant2	2462	18.084	2452.977	2471.061	PASS
11N40MIMO	Ant1	2422	36.174	2403.998	2440.172	PASS
	Ant2	2422	36.239	2403.965	2440.204	PASS
	Ant1	2437	36.201	2418.980	2455.181	PASS
	Ant2	2437	36.205	2418.983	2455.188	PASS
	Ant1	2452	36.104	2434.021	2470.125	PASS
	Ant2	2452	36.217	2433.983	2470.200	PASS



11.2.2. Test Graphs



















11.3. Appendix C: Maximum conducted output power

11.3.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	15.68	<=30	PASS
	Ant2	2412	15.54	<=30	PASS
	Ant1	2437	15.86	<=30	PASS
	Ant2	2437	14.86	<=30	PASS
	Ant1	2462	15.46	<=30	PASS
	Ant2	2462	14.64	<=30	PASS
11G	Ant1	2412	14.57	<=30	PASS
	Ant2	2412	14.22	<=30	PASS
	Ant1	2437	14.69	<=30	PASS
	Ant2	2437	13.36	<=30	PASS
	Ant1	2462	14.34	<=30	PASS
	Ant2	2462	13.22	<=30	PASS
11N20MIMO	Ant1	2412	13.72	<=30	PASS
	Ant2	2412	13.20	<=30	PASS
	total	2412	16.48	<=30	PASS
	Ant1	2437	13.59	<=30	PASS
	Ant2	2437	12.05	<=30	PASS
	total	2437	15.90	<=30	PASS
	Ant1	2462	12.54	<=30	PASS
	Ant2	2462	11.62	<=30	PASS
11N40MIMO	total	2462	15.11	<=30	PASS
	Ant1	2422	13.05	<=30	PASS
	Ant2	2422	12.45	<=30	PASS
	total	2422	15.77	<=30	PASS
	Ant1	2437	13.19	<=30	PASS
	Ant2	2437	12.37	<=30	PASS
	total	2437	15.81	<=30	PASS
	Ant1	2452	13.52	<=30	PASS
	Ant2	2452	12.52	<=30	PASS
	total	2452	16.06	<=30	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.1) had already compensated to the test data.


11.4. Appendix D: Maximum power spectral density


11.4.1. Test Result


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-14.81	<=8	PASS
		2437	-14.75	<=8	PASS
		2462	-15.14	<=8	PASS
11G	Ant1	2412	-14.15	<=8	PASS
		2437	-14.08	<=8	PASS
		2462	-14.3	<=8	PASS
11N20MIMO	Ant1	2412	-14.37	<=8	PASS
	Ant2	2412	-14.85	<=8	PASS
	total	2412	-11.59	<=8	PASS
	Ant1	2437	-14.55	<=8	PASS
	Ant2	2437	-15.97	<=8	PASS
	total	2437	-12.19	<=8	PASS
	Ant1	2462	-15.1	<=8	PASS
	Ant2	2462	-16.41	<=8	PASS
	total	2462	-12.70	<=8	PASS
11N40MIMO	Ant1	2422	-15.76	<=8	PASS
	Ant2	2422	-16.14	<=8	PASS
	total	2422	-12.94	<=8	PASS
	Ant1	2437	-15.56	<=8	PASS
	Ant2	2437	-16.18	<=8	PASS
	total	2437	-12.85	<=8	PASS
	Ant1	2452	-15.46	<=8	PASS
	Ant2	2452	-16.4	<=8	PASS
	total	2452	-12.89	<=8	PASS


Note: For 802.11b & g modes, both antennas had been tested, only the worst data was recorded in the report.


11.4.2. Test Graphs
















11.5. Appendix E: Band edge measurements

11.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	5.58	-34.98	<=-24.43	PASS
		High	2462	5.27	-40.62	<=-24.73	PASS
11G	Ant1	Low	2412	0.28	-32.48	<=-29.72	PASS
		High	2462	-0.09	-40.75	<=-30.09	PASS
11N20MIMO	Ant1	Low	2412	-0.52	-33.5	<=-30.52	PASS
	Ant2	Low	2412	-0.93	-33.76	<=-30.93	PASS
	Ant1	High	2462	-1.29	-40.72	<=-31.29	PASS
	Ant2	High	2462	-2.68	-40.3	<=-32.68	PASS
11N40MIMO	Ant1	Low	2422	-3.49	-40.58	<=-33.49	PASS
	Ant2	Low	2422	-3.77	-40.7	<=-33.77	PASS
	Ant1	High	2452	-2.81	-39.82	<=-32.81	PASS
	Ant2	High	2452	-3.86	-40.83	<=-33.86	PASS


Note: For 802.11b & g modes, both antennas had been tested, only the worst data was recorded in the report.



11.5.2. Test Graphs







11N20MIMO Ant1 High 2462



11N20MIMO Ant2 High 2462



11N40MIMO Ant1 Low 2422




**11.6. Appendix F: Conducted Spurious Emission****11.6.1. Test Result**


Test Mode	Antenna	Channel	FreqRange [Mhz]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	5.57	---	PASS
			30~1000	-53.52	<=-24.43	PASS
			1000~26500	-44.36	<=-24.43	PASS
		2437	Reference	5.62	---	PASS
			30~1000	-52.99	<=-24.38	PASS
			1000~26500	-44.26	<=-24.38	PASS
		2462	Reference	5.14	---	PASS
			30~1000	-53.37	<=-24.87	PASS
			1000~26500	-44.75	<=-24.87	PASS
11G	Ant1	2412	Reference	0.25	---	PASS
			30~1000	-52.93	<=-29.75	PASS
			1000~26500	-44.07	<=-29.75	PASS
		2437	Reference	0.41	---	PASS
			30~1000	-53.06	<=-29.59	PASS
			1000~26500	-44.2	<=-29.59	PASS
		2462	Reference	-0.04	---	PASS
			30~1000	-53.6	<=-30.04	PASS
			1000~26500	-44.49	<=-30.04	PASS
11N20MIMO	Ant1	2412	Reference	-0.67	---	PASS
			30~1000	-53.88	<=-30.67	PASS
			1000~26500	-44.78	<=-30.67	PASS
	Ant2	2412	Reference	-1.27	---	PASS
			30~1000	-53.67	<=-31.27	PASS
			1000~26500	-44.8	<=-31.27	PASS
	Ant1	2437	Reference	-1.16	---	PASS
			30~1000	-52.95	<=-31.16	PASS
			1000~26500	-44.19	<=-31.16	PASS
	Ant2	2437	Reference	-2.19	---	PASS
			30~1000	-53.27	<=-32.19	PASS
			1000~26500	-44.75	<=-32.19	PASS
	Ant1	2462	Reference	-1.69	---	PASS
			30~1000	-53.05	<=-31.69	PASS
			1000~26500	-43.61	<=-31.69	PASS
	Ant2	2462	Reference	-2.72	---	PASS
			30~1000	-53.75	<=-32.72	PASS
			1000~26500	-44.81	<=-32.72	PASS
11N40MIMO	Ant1	2422	Reference	-3.29	---	PASS
			30~1000	-53.47	<=-33.29	PASS
			1000~26500	-44.42	<=-33.29	PASS
	Ant2	2422	Reference	-3.72	---	PASS
			30~1000	-52.82	<=-33.72	PASS
			1000~26500	-44.98	<=-33.72	PASS
	Ant1	2437	Reference	-3.22	---	PASS
			30~1000	-52.61	<=-33.22	PASS
			1000~26500	-44.14	<=-33.22	PASS
	Ant2	2437	Reference	-3.77	---	PASS
			30~1000	-53.04	<=-33.77	PASS
			1000~26500	-44.84	<=-33.77	PASS
	Ant1	2452	Reference	-2.95	---	PASS
			30~1000	-53.14	<=-32.95	PASS
			1000~26500	-44.26	<=-32.95	PASS
	Ant2	2452	Reference	-3.78	---	PASS
			30~1000	-53.86	<=-33.78	PASS
			1000~26500	-44.94	<=-33.78	PASS





Note: For 802.11b & g modes, both antennas had been tested, only the worst data was recorded in the report.

11.6.2. Test Graphs











































11.7. Appendix G: Duty Cycle

11.7.1. Test Result

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11B	100	100	1.0000	100.00	0.00	0.01	0.01
11G	100	100	1.0000	100.00	0.00	0.01	0.01
11N20MIMO	100	100	1.0000	100.00	0.00	0.01	0.01
11N40MIMO	100	100	1.0000	100.00	0.00	0.01	0.01

Note:

Duty Cycle Correction Factor= $10\log(1/x)$.

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.




11.7.2. Test Graphs





11N20MIMO Ant1 2437



11N40MIMO Ant1 2437

END OF REPORT