



FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

CONSUMER CAMERA

MODEL NUMBER: IPC-F42FEP-C

**ADDITIONAL MODEL NUMBER: IPC-F42FEP-C-imou; IPC-F42FEP-C-0280B-imou;
IPC-F42FEP-C-0360B-imou; IPC-F42FEP-C-0600B-imou; IPC-F42FEN-C; IPC-
F42FEN-C-imou; IPC-F42FEN-C-0280B-imou; IPC-F42FEN-C-0360B-imou; IPC-
F42FEN-C-0600B-imou; LC-K32F-4M-C; IPC-F42FE-C-LC; IPC-F42FE-C-0280B-LC;
IPC-F42FE-C-0360B-LC; IPC-F42FE-C-0600B-LC; IPC-F42FEP-C-0280B; IPC-F42FEP-
C-0360B; IPC-F42FEP-C-0600B; IPC-F42FEN-C-0280B; IPC-F42FEN-C-0360B; IPC-
F42FEN-C-0600B**

PROJECT NUMBER: 4790033180-3

REPORT NUMBER: 4790033180-3-3

FCC ID: 2AVYF-IPC-F4XFE-C

ISSUE DATE: Aug 02, 2021

Prepared for

Hangzhou Huacheng Network Technology Co.,Ltd.

Prepared by

UL-CCIC COMPANY LIMITED

No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China

Tel: + 86-512-6808 6400

Fax: + 86-512-6808 4099

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	08/02/2021	Initial Issue	



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER	9
5.3. CHANNEL LIST.....	9
5.4. TEST CHANNEL CONFIGURATION.....	10
5.5. THE WORSE CASE POWER SETTING PARAMETER.....	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS.....	11
5.7. THE WORSE CASE CONFIGURATIONS	11
5.8. TEST ENVIRONMENT	12
5.9. DESCRIPTION OF TEST SETUP	13
5.10. MEASURING INSTRUMENT AND SOFTWARE USED	14
6. MEASUREMENT METHODS	15
7. ANTENNA PORT TEST RESULTS	16
7.1. ON TIME AND DUTY CYCLE.....	16
7.2. 6 dB BANDWIDTH	20
7.3. CONDUCTED POWER	31
7.4. POWER SPECTRAL DENSITY.....	33
7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS	44
7.6. RADIATED TEST RESULTS.....	89
7.6.1. LIMITS AND PROCEDURE	89
7.6.2. RESTRICTED BANDEDGE	94
7.6.3. SPURIOUS EMISSIONS	111
8. AC POWER LINE CONDUCTED EMISSIONS	168
9. ANTENNA REQUIREMENTS.....	171



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hangzhou Huacheng Network Technology Co.,Ltd.
Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

Manufacturer Information

Company Name: Hangzhou Huacheng Network Technology Co.,Ltd.
Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

EUT Description

Product Name: CONSUMER CAMERA
Model Name: IPC-F42FEP-C
Additional No. : IPC-F42FEP-C-imou;IPC-F42FEP-C-0280B-imou; IPC-F42FEP-C-0360B-imou; IPC-F42FEP-C-0600B-imou; IPC-F42FEN-C; IPC-F42FEN-C-imou; IPC-F42FEN-C-0280B-imou; IPC-F42FEN-C-0360B-imou; IPC-F42FEN-C-0600B-imou; LC-K32F-4M-C; IPC-F42FE-C-LC; IPC-F42FE-C-0280B-LC; IPC-F42FE-C-0360B-LC; IPC-F42FE-C-0600B-LC; IPC-F42FEP-C-0280B; IPC-F42FEP-C-0360B; IPC-F42FEP-C-0600B; IPC-F42FEN-C-0280B; IPC-F42FEN-C-0360B; IPC-F42FEN-C-0600B
Sample Number: 4083927
Data of Receipt Sample: Jul 20, 2021
Date Tested: Jul 20, 2021~ Aug 02, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	PASS



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6db DTS Bandwidth	FCC 15.247 (a) (2)	PASS
2	Conducted Power	FCC 15.247 (b) (3)	PASS
3	Power Spectral Density	FCC 15.247 (e)	PASS
4	Conducted Band edge And Spurious emission	FCC 15.247 (d)	PASS
5	Radiated Band edges and Spurious emission	FCC 15.247 (d) FCC 15.209 FCC 15.205	PASS
6	Conducted Emission Test For AC Power Port	FCC 15.207	PASS
7	Antenna Requirement	FCC 15.203	PASS
Remark: 1) The measurement result for the sample received is <Pass> according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15C> when <Accuracy Method> decision rule is applied.			

Prepared By:

Tom Tang

Tom Tang
Project Engineer

Reviewed By:

Leon Wu

Leon Wu
Senior Project Engineer

Authorized By:

Chris Zhong

Chris Zhong
Laboratory Leader



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.1dB
Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	3.4dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	3.4dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	3.9dB (1GHz-18Gz)
	4.2dB (18GHz-26.5Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Product Name:	CONSUMER CAMERA
Model No.:	IPC-F42FEP-C
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n (HT20 and HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Channels Step:	Channels with 5MHz step
Sample Type:	Fixed production
Test software of EUT:	Secure CRT (manufacturer declare)
Antenna Type:	Monopole Antenna
Antenna Gain:	Antenna1: 1.43 dBi Antenna2: 1.43 dBi Remark: This data is provided by customer and our lab isn't responsible for this data
Adapter	NAME: Power Adapter MODEL: ADS-12AM-12 12012EPCU INPUT:100-240V,50/60Hz, 0.3A OUTPUT:12V  1A

Remark:

Model No.:

Number:	Name:	Number:	Name:	Number:	Name:
1	IPC-F42FEP-C	2	IPC-F42FEP-C-imou	3	IPC-F42FEP-C-0280B-imou
4	IPC-F42FEP-C-0360B-imou	5	IPC-F42FEP-C-0600B-imou	6	IPC-F42FEN-C
7	IPC-F42FEN-C-imou	8	IPC-F42FEN-C-0280B-imou	9	IPC-F42FEN-C-0360B-imou
10	IPC-F42FEN-C-0600B-imou	11	LC-K32F-4M-C	12	IPC-F42FE-C-LC
13	IPC-F42FE-C-0280B-LC	14	IPC-F42FE-C-0360B-LC	15	IPC-F42FE-C-0600B-LC
16	IPC-F42FEP-C-0280B	17	IPC-F42FEP-C-0360B	18	IPC-F42FEP-C-0600B
19	IPC-F42FEN-C-0280B	20	IPC-F42FEN-C-0360B	21	IPC-F42FEN-C-0600B

Only the main model **IPC-F42FEP-C** was tested and only the data of this model is shown in this test report. Since Their electrical circuit design, layout, components used and internal wiring are identical, only the name of the models.



5.2. MAXIMUM OUTPUT POWER

Number of Transmit Chains (NTX)	IEE Std. 802.11	Channel Number	Max AV Conducted Power (dBm)
1	IEEE 802.11B SISO	1-11[11]	15.64
1	IEEE 802.11G SISO	1-11[11]	15.24
1/2	IEEE 802.11nHT20	1-11[11]	17.12
1/2	IEEE 802.11nHT40	3-9[7]	16.73

5.3. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452		

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447		



5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
WiFi TX(802.11b)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11g)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT20)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT40)	CH 3, CH 6, CH 9	2422MHz, 2437MHz, 2452MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		EspRFtestTool					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	N/A	N/A	N/A	/		
802.11g	1	N/A	N/A	N/A			
802.11n HT20	1/2	N/A	N/A	N/A			
802.11n HT40	1/2	/			N/A	N/A	N/A



5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)	Directional gain(dBi)
1	2400-2483.5	Monopole Antenna	1.43	4.44
2	2400-2483.5	Monopole Antenna	1.43	

Note:

- 1) Directional gain= $10\log [(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}] = 4.44$ dBi
- 2) N_{ANT} : the number of Antenna
- 3) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 and 802.11N HT40 modes can support both the SISO and MIMO technical. For the modes of 11B&11G only the antenna1 is working.

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
IEEE 802.11g	☒1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
IEEE 802.11N (HT20) MIMO	☒2TX, 2RX	Antenna1 or Antenna2 can be used as transmitting/receiving antenna independently.
IEEE 802.11N (HT40) MIMO	☒2TX, 2RX	Antenna1 or Antenna2 can be used as transmitting/receiving antenna independently.

Remark:

- 1) For this product, it has two antennas, antenna1 and antenna2, only the 802.11N HT20 and 802.11N HT40 modes can support both the SISO and MIMO technical. For the modes of 11B&11G only the antenna1 is working.
- 2) For the 11N mode (including the 11N HT20 SISO, 11N HT20 MIMO, 11N HT40 SISO, 11N HT40 MIMO), pre-testing all test modes, only the worst case modes is included in this report.

5.7. THE WORSE CASE CONFIGURATIONS

For the product, there two transmission antennas, and pre-testing both of them, only the worse data for the antenna is recorded in the report.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0



5.8. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1001Pa	
Temperature	TN	20 ~ 28°C
Voltage :	VL	N/A
	VN	AC 120V
	VH	N/A

Note: VL= Lower Extreme Test Voltage
VN= Nominal Voltage
VH= Upper Extreme Test Voltage
TN= Normal Temperature



5.10. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions (Instrument)								
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.	
☒	EMI Test Receiver	R&S	ESR3	126700	2019-12-12	2020-12-05	2021-12-04	
☒	Two-Line V-Network	R&S	ENV216	126701	2019-12-12	2020-12-05	2021-12-04	
☒	Artificial Mains Networks	R&S	ENY81	126711	2019-12-12	2020-12-05	2021-12-04	
Software								
Used	Description		Manufacturer		Name	Version		
☒	Test Software for Conducted disturbance		R&S		EMC32	Ver. 9.25		
Radiated Emissions (Instrument)								
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.	
☒	Spectrum Analyzer	Keysight	N9010B	MY57110128	2020-05-10	2021-05-09	2022-05-08	
☒	EMI test receiver	R&S	ESR26	1267603	2019-12-12	2020-12-05	2021-12-04	
☒	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	513-265	2018-06-15	2021-06-03	2022-06-02	
☒	Receiver Antenna (30MHz-1GHz)	SunAR RF Motion	JB1	177821	N/A	2019-01-28	2022-01-27	
☒	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2018-01-29	2019-01-28	2022-01-27	
☒	Receiver Antenna (18GHz-26.5GHz)	Schwarzbeck	BBHA9170	126706	2018-01-06	2019-01-05	2022-01-04	
☒	Pre-amplification (To 18GHz)	Compliance Direction System Inc.	PAP-1G18-50	14140-13467	2019-03-18	2020-12-05	2021-12-04	
☒	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	134668	2019-02-06	2020-09-27	2021-09-26	
☒	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	1	2020-05-10	2021-05-09	2022-05-08	
☒	Highpass Filter	Wainwright	WHKX10-2700-3000-18000-40SS	2	2020-05-10	2021-05-09	2022-05-08	
Software								
Used	Description		Manufacturer		Name		Version	
☒	Test Software for Radiated disturbance		Tonscend		JS32		V1.0	
Other instruments								
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.	
☒	Spectrum Analyzer	Keysight	N9010B	MY57110128	2020-05-10	2021-05-09	2022-05-08	
☒	Power Meter	Keysight	U2021XA	MY57110002	2020-05-10	2021-05-09	2022-05-08	



6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Conducted Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.1.3/8.3.2.3
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test For AC Power Port	ANSI C63.10-2013	6.2



7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

FCC KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



RESULTS


Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (KHz)
11B	100	100	1	100	0	0.01
11G	100	100	1	100	0	0.01
11N HT20	100	100	1	100	0	0.01
11N HT40	100	100	1	100	0	0.01

Note: 1) Duty Cycle Correction Factor= $10\log(1/x)$.


2) Where: x is Duty Cycle(Linear)



3) Where: T is On Time (transmit duration)

4) Pre-testing Antenna 1 and Antenna2, and pre-testing SISO and MIMO modes, only the data of worse case is shown in this test report.



11G ON TIME AND DUTY CYCLE MID CH (WORSE CASE)







7.2. 6 dB BANDWIDTH

LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(a)(2)	6dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5


TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyzer and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6dB Bandwidth :100K
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP





RESULTS



Test Mode	Test Antenna	Test Channel	6dB bandwidth (MHz)	Result
11B SISO	Antenna 1	LCH	10.07	Pass
		MCH	10.07	Pass
		HCH	10.07	Pass
11G SISO	Antenna 1	LCH	16.53	Pass
		MCH	16.53	Pass
		HCH	16.55	Pass
11N20MIMO	Antenna 1	LCH	17.68	Pass
		MCH	17.67	Pass
		HCH	17.67	Pass
	Antenna 2	LCH	17.71	Pass
		MCH	17.68	Pass
		HCH	17.73	Pass
11N40MIMO	Antenna 1	LCH	36.37	Pass
		MCH	36.36	Pass
		HCH	36.36	Pass
	Antenna 2	LCH	36.39	Pass
		MCH	36.37	Pass
		HCH	36.39	Pass



Remark:



- 1) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 and 802.11N HT40 modes can support both the SISO and MIMO technical. But for the modes of 11B & 11G, only the antenna 1 is working.
- 2) Through pre-testing all the test modes of 11N 20 and 11N40, including SISO and MIMO, but only the data if worse case is included in this test report.







Test Graphs
For Antenna1 part:























For Antenna 2 part:









7.3. CONDUCTED POWER


LIMITS

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5
If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.			

TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
Measure the power of each channel.
AVG Detector use for AVG result.

TEST SETUP





RESULTS

Test Mode	Test Antenna	Test Channel	Maximum Average Conducted Output Power (dBm)	Result
11B	Antenna 1	LCH	15.64	Pass
		MCH	15.30	Pass
		HCH	15.56	Pass
11G	Antenna 1	LCH	15.24	Pass
		MCH	14.88	Pass
		HCH	14.70	Pass
11N20MIMO	Antenna 1	LCH	14.37	Pass
		MCH	13.86	Pass
		HCH	13.71	Pass
	Antenna 2	LCH	13.83	Pass
		MCH	13.15	Pass
		HCH	13.09	Pass
	Antenna 1+2	LCH	17.12	Pass
		MCH	16.53	Pass
		HCH	16.42	Pass
11N40MIMO	Antenna 1	LCH	13.70	Pass
		MCH	13.65	Pass
		HCH	13.76	Pass
	Antenna 2	LCH	13.73	Pass
		MCH	13.36	Pass
		HCH	13.54	Pass
	Antenna 1+2	LCH	16.73	Pass
		MCH	16.52	Pass
		HCH	16.66	Pass

Remark:

- 1) For all the test results has been adjusted the duty cycle factor.
- 2) For Correction Factor is refer to the result in section 7.1
- 3) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 and 802.11N HT40 modes can support both the SISO and MIMO technical. But for the modes of 11B & 11G, only the antenna 1 is working.
- 4) Through pre-testing all the test modes of 11N 20 and 11N40, including SISO and MIMO, but only the data if worse case is included in this test report.



7.4. POWER SPECTRAL DENSITY

LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5
If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.			

TEST PROCEDURE


Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP









RESULTS



Test Mode	Test Antenna	Test Channel	Maximum Peak power spectral density(dBm/30kHz)	Result
11B	Antenna 1	LCH	0.75	Pass
		MCH	0.39	Pass
		HCH	0.68	Pass
11G	Antenna 1	LCH	-1.78	Pass
		MCH	-2.21	Pass
		HCH	-2.45	Pass
11N20MIMO	Antenna 1	LCH	-2.42	Pass
		MCH	-2.98	Pass
		HCH	-3.06	Pass
	Antenna 2	LCH	-3.15	Pass
		MCH	-3.61	Pass
		HCH	-3.70	Pass
	Antenna 1+2	LCH	0.24	Pass
		MCH	-0.27	Pass
		HCH	-0.36	Pass
11N40MIMO	Antenna 1	LCH	-6.04	Pass
		MCH	-6.37	Pass
		HCH	-6.24	Pass
	Antenna 2	LCH	-6.46	Pass
		MCH	-6.73	Pass
		HCH	-6.28	Pass
	Antenna 1+2	LCH	-3.23	Pass
		MCH	-3.54	Pass
		HCH	-3.25	Pass







Test Graphs:
For Antenna 1 Part:






















Test Graphs:
For Antenna 2 Part:









7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

LIMITS

FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	At least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


settings:

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

TEST SETUP





Part I :Conducted Bandedge

RESULTS TABLE



Test Mode	Test Antenna	Test Channel	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
11B	Antenna 1	LCH	5.818	-41.73	-24.18	PASS
		HCH	5.737	-42.03	-24.26	PASS
11G	Antenna 1	LCH	0.978	-41.20	-29.02	PASS
		HCH	0.583	-41.05	-29.42	PASS
11N20MIMO	Antenna 1	LCH	0.483	-41.23	-29.52	PASS
		HCH	-0.681	-40.82	-30.68	PASS
	Antenna 2	LCH	-0.323	-41.48	-30.32	PASS
		HCH	-0.693	-41.03	-30.69	PASS
11N40MIMO	Antenna 1	LCH	-3.606	-41.66	-33.61	PASS
		HCH	-3.459	-39.83	-33.46	PASS
	Antenna 2	LCH	-3.323	-41.10	-33.32	PASS
		HCH	-3.629	-38.82	-33.63	PASS

Remark:

- 1) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 and 802.11N HT40 modes can support both the SISO and MIMO technical. But for the modes of 11B & 11G, only the antenna 1 is working.
- 2) Through pre-testing all the test modes of 11N 20 and 11N40, including SISO and MIMO, but only the data if worse case is included in this test report.







TEST GRAPHS
For Antenna 1 Part





UL-CCIC COMPANY LIMITED

This report shall not be reproduced except in full, without the written approval of UL-CCIC COMPANY LIMITED.













For Antenna 2 Part:







Part II :Conducted Emission

Test Result Table

Test Mode	Test Antenna	Channel	Pref(dBm)	Puw(dBm)	Verdict
11B SISO	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
11G SISO	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
11N MIMO20	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
	Antenna 2	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
11N MIMO40	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
	Antenna 2	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS


Remark:

- 1) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 and 802.11N HT40 modes can support both the SISO and MIMO technical. But for the modes of 11B & 11G, only the antenna 1 is working.
- 2) Through pre-testing all the test modes of 11N 20 and 11N40, including SISO and MIMO, but only the data if worse case is included in this test report.

**Test Plots****For Antenna 1 Part:**



Test Mode	Channel	Verdict
11B	LCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11B	MCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11B	HCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11G	LCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11G	MCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11G	HCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT20	LCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT20	MCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT20	HCH	PASS

Pref test Plot





Puw test Plot





Test Mode	Channel	Verdict
11N HT40	LCH	PASS

Pref test Plot

