





5.5 Carrier Frequencies Separation


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Hop	1.006	≥ 0.633	PASS
2DH5	Hop	0.988	≥ 0.860	PASS
3DH5	Hop	1.081	≥ 0.840	PASS

Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.95	≥ 0.633
$\pi/4$ DQPSK	1.29	≥ 0.860
8DPSK	1.26	≥ 0.840


Test plot as follows:





Date: 29.OCT.2025 16:41:15


5.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
$\pi/4$ DQPSK	79	≥15
8DPSK	79	≥15

Test plot as follows:





5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass


Measurement Data


TestMode	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.404	320	0.129	≤0.4	PASS
DH3	Hop	1.653	200	0.331	≤0.4	PASS
DH5	Hop	2.893	130	0.376	≤0.4	PASS
2DH1	Hop	0.414	320	0.132	≤0.4	PASS
2DH3	Hop	1.659	160	0.265	≤0.4	PASS
2DH5	Hop	2.899	130	0.377	≤0.4	PASS
3DH1	Hop	0.415	330	0.137	≤0.4	PASS
3DH3	Hop	1.655	170	0.281	≤0.4	PASS
3DH5	Hop	2.900	130	0.377	≤0.4	PASS

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test plot as follows:






Date: 29.OCT.2025 16:12:04




Date: 29.OCT.2025 16:12:10

DH5_Ant1_Hop




Date: 29.OCT.2025 16:46:12




Date: 29.OCT.2025 16:46:17

2DH1_Ant1_Hop




Date: 29.OCT.2025 16:31:03




Date: 29.OCT.2025 16:31:08

2DH3_Ant1_Hop




Date: 29.OCT.2025 16:32:20




Date: 29.OCT.2025 16:32:25

2DH5_Ant1_Hop




Date: 29.OCT.2025 16:30:16




Date: 29.OCT.2025 16:30:22

3DH1_Ant1_Hop




Date: 29.OCT.2025 16:38:54




Date: 29.OCT.2025 16:39:00

3DH3_Ant1_Hop




Date: 29.OCT.2025 16:40:06




Date: 29.OCT.2025 16:40:12

3DH5_Ant1_Hop




Date: 29.OCT.2025 16:41:30



Date: 29.OCT.2025 16:41:36


5.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2020
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Low	2402	5.61	-48.8	≤ -14.39	PASS
	High	2480	7.92	-51.55	≤ -12.08	PASS
	Low	Hop_2402	6.16	-50.08	≤ -13.84	PASS
	High	Hop_2480	7.31	-51.33	≤ -12.69	PASS
2DH5	Low	2402	4.42	-50.32	≤ -15.58	PASS
	High	2480	6.74	-51.12	≤ -13.26	PASS
	Low	Hop_2402	0.49	-52.62	≤ -19.51	PASS
	High	Hop_2480	4.35	-51.52	≤ -15.65	PASS
3DH5	Low	2402	4.60	-49.87	≤ -15.4	PASS
	High	2480	6.84	-50.57	≤ -13.16	PASS
	Low	Hop_2402	3.82	-50.99	≤ -16.18	PASS
	High	Hop_2480	4.68	-51.62	≤ -15.32	PASS


Test plot as follows:






Date: 29.OCT.2025 15:52:43

DH5_Ant1_High_Hop_2480




Date: 29.OCT.2025 16:13:12

2DH5_Ant1_Low_2402




Date: 29.OCT.2025 15:00:44

2DH5_Ant1_High_2480




Date: 29.OCT.2025 15:04:40

2DH5_Ant1_Low_Hop_2402




Date: 29.OCT.2025 16:28:33

2DH5_Ant1_High_Hop_2480




Date: 29.OCT.2025 16:34:04

3DH5_Ant1_Low_2402




Date: 29.OCT.2025 15:09:00

3DH5_Ant1_High_2480




Date: 29.OCT.2025 15:14:28

3DH5_Ant1_Low_Hop_2402




Date: 29.OCT.2025 16:34:44

3DH5_Ant1_High_Hop_2480




Date: 29.OCT.2025 16:40:29

5.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2020
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Pass

DH5_Ant1_2402_0~Reference




Date: 29.OCT.2025 14:54:39

DH5_Ant1_2402_30~1000



Date: 29.OCT.2025 14:54:44


DH5_Ant1_2402_1000~26500




DH5_Ant1_2441_0~Reference



DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~26500




Date: 29.OCT.2025 14:58:03

DH5_Ant1_2480_0~Reference




Date: 29.OCT.2025 14:59:32

DH5_Ant1_2480_30~1000



Date: 29.OCT.2025 14:59:37


DH5_Ant1_2480_1000~26500



2DH5_Ant1_2402_0~Reference



2DH5_Ant1_2402_30~1000



2DH5_Ant1_2402_1000~26500