

Prüfbericht-Nr.: <i>Test report no.:</i>	IN26U4XI 001	Auftrags-Nr.: <i>Order no.:</i>	147138090 010	Seite 1 von 40 Page 1 of 40
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	2566340	Auftragsdatum: <i>Order date:</i>	2025-12-05	
Auftraggeber: <i>Client:</i>	75F Inc. , 1650 W, 82nd St, #200, Bloomington, Minnesota, USA - 55431			
Prüfgegenstand: <i>Test item:</i>	Wireless MultiSensor			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	Main Model: 7C-SE-C75X-X Associated Model: 7X-SE-C75X-X			
Auftrags-Inhalt: <i>Order content:</i>	Testing and issue of Test Report			
Prüfgrundlage: <i>Test specification:</i>	FCC Part15 SubpartC 15.247; 15.205; 15.207; 15.209 RSS Gen Issue 5; RSS 247 Issue 4			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2025-12-09			
Prüfmuster-Nr.: <i>Test sample no:</i>	A004181916-003 A004181916-004			
Prüfzeitraum: <i>Testing period:</i>	2025-12-12 - 2025-12-28			
Ort der Prüfung: <i>Place of testing:</i>	Wireless laboratory, Bangalore			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (India) Pvt.Ltd., 27/B, 2nd Cross, Electronic City Phase1 Bangalore -560 100, India			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i> 2026-03-24	Ausstellungsdatum: <i>Issue date:</i> 2026-03-24			
Stellung / Position:	M.V.Naveen Kumar Senior Engineer	Stellung / Position:	Vinay N Manager	
Sonstiges / <i>Other:</i>	FCC ID: 2AVZO-101317 IC: 25972-101317			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 2 von 40

Page 2 of 40

- | | |
|---|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 3 von 40
Page 3 of 40

4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>
5	Other <i>Sonstiges</i>
	Test sample(s), as well sample information, description, product details and intended usage was provided by customer. The Laboratory is not be responsible for the information/data provided by the customer which can affect the validity of results.
6	Test sample obtaining <i>Prüfmusterbereitstellung</i>
	☒ Sending by customer ☐ Sampling by TÜV Rheinland Group ☐ Others:
7	Additional Information
	FCC Test site registration number: 570793 ISED Test site registration number: 27711 Refer the Appendix of 1 for Test Setup Photos Refer the Appendix of 2 for External Photos Refer the Appendix of 3 for Internal Photos

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 4 von 40
Page 4 of 40

TEST SUMMARY

Test Item	FCC	ISED	Result
Maximum conducted (Peak) output power	15.247 (b)(3)	RSS 247 Issue 4 Section 6.3.2	Pass
Maximum Power Spectral Density	FCC 15.247(e)	RSS 247 Issue 4 Section 6.3.1	Pass
DTS Bandwidth & 99% Bandwidth	FCC 15.247(a)(2)	RSS 247 Issue 4 Section 6.3.1 RSS Gen Issue 5 Section 6.7	Pass
Emissions in non-restricted frequency bands	15.247 (d)	RSS 247 Issue 4 Section 6.6	Pass
Spurious Radiated Emissions and Restricted Bands of Operation	15.247 (d) / FCC 15.209 / FCC 15.205	RSS-Gen Issue 5, Section 8.9 /8.10	Pass
AC Power lines Conducted emission	FCC 15.207	RSS Gen Issue 5 Section 8.8	Pass
Antenna Requirement	FCC 15.203	RSS Gen Issue 5 Section 6.8	Complied

Product Category: Electronics Testing

Test Discipline: EMC Test Facility

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 5 von 40
Page 5 of 40

REVISION HISTORY OF THIS REPORT

Report Number	Version	Description	Issue date
IN26U4XI 001	01	Initial issue of report	2026-03-24

***Note: Wireless Sensor** product having different models & all models are electrically identical and no RF changes.
Hence, we tested **7X-SE-C75X-X**

Sl.No	Product Name	Model No	HVIN
1	Wireless Sensor	7X-SE-C75X-X	7X-SE-C75X-X
2		7C-SE-C75X-X	7C-SE-C75X-X

Table of Contents

1	GENERAL REMARKS	7
1.1	Attachments	7
2	TEST SITES	8
2.1	Testing Facilities	8
2.2	List of Test and Measurement Instruments.....	8
3	GENERAL PRODUCT INFORMATION.....	9
3.1	Product Function and Intended Use	9
3.2	Ratings and System Details of Equipment under Test	9
3.3	Measurement Uncertainty:	10
4	TEST SET-UP AND OPERATION MODE.....	11
4.1	Principle of Configuration Selection	11
4.2	Test Operation and Test Software	11
4.3	Special Accessories and Auxiliary Equipment	11
4.4	Simultaneous Transmission	11
4.5	Countermeasures to achieve EMC Compliance	11
4.6	List of frequencies	11
4.7	TUV Sample Identification.....	12
5	Operational Description	13
6	TEST METHODOLOGY	14
6.1	Radiated Emission Test	14
6.1.1	Test Setup Configuration.....	14
7	TEST RESULTS	16
7.1	Maximum Peak Conducted Output Power.....	16
7.2	DTS Bandwidth & 99% Bandwidth.....	18
7.3	Power Spectral Density.....	21
7.4	Emissions in non-restricted frequency bands and Conducted Spurious Emission.....	23
7.4.1	Out-Of-Band Emissions.....	26
7.5	Spurious Radiated Emissions & Restricted Bands of Operation	29
8	LIST OF TABLES.....	40
9	List of Figures	40

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 7 von 40

Page 7 of 40

1 GENERAL REMARKS

1.1 Attachments

All attachments are part of this test report and are issued in separate document

1. FCC Label and Label Location
2. Block Diagram
3. Specification of EUT
4. Schematic Diagrams
5. Bill of Material
6. User Manual

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 8 von 40
Page 8 of 40

2 TEST SITES

2.1 Testing Facilities

1. TÜV Rheinland (India) Pvt.Ltd.,
27/B, 2nd Cross,
ElectronicCityPhase1
Bangalore – 560 100,
India
2. TUV Rheinland (India) Pvt.Ltd.,
108, Beside ISBR Business School,
Electronic city Phase I
Bangalore - 560 100,
India

2.2 List of Test and Measurement Instruments

Table 1: List of test and measurement instruments

Equipment	Manufacturer	Model Name	Serial Number	Firmware Versions	Calibration Due Date	Periodicity	Test Facility
EMI Receiver	Rohde & Schwarz	ESW 44	103384	3.20SP2	24.06.2026	Yearly	Radiated Spurious Emission
Active loop antenna	Frankonia	LAX-10	LAX-10-800	-	16.04.2026	Yearly	
Balun & Biconical Antenna	Schwarzbeck mess-elektronik	BBA 9106+VH BB 9124	9124-1117	-	27.05.2026	Yearly	
Log-Periodic Antenna	Schwarzbeck mess-elektronik	VUSLP 9111B	9111B-324	-	26.05.2026	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-1944	-	11.11.2026	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA 9170-0904	-	14.02.2026	Yearly	
EMI Test Receiver	Rohde & Schwarz	ESW44	101773	1.72.SP1	26.01.2026	Yearly	
Semi Anechoic Chamber	Frankonia	-	-	-	-	-	
Fully Anechoic Chamber	Albatross	-	-	-	-	-	
Spectrum Analyzer	Agilent	E4407B	US411927 72	A.14.07	16.01.2026	Yearly	Conducted Test Parameters
10 dB RF Attenuator (DUT-1)	Rohde & Schwarz	-	-	-	10.10.2026	Yearly	
EMI Receiver	Rohde & Schwarz	ESR7	101133	3.48 SP3	20.05.2026	Yearly	Conducted AC Power line Test
Two Line LISN	Scientific	SMLIN6 3-2	161101	-	06.03.2026	Yearly	
Pulse limiter [0 - 30 MHz]	Rohde & Schwarz	ESH3-Z2	100811	-	26.06.2026	Yearly	

Table 2: Instrument application Software versions

SL. No.	Test Type	Application software	Version
1	Radiated spurious emission measurement in FAC	EMC 32	10.60.20
2	Radiated spurious emission measurement in 10mtr SAC	BAT EMC	3.20.0.17
3	Conducted Emissions on a.c power Lines	BAT EMC	3.20.0.17

3 GENERAL PRODUCT INFORMATION

3.1 Product Function and Intended Use

The 75F Multi Sensor provides precise measurements of CO₂, occupancy, temperature, and humidity, and seamlessly connects to the 75F® Smart Node or HyperStat over Bluetooth to deliver real-time data that guides equipment control. This sensor can create a scalable network, expanding monitoring capabilities throughout the building.

3.2 Ratings and System Details of Equipment under Test

Table 3: Ratings and System Details as declared by Client*

Protocol		BLE (Bluetooth Low Energy)
Operating Frequency Range		2402MHz to 2480MHz
Channel Spacing		2MHz
Measured e.i.r.p (dBm)		3.39dBm@2480MHz
Modulation		GFSK
Data Rate		1Mbps
Number of antennas		1
Antenna Gain & Antenna Type		1.5dBi & RF ceramic chip antennas
Antenna Part Number		2450AT18D0100
Supply Voltage to Product		2*AA batteries of (1.5V of each)
Environmental conditions	Operating Condition	0°C to +50°C
	Storage Condition	-10°C to +60°C
EUT Dimension		45mm dia & 30mm depth

***Disclaimer:** The information/data is supplied by the client and the same is considered to arrive at the final value. Any changes made apart from the specified specification, can directly impact on the tests results. Refer the products user manual for more details.

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 10 von 40

Page 10 of 40

3.3 Measurement Uncertainty:

Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$

Table 4: Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	± 0.87 dB
Power Spectral Density, conducted	± 1.07 dB
Bandwidth, conducted	0.36 %
Unwanted Emissions, conducted	± 2.13 dB
All emissions, radiated	± 4.61 dB

4 TEST SET-UP AND OPERATION MODE

4.1 Principle of Configuration Selection

Transmission was enabled with highest possible duty cycle transmission on low, mid and high channel.

4.2 Test Operation and Test Software

Hardware Version Identification Number (HVIN):	Refer Page No: 4
Test Firmware:	1.0
Software Name:	Tera Term
Hardware Name:	WMS
Hardware revision:	1.2

4.3 Special Accessories and Auxiliary Equipment

- None

4.4 Simultaneous Transmission

- None

4.5 Countermeasures to achieve EMC Compliance

- None

4.6 List of frequencies

Frequency Band (MHz)	Channel No.	Channel Frequency (MHz)
2402 – 2480 BLE	0	2402
	1	2404
	2	2406
	3	2408
	:	:
	11	2424
	12	2426
	:	:
	19	2440
	20	2442
	:	:
	:	:
	:	:
	:	:
	36	2474
	37	2476
	38	2478
	39	2480

Table 5: List of BLE Centre frequencies

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 12 von 40

Page 12 of 40

Channel used for BLE testing.

Channel low: 2402MHz

Channel mid: 2440MHz

Channel high : 2480MHz

4.7 TUV Sample Identification

TUV Sample Identification number: A004181916-003 – Radiated test Sample.

A004181916-004 --Conducted test Sample

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 13 von 40

Page 13 of 40

5 Operational Description

The 75F® Wireless Multi Sensor is an all-in-one sensor providing temperature, humidity, occupancy, and CO₂ to augment the 75F® Smart Node for high-quality in zoning systems. This small sensor informs air quality and occupancy-based energy sequences for optimal IAQ and efficiency.

The sensor communicates to the nodes and stats via Bluetooth. The modern, low-profile design appeals to aesthetics and allows the sensor to blend in with office environments.

6 TEST METHODOLOGY

6.1 Radiated Emission Test

The radiated emission measurement was performed according to the procedures in ANSI C63.10-2020. The equipment under test (EUT) was placed at the middle of the 80 cm high turntable for below 1 GHz & 1.5 m height for above 1 GHz measurement, and the EUT is 3 meters far from the measuring antenna. The turntable was rotated 360° for obtaining the maximum emission. The height of the measuring antennas was scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained. The measurement above 1000 MHz was performed by horn antenna, the measurement below 30 MHz was performed by loop antenna, Measurement from 30 MHz to 200 MHz was performed by Balloon and Biconical Antenna, and measurement from 200 MHz to 1 GHz was performed by Log-Periodic Antenna.

The EUT was rotated around the X-, Y-, and Z-Axis and the results from worst case axis are recorded

6.1.1 Test Setup Configuration




Figure 1: Frequency Range 9 kHz- 30 MHz




Figure 2: Frequency Range 30 MHz – 200 MHz




Figure 3: Frequency Range 200 MHz - 1GHz




Figure 4: Frequency Range above 1 GHz

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 16 von 40
Page 16 of 40

7 TEST RESULTS


7.1 Maximum Peak Conducted Output Power

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (b)(3)/ RSS 247 Issue 4 Section 6.3.2 (a)
Test Method	ANSI C63.10:2020 and ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Measurement Bandwidth	1MHz
Detector	Peak
Port of testing	Conducted mode
Requirement	Power ≤ 1 W (30 dBm) & e.i.r.p ≤ 4 W (36dBm)

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = +21.8°C

Voltage = 2*AA batteries

Relative humidity: 55%

KDB Guidelines applied:

Measurements were made as per section 8.3.1.1 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 17 von 40
Page 17 of 40

Test results:


Note:

1. All the losses are included during measurement and final values are mentioned in the test report
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Cable loss (0.6dB)
3. This product does not support additional beamforming gain / directional gain, it uses single antenna and hence Directional gain of the single antenna is 1.5 dBi

Data rate	Channel frequency	Total Peak Output power (dBm)	Measured e.i.r.p (dBm)	FCC/ISED Limit (dBm)	e.i.r.p limit (dBm)
1 Mbps	2402.00	1.62	3.12	30.00	36.00
	2440.00	1.42	2.92	30.00	36.00
	2480.00	1.89	3.39	30.00	36.00

Test Plots:

Data Rate: 1Mbps



Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 18 von 40
Page 18 of 40


7.2 DTS Bandwidth & 99% Bandwidth

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (a) (2)/ RSS 247 Issue 4 Section 6.3.1 RSS Gen Issue 5 Section 6.7
Test Method	ANSI C63.10:2020 and ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Measurement Bandwidth	100 kHz for DTS Bandwidth 1% to 5% of OBW
Detector	Peak
Port of testing	Conducted mode
Requirement	Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = +21.8°C

Voltage = 2*AA batteries

Relative humidity: 55%

KDB Guidelines applied:

Measurements were made as per section 8.2 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 19 von 40
Page 19 of 40

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report.

Data rate	Channel frequency	99% BW (MHz)	6dB BW (MHz)	Limit (MHz)
1 Mbps	2402.00	1.01	0.63	0.50
	2440.00	1.01	0.63	0.50
	2480.00	1.00	0.63	0.50

Test Plots:

99% Bandwidth:
Data Rate: 1Mbps




Prüfbericht - Nr.:
Test Report No.:


IN26U4XI 001

Seite 20 von 40
Page 20 of 40


DTS Bandwidth:
Data Rate: 1Mbps



Channel frequency: 2402MHz



Channel frequency: 2440MHz



Channel frequency: 2480MHz

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 21 von 40
Page 21 of 40


7.3 Power Spectral Density

Result

Pass

Test Specification	FCC Part 15 Subpart C Section 15.247 (e)/ RSS 247 Issue 4 Section 6.3.1
Test Method	ANSI C63.10:2020 and ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Measurement Bandwidth	3 kHz
Detector	Peak
Port of testing	Conducted mode
Requirement	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 100 kHz band during any time interval of continuous transmission.

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = +21.8°C

Voltage = 2*AA batteries

Relative humidity: 55%

KDB Guidelines applied:

Measurements were made as per section 8.4 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001


Seite 22 von 40
Page 22 of 40

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report.

Data rate	Channel Frequency (MHz)	Measured PSD (dBm)	Limit (dBm in any 3kHz)
1 Mbps	2402.00	-5.10	8.00
	2440.00	-5.24	8.00
	2480.00	-4.78	8.00

Test Plots:



Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 23 von 40
Page 23 of 40


7.4 Emissions in non-restricted frequency bands and Conducted Spurious Emission

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d)/ RSS 247 Issue 4 Section 6.6
Test Method	ANSI C63.10:2020 and ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Measurement Bandwidth	100 kHz
Detector	Peak
Port of testing	Conducted mode
Requirement	In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = +21.8°C

Voltage = 2*AA batteries

Relative humidity: 55%

KDB Guidelines applied:

Measurements were made as per section 8.5 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 24 von 40
Page 24 of 40

Test results:


Note: All the losses are included during measurement and final values are mentioned in the test report

Band edge


Data rate	Channel Frequency (MHz)	Band edge frequency (MHz)	Value at band edge (A) (dBm)	Reference value (B) (dBm)	A-B (dBc)	Minimum Limit (dBc)
1 Mbps	2402.00	2400.00	-54.30	1.62	-55.92	-20.00
	2480.00	2483.50	-54.18	1.94	-56.12	-20.00

Reference Plots:


Data Rate: 1Mbps



Channel frequency: 2402MHz



Channel frequency: 2440MHz



Channel frequency: 2480MHz


Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001


Seite 25 von 40
Page 25 of 40

Bandedge Plots:

Data Rate: 1Mbps



Channel frequency: 2402MHz



Channel frequency: 2480MHz


Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 26 von 40
Page 26 of 40


7.4.1 Out-Of-Band Emissions

Data Rate: 1Mbps



Channel Frequency: 2402MHz

Frequency Range 30MHz – 1GHz




Channel Frequency: 2402MHz

Frequency Range 1GHz to 26.5GHz

Prüfbericht - Nr.:
Test Report No.:


IN26U4XI 001

Seite 27 von 40
Page 27 of 40



Channel Frequency: 2440MHz

Frequency Range: 30MHz – 1GHz




Channel Frequency: 2440MHz

Frequency Range: 1GHz – 26.5GHz

Prüfbericht - Nr.:
Test Report No.:


IN26U4XI 001

Seite 28 von 40
Page 28 of 40



Channel Frequency: 2480MHz

Frequency Range 30MHz – 1GHz



Channel Frequency: 2480MHz

Frequency Range: 1GHz – 26.5GHz

Prüfbericht - Nr.:
Test Report No.:

IN26U4XI 001

Seite 29 von 40
Page 29 of 40

7.5 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205)/ RSS-Gen Issue 5, Section 8.9 /8.10
Test Method	ANSI C63.10:2020 and ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Measurement Location	Semi Anechoic Chamber 9kHz - 1 GHz Fully Anechoic Chamber 1 GHz - 26GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

Table 6: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Conditions:

Temperature (Norm) = +21.8°C

Voltage = 2*AA batteries

Relative humidity: 55%

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 30 von 40

Page 30 of 40

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details


Test results for frequency range 9kHz – 30MHz

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported.

Table 7: Test results for frequency range 30MHz – 200MHz


Antenna Polarization	Measured Frequency (MHz)	Measured emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Vertical	58.23	32.96	40.00	-7.04
	60.54 (QP)	33.11	40.00	-38.74
	71.70	24.80	40.00	-15.20
Horizontal	31.36	5.53	40.00	-34.47
	45.81	2.88	40.00	-37.12
	48.60	2.00	40.00	-38.00
	50.17	2.56	40.00	-37.44

Test Plots:



Channel Frequency 30MHz – 200MHz

Polarization Vertical




Channel Frequency 30MHz – 200MHz

Polarization Horizontal

Table 8: Test results for frequency range 200MHz – 1GHz

Antenna Polarization	Measured Frequency (MHz)	Measured emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Vertical	292.79	18.36	46.00	-27.64
	325.49	18.81	46.00	-27.19
	364.97	20.99	46.00	-25.01
	717.32	21.64	46.00	-24.36
Horizontal	245.39	18.31	46.00	-27.69
	298.70	15.29	46.00	-30.71
	359.30	15.51	46.00	-30.49



Channel Frequency 200MHz – 1GHz

Polarization Vertical


Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 32 von 40

Page 32 of 40



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001

Seite 33 von 40

Page 33 of 40

Table 9: Test results for the frequencies above 1GHz:

Data Rate: 1Mbps

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Measured Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2402	2402(Pk)	Vertical	75.14	-	-
	2402(Av)		70.45	-	-
	2390(Pk)		37.85	74.00*	-36.15
	2390(Av)		24.18	54.00*	-29.82
	4804(Pk)		49.08	74.00	-24.92
	4804(Av)		40.23	54.00	-13.77
	7206(Pk)		51.17	74.00	-22.83
	7206(Av)		40.06	54.00	-13.94
	2402(Pk)	Horizontal	80.03	-	-
	2402(Av)		75.31	-	-
	2390(Pk)		37.47	74.00*	-36.53
	2390(Av)		24.29	54.00*	-29.71
	4804(Pk)		45.85	74.00	-28.15
	4804(Av)		35.85	54.00	-18.15
	7206(Pk)		49.81	74.00	-24.19
	7206(Av)		38.69	54.00	-15.31
2440	2440(Pk)	Vertical	77.46	-	-
	2440(Av)		72.78	-	-
	4880(Pk)		45.12	74.00	-28.88
	4880(Av)		34.91	54.00	-19.09
	7320(Pk)		48.57	74.00	-25.43
	7320(Av)		35.25	54.00	-18.75
	2440(Pk)	Horizontal	80.58	-	-
	2440(Av)		75.92	-	-
	4880(Pk)		43.58	74.00	-30.42
	4880(Av)		32.75	54.00	-21.25
	7320(Pk)		49.30	74.00	-24.70
	7320(Av)		37.42	54.00	-16.58
2480	2480(Pk)	Vertical	76.42	-	-
	2480(Av)		71.70	-	-
	2483.5(Pk)		37.17	74.00*	-36.83
	2483.5(Av)		23.87	54.00*	-30.13
	4960(Pk)		49.47	74.00	-24.53
	4960(Av)		40.68	54.00	-13.32
	7440(Pk)		49.06	74.00	-24.94
	7440(Av)		37.57	54.00	-16.43
	2480(Pk)	Horizontal	79.37	-	-
	2480(Av)		74.67	-	-
	2483.5(Pk)		37.19	74.00*	-36.81
	2483.5(Av)		23.94	54.00*	-30.06
	4960(Pk)		49.95	74.00	-24.05
	4960(Av)		37.46	54.00	-16.54
	7440(Pk)		48.90	74.00	-25.10
	7440(Av)		36.20	54.00	-17.80

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector;

Av: Average Detector

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001


Seite 34 von 40

Page 34 of 40

Test Plots:


Restricted Bands of Operation

Data Rate: 1Mbps




Channel Frequency: 2402MHz

Polarization: Vertical




Channel Frequency: 2402MHz

Polarization: Horizontal




Channel Frequency: 2440MHz

Polarization: Vertical




Channel Frequency: 2440MHz

Polarization: Horizontal



Channel Frequency: 2480MHz

Polarization: Vertical



Channel Frequency: 2480MHz

Polarization: Horizontal

Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001


Seite 37 von 40

Page 37 of 40

Spurious Radiated emission:


Data Rate: 1Mbps

Channel frequency: 2402MHz



Polarization: Vertical


Frequency range: 1GHz to 18GHz



Polarization: Horizontal


Frequency range: 1GHz to 18GHz

Channel frequency: 2440MHz



Polarization: Vertical

Frequency range: 1GHz to 18GHz



Polarization: Horizontal

Frequency range: 1GHz to 18GHz


Prüfbericht - Nr.:

Test Report No.:

IN26U4XI 001


Seite 39 von 40
Page 39 of 40

Channel frequency: 2480MHz



Polarization: Vertical

Frequency range: 1GHz to 18GHz



Polarization: Horizontal

Frequency range: 1GHz to 18GHz

8 LIST OF TABLES

Table 1: List of test and measurement instruments	8
Table 2: Instrument application Software versions	8
Table 3: Ratings and System Details as declared by Client*	9
Table 4: Measurement Uncertainty	10
Table 5: List of BLE Centre frequencies	11
Table 6: Transmitter limits for Radiated emission	29
Table 7: Test results for frequency range 30MHz – 200MHz	30
Table 8: Test results for frequency range 200MHz – 1GHz	31
Table 9: Test results for the frequencies above 1GHz:	33

9 List of Figures

Figure 1: Frequency Range 9 kHz- 30 MHz	14
Figure 2: Frequency Range 30 MHz – 200 MHz	14
Figure 3: Frequency Range 200 MHz - 1GHz	15
Figure 4: Frequency Range above 1 GHz	15

End of test report