FCC REPORT
(BLE)

Applicant:	Wavee Group Inc.
Address of Applicant:	232 Manning Avenue, Toronto, Ontario, M6J 2K7, Canada
Equipment Under Test (EUT)	
Product Name:	WAVEE W-1 Electric Toothbrush Speaker System
Model No.:	W1BTS
FCC ID:	2AW2XW1BTS
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	13 Jul., 2020
Date of Test:	14 Jul., to 20 Aug., 2020
Date of report issued:	21 Aug., 2020
Test Result:	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	*21 Aug., 2020*	*Original*

Tested by: YT Yang ***Date:*** *21 Aug., 2020*

Test Engineer

Reviewed by: Winner zhang ***Date:*** *21 Aug., 2020*

Project Engineer

3 Contents

Page

1 COVER PAGE 1
2 VERSION 2
3 CONTENTS 3
4 TEST SUMMARY 4
5 GENERAL INFORMATION 5
5.1 CLIENT INFORMATION 5
5.2 GENERAL DESCRIPTION OF E.U.T 5
5.3 TEST ENVIRONMENT AND MODE, AND TEST SAMPLES PLANS 6
5.4 DESCRIPTION OF SUPPORT UNITS 6
5.5 MEASUREMENT UNCERTAINTY 6
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD 6
5.7 LABORATORY FACILITY 6
5.8 LABORATORY LOCATION 7
5.9 TEST INSTRUMENTS LIST 7
6 TEST RESULTS AND MEASUREMENT DATA 8
6.1 ANTENNA REQUIREMENT: 8
6.2 CONDUCTED EMISSION 9
6.3 CONDUCTED OUTPUT POWER 12
6.4 OCCUPY BANDWIDTH 14
6.5 POWER SPECTRAL DENSITY 17
6.6 BAND EDGE 19
6.6.1 Conducted Emission Method 19
6.6.2 Radiated Emission Method 21
6.7 SPURIOUS EMISSION 30
6.7.1 Conducted Emission Method 30
6.7.2 Radiated Emission Method 32
7 TEST SETUP PHOTO 38
8 EUT CONSTRUCTIONAL DETAILS 40

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna requirement	15.203 & 15.247 (b)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247 (d)	Pass
Spurious Emission	15.205 & 15.209	Pass

Remark:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *N/A: Not Applicable.*
3. *The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).*

Test Method:	*ANSI C63.10-2013* *KDB 558074 D01 15.247 Meas Guidance v05r02*

5 General Information

5.1 Client Information

Applicant:	Wavee Group Inc.
Address:	232 Manning Avenue, Toronto, Ontario, M6J 2K7, Canada
Manufacturer:	Wavee Group Inc.
Address:	232 Manning Avenue, Toronto, Ontario, M6J 2K7, Canada
Factory:	SHENZHEN YINHONG ELECTRONICS CO., LTD
Address:	2nd floor 2# building Hongzhu Yongqi Techno park, lezhujiao village, xixiang Baoan district, Shenzhen

5.2 General Description of E.U.T.

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System
Model No.:	W1BTS
Operation Frequency:	2402-2480 MHz
Channel numbers:	40
Channel separation:	2 MHz
Modulation technology:	GFSK
Data speed :	1Mbps & 2Mbps
Antenna Type:	PCB Antenna
Antenna gain:	1.5 dBi
Power supply:	Rechargeable Li-ion Polymer Battery DC3.7V, 2800mAh
AC adapter:	Model: W&T-AD1812B050200UU Input: AC100-240V, 50/60Hz, 0.35A Output: DC 5.0V, 2A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test. Channel No. 0, 20 & 39 were selected as Lowest, Middle and Highest channel.

5.3 Test environment and mode, and test samples plans

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Radiated Emission: The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.	
Test Samples Plans:	
Samples Number	**Used for Test Items**
4#	Radiated measurements test method
Remark: *Shenzhen Zhongjian* Nanfang *Testing Co., Ltd. is only responsible for the test project data of the above samples, and will keep the above samples for a month.*	

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.9 Test Instruments list

Radiated Emission:

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
				07-22-2020	07-21-2023
Loop Antenna	SCHWARZBECK	FMZB1519B	044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021
RF Switch Unit	MWRFTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTEST	MTS8200	Version: 2.0.0.0		

Conducted Emission:

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
				07-21-2020	07-20-2023
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data

6.1 Antenna requirement:

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The BLE antenna is an PCB Antenna which cannot replace by end-user, the best-case gain of the antenna is 1.5 dBi.	

6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207
Test Frequency Range:	150 kHz to 30 MHz
Class / Severity:	Class B
Receiver setup:	RBW=9kHz, VBW=30kHz
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Product name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product model:**	W1BTS
Test by:	YT	**Test mode:**	BLE Tx mode
Test frequency:	150 kHz ~ 30 MHz	**Phase:**	Line
Test voltage:	AC 120 V/60 Hz	**Environment:**	Temp: 22.5℃ Huni: 55%



	Freq	Read Level	LISN Factor	Cable Loss	Aux Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.162	33.00	-0.58	10.77	-0.08	43.11	65.34	-22.23	QP
2	0.174	19.33	-0.58	10.77	-0.11	29.41	54.77	-25.36	Average
3	0.186	17.41	-0.59	10.76	-0.13	27.45	54.20	-26.75	Average
4	0.198	32.26	-0.59	10.76	-0.16	42.27	63.71	-21.44	QP
5	0.249	28.93	-0.57	10.75	-0.22	38.89	61.78	-22.89	QP
6	0.358	16.33	-0.51	10.73	0.16	26.71	48.78	-22.07	Average
7	0.361	28.97	-0.51	10.73	0.17	39.36	58.69	-19.33	QP
8	0.447	16.96	-0.46	10.74	0.05	27.29	46.93	-19.64	Average
9	0.567	29.98	-0.47	10.76	-0.37	39.90	56.00	-16.10	QP
10	0.579	19.71	-0.47	10.76	-0.37	29.63	46.00	-16.37	Average
11	22.535	27.00	-0.98	10.90	0.94	37.86	60.00	-22.14	QP
12	22.535	14.75	-0.98	10.90	0.94	25.61	50.00	-24.39	Average

Notes:

1. *An initial pre-scan was performed on the line and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level =Receiver Read level + LISN Factor + Aux Factor + Cable Loss.*

Product name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product model:**	W1BTS
Test by:	YT	**Test mode:**	BLE Tx mode
Test frequency:	150 kHz ~ 30 MHz	**Phase:**	Neutral
Test voltage:	AC 120 V/60 Hz	**Environment:**	Temp: 22.5℃ Huni: 55%



	Freq	Read Level	LISN Factor	Cable Loss	Aux Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	29.71	-0.69	10.78	0.01	39.81	66.00	-26.19	QP
2	0.166	28.52	-0.68	10.77	0.01	38.62	65.16	-26.54	QP
3	0.230	25.76	-0.67	10.75	0.00	35.84	62.44	-26.60	QP
4	0.513	21.44	-0.65	10.76	0.03	31.58	46.00	-14.42	Average
5	0.579	32.38	-0.65	10.76	0.03	42.52	56.00	-13.48	QP
6	0.582	28.06	-0.65	10.76	0.03	38.20	46.00	-7.80	Average
7	0.984	22.68	-0.68	10.87	0.08	32.95	56.00	-23.05	QP
8	0.984	22.25	-0.68	10.87	0.08	32.52	46.00	-13.48	Average
9	1.135	18.48	-0.69	10.89	0.10	28.78	46.00	-17.22	Average
10	1.197	17.36	-0.69	10.89	0.10	27.66	46.00	-18.34	Average
11	22.535	23.47	-1.31	10.90	0.50	33.56	60.00	-26.44	QP
12	22.535	15.89	-1.31	10.90	0.50	25.98	50.00	-24.02	Average

Notes:

1. *An initial pre-scan was performed on the line and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.*

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Test CH	Maximum Conducted Output Power (dBm)		Limit(dBm)	Result
	1M PHY	2M PHY		
Lowest	3.32	3.10	30.00	Pass
Middle	2.67	2.61		
Highest	2.06	1.97		

Test plot as follows:

1M PHY	2M PHY
	
Date: 19.AUG.2020 11:56:02	Date: 19.AUG.2020 11:58:28
Lowest channel	Lowest channel
	
Date: 19.AUG.2020 11:56:23	Date: 19.AUG.2020 11:58:01
Middle channel	Middle channel
	
Date: 19.AUG.2020 11:56:49	Date: 19.AUG.2020 11:57:42
Highest channel	Highest channel

6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Test CH	6dB Emission Bandwidth (MHz)		Limit(kHz)	Result
	1M PHY	2M PHY		
Lowest	0.732	1.280	>500	Pass
Middle	0.708	1.280		
Highest	0.726	1.280		
Test CH	99% Occupy Bandwidth (MHz)		Limit(kHz)	Result
	1M PHY	2M PHY		
Lowest	2.020	2.080	N/A	N/A
Middle	1.026	2.020		
Highest	1.032	2.020		

Test plot as follows:

1M PHY

6dB EBW



Date: 19.AUG.2020 12:05:51

Lowest channel

99% OBW



Date: 19.AUG.2020 12:08:09

Lowest channel



Date: 19.AUG.2020 12:05:10

Middle channel



Date: 19.AUG.2020 12:06:46

Middle channel



Date: 19.AUG.2020 12:04:26

Highest channel



Date: 19.AUG.2020 12:07:03

Highest channel

2M PHY

6dB EBW



Date: 19.AUG.2020 12:00:07

Lowest channel

99% OBW



Date: 19.AUG.2020 14:10:54

Lowest channel



Date: 19.AUG.2020 12:01:01

Middle channel



Date: 19.AUG.2020 12:07:52

Middle channel



Date: 19.AUG.2020 12:03:27

Highest channel



Date: 19.AUG.2020 12:07:30

Highest channel

6.5 Power Spectral Density

Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8 dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Test CH	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	1M PHY	2M PHY		
Lowest	-12.78	-16.40	8.00	Pass
Middle	-13.46	-17.05		
Highest	-14.48	-17.54		

Test plots as follow:

1M PHY	2M PHY
	
Date: 19.AUG.2020 12:10:49	Date: 19.AUG.2020 12:08:58
Lowest channel	Lowest channel
	
Date: 19.AUG.2020 12:10:31	Date: 19.AUG.2020 12:09:19
Middle channel	Middle channel
	
Date: 19.AUG.2020 12:10:12	Date: 19.AUG.2020 12:09:41
Highest channel	Highest channel

6.6 Band Edge

6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plots as follow:

1M PHY



Date: 19.AUG.2020 12:12:10

Lowest Channel



Date: 19.AUG.2020 12:15:10

Highest Channel

2M PHY



Date: 19.AUG.2020 12:13:13

Lowest Channel



Date: 19.AUG.2020 12:14:19

Highest Channel

6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.205 and 15.209
Test Frequency Range:	2310 MHz to 2390 MHz and 2483.5MHz to 2500 MHz
Test Distance:	3m

Receiver setup:

Frequency	Detector	RBW	VBW	Remark
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	RMS	1MHz	3MHz	Average Value

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
Above 1GHz	54.00	Average Value
	74.00	Peak Value

Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test setup:



Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

1M PHY:

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Lowest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	19.21	27.03	4.28	1.68	0.00	52.20	74.00	-21.80	Peak
2	2390.000	11.08	27.03	4.28	1.68	0.00	44.07	54.00	-9.93	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Lowest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.06	27.03	4.28	1.68	0.00	54.05	74.00	-19.95	Peak
2	2390.000	13.93	27.03	4.28	1.68	0.00	46.92	54.00	-7.08	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Highest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.15	27.27	4.38	1.70	0.00	54.50	74.00	-19.50	Peak
2	2483.500	13.23	27.27	4.38	1.70	0.00	46.58	54.00	-7.42	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Highest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.55	27.27	4.38	1.70	0.00	54.90	74.00	-19.10	Peak
2	2483.500	13.23	27.27	4.38	1.70	0.00	46.58	54.00	-7.42	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

2M PHY:

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Lowest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.91	27.03	4.28	1.68	0.00	54.90	74.00	-19.10	Peak
2	2390.000	13.05	27.03	4.28	1.68	0.00	46.04	54.00	-7.96	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Lowest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.70	27.03	4.28	1.68	0.00	53.69	74.00	-20.31	Peak
2	2390.000	12.90	27.03	4.28	1.68	0.00	45.89	54.00	-8.11	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Highest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.15	27.27	4.38	1.70	0.00	55.50	74.00	-18.50	Peak
2	2483.500	14.78	27.27	4.38	1.70	0.00	48.13	54.00	-5.87	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Channel:	Highest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.78	27.27	4.38	1.70	0.00	56.13	74.00	-17.87	Peak
2	2483.500	14.93	27.27	4.38	1.70	0.00	48.28	54.00	-5.72	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

6.7 Spurious Emission

6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:

1M PHY	2M PHY
	
Date: 19.AUG.2020 13:45:44	Date: 19.AUG.2020 13:42:36
Lowest channel	Lowest channel
	
Date: 19.AUG.2020 13:46:58	Date: 19.AUG.2020 13:38:24
Middle channel	Middle channel
	
Date: 19.AUG.2020 13:48:56	Date: 19.AUG.2020 13:40:32
Highest channel	Highest channel

6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.205 and 15.209
Test Frequency Range:	9kHz to 25GHz
Test Distance:	3m

Receiver setup:

Frequency	Detector	RBW	VBW	Remark
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	RMS	1MHz	3MHz	Average Value

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
	74.0	Peak Value

Test Procedure:

1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test setup:

Below 1GHz



Above 1GHz

	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 2. 9 kHz to 30MHz is lower than the limit 20dB, so only shows the data of above 30MHz in this report.

Measurement Data (worst case):

Below 1GHz:

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	30.424	50.69	11.87	0.39	0.00	29.98	32.97	40.00	-7.03	QP
2	73.359	52.12	11.06	0.45	0.00	29.69	33.94	40.00	-6.06	QP
3	145.861	50.66	13.98	0.61	0.00	29.24	36.01	43.50	-7.49	QP
4	183.201	45.95	17.09	0.69	0.00	28.95	34.78	43.50	-8.72	QP
5	218.309	44.39	18.38	0.74	0.00	28.72	34.79	46.00	-11.21	QP
6	339.589	44.73	18.78	0.92	0.00	28.54	35.89	46.00	-10.11	QP

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*
3. *The Aux Factor is a notch filter switch box loss, this item is not used.*

Product Name:	WAVEE W-1 Electric Toothbrush Speaker System	**Product Model:**	W1BTS
Test By:	YT	**Test mode:**	BLE Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	173.205	45.46	16.69	0.66	0.00	29.02	33.79	43.50	-9.71	QP
2	191.745	42.57	17.55	0.70	0.00	28.89	31.93	43.50	-11.57	QP
3	215.268	40.57	18.37	0.74	0.00	28.73	30.95	43.50	-12.55	QP
4	305.680	43.47	18.71	0.87	0.00	28.46	34.59	46.00	-11.41	QP
5	329.039	44.50	18.76	0.90	0.00	28.51	35.65	46.00	-10.35	QP
6	609.922	41.37	19.94	1.22	0.00	28.91	33.62	46.00	-12.38	QP

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*
3. *The Aux Factor is a notch filter switch box loss, this item is not used.*

Above 1GHz
1M PHY:

Test channel: Lowest channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	52.87	30.78	6.80	2.44	41.81	51.08	74.00	-22.92	Vertical
4804.00	56.44	30.78	6.80	2.44	41.81	54.65	74.00	-19.35	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	48.22	30.78	6.80	2.44	41.81	46.43	54.00	-7.57	Vertical
4804.00	48.86	30.78	6.80	2.44	41.81	47.07	54.00	-6.93	Horizontal
Test channel: Middle channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	52.90	30.96	6.86	2.47	41.84	51.35	74.00	-22.65	Vertical
4884.00	56.31	30.96	6.86	2.47	41.84	54.76	74.00	-19.24	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	48.66	30.96	6.86	2.47	41.84	47.11	54.00	-6.89	Vertical
4884.00	48.62	30.96	6.86	2.47	41.84	47.07	54.00	-6.93	Horizontal
Test channel: Highest channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	53.20	31.11	6.91	2.49	41.87	51.84	74.00	-22.16	Vertical
4960.00	56.61	31.11	6.91	2.49	41.87	55.25	74.00	-18.75	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	48.40	31.11	6.91	2.49	41.87	47.04	54.00	-6.96	Vertical
4960.00	48.49	31.11	6.91	2.49	41.87	47.13	54.00	-6.87	Horizontal

Remark:
1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss + Aux Factor – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

2M PHY:

Test channel: Lowest channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	52.16	30.78	6.80	2.44	41.81	50.37	74.00	-23.63	Vertical
4804.00	56.56	30.78	6.80	2.44	41.81	54.77	74.00	-19.23	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	48.66	30.78	6.80	2.44	41.81	46.87	54.00	-7.13	Vertical
4804.00	48.83	30.78	6.80	2.44	41.81	47.04	54.00	-6.96	Horizontal
Test channel: Middle channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	52.28	30.96	6.86	2.47	41.84	50.73	74.00	-23.27	Vertical
4884.00	56.87	30.96	6.86	2.47	41.84	55.32	74.00	-18.68	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	48.87	30.96	6.86	2.47	41.84	47.32	54.00	-6.68	Vertical
4884.00	48.98	30.96	6.86	2.47	41.84	47.43	54.00	-6.57	Horizontal
Test channel: Highest channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	51.99	31.11	6.91	2.49	41.87	50.63	74.00	-23.37	Vertical
4960.00	56.46	31.11	6.91	2.49	41.87	55.10	74.00	-18.90	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	48.48	31.11	6.91	2.49	41.87	47.12	54.00	-6.88	Vertical
4960.00	49.32	31.11	6.91	2.49	41.87	47.96	54.00	-6.04	Horizontal

Remark:

3. *Final Level =Receiver Read level + Antenna Factor + Cable Loss + Aux Factor – Preamplifier Factor.*
4. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*