

# TEST REPORT

**Application No.:** SZCR2507002930AT  
**Applicant:** Solaborate Inc.  
**Address of Applicant:** 2605 Enterprise RD E Suite 150, Clearwater, Florida, 33759, United States  
**Manufacturer:** Solaborate Inc.  
**Address of Manufacturer:** 2605 Enterprise RD E Suite 150, Clearwater, Florida, 33759, United States  
**Equipment Under Test (EUT):**  
**EUT Name:** Whiteboard  
**Model No.:** HC2705T, HC3205T ♣  
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.  
**Trade Mark:** hellocare.ai  
**FCC ID:** 2AW3MWHITEBOARD-HDC  
**Standard(s) :** 47 CFR Part 15, Subpart C  
**Date of Receipt:** 2025-07-07  
**Date of Test:** 2025-07-12 to 2025-08-18  
**Date of Issue:** 2025-08-19

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu  
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (EMC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700293006

Page: 2 of 29

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2025-08-19 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                            |  |  |
|--------------------------|--|----------------------------|--|--|
| Authorized for issue by: |  |                            |  |  |
|                          |  | Edison Li                  |  |  |
|                          |  | Edison Li/Project Engineer |  |  |
|                          |  | Eric Fu                    |  |  |
|                          |  | Eric Fu/Reviewer           |  |  |



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 2 Test Summary

| Radio Spectrum Technical Requirement |                           |        |                                  |        |
|--------------------------------------|---------------------------|--------|----------------------------------|--------|
| Item                                 | Standard                  | Method | Requirement                      | Result |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C | N/A    | 47 CFR Part 15, Subpart C 15.203 | Pass   |

| Radio Spectrum Matter Part                                |                           |                                 |                                           |        |
|-----------------------------------------------------------|---------------------------|---------------------------------|-------------------------------------------|--------|
| Item                                                      | Standard                  | Method                          | Requirement                               | Result |
| 20dB Bandwidth                                            | 47 CFR Part 15, Subpart C | ANSI C63.10-2020 Section 6.9.2  | 47 CFR Part 15, Subpart C 15.215          | Pass   |
| Conducted Emissions at AC Mains Power Port (150kHz-30MHz) |                           | ANSI C63.10-2020 Section 6.2    | 47 CFR Part 15, Subpart C 15.207          | Pass   |
| Restricted Bands                                          |                           | ANSI C63.10-2020 Section 6.10.5 | 47 CFR Part 15, Subpart C 15.205          | Pass   |
| Radiated Emissions (9kHz-30MHz)                           |                           | ANSI C63.10-2020 Section 6.4    | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Emissions (30MHz-1GHz)                           |                           | ANSI C63.10-2020 Section 6.5    | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |

### Declaration of EUT Family Grouping:

Model No.: HC2705T, HC3205T

The model HC2705T and HC3205T were tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model No., appearance size, power adapter, color and antenna(same antenna type, different antenna gain).



### 3 Contents

|                                                                 | Page |
|-----------------------------------------------------------------|------|
| 1 Cover Page .....                                              | 1    |
| 2 Test Summary .....                                            | 3    |
| 3 Contents .....                                                | 4    |
| 4 General Information .....                                     | 6    |
| 4.1 Details of E.U.T. ....                                      | 6    |
| 4.2 Description of Support Units .....                          | 6    |
| 4.3 Measurement Uncertainty .....                               | 6    |
| 4.4 Test Location .....                                         | 7    |
| 4.5 Test Facility .....                                         | 7    |
| 4.6 Deviation from Standards .....                              | 7    |
| 4.7 Abnormalities from Standard Conditions .....                | 7    |
| 5 Equipment List .....                                          | 8    |
| 6 Radio Spectrum Technical Requirement .....                    | 10   |
| 6.1 Antenna Requirement .....                                   | 10   |
| 6.1.1 Test Requirement: .....                                   | 10   |
| 6.1.2 Conclusion .....                                          | 10   |
| 7 Radio Spectrum Matter Test Results .....                      | 11   |
| 7.1 Conducted Emissions at Mains Terminals (150kHz-30MHz) ..... | 11   |
| 7.1.1 E.U.T. Operation .....                                    | 11   |
| 7.1.2 Test Mode Description .....                               | 11   |
| 7.1.3 Test Setup Diagram .....                                  | 11   |
| 7.1.4 Measurement Procedure and Data .....                      | 12   |
| 7.2 20dB Bandwidth .....                                        | 15   |
| 7.2.1 E.U.T. Operation .....                                    | 15   |
| 7.2.2 Test Mode Description .....                               | 15   |
| 7.2.3 Test Setup Diagram .....                                  | 15   |
| 7.2.4 Measurement Procedure and Data .....                      | 15   |
| 7.3 Restricted Bands .....                                      | 17   |
| 7.3.1 E.U.T. Operation .....                                    | 17   |
| 7.3.2 Test Mode Description .....                               | 17   |
| 7.3.3 Test Setup Diagram .....                                  | 17   |
| 7.3.4 Measurement Procedure and Data .....                      | 17   |
| 7.3.5 Measurement Procedure and Data .....                      | 18   |
| 7.4 Radiated Emissions (9kHz-30MHz) .....                       | 19   |
| 7.4.1 E.U.T. Operation .....                                    | 20   |
| 7.4.2 Test Mode Description .....                               | 20   |
| 7.4.3 Test Setup Diagram .....                                  | 20   |
| 7.4.4 Measurement Procedure and Data .....                      | 20   |
| 7.5 Radiated Emissions (30MHz-1GHz) .....                       | 25   |



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700293006

Page: 5 of 29

|       |                                               |    |
|-------|-----------------------------------------------|----|
| 7.5.1 | E.U.T. Operation .....                        | 25 |
| 7.5.2 | Test Mode Description .....                   | 25 |
| 7.5.3 | Test Setup Diagram .....                      | 25 |
| 7.5.4 | Measurement Procedure and Data.....           | 26 |
| 8     | Test Setup Photo .....                        | 29 |
| 9     | EUT Constructional Details (EUT Photos) ..... | 29 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:        | <p>Switching Adapter(HC2705T)<br/>Model: FJ-SW20171204000<br/>Input: AC 100-240V, 50/60Hz, 1.5A Max<br/>Output: DC 12.0V, 4.0A, 48.0W</p> <p>Switching Adapter(HC3205T)<br/>Model: S065-1A120500B3<br/>Input: AC 100-240V, 50/60Hz, 1.5A Max<br/>Output: DC 12.0V, 5.0A 60.0W</p> <p>Note: The differences between all adapters are evaluated in the FCC part15B report, and this report only shows the results for the worst adapters.</p> |
| Cable(s):            | <p>AC cable:140cm unshielded<br/>DC cable:140cm with a ferrite core</p>                                                                                                                                                                                                                                                                                                                                                                     |
| Operation Frequency: | 125KHz                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Modulation Type:     | ASK                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Antenna Type:        | Loop Antenna                                                                                                                                                                                                                                                                                                                                                                                                                                |

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

### 4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|-------------|--------------|-----------|------------|
| --          | --           | --        | --         |

The EUT has been tested as an independent unit.

### 4.3 Measurement Uncertainty

| Test Item                                             | Measurement Uncertainty                               |
|-------------------------------------------------------|-------------------------------------------------------|
| Conducted Emissions at Mains Terminals (150kHz-30MHz) | $\pm 3.1\text{dB}$                                    |
| 20dB Bandwidth                                        | $\pm 3\%$                                             |
| Restricted Bands                                      | $\pm 0.3\%$                                           |
| Radiated Emissions (9kHz-30MHz)                       | $\pm 3.6\text{dB}$                                    |
| Radiated Emissions (30MHz-1GHz)                       | $\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m |

Remark:

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR/ETSI}}$  (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700293006

Page: 7 of 29

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 4.6 Deviation from Standards

None

### 4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 5 Equipment List

| Conducted Emissions at Mains Terminals (150kHz-30MHz) |                  |                  |               |            |              |
|-------------------------------------------------------|------------------|------------------|---------------|------------|--------------|
| Equipment                                             | Manufacturer     | Model No.        | Inventory No. | Cal Date   | Cal Due Date |
| Shielding Room                                        | ZhongYu Electron | GB-88            | SEM001-06     | 2025-05-07 | 2028-05-06   |
| EMI Test Receiver                                     | Rohde&Schwarz    | ESR              | SZ-WRG-M-047  | 2025-01-08 | 2026-01-07   |
| Measurement Software                                  | AUDIX            | e3 V8.2014-6-27a | N/A           | N/A        | N/A          |
| Coaxial Cable                                         | SGS              | N/A              | SEM024-01     | 2025-07-05 | 2026-07-04   |
| LISN                                                  | Rohde&Schwarz    | ENV216           | SEM007-01     | 2025-07-25 | 2026-07-24   |
| LISN                                                  | ETS-LINDGREN     | 3816/2           | SEM007-02     | 2025-03-03 | 2026-03-02   |

| 20dB Bandwidth       |                 |               |               |            |              |
|----------------------|-----------------|---------------|---------------|------------|--------------|
| Equipment            | Manufacturer    | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| DC Power Supply      | Zhao Xin        | PS-305D       | SEM011-13     | 2025-07-24 | 2026-07-23   |
| Spectrum Analyzer    | Rohde & Schwarz | FSP30         | SEM004-06     | 2024-09-14 | 2025-09-13   |
| Measurement Software | TST PASS        | TST PASS V2.0 | N/A           | N/A        | N/A          |
| Coaxial Cable        | SGS             | N/A           | SEM031-01     | 2025-07-05 | 2026-07-04   |
| Attenuator           | Huber+Suhner    | 6620_SMA-50-1 | SEM021-09     | 2025-03-03 | 2026-03-02   |

| Restricted Bands          |                      |                 |               |            |              |
|---------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                 | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| 10m Semi-Anechoic Chamber | SAEMC                | FSAC1018        | SEM001-03     | 2025-03-21 | 2026-03-20   |
| MXE EMI receiver          | KEYSIGHT             | N9038A          | SEM004-16     | 2025-07-25 | 2026-07-24   |
| Trilog-Broadband Antenna  | Schwarzbeck          | VULB9168        | SEM003-18     | 2023-09-23 | 2025-09-22   |
| Pre-amplifier             | Sonoma Instrument Co | 310N            | SEM005-04     | 2025-03-04 | 2026-03-03   |
| Loop Antenna              | ETS-Lindgren         | 6502            | SEM003-08     | 2023-11-20 | 2025-11-19   |
| Measurement Software      | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable             | SGS                  | N/A             | SEM029-01     | 2025-07-05 | 2026-07-04   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch  
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700293006

Page: 9 of 29

| Radiated Emissions (9kHz-30MHz) |                      |                 |               |            |              |
|---------------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                       | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| 10m Semi-Anechoic Chamber       | SAEMC                | FSAC1018        | SEM001-03     | 2025-03-21 | 2026-03-20   |
| MXE EMI receiver                | KEYSIGHT             | N9038A          | SEM004-16     | 2025-07-25 | 2026-07-24   |
| Trilog-Broadband Antenna        | Schwarzbeck          | VULB9168        | SEM003-18     | 2023-09-23 | 2025-09-22   |
| Pre-amplifier                   | Sonoma Instrument Co | 310N            | SEM005-04     | 2025-03-04 | 2026-03-03   |
| Loop Antenna                    | ETS-Lindgren         | 6502            | SEM003-08     | 2023-11-20 | 2025-11-19   |
| Measurement Software            | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable                   | SGS                  | N/A             | SEM029-01     | 2025-07-05 | 2026-07-04   |

| Radiated Emissions (30MHz-1GHz) |                      |                 |               |            |              |
|---------------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                       | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber        | ETS-LINDGREN         | N/A             | SEM001-01     | 2023-06-19 | 2026-06-18   |
| MXE EMI Receiver                | Agilent Technologies | N9038A          | SEM004-15     | 2025-07-25 | 2026-07-24   |
| BiConiLog Antenna               | ETS-LINDGREN         | 3142C           | SEM003-01     | 2023-09-16 | 2025-09-15   |
| Pre-Amplifier                   | Agilent Technologies | 8447D           | SEM005-01     | 2025-03-04 | 2026-03-03   |
| Measurement Software            | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable                   | SGS                  | N/A             | SEM025-01     | 2025-07-05 | 2026-07-04   |

| General used equipment          |                                           |           |               |            |              |
|---------------------------------|-------------------------------------------|-----------|---------------|------------|--------------|
| Equipment                       | Manufacturer                              | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| Humidity/ Temperature Indicator | deli                                      | 8838      | SEM002-32     | 2025-07-23 | 2026-07-22   |
| Humidity/ Temperature Indicator | deli                                      | 8838      | SEM002-33     | 2025-07-23 | 2026-07-22   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3      | SEM002-01     | 2025-03-03 | 2026-03-02   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to Internal photos



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C


Humidity: 44.5 % RH

Atmospheric Pressure: 1020 mbar

#### 7.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                      |
|-----------------------|-----------|----------------------------------|
| Final test            | 11        | TX mode with modulation(125KHz). |

#### 7.1.3 Test Setup Diagram




## 7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 11; Line: Live line



Site : Shielding Room

Condition: Line


Job No. : 02930AT

Test mode: 11

|     | Freq    | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|-----|---------|------------|-------------|------------|-------|------------|------------|---------|
|     | MHz     | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1 * | 0.1540  | 0.01       | 10.19       | 48.01      | 58.21 | 65.78      | -7.57      | QP      |
| 2 * | 0.1540  | 0.01       | 10.19       | 29.40      | 39.60 | 55.78      | -16.18     | Average |
| 3   | 0.3003  | 0.01       | 9.85        | 27.02      | 36.88 | 60.24      | -23.36     | QP      |
| 4   | 0.3003  | 0.01       | 9.85        | 16.15      | 26.01 | 50.24      | -24.23     | Average |
| 5   | 0.9233  | 0.01       | 9.60        | 11.06      | 20.67 | 56.00      | -35.33     | QP      |
| 6   | 0.9233  | 0.01       | 9.60        | 1.41       | 11.02 | 46.00      | -34.98     | Average |
| 7   | 1.5851  | 0.01       | 9.58        | 10.08      | 19.67 | 56.00      | -36.33     | QP      |
| 8   | 1.5851  | 0.01       | 9.58        | 0.39       | 9.98  | 46.00      | -36.02     | Average |
| 9   | 3.7594  | 0.01       | 9.65        | 14.48      | 24.14 | 56.00      | -31.86     | QP      |
| 10  | 3.7594  | 0.01       | 9.65        | 2.85       | 12.51 | 46.00      | -33.49     | Average |
| 11  | 12.9885 | 0.24       | 9.84        | 31.05      | 41.13 | 60.00      | -18.87     | QP      |
| 12  | 12.9885 | 0.24       | 9.84        | 23.72      | 33.80 | 50.00      | -16.20     | Average |



Test Mode: 11; Line: Live line



Site : Shielding Room

Condition: Neutral

Job No. : 02930AT

Test mode: 11

|     | Freq    | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|-----|---------|------------|-------------|------------|-------|------------|------------|---------|
|     | MHz     | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1 * | 0.1508  | 0.01       | 10.15       | 48.91      | 59.07 | 65.96      | -6.89      | QP      |
| 2 * | 0.1508  | 0.01       | 10.15       | 32.11      | 42.27 | 55.96      | -13.69     | Average |
| 3   | 0.3067  | 0.01       | 9.77        | 29.13      | 38.91 | 60.06      | -21.15     | QP      |
| 4   | 0.3067  | 0.01       | 9.77        | 20.58      | 30.36 | 50.06      | -19.70     | Average |
| 5   | 0.9136  | 0.01       | 9.57        | 10.35      | 19.93 | 56.00      | -36.07     | QP      |
| 6   | 0.9136  | 0.01       | 9.57        | -1.51      | 8.07  | 46.00      | -37.93     | Average |
| 7   | 1.7716  | 0.01       | 9.55        | 6.58       | 16.14 | 56.00      | -39.86     | QP      |
| 8   | 1.7716  | 0.01       | 9.55        | -3.44      | 6.12  | 46.00      | -39.88     | Average |
| 9   | 3.9850  | 0.01       | 9.55        | 14.92      | 24.48 | 56.00      | -31.52     | QP      |
| 10  | 3.9850  | 0.01       | 9.55        | 2.11       | 11.67 | 46.00      | -34.33     | Average |
| 11  | 13.5509 | 0.08       | 9.78        | 31.76      | 41.62 | 60.00      | -18.38     | QP      |
| 12  | 13.5509 | 0.08       | 9.78        | 19.91      | 29.77 | 50.00      | -20.23     | Average |



### 7.2 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.215

Test Method: ANSI C63.10 (2020) Section 6.9

#### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 24.5 °C Humidity: 41.5 % RH Atmospheric Pressure: 1020 mbar

#### 7.2.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                      |
|-----------------------|-----------|----------------------------------|
| Final test            | 11        | TX mode with modulation(125KHz). |

#### 7.2.3 Test Setup Diagram




#### 7.2.4 Measurement Procedure and Data


The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

| Model No. | Test Frequency(KHz) | 20dB bandwidth(kHz) | Limit(kHz) | Results |
|-----------|---------------------|---------------------|------------|---------|
| HC2705T   | 125KHz              | 1.410               | N/A        | Pass    |
| HC3205T   | 125KHz              | 1.314               | N/A        | Pass    |

### Test data for HC2705T



### Test data for HC3205T



### 7.3 Restricted Bands

Test Requirement 47 CFR Part 15, Subpart C 15.205

Test Method: ANSI C63.10 (2020) Section 6.10.5

Limit:

The fundamental wave could not fall in the restricted band 90KHz-110KHz

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C


Humidity: 41.5 % RH

Atmospheric Pressure: 1020 mbar

#### 7.3.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                      |
|-----------------------|-----------|----------------------------------|
| Final test            | 11        | TX mode with modulation(125KHz). |

#### 7.3.3 Test Setup Diagram




#### 7.3.4 Measurement Procedure and Data




### 7.3.5 Measurement Procedure and Data

| Model No. | $f_L$ (MHz) | $f_H$ (MHz) | $f_c$ (MHz) | Limit (dBm) | Result |
|-----------|-------------|-------------|-------------|-------------|--------|
| HC2705T   | 123.93      | 126.29      | 0.125000    | N/A         | PASS   |
| HC3205T   | 123.89      | 126.29      | 0.125000    | N/A         | PASS   |

Test plot for HC2705T



Test plot for HC3205T



## 7.4 Radiated Emissions (9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4

Measurement Distance: 3m

Limit:

| Frequency(MHz) | Field strength (microvolts/meter) | Limit (dBuV/m) | Detector | Measurement Distance (meters) |
|----------------|-----------------------------------|----------------|----------|-------------------------------|
| 0.009-0.490    | 2400/F(kHz)                       | -              | -        | 300                           |
| 0.490-1.705    | 24000/F(kHz)                      | -              | -        | 30                            |
| 1.705-30       | 30                                | -              | -        | 30                            |

### Below 30MHz

If field strength is measured at only a single point, then that point shall be at the radial from the EUT that produces the maximum emission at the frequency being measured, as described in 5.4. If that point is closer to the EUT than  $\lambda/2\pi$  and the limit distance is greater than  $\lambda/2\pi$ , the measurement shall be extrapolated to the limit distance by conservatively presuming that the field strength decreases at a 40 dB/decade of distance rate to the  $\lambda/2\pi$  distance, and at a 20 dB/decade of distance rate beyond  $\lambda/2\pi$ . This shall be accomplished using Equation (2):

$$FS_{(10m)} = FS_{(30/300m)} + 40\log\{d_{(near\ field)}/d_{(10m)}\} + 20\log\{d_{(30/300m)}/d_{(near\ field)}\} \quad (2)$$

If the single point measured is at a distance greater than  $\lambda/2\pi$ , then extrapolation to the limit distance shall be calculated using Equation (3):

$$FS_{(10m)} = FS_{(30/300m)} + 20\log\{d_{(30/300m)}/d_{(10m)}\} \quad (3)$$

If both the single point and the limit distance are equal to or closer to the EUT than  $\lambda/2\pi$ , then extrapolation to the limit distance shall be calculated using Equation (4):

$$FS_{(10m)} = FS_{(30/300m)} + 40\log\{d_{(30/300m)}/d_{(10m)}\} \quad (4)$$

Remark:

$$d_{near\ field} = 47.77 / f_{MHz}$$

where  $f_{MHz}$  is the frequency of the emission being measured in MHz.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor



$$FS_{\text{limit}} = FS_{\text{max}} - 40 \log \left( \frac{d_{\text{limit}}}{d_{\text{measure}}} \right)$$

where

$FS_{\text{limit}}$  is the calculation of field strength at the limit distance, expressed in dBμV/m  
 $FS_{\text{max}}$  is the measured field strength, expressed in dBμV/m  
 $d_{\text{measure}}$  is the distance of the measurement point from the EUT  
 $d_{\text{limit}}$  is the reference distance or the distance of the  $\lambda/2\pi$  point

### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C


Humidity: 48.1 % RH

Atmospheric Pressure: 1020 mbar

### 7.4.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                      |
|-----------------------|-----------|----------------------------------|
| Final test            | 11        | TX mode with modulation(125KHz). |

### 7.4.3 Test Setup Diagram




### 7.4.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.



Test data for HC2705T




Condition: 3m

Job No. : 02930AT

Test Mode: 11

|      | Freq  | Read Level | Ant Factor | Cable Loss | Preamp Factor | Level  | Limit  | Over Limit | Remark  |
|------|-------|------------|------------|------------|---------------|--------|--------|------------|---------|
|      | MHz   | dBuV       | dB/m       | dB         | dB            | dBuV/m | dBuV/m | dB         |         |
| 1    | 0.009 | 67.61      | 19.08      | 0.10       | 31.10         | 55.69  | 128.48 | -72.79     | Average |
| 2    | 0.034 | 69.52      | 11.88      | 0.12       | 32.03         | 49.49  | 117.02 | -67.53     | Average |
| 3 pp | 0.125 | 103.32     | 10.53      | 0.14       | 32.40         | 81.59  | 105.66 | -24.07     | Average |





Condition: 3m


Job No. : 02930AT

Test Mode: 11

|   |      | Read  | Ant    | Cable | Preamp |        | Limit  | Over   |                |
|---|------|-------|--------|-------|--------|--------|--------|--------|----------------|
|   | Freq | Level | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark         |
|   | MHz  | dBuV  | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |                |
| 1 | av   | 0.168 | 68.90  | 10.49 | 0.15   | 32.40  | 47.14  | 103.11 | -55.97 Average |
| 2 | pp   | 0.544 | 61.76  | 10.37 | 0.29   | 32.51  | 39.91  | 72.89  | -32.98 QP      |
| 3 |      | 0.637 | 60.04  | 10.36 | 0.31   | 32.53  | 38.18  | 71.50  | -33.32 QP      |



Test data for HC3205T




Condition: 3m

Job No. : 02930AT

Test Mode: 11

|      |       | Read   | Ant    | Cable | Preamp |        | Limit  | Over   |         |
|------|-------|--------|--------|-------|--------|--------|--------|--------|---------|
|      | Freq  | Level  | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark  |
|      | MHz   | dBuV   | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |         |
| 1    | 0.010 | 71.87  | 18.53  | 0.10  | 31.15  | 59.35  | 127.91 | -68.56 | Average |
| 2    | 0.015 | 73.24  | 16.00  | 0.11  | 31.45  | 57.90  | 124.10 | -66.20 | Average |
| 3 pp | 0.125 | 102.84 | 10.53  | 0.14  | 32.40  | 81.11  | 105.66 | -24.55 | Average |





Condition: 3m

Job No. : 02390AT

Test Mode: 11

|      |       | Read  | Ant    | Cable | Preamp |        | Limit  | Over   |         |
|------|-------|-------|--------|-------|--------|--------|--------|--------|---------|
|      | Freq  | Level | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark  |
|      | MHz   | dBuV  | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |         |
| 1    | 0.185 | 72.41 | 10.47  | 0.16  | 32.40  | 50.64  | 102.24 | -51.60 | Average |
| 2 av | 0.373 | 67.45 | 10.39  | 0.25  | 32.44  | 45.65  | 96.17  | -50.52 | Average |
| 3 pp | 0.555 | 61.32 | 10.36  | 0.29  | 32.52  | 39.45  | 72.71  | -33.26 | QP      |



### 7.5 Radiated Emissions (30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.5

Measurement Distance: 3m

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.7 °C


Humidity: 50.2 % RH

Atmospheric Pressure: 1020 mbar

#### 7.5.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                      |
|-----------------------|-----------|----------------------------------|
| Final test            | 11        | TX mode with modulation(125KHz). |


#### 7.5.3 Test Setup Diagram



## 7.5.4 Measurement Procedure and Data

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground for below 1GHz at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Test Mode: 11; Polarity: Horizontal




Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : 02930AT  
Test Mode: 11

|     | Ant     | Cable  | Preamp | Read   |       | Limit  | Over   |              |
|-----|---------|--------|--------|--------|-------|--------|--------|--------------|
|     | Freq    | Factor | Loss   | Factor | Level | Level  | Line   | Limit Remark |
|     | MHz     | dB/m   | dB     | dB     | dBuV  | dBuV/m | dBuV/m | dB           |
| 1   | 30.000  | 21.20  | 0.74   | 27.65  | 27.15 | 21.44  | 40.00  | -18.56 QP    |
| 2   | 79.800  | 10.44  | 1.10   | 27.61  | 39.65 | 23.58  | 40.00  | -16.42 QP    |
| 3   | 199.986 | 14.10  | 1.70   | 27.80  | 37.65 | 25.65  | 43.50  | -17.85 QP    |
| 4   | 232.532 | 16.77  | 1.85   | 27.69  | 41.02 | 31.95  | 46.00  | -14.05 QP    |
| 5   | 665.804 | 25.41  | 3.31   | 27.92  | 31.30 | 32.10  | 46.00  | -13.90 QP    |
| 6 q | 896.997 | 27.93  | 3.97   | 26.98  | 37.08 | 42.00  | 46.00  | -4.00 QP     |



Test Mode: 11; Polarity: Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : 02930AT  
Test Mode: 11

|      | Ant     | Cable | Preamp | Read  |        | Limit  | Over  |           |
|------|---------|-------|--------|-------|--------|--------|-------|-----------|
| Freq | Factor  | Loss  | Factor | Level | Level  | Line   | Limit | Remark    |
| MHz  | dB/m    | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB    |           |
| 1    | 119.856 | 11.11 | 1.35   | 27.65 | 46.47  | 31.28  | 43.50 | -12.22 QP |
| 2    | 149.486 | 12.98 | 1.50   | 27.72 | 38.72  | 25.48  | 43.50 | -18.02 QP |
| 3    | 235.816 | 17.07 | 1.87   | 27.68 | 38.64  | 29.90  | 46.00 | -16.10 QP |
| 4    | 452.720 | 21.20 | 2.67   | 27.86 | 36.88  | 32.89  | 46.00 | -13.11 QP |
| 5 q  | 893.857 | 28.02 | 3.96   | 27.00 | 34.20  | 39.18  | 46.00 | -6.82 QP  |



## 8 Test Setup Photo

Refer to Appendix – Test Setup NFC Photos for SZCR2507002930AT

## 9 EUT Constructional Details (EUT Photos)

Refer to Appendix - External and Internal photos for SZCR2507002930AT

- End of the Report -

