

RF Exposure Evaluation  
For  
Shenzhen Annaijia Electronics Co., Ltd  
Vacuum Suction Magnetic Wireless Charger  
Test Model: CZ-40




|                                |   |                                                                                                        |
|--------------------------------|---|--------------------------------------------------------------------------------------------------------|
| Prepared for                   | : | Shenzhen Annaijia Electronics Co., Ltd                                                                 |
| Address                        | : | 3 Building, Quanxinyuan Industrial Park, Huafan Road, Dalang Street, Longhua District, Shenzhen, China |
| Prepared by                    | : | Guangzhou LCS Compliance Testing Laboratory Ltd.                                                       |
| Address                        | : | No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China                       |
| Tel                            | : | (+86) 020-39166689                                                                                     |
| Fax                            | : | (+86) 020-39166619                                                                                     |
| Web                            | : | www.LCS-cert.com                                                                                       |
| Mail                           | : | webmaster@LCS-cert.com                                                                                 |
| Date of receipt of test sample | : | September 16, 2025                                                                                     |
| Number of tested samples       | : | 2                                                                                                      |
| Sample No.                     | : | C250911008-1, C250911008-2                                                                             |
| Serial number                  | : | Prototype                                                                                              |
| Date of Test                   | : | September 16, 2025 ~ September 27, 2025                                                                |
| Date of Report                 | : | September 28, 2025                                                                                     |

| <b>RF Exposure Evaluation</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Reference No.</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>LCSC09125023EB</b>                                                                                                                                                                                          |
| <b>Date Of Issue</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | September 28, 2025                                                                                                                                                                                             |
| <b>Testing Laboratory Name</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | <b>Guangzhou LCS Compliance Testing Laboratory Ltd.</b>                                                                                                                                                        |
| <b>Address</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | No.44-1,Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China                                                                                                                                |
| <b>Testing Location/ Procedure</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <input checked="" type="checkbox"/> Full application of Harmonised standards<br><input type="checkbox"/> Partial application of Harmonised standards<br><input type="checkbox"/> Other standard testing method |
| <b>Applicant's Name</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <b>Shenzhen Annaijia Electronics Co., Ltd</b>                                                                                                                                                                  |
| <b>Address</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3 Building, Quanxinyuan Industrial Park, Huafan Road, Dalang Street, Longhua District, Shenzhen, China                                                                                                         |
| <b>Test Specification</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                |
| <b>Standard</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | FCC KDB publication 680106 D01 Wireless Power Transfer v04<br>FCC CFR 47 part1 1.1310<br>FCC CFR 47 part2 2.1091<br>FCC CFR 47 part 18.107                                                                     |
| <b>Test Report Form No.</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | TRF-4-E-214 A/0                                                                                                                                                                                                |
| <b>TRF Originator</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Guangzhou LCS Compliance Testing Laboratory Ltd.                                                                                                                                                               |
| <b>Master TRF</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Dated 2011-03                                                                                                                                                                                                  |
| <b>Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.</b><br>This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. |                                                                                                                                                                                                                |
| <b>Test Item Description</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | <b>Vacuum Suction Magnetic Wireless Charger</b>                                                                                                                                                                |
| <b>Trade Mark</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | N/A                                                                                                                                                                                                            |
| <b>Test Model</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | CZ-40                                                                                                                                                                                                          |
| <b>Power Supply</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Please Refer to Page 6                                                                                                                                                                                         |
| <b>Result</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | <b>PASS</b>                                                                                                                                                                                                    |

Compiled by:

Supervised by:

Approved by:

Lifeng Le / File administrators

Justin Zhu / Technique Director

Gavin Liang/ Manager

## RF Exposure Evaluation

|                                         |                                            |
|-----------------------------------------|--------------------------------------------|
| Test Report No. : <b>LCSC09125023EB</b> | <u>September 28, 2025</u><br>Date of issue |
|-----------------------------------------|--------------------------------------------|

Test Model..... : CZ-40

EUT..... : Vacuum Suction Magnetic Wireless Charger

**Applicant..... : Shenzhen Annaijia Electronics Co., Ltd**

Address..... : 3 Building, Quanxinyuan Industrial Park, Huafan Road,  
Dalang Street, Longhua District, Shenzhen, China

Telephone..... : /

Fax..... : /

**Manufacturer..... : Shenzhen Annaijia Electronics Co., Ltd**

Address..... : 3 Building, Quanxinyuan Industrial Park, Huafan Road, Dalang  
Street, Longhua District, Shenzhen, China

Telephone..... : /

Fax..... : /

**Factory..... : Shenzhen Annaijia Electronics Co., Ltd**

Address..... : 3 Building, Quanxinyuan Industrial Park, Huafan Road, Dalang  
Street, Longhua District, Shenzhen, China

Telephone..... : /

Fax..... : /

|                    |             |
|--------------------|-------------|
| <b>Test Result</b> | <b>PASS</b> |
|--------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

| Report Version | Issue Date         | Revision Content | Revised By |
|----------------|--------------------|------------------|------------|
| 000            | September 28, 2025 | Initial Issue    | --         |
|                |                    |                  |            |
|                |                    |                  |            |

## TABLE OF CONTENTS

| Description                               | Page |
|-------------------------------------------|------|
| 1.PRODUCT INFORMATION .....               | 6    |
| 2.EVALUATION METHOD .....                 | 6    |
| 3.EVALUATION LIMIT .....                  | 9    |
| 4.TEST SETUP DIAGRAM .....                | 11   |
| 5.TEST EQUIPMENT .....                    | 11   |
| 6.MEASUREMENT PROCEDURE .....             | 11   |
| 7.EQUIPMENT APPROVAL CONSIDERATIONS ..... | 12   |
| 8.E AND H FIELD STRENGTH .....            | 13   |
| 9.TEST SETUP PHOTOS .....                 | 15   |
| 10.CONCLUSION .....                       | 18   |
| 11.DESCRPTION OF TEST LAB .....           | 18   |
| 12. MEASUREMENT UNCERTAINTY .....         | 18   |

## 1.Product Information

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Product Name      | Vacuum Suction Magnetic Wireless Charger            |
| Model Number      | CZ-40                                               |
| Power Supply      | Input:DC 5V,3A; DC 9V,3A<br>Output: 15W/10W/7.5W/5W |
| Modulation Type   | ASK                                                 |
| Frequency Range   | 110.2~148.0KHz                                      |
| Antenna Type      | Coil Antenna                                        |
| Hardware version  | /                                                   |
| Software version  | /                                                   |
| Accessories       | /                                                   |
| Exposure category | General population/uncontrolled environment         |
| EUT Type          | Production Unit                                     |
| Device Type       | Mobile Device                                       |

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

## 2.Evaluation Method

Per KDB 680106 D01 Section 3. RF Exposure Requirements;

- 1) Wireless power transfer devices must comply with RF exposure requirements for all design configurations in which they can operate. At a minimum, RF exposure must be evaluated for the worst-case scenario, typically when the transmitter, while delivering energy to a client device, is operating at maximum output power. RF exposure compliance for equipment authorization must be determined following the guidance of KDB447498, which includes consideration of the different test requirements for *Mobile Device* and *Portable Device* exposure categories, as defined in §§ 2.1091 and 2.1093 of the Rules.
- 2) The RF exposure limits, as set forth in § 1.1310, do not cover the frequency range below 100 kHz for Specific Absorption Rate (SAR) and below 300 kHz for Maximum Permitted Exposure (MPE). In addition, present limitations of RF exposure evaluation systems prevent an accurate evaluation of SAR below 4 MHz. For these reasons, a specific MPE-based RF Exposure compliance procedure for devices operating in the aforementioned low-frequency ranges has been set in place. This procedure is applicable to Equipment Authorization of all RF devices, thus including, but not limited to, Part 18 and WPT devices. Accordingly, for § 2.1091-*Mobile* devices, the MPE limits between 100 kHz to 300 kHz are to be considered the same as those at 300 kHz in Table 1 of § 1.1310, that is, 614 V/m and 1.63 A/m, for the electric field and magnetic field, respectively. For § 2.1093-*Portable* devices below 4 MHz and down to 100 kHz, the MPE limits in § 1.1310 (with the 300 kHz limit applicable all the way down to 100 kHz) can be used for the purpose of equipment authorization in lieu of SAR evaluations.

Furthermore, consistent with FCC's equipment authorization RF exposure guidance, any device (both portable and mobile) operating at frequencies below 100 kHz is considered compliant for the purpose of equipment authorization when the external (unperturbed) temporal peak field strengths do not exceed the following reference levels:

83 V/m for the electric field strength (*E*)

and 90 A/m for the magnetic field strength (*H*)

These data may be provided through measurements and/or numerical simulations, and for all the

positions in space relevant for any possible body exposure.

- 3) “Large size” probes may prevent the measurement of E- and/or H-fields near the surface of the radiating structure (e.g., a WPT source coil), as in the example shown in Figure 1.

If the center of the probe sensing element is located more than 5 mm from the probe outer surface, the field strengths need to be estimated through modeling for those positions that are not reachable. The estimates may be done either via numerical calculation, or via analytic model: e.g., approximated formulas for circular coils, dipoles, etc., may be acceptable if it is shown that the model is applicable for the design parameters considered. A typical example is the use of a quasi-static approximation formula for a low-frequency magnetic field source. These estimates shall include points spaced no more than 2 cm from each other. Thus, in the example of

Figure 1, at least the estimates at 0 cm and 2 cm are required, while only one point would not be sufficient. In addition, the model needs to be validated through the probe measurements for the two closest points to the device surface, and with 2-cm increments, as indicated in Figure 1. In that example, the same model must also be applied to the 4 cm and 6 cm positions, and then compared with the measured data, for validation purposes. The validation is considered sufficient if a 30% agreement between the model and the (E- and/or H-field) probe measurements is demonstrated. If such a level of agreement cannot be shown, a more accurate model (and/or a smaller probe) shall be used.




**Figure 1. Example of probe (in yellow) measurements in points close to the WPT device (in red/brown). The probe radius is 4 cm, thus the closest point to the device where the field can be measured is at 4 cm from the surface (this example assumes that the probe calibration refers to the center of the sensing element structure, in this case a sphere of 4 cm radius). Data at 0 cm and 2 cm must be estimated through a model, and then the same model must be validated via comparison with the actual measurements at 4 cm and 6 cm, where the probe center can be positioned and collect valid data.**

- 4) Part 18 Wireless Power Transfer up to One-Meter Distance. This section applies only to WPT transmitters that, by design, can provide power to a load located at a distance no greater than one meter. This distance shall be measured between the closest points between the transmitter and the receiver enclosure surfaces. For instance, two coils positioned as in Figure 2-a may be operated and considered under the provisions of this section, because both receivers are within one-meter distance from the transmitter. However, the case in Figure 2-b cannot be considered in the same way, and it is treated according to the prescription of Section 5.3.

For WPT designs with more than one radiating structure the distance to the load shall be considered as in Figure 3, thus measured between the receiver and the closest transmitting structure.




**Figure 2-a)** For multiple-receiver systems (here shown with two receivers, indicated with RX1 and RX2) the one-meter distance limit must apply for all the receivers that are engaged in the charging process. **b)** The WPT system is considered "at-a-distance" because it can function when the RX2 is further away than one meter from the transmitter.




**Figure 3.** For multiple-coil transmitter systems, the one-meter distance limit is measured from the closest coil edge. A WPT within one meter operates with loads configured as those labeled in green font, if a load can be powered beyond one meter (in red), then it shall be considered "at-a-distance"

There might be situations where the WPT RF emissions are limited enough that even operations in a "crowded" environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an "Equipment Compliance Review" KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met:

- (1) The power transfer frequency is below 1 MHz.

- (2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
- (4) Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093 – Portable exposure conditions).
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
- 5) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested

### 3.Evaluation Limit

#### 3.1 Refer evaluation method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 680106 D01 RF Exposure Wireless Charging Apps v03](#): RF Exposure Considerations for Low Power Consumer Wireless Power Transfer Applications

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

[FCC CFR 47 part 18.107](#): Industrial, Scientific, and Medical Equipment

### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz)                        | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|---------------------------------------------|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure |                              |                              |                                     |                         |
| 0.3-3.0                                     | 614                          | 1.63                         | *100                                | 6                       |
| 3.0-30                                      | 1842/f                       | 4.89/f                       | *900/f <sup>2</sup>                 | 6                       |
| 30-300                                      | 61.4                         | 0.163                        | 1.0                                 | 6                       |
| 300-1,500                                   | /                            | /                            | f/300                               | 6                       |
| 1,500-100,000                               | /                            | /                            | 5                                   | 6                       |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz)                                | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|-----------------------------------------------------|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for General Population/Uncontrolled Exposure |                              |                              |                                     |                         |
| 0.3-1.34                                            | 614                          | 1.63                         | *100                                | 30                      |
| 1.34-30                                             | 824/f                        | 2.19/f                       | *180/f <sup>2</sup>                 | 30                      |
| 30-300                                              | 27.5                         | 0.073                        | 0.2                                 | 30                      |
| 300-1,500                                           | /                            | /                            | f/1500                              | 30                      |
| 1,500-100,000                                       | /                            | /                            | 1.0                                 | 30                      |

F=frequency in MHz


\*=Plane-wave equivalent power density

According to FCC KDB 680106 D01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section 1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):

|                   | E-Field                         | */*                               | B-Field |
|-------------------|---------------------------------|-----------------------------------|---------|
| Frequency         | V/m                             | A/m                               | uT      |
| 0.3 MHz – 3.0 MHz | 614                             | 1.613                             | 2.0     |
| 3.0 MHz – 30 MHz  | 824/f (=27.5 <sub>30MHz</sub> ) | 2.19/f (=0.073 <sub>30MHz</sub> ) | --      |

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.

#### 4.Test Setup Diagram



#### 5.Test Equipment

| Equipment             | Manufacturer | Model   | Serial no. | Calibrated date | Calibrated Due |
|-----------------------|--------------|---------|------------|-----------------|----------------|
| Exposure Level Tester | Narda        | ELT-400 | N-0713     | 2024-11-11      | 2025-11-10     |
| B-Field Probe         | Narda        | ELT-400 | M-1154     | 2024-10-08      | 2025-10-07     |
| Electric field probe  | Narda        | EP601   | 611WX70332 | N/A             | N/A            |

#### 6.Measurement Procedure

- The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- The measurement probe was placed at test distance (15cm and 20cm) which is between the edges of the charger and the geometric center of probe.
- The turn table was rotated 360d degree to search of highest strength.
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- The EUT were measured according to the dictates of KDB 680106D01v03.

## 7. Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01v04 as follows table;

| Requirements of KDB 680106 D01                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Yes / No | Description                                                                                                                                                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power transfer frequency is less than 1 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Yes      | The device operates in the frequency range 110.2kHz - 148.0 kHz                                                                                                                           |
| The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Yes      | The maximum output power of the primary coil is 15W.                                                                                                                                      |
| A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Yes      | Client device is placed directly in contact with the transmitter.                                                                                                                         |
| Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Yes      | Mobile exposure conditions only                                                                                                                                                           |
| The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power. | Yes      | The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. |
| For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well.                                                                                                                                                                                                                                                                                                                                                               | Yes      | Only one radiating structure and tested at maximum Output Power                                                                                                                           |

|                                                                                                                                         |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------------|--|--|
| For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------------|--|--|

There might be situations where the WPT RF emissions are limited enough that even operations in a “crowded” environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an “Equipment Compliance Review” KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met.

### 8.E and H field Strength

| Test Modes                                                                                |                                                              |            |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------|------------|
| Mode 1                                                                                    | AC/DC Adapter(9V/3A)+EUT+mobile phone (Battery Status: <1%)  | Record     |
| Mode 2                                                                                    | AC/DC Adapter(9V/3A)+EUT+mobile phone (Battery Status: <50%) | Record     |
| Mode 3                                                                                    | AC/DC Adapter(9V/3A)+EUT+mobile phone (Battery Status: 100%) | Record     |
| Mode 4                                                                                    | AC/DC Adapter(5V/3A)+EUT+mobile phone (Battery Status: <1%)  | Pre-tested |
| Mode 5                                                                                    | AC/DC Adapter(5V/3A)+EUT+mobile phone (Battery Status: <50%) | Pre-tested |
| Mode 6                                                                                    | AC/DC Adapter(5V/3A)+EUT+mobile phone (Battery Status: 100%) | Pre-tested |
| Note: All test modes were pre-tested, but we only recorded the worst case in this report. |                                                              |            |

Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

| Load mode | Frequency Range (kHz) | Field Strength | Measured Field Strength Values |                 |                 |                 |                 | 50% Limits | Limits |
|-----------|-----------------------|----------------|--------------------------------|-----------------|-----------------|-----------------|-----------------|------------|--------|
|           |                       |                | Test Position A                | Test Position B | Test Position C | Test Position D | Test Position E |            |        |
| Mode 1    | 110.2~148.0           | uT             | 0.143                          | 0.137           | 0.133           | 0.147           | 0.138           | --         | --     |
| Mode 1    | 110.2~148.0           | A/m            | 0.114                          | 0.110           | 0.107           | 0.117           | 0.110           | 0.815      | 1.63   |
| Mode 1    | 110.2~148.0           | V/m            | 42.886                         | 41.257          | 40.124          | 44.098          | 41.404          | 307.0      | 614.0  |
| Mode 2    | 110.2~148.0           | uT             | 0.142                          | 0.135           | 0.133           | 0.145           | 0.136           | --         | --     |
| Mode 2    | 110.2~148.0           | A/m            | 0.114                          | 0.108           | 0.106           | 0.116           | 0.109           | 0.815      | 1.63   |
| Mode 2    | 110.2~148.0           | V/m            | 42.734                         | 40.448          | 39.858          | 43.652          | 40.783          | 307.0      | 614.0  |
| Mode 3    | 110.2~148.0           | uT             | 0.134                          | 0.134           | 0.130           | 0.145           | 0.132           | --         | --     |
| Mode 3    | 110.2~148.0           | A/m            | 0.107                          | 0.107           | 0.104           | 0.116           | 0.106           | 0.815      | 1.63   |
| Mode 3    | 110.2~148.0           | V/m            | 40.352                         | 40.394          | 39.081          | 43.478          | 39.752          | 307.0      | 614.0  |

Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT


| Load mode | Frequency Range (kHz) | Field Strength | Measured Field Strength Values | 50% Limits | Limits |
|-----------|-----------------------|----------------|--------------------------------|------------|--------|
|           |                       |                | Test Position E                |            |        |
| Mode 1    | 110.2~148.0           | uT             | 0.145                          | --         | --     |
| Mode 1    | 110.2~148.0           | A/m            | 0.116                          | 0.815      | 1.63   |
| Mode 1    | 110.2~148.0           | V/m            | 43.679                         | 307        | 614    |
| Mode 2    | 110.2~148.0           | uT             | 0.140                          | --         | --     |
| Mode 2    | 110.2~148.0           | A/m            | 0.112                          | 0.815      | 1.63   |
| Mode 2    | 110.2~148.0           | V/m            | 42.234                         | 307        | 614    |
| Mode 3    | 110.2~148.0           | uT             | 0.136                          | --         | --     |
| Mode 3    | 110.2~148.0           | A/m            | 0.109                          | 0.815      | 1.63   |
| Mode 3    | 110.2~148.0           | V/m            | 41.011                         | 307        | 614    |

Note:  $V/m = 10(((20 \lg(A/m \cdot 10^6) + 51.5) - 120)/20)$

Note:  $A/m = uT/1.25$


## 9.Test Setup Photos

### 9.1.Test Position A - Exposure photo from side edge surface-Rear





(TM1)

### 9.2.Test Position B - Exposure photo from side edge surface-Left



(TM1)

**9.3.Test Position C - Exposure photo from side edge surface-Front****(TM1)****9.4.Test Position D - Exposure photo from side edge surface-Right****(TM1)**

**9.5.Test Position E - Exposure photo from top surface (20cm)****(TM1)****9.6.Test Position E- Exposure photo from top surface (15cm)****(TM1)**

## 10.Conclusion

A minimum safety distance of at 15 cm surrounding the device and 20 cm above the top surface of the device is required when the device is charging a smart phone. The detected emissions with a distance of 15 cm surrounding the device and 20 cm above the top surface of the device are below the limitations according to FCC KDB 680106 D01 Section 3. RF Exposure Requirement Clause 3.

## 11.Description of Test Lab

CNAS Registration Number is L11555  
A2LA Certificate Number: 5099.01  
FCC Designation Number is CN1379  
Test Firm Registration Number: 729882

## 12. Measurement Uncertainty

| Test Item                  | Frequency Range | Uncertainty | Note |
|----------------------------|-----------------|-------------|------|
| Field Strength Uncertainty | 1Hz~400KHz      | 1%          | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....END OF REPORT.....