intertek
Total Quality. Assured.

Chongqing Qianxing Technology Co., Ltd.

RF TEST REPORT

Report Type:
FCC Part 15.247 & ISED RSS-247 RF report

Model:
TWSEJ061LS

REPORT NUMBER:
200702629SHA-002

ISSUE DATE:
September 10, 2020

DOCUMENT CONTROL NUMBER:
TTRF15.247-01_V1 © 2018 Intertek

Intertek Testing Services Shanghai
Building No.86, 1198 Qinzhou Road (North)
Caohejing Development Zone
Shanghai 200233, China

Telephone: 86 21 6127 8200
www.intertek.com

Total Quality. Assured.

TEST REPORT

Report no.: 200702629SHA-002

Applicant:	Chongqing Qianxing Technology Co., Ltd. No.60 Industrial Main Avenue Pulv Sub-district Tongliang District Chongqing Municipality China
Manufacturer:	Chongqing Qianxing Technology Co., Ltd. No.60 Industrial Main Avenue Pulv Sub-district Tongliang District Chongqing Municipality China
FCC ID:	2AW4L-TWSEJ061LS
IC:	26401-TWSEJ061LS

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2019): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 2 (February 2017): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5, Amendment 1(March 2019): General Requirements for Compliance of Radio Apparatus

PREPARED BY:	REVIEWED BY:
Project Engineer Erick Liu	Reviewer Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Content

REVISION HISTORY **5**

MEASUREMENT RESULT SUMMARY **6**

1 GENERAL INFORMATION **7**

1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) 7
1.2 TECHNICAL SPECIFICATION 7
1.3 FREQUENCY HOPPING SYSTEM REQUIREMENT 8
1.4 DESCRIPTION OF TEST FACILITY 10

2 TEST SPECIFICATIONS **11**

2.1 STANDARDS OR SPECIFICATION 11
2.2 MODE OF OPERATION DURING THE TEST 11
2.3 TEST SOFTWARE LIST 12
2.4 TEST PERIPHERALS LIST 12
2.5 TEST ENVIRONMENT CONDITION: 12
2.6 INSTRUMENT LIST 13
2.7 MEASUREMENT UNCERTAINTY 15

3 20DB BANDWIDTH **16**

3.1 LIMIT 16
3.2 MEASUREMENT PROCEDURE 16
3.3 TEST CONFIGURATION 17
3.4 TEST RESULTS OF 20DB BANDWIDTH 17

4 CARRIER FREQUENCY SEPARATION **18**

4.1 LIMIT 18
4.2 TEST CONFIGURATION 18
4.3 TEST PROCEDURE AND TEST SETUP 18
4.4 TEST RESULTS OF CARRIER FREQUENCY SEPARATION 18

5 OUTPUT POWER **19**

5.1 LIMIT 19
5.2 TEST CONFIGURATION 19
5.3 MEASUREMENT PROCEDURE 19
5.4 TEST RESULTS OF OUTPUT POWER 19

6 RADIATED EMISSIONS **20**

6.1 LIMIT 20
6.2 MEASUREMENT PROCEDURE 20
6.3 TEST RESULTS OF RADIATED EMISSIONS 22

7 CONDUCTED SPURIOUS EMISSIONS & BAND EDGE **26**

7.1 LIMIT 26
7.2 TEST CONFIGURATION 26
7.3 MEASUREMENT PROCEDURE 26
7.4 TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS & BAND EDGE 27

8 POWER LINE CONDUCTED EMISSION **28**

8.1 LIMIT 28
8.2 TEST CONFIGURATION 28
8.3 MEASUREMENT PROCEDURE 29

8.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION 30

9 NUMBER OF HOPPING FREQUENCIES 32

9.1 LIMIT 32
9.2 TEST CONFIGURATION 32
9.3 TEST PROCEDURE AND TEST SETUP 32
9.4 TEST RESULTS OF NUMBER OF HOPPING FREQUENCIES 32

10 DWELL TIME 33

10.1 LIMIT 33
10.2 TEST CONFIGURATION 33
10.3 TEST PROCEDURE AND TEST SETUP 33
10.4 TEST RESULTS OF DWELL TIME 34

11 OCCUPIED BANDWIDTH 35

11.1 LIMIT 35
11.2 MEASUREMENT PROCEDURE 35
11.3 TEST CONFIGURATION 35
11.4 THE RESULTS OF OCCUPIED BANDWIDTH 35

12 ANTENNA REQUIREMENT 36

APPENDIX A: TEST RESULTS 37

1.1 RF OUTPUT POWER 37
1.1.1 Test Result and Data 37
1.2 20DB DOWN BANDWIDTH 40
1.2.1 Test Result and Data 40
1.3 99% BANDWIDTH 43
1.3.1 Test Result and Data 43
1.4 TRANSMITTER SPURIOUS EMISSION 46
1.4.1 Test Result and Data 46
1.5 FREQUENCY BAND EDGE 54
1.5.1 Test Result and Data 54
1.6 DWELL TIME 56
1.6.1 Test Result and Data 56
1.7 CARRIER FREQUENCY SEPARATION 59
1.7.1 Test Result and Data 59
1.8 HOPPING CHANNEL NUMBERS 60
1.8.1 Test Result and Data 60

Revision History

Report No.	Version	Description	Issued Date
200702629SHA-002	Rev. 01	Initial issue of report	September 10, 2020

Measurement result summary

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
20 dB Bandwidth	15.247(a)(1)	RSS-247 Issue 2 Clause 5.1	Pass
Carrier Frequency Separation	15.247(a)(1)	RSS-247 Issue 2 Clause 5.1	Pass
Output power	15.247(b)(1)	RSS-247 Issue 2 Clause 5.4	Pass
Radiated Emissions	15.205 & 15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Conducted Spurious Emissions & Band Edge	15.247(d)	RSS-247 Issue 2 Clause 5.5	Pass
Power line conducted emission	15.207	RSS-Gen Issue 5 Clause 8.8	Pass
Number of Hopping Frequencies	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5.1	
Dwell time	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5.1	
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.6	Tested
Antenna requirement	15.203	-	Pass

Notes: 1: NA =Not Applicable
2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.
3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Mi True Wireless Earbuds Basic 2
Type/Model:	TWSEJ061LS
Description of EUT:	EUT is a wireless earphone which has BT and BLE function, it has only one model.
Rating:	Input (earbuds): 5V, 100mA Input (Charging case): 5V, 500mA Output (Charging case): 5V, 150mA
Category of EUT:	Class B
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	August 11, 2020
Date of test:	August 12, 2020 – September 10, 2020

1.2 Technical Specification

Frequency Range:	2402MHz ~ 2480MHz
Support Standards:	Bluetooth 5.0 (BR+EDR)
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, π/4 DQPSK, 8DPSK
Channel Number:	79 (0 - 78)
Channel Separation:	1 MHz
Antenna:	PCB antenna, 0.9dBi

1.3 Frequency Hopping System Requirement

Test Requirement: Section 15.247 (a)(1), (g), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs;
i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 2^9 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.
According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.
According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

1.4 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2019)
ANSI C63.10 (2013)
RSS-247 Issue 2 (February 2017)
RSS-Gen Issue 5, Amendment 1(March 2019)
KDB 558074 (v05)

2.2 Mode of operation during the test

While testing the transmitter mode of the EUT, the internal modulation is applied.
All the functions of the host device except the BT module were set on stand-by mode.

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

The worst-case modulation configuration:

Worst Modulation Used for Conformance Testing			
Bluetooth Mode	**Data Rate**	**Packet Type**	**Worst Mode**
GFSK	BR-1Mbps	DH1, DH3, DH5	**BR-1Mbps DH5** EDR-2Mbps 2DH5 EDR-3Mbps 3DH5
π/4 DQPSK	EDR-2Mbps	2DH1, 2DH3, 2DH5	
8DPSK	EDR-3Mbps	3DH1, 3DH3, 3DH5	
Note: The BR-1Mbps DH5 mode was chosen for radiation emission as representative in this report.			

The power setting parameter:

The worst-case power setting parameter			
Test software Version	Bluetooth RF Test Tool		
Modulation Mode	2402MHz	2441MHz	2480MHz
BR-1Mbps	0x34	0x34	0x34
EDR-2Mbps	0x34	0x34	0x34
EDR-3Mbps	0x34	0x34	0x34

Radiated test mode: EUT transmitted signal with BT antenna;
Conducted test mode: EUT transmitted signal from BT RF port connected to SPA directly;

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Laptop computer	HP	-

2.5 Test environment condition:

Test items	Temperature	Humidity
20 dB Bandwidth	23°C	52% RH
Output power		
Carrier Frequency Separation		
Number of Hopping Frequencies		
Dwell time		
Occupied bandwidth		
Conducted Spurious Emissions & Band Edge		
Power line conducted emission	22°C	53% RH
Radiated Emissions	22°C	55% RH

2.6 Instrument list

Conducted Emission/Disturbance Power/Tri-loop Test/CDN method					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☑	Test Receiver	R&S	ESCS 30	EC 2107	2021-07-15
☑	A.M.N.	R&S	ESH2-Z5	EC 3119	2020-11-30
☐	A.M.N.	R&S	ENV 216	EC 3393	2021-07-04
☐	A.M.N.	R&S	ENV4200	EC 3558	2021-06-10
☐	Absorbing clamp	R&S	MDS 21	EC 2108	2021-06-19
☐	CDN	Frankonia	CDN M2M316	EC 5969	2021-03-15
☐	CDN	Schaffner	CDN M316	EC 2113-1	2021-07-16
☐	Attenuator	Weinschel	68-6-44	EC 3043-9	2021-02-05
☐	Tri-loop	Schwarzbeck	HXYZ 9170	EC 3384	2020-10-10
☐	Voltage Probe	Schwarzbeck	TK9420	EC 4888	2021-09-12
☐	Current probe	R&S	EZ-17	EC 3221	2021-03-15
☐	I.S.N.	FCC	FCC-TLISN -T2-02	EC 3754	2021-02-05
☐	I.S.N.	FCC	FCC-TLISN -T4-02	EC 3755	2021-02-05
☐	I.S.N.	FCC	FCC-TLISN -T8-02	EC 3756	2021-02-05
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☑	Test Receiver	R&S	ESIB 26	EC 3045	2021-09-12
☑	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2021-06-10
☑	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC5262	2021-06-10
☑	Horn antenna	R&S	HF 906	EC 3049	2020-11-17
☑	Horn antenna	ETS	3117	EC 4792-1	2021-01-09
☐	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2021-07-09
☑	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2021-03-07

		EM TEST	NETWAVE-30-400	EC 5383-2	2021-06-19
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☑	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2021-03-05
☑	Power sensor	Agilent	U2021XA	EC 5338-1	2021-03-05
☑	Vector Signal Generator	Agilent	N5182B	EC 5175	2021-03-05
☑	Spectrum analyzer	R&S	CMW500	EC5944	2020-12-23
☑	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2021-03-05
☐	Mobile Test System	Litepoint	Iqxel	EC 5176	2021-01-09
☐	Test Receiver	R&S	ESCI 7	EC 4501	2021-09-12
Tet Site					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☐	Shielded room	Zhongyu	-	EC 2838	2021-01-07
☐	Shielded room	Zhongyu	-	EC 2839	2021-01-14
☑	Semi-anechoic chamber	Albatross project	-	EC 3048	2021-07-31
☐	Fully-anechoic chamber	Albatross project	-	EC 3047	2021-07-31
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☑	Spectrum analyzer	Agilent	E7402A	EC 2254	2021-07-15
☐	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2021-02-28
☐	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 2122	2021-03-11
☑	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 5198	2021-01-18
☐	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3326	2021-03-28
☐	Pressure meter	YM3	Shanghai Mengde	EC 3320	2021-07-01

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	± 0.74dB
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Emission outside the frequency band	± 2.89dB
Power line conducted emission	± 3.19dB

3 20dB bandwidth

Test result: Pass

3.1 Limit

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

3.2 Measurement Procedure

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
d) Steps a) through c) might require iteration to adjust within the specified tolerances.
e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target "−xx dB down" requirement; that is, if the requirement calls for measuring the −20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
f) Set detection mode to peak and trace mode to max hold.
g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
h) Determine the "−xx dB down amplitude" using [(reference value) − xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the "−xx dB down amplitude" determined in step h). If a marker is below this "−xx dB down amplitude" value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the "−xx dB down amplitude" determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker

amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.3 Test Configuration



3.4 Test Results of 20dB bandwidth

Please refer to Appendix A.

4 Carrier Frequency Separation

Test result: Pass

4.1 Limit

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

4.2 Test Configuration



4.3 Test Procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

4.4 Test Results of Carrier Frequency Separation

Please refer to Appendix A.

5 Output power

Test result: Pass

5.1 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.2 Test Configuration



5.3 Measurement Procedure

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:
   1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW ≥ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.
b) Allow trace to stabilize.
c) Use the marker-to-peak function to set the marker to the peak of the emission.
d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
e) A plot of the test results and setup description shall be included in the test report.

5.4 Test Results of Output Power

Please refer to Appendix A.

6 Radiated Emissions

Test result: **Pass**

6.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

6.2 Measurement Procedure

For Radiated emission below 30MHz:

a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c) Both X and Y axes of the antenna are set to make the measurement.
d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 3 x RBW (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported

6.3 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

EUT was tested with wireless module on and off, and the worst data was listed in the report and the worst waveform from 30MHz to 1000MHz is listed as below:

Charging mode: Horizontal

Vertical



Working mode:

Horizontal



Vertical

Test data below 1GHz

Charging mode:

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.00	21.80	19.40	40.00	18.20	PK
H	142.75	20.50	12.40	43.50	23.00	PK
H	319.64	19.90	15.40	46.00	26.10	PK
H	467.37	24.20	19.00	46.00	21.80	PK
H	683.15	27.00	21.40	46.00	19.00	PK
H	873.65	34.00	23.40	46.00	12.00	PK
V	30.00	21.60	19.40	40.00	18.40	PK
V	121.36	23.20	13.20	43.50	20.30	PK
V	125.25	23.90	13.10	43.50	19.60	PK
V	484.87	23.80	19.30	46.00	22.20	PK
V	617.05	27.00	21.00	46.00	19.00	PK
V	873.65	34.80	23.40	46.00	11.20	PK

Working mode:

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.00	21.80	19.40	40.00	18.20	PK
H	74.71	14.30	7.80	40.00	25.70	PK
H	337.13	20.20	15.90	46.00	25.80	PK
H	480.98	23.80	19.20	46.00	22.20	PK
H	685.09	27.90	21.40	46.00	18.10	PK
H	881.42	35.80	23.50	46.00	10.20	PK
V	30.00	21.50	19.40	40.00	18.50	PK
V	76.65	14.10	7.80	40.00	25.90	PK
V	119.42	17.70	13.20	43.50	25.80	PK
V	494.59	24.10	19.50	46.00	21.90	PK
V	694.81	26.80	21.50	46.00	19.20	PK

V	881.42	34.20	23.50	46.00	11.80	PK

Test result of 1GHz to 25GHz:

GFSK (DH5) Modulation:

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	30.70	96.70	Fundamental	/	PK
	V	2402.00	30.70	91.70	Fundamental	/	PK
	H	2390.00	30.30	51.40	74.00	22.60	PK
	V	2390.00	30.30	49.80	74.00	24.20	PK
	H	4804.00	-1.50	38.20	74.00	35.80	PK
	V	4804.00	-1.50	39.70	74.00	34.30	PK
M	H	2440.00	30.70	99.30	Fundamental	/	PK
	V	2440.00	30.70	95.40	Fundamental	/	PK
	H	4880.00	-1.10	40.10	74.00	33.90	PK
	V	4880.00	-1.10	39.80	74.00	34.20	PK
H	H	2480.00	30.70	97.60	Fundamental	/	PK
	V	2480.00	30.70	95.90	Fundamental	/	PK
	H	2483.50	30.80	50.48	74.00	23.52	PK
	V	2483.50	30.80	48.60	74.00	25.40	PK
	H	4960.00	-0.80	40.50	74.00	33.50	PK
	V	4960.00	-0.80	38.70	74.00	35.30	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

7 Conducted Spurious Emissions & Band Edge

Test result: **Pass**

7.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Measurement Procedure

a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e)
b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3. of ANSI C63.10.
d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6 of ANSI C63.10, and orient the EUT and measurement antenna positions to produce the highest emission level.
e) Perform the test as follows:
   1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
   2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
   3) Attenuation: Auto (at least 10 dB preferred).
   4) Sweep time: Coupled.
   5) Resolution bandwidth: 100 kHz
   6) Video bandwidth: 300 kHz
   7) Detector: Peak
   8) Trace: Max hold
f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several

minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.

g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

h) Repeat step c) through step e) for every applicable modulation.

i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).

j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

7.4 Test Results of Conducted Spurious Emissions & Band Edge

Please refer to Appendix A

8 Power line conducted emission

Test result: **Pass**

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

8.2 Test Configuration



8.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

8.4 Test Results of Power line conducted emission

Test Curve:

L Line



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.20	42.6	63.68	21.05	21.32	53.68	32.36
0.72	29.58	56.00	26.42	16.45	46.00	29.55
1.09	20.64	56.00	35.36	11.64	46.00	34.36
1.24	18.43	56.00	37.57	11.86	46.00	34.14
2.31	18.09	56.00	37.91	5.03	46.00	40.97
4.16	19.60	56.00	36.40	7.27	46.00	38.73

Test Curve:

N Line



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.19	40.38	63.88	23.50	17.89	53.88	35.99
0.73	27.53	56.00	28.47	18.04	46.00	27.96
1.32	22.12	56.00	33.88	17.83	46.00	28.17
5.20	19.89	60.00	40.11	10.04	50.00	39.96
6.10	21.44	60.00	38.56	11.45	50.00	38.55
12.49	19.27	60.00	40.73	10.06	50.00	39.94

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

9 Number of Hopping Frequencies

Test result: **Pass**

9.1 Limit

Number of Hopping Frequencies in the 2400-2483.5 MHz band shall use at least 15 channels.

9.2 Test Configuration



9.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c) VBW ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

9.4 Test Results of Number of Hopping Frequencies

Please refer to Appendix A

10 Dwell Time

Test result: **Pass**

10.1 Limit

The dwell time on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2 Test Configuration



10.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: Zero span, centered on a hopping channel.
b) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d) Detector function: Peak.
e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:
(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) × (period specified in the requirements / analyzer sweep time)

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

10.4 Test Results of Dwell Time

Please refer to Appendix A

11 Occupied Bandwidth

Test result: **Tested**

11.1 Limit

None

11.2 Measurement Procedure

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

11.3 Test Configuration



11.4 The results of Occupied Bandwidth

Please refer to Appendix A

12 Antenna requirement

Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:
EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

Appendix A: Test results

1.1 RF Output Power

1.1.1 Test Result and Data

BT Maximum Output Power					
Mode	Test Frequency (MHz)	Packet Type	Power (dBm)	EIRP(dBm)	Result
GFSK	2402	DH5	2.57	3.47	Pass
GFSK	2441	DH5	2.94	3.84	Pass
GFSK	2480	DH5	2.73	3.63	Pass
DQPSK	2402	2DH5	1.62	2.52	Pass
DQPSK	2441	2DH5	2.07	2.97	Pass
DQPSK	2480	2DH5	1.81	2.71	Pass
8DPSK	2402	3DH5	2.12	3.02	Pass
8DPSK	2441	3DH5	2.52	3.42	Pass
8DPSK	2480	3DH5	2.22	3.12	Pass

The max EIRP = 3.91dBm = 2.42mW < 4mW.

GFSK,2402MHz,DH5



GFSK,2441MHz,DH5



GFSK,2480MHz,DH5



DQPSK,2402MHz,2DH5



DQPSK,2441MHz,2DH5



DQPSK,2480MHz,2DH5



8DPSK,2402MHz,3DH5

8DPSK,2441MHz,3DH5

TEST REPORT





8DPSK,2480MHz,3DH5



1.2 20dB Down Bandwidth

1.2.1 Test Result and Data

BT Occupied 20dB Bandwidth				
Mode	Test Frequency (MHz)	Packet Type	20dB Bandwidth (kHz)	Result
GFSK	2402	DH5	976.6	Pass
GFSK	2441	DH5	958.8	Pass
GFSK	2480	DH5	961.8	Pass
DQPSK	2402	2DH5	1363.1	Pass
DQPSK	2441	2DH5	1364.3	Pass
DQPSK	2480	2DH5	1364.8	Pass
8DPSK	2402	3DH5	1344.2	Pass
8DPSK	2441	3DH5	1352.1	Pass
8DPSK	2480	3DH5	1348.5	Pass

GFSK,2402MHz,DH5

GFSK,2441MHz,DH5

GFSK,2480MHz,DH5

DQPSK,2402MHz,2DH5



DQPSK,2441MHz,2DH5



DQPSK,2480MHz,2DH5

8DPSK,2402MHz,3DH5

8DPSK,2441MHz,3DH5



8DPSK,2480MHz,3DH5

1.3 99% BandWidth

1.3.1 Test Result and Data

BT 99% Occupied Bandwidth				
Mode	Test Frequency (MHz)	Packet Type	99% Occupied Bandwidth (kHz)	Result
GFSK	2402	DH5	903.24	Pass
GFSK	2441	DH5	904.21	Pass
GFSK	2480	DH5	901.50	Pass
DQPSK	2402	2DH5	1202.50	Pass
DQPSK	2441	2DH5	1201.42	Pass
DQPSK	2480	2DH5	1201.35	Pass
8DPSK	2402	3DH5	1203.35	Pass
8DPSK	2441	3DH5	1203.77	Pass
8DPSK	2480	3DH5	1204.02	Pass

GFSK,2402MHz,DH5

GFSK,2441MHz,DH5

GFSK,2480MHz,DH5

DQPSK,2402MHz,2DH5

DQPSK,2441MHz,2DH5



DQPSK,2480MHz,2DH5



8DPSK,2402MHz,3DH5

8DPSK,2441MHz,3DH5



8DPSK,2480MHz,3DH5

1.4 Transmitter Spurious Emission

1.4.1 Test Result and Data

BT Transmitter Spurious Emission					
Mode	Test Frequency (MHz)	Packet Type	Frequency Range	Power (dBm)	Result
GFSK	2402	DH5	0.009MHz~2380MHz	-56.25	Pass
GFSK	2402	DH5	10000MHz~25000MHz	-50.64	Pass
GFSK	2402	DH5	2410MHz~10000MHz	-54.37	Pass
GFSK	2402	DH5	Band Edge	-55.88	Pass
GFSK	2441	DH5	0.009MHz~2300MHz	-56.08	Pass
GFSK	2441	DH5	10000MHz~25000MHz	-50.86	Pass
GFSK	2441	DH5	2500MHz~10000MHz	-53.96	Pass
GFSK	2441	DH5	Band Edge	-58.29	Pass
GFSK	2480	DH5	0.009MHz~2475MHz	-56.39	Pass
GFSK	2480	DH5	10000MHz~25000MHz	-50.08	Pass
GFSK	2480	DH5	2505MHz~10000MHz	-53.47	Pass
GFSK	2480	DH5	Band Edge	-56.13	Pass
DQPSK	2402	2DH5	0.009MHz~2380MHz	-56.58	Pass
DQPSK	2402	2DH5	10000MHz~25000MHz	-49.67	Pass
DQPSK	2402	2DH5	2410MHz~10000MHz	-52.38	Pass
DQPSK	2402	2DH5	Band Edge	-53.98	Pass
DQPSK	2441	2DH5	0.009MHz~2300MHz	-57.04	Pass
DQPSK	2441	2DH5	10000MHz~25000MHz	-50.16	Pass
DQPSK	2441	2DH5	2500MHz~10000MHz	-51.20	Pass
DQPSK	2441	2DH5	Band Edge	-58.70	Pass
DQPSK	2480	2DH5	0.009MHz~2475MHz	-56.53	Pass
DQPSK	2480	2DH5	10000MHz~25000MHz	-50.77	Pass
DQPSK	2480	2DH5	2505MHz~10000MHz	-53.54	Pass
DQPSK	2480	2DH5	Band Edge	-56.30	Pass
8DPSK	2402	3DH5	0.009MHz~2380MHz	-56.69	Pass
8DPSK	2402	3DH5	10000MHz~25000MHz	-51.05	Pass

8DPSK	2402	3DH5	2410MHz~10000MHz	-52.29	Pass
8DPSK	2402	3DH5	Band Edge	-53.21	Pass
8DPSK	2441	3DH5	0.009MHz~2300MHz	-48.23	Pass
8DPSK	2441	3DH5	10000MHz~25000MHz	-49.93	Pass
8DPSK	2441	3DH5	2500MHz~10000MHz	-52.86	Pass
8DPSK	2441	3DH5	Band Edge	-58.07	Pass
8DPSK	2480	3DH5	0.009MHz~2475MHz	-55.91	Pass
8DPSK	2480	3DH5	10000MHz~25000MHz	-50.18	Pass
8DPSK	2480	3DH5	2505MHz~10000MHz	-52.20	Pass
8DPSK	2480	3DH5	Band Edge	-56.46	Pass

GFSK,2402MHz,DH5,Plot 1,Band Edge

GFSK,2402MHz,DH5,Plot 2,0.009MHz~2380 MHz



GFSK,2402MHz,DH5,Plot 3,2410MHz~10000 MHz



GFSK,2402MHz,DH5,Plot 4,10000MHz~25000MHz



GFSK,2441MHz,DH5,Plot 1,Band Edge



GFSK,2441MHz,DH5,Plot 2,0.009MHz~2300 MHz



GFSK,2441MHz,DH5,Plot 3,2500MHz~10000 MHz

GFSK,2441MHz,DH5,Plot 4,10000MHz~25000MHz



GFSK,2480MHz,DH5,Plot 1,Band Edge



GFSK,2480MHz,DH5,Plot 2,0.009MHz~2475 MHz

GFSK,2480MHz,DH5,Plot 3,2505MHz~10000 MHz



GFSK,2480MHz,DH5,Plot 4,10000MHz~25000MHz



DQPSK,2402MHz,2DH5,Plot 1,Band Edge



DQPSK,2402MHz,2DH5,Plot 2,0.009MHz~2380MHz

DQPSK,2402MHz,2DH5,Plot 3,2410MHz~10000MHz



DQPSK,2402MHz,2DH5,Plot 4,10000MHz~25000MHz



DQPSK,2441MHz,2DH5,Plot 1,Band Edge



DQPSK,2441MHz,2DH5,Plot 2,0.009MHz~2300MHz



DQPSK,2441MHz,2DH5,Plot 3,2500MHz~10000MHz



DQPSK,2441MHz,2DH5,Plot 4,10000MHz~25000MHz



DQPSK,2480MHz,2DH5,Plot 1,Band Edge



DQPSK,2480MHz,2DH5,Plot 2,0.009MHz~2475MHz

DQPSK,2480MHz,2DH5,Plot 3,2505MHz~10000MHz



DQPSK,2480MHz,2DH5,Plot 4,10000MHz~25000MHz



8DPSK,2402MHz,3DH5,Plot 1,Band Edge



8DPSK,2402MHz,3DH5,Plot 2,0.009MHz~2380MHz



8DPSK,2402MHz,3DH5,Plot 3,2410MHz~10000MHz



8DPSK,2402MHz,3DH5,Plot 4,10000MHz~25000MHz



8DPSK,2441MHz,3DH5,Plot 1,Band Edge



8DPSK,2441MHz,3DH5,Plot 2,0.009MHz~2300MHz



8DPSK,2441MHz,3DH5,Plot 3,2500MHz~10000MHz



8DPSK,2441MHz,3DH5,Plot 4,10000MHz~25000MHz