



MPE ESTIMATION

FCC ID: 2AW52-UCTT4401

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm ²)
2.4G WIFI Ant1	14.46	14±1(15)	31.62	1	1.2589	0.00792
2.4G WIFI Ant2	14.52	14±1(15)	31.62	1	1.2589	0.00792
MIMO	/	/	/	/	/	0.01584
$Pd = \frac{P_{out} * G}{4\pi r^2};$						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power. Conducted power see the test report HK1911273099-E , Antenna port 1:1dBi and Antenna port 2:1dBi, MIMO:4.010dBi						

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01584mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----