

Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6665MHz (U-NII-7) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13330.132	48.56	9.91	58.47	74.00	-15.53	peak	P
2 *	13330.522	38.60	9.91	48.51	54.00	-5.49	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13330.258	38.48	9.91	48.39	54.00	-5.61	AVG	P
2	13330.335	48.21	9.91	58.12	74.00	-15.88	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6825MHz (U-NII-7) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13650.368	38.45	10.12	48.57	68.20	-19.63	AVG	P
2	13650.725	48.46	10.12	58.58	88.20	-29.62	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13650.255	48.44	10.12	58.56	88.20	-29.64	peak	P
2 *	13650.638	39.44	10.12	49.56	68.20	-18.64	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11a Mode 6895MHz (U-NII-8)-CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13790.357	49.49	10.14	59.63	88.20	-28.57	peak	P
2 *	13790.358	40.22	10.14	50.36	68.20	-17.84	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13790.235	39.54	10.14	49.68	68.20	-18.52	AVG	P
2	13790.587	48.64	10.14	58.78	88.20	-29.42	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11a Mode 6995MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13990.332	49.38	10.47	59.85	88.20	-28.35	peak	P
2 *	13990.536	38.28	10.47	48.75	68.20	-19.45	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13990.188	49.42	10.47	59.89	88.20	-28.31	peak	P
2 *	13990.618	39.26	10.47	49.73	68.20	-18.47	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11a Mode 7095MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14190.257	38.33	10.25	48.58	68.20	-19.62	AVG	P
2	14190.882	49.53	10.25	59.78	88.20	-28.42	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14190.271	49.68	10.25	59.93	88.20	-28.27	peak	P
2 *	14190.662	39.53	10.25	49.78	68.20	-18.42	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6895MHz (U-NII-8)-CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13790.435	38.43	10.14	48.57	68.20	-19.63	AVG	P
2	13790.527	49.69	10.14	59.83	88.20	-28.37	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13790.196	48.57	10.14	58.71	88.20	-29.49	peak	P
2 *	13790.337	39.44	10.14	49.58	68.20	-18.62	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6995MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13990.021	48.52	10.47	58.99	88.20	-29.21	peak	P
2 *	13990.220	39.65	10.47	50.12	68.20	-18.08	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13990.369	49.15	10.47	59.62	88.20	-28.58	peak	P
2 *	13990.782	39.65	10.47	50.12	68.20	-18.08	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 7095MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14190.117	48.91	10.25	59.16	88.20	-29.04	peak	P
2 *	14190.427	39.89	10.25	50.14	68.20	-18.06	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14190.552	49.00	10.25	59.25	88.20	-28.95	peak	P
2 *	14190.635	39.31	10.25	49.56	68.20	-18.64	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6925MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13850.447	37.99	10.57	48.56	68.20	-19.64	AVG	P
2	13850.893	49.00	10.58	59.58	88.20	-28.62	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13850.441	38.30	10.57	48.87	68.20	-19.33	AVG	P
2	13850.625	49.01	10.57	59.58	88.20	-28.62	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6965MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13930.577	38.89	10.84	49.73	68.20	-18.47	AVG	P
2	13930.835	49.02	10.84	59.86	88.20	-28.34	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13930.054	48.74	10.84	59.58	88.20	-28.62	peak	P
2 *	13930.878	37.95	10.84	48.79	68.20	-19.41	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 7085MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14170.257	49.33	10.23	59.56	88.20	-28.64	peak	P
2 *	14170.631	39.29	10.23	49.52	68.20	-18.68	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14170.112	48.35	10.23	58.58	88.20	-29.62	peak	P
2 *	14170.328	38.33	10.23	48.56	68.20	-19.64	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6945MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13890.477	48.59	10.93	59.52	88.20	-28.68	peak	P
2 *	13890.532	37.65	10.93	48.58	68.20	-19.62	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13890.447	47.85	10.93	58.78	88.20	-29.42	peak	P
2 *	13890.498	37.63	10.93	48.56	68.20	-19.64	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode7025MHz (U-NII-8) -CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14050.298	49.34	10.29	59.63	88.20	-28.57	peak	P
2 *	14050.367	38.23	10.29	48.52	68.20	-19.68	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14050.256	39.24	10.29	49.53	68.20	-18.67	AVG	P
2	14050.452	48.42	10.29	58.71	88.20	-29.49	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	23.2°C	Relative Humidity:	48%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6985MHz (U-NII-8)-CDD							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13970.144	47.58	10.59	58.17	88.20	-30.03	peak	P
2 *	13970.586	37.94	10.59	48.53	68.20	-19.67	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13970.358	37.99	10.59	48.58	68.20	-19.62	AVG	P
2	13970.635	48.96	10.59	59.55	88.20	-28.65	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 5955MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	11910.424	41.38	8.88	50.26	54.00	-3.74	AVG	P
2	11910.526	50.75	8.88	59.63	74.00	-14.37	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11910.354	50.05	8.88	58.93	74.00	-15.07	peak	P
2 *	11910.635	40.70	8.88	49.58	54.00	-4.42	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6175MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12350.278	49.91	8.82	58.73	74.00	-15.27	peak	P
2 *	12350.577	40.86	8.82	49.68	54.00	-4.32	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12350.456	50.75	8.82	59.57	74.00	-14.43	peak	P
2 *	12350.685	40.15	8.82	48.97	54.00	-5.03	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6415MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12830.545	50.31	9.27	59.58	88.20	-28.62	peak	P
2 *	12830.637	39.47	9.27	48.74	68.20	-19.46	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12830.221	49.12	9.27	58.39	88.20	-29.81	peak	P
2 *	12830.257	40.29	9.27	49.56	68.20	-18.64	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 5965MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11930.435	50.60	8.96	59.56	74.00	-14.44	peak	P
2 *	11930.452	39.91	8.96	48.87	54.00	-5.13	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	11930.454	39.79	8.96	48.75	54.00	-5.25	AVG	P
2	11930.653	49.77	8.96	58.73	74.00	-15.27	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6165MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12330.472	39.81	8.90	48.71	54.00	-5.29	AVG	P
2	12330.535	50.86	8.90	59.76	74.00	-14.24	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12330.215	40.68	8.90	49.58	54.00	-4.42	AVG	P
2	12330.514	49.47	8.90	58.37	74.00	-15.63	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6405MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12810.657	39.37	9.34	48.71	68.20	-19.49	AVG	P
2	12810.671	49.62	9.34	58.96	88.20	-29.24	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12810.264	40.51	9.34	49.85	68.20	-18.35	AVG	P
2	12810.635	49.37	9.34	58.71	88.20	-29.49	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 5985MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	11970.365	39.86	9.09	48.95	54.00	-5.05	AVG	P
2	11970.428	49.62	9.09	58.71	74.00	-15.29	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11970.644	49.36	9.09	58.45	74.00	-15.55	peak	P
2 *	11970.644	39.67	9.09	48.76	54.00	-5.24	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6145MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12290.265	49.82	9.02	58.84	74.00	-15.16	peak	P
2 *	12290.362	39.69	9.02	48.71	54.00	-5.29	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12290.633	49.70	9.02	58.72	74.00	-15.28	peak	P
2 *	12290.637	40.54	9.02	49.56	54.00	-4.44	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6385MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12770.634	49.27	9.45	58.72	88.20	-29.48	peak	P
2 *	12770.678	39.32	9.45	48.77	68.20	-19.43	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12770.215	49.04	9.45	58.49	88.20	-29.71	peak	P
2 *	12770.637	39.27	9.45	48.72	68.20	-19.48	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6025MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12050.367	38.24	9.29	47.53	54.00	-6.47	AVG	P
2	12050.561	49.45	9.29	58.74	74.00	-15.26	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12050.367	48.20	9.29	57.49	74.00	-16.51	peak	P
2 *	12050.613	39.22	9.29	48.51	54.00	-5.49	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6185MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12370.519	38.77	8.75	47.52	54.00	-6.48	AVG	P
2	12370.761	49.81	8.75	58.56	74.00	-15.44	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12370.425	39.97	8.75	48.72	54.00	-5.28	AVG	P
2	12370.524	50.00	8.75	58.75	74.00	-15.25	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6345MHz (U-NII-5) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12690.412	37.89	9.64	47.53	54.00	-6.47	AVG	P
2	12690.524	47.88	9.64	57.52	74.00	-16.48	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12690.335	48.22	9.64	57.86	74.00	-16.14	peak	P
2 *	12690.574	39.09	9.64	48.73	54.00	-5.27	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6435MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12870.638	39.76	9.13	48.89	68.20	-19.31	AVG	P
2	12870.687	49.63	9.13	58.76	88.20	-29.44	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12870.227	39.39	9.14	48.53	68.20	-19.67	AVG	P
2	12870.524	48.83	9.13	57.96	88.20	-30.24	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6475MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12950.164	48.54	9.31	57.85	88.20	-30.35	peak	P
2 *	12950.457	39.65	9.31	48.96	68.20	-19.24	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12950.296	48.37	9.31	57.68	88.20	-30.52	peak	P
2 *	12950.678	39.40	9.31	48.71	68.20	-19.49	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6515MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13030.685	40.17	9.68	49.85	68.20	-18.35	AVG	P
2	13030.725	48.99	9.68	58.67	88.20	-29.53	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13030.197	39.06	9.67	48.73	68.20	-19.47	AVG	P
2	13030.225	48.99	9.67	58.66	88.20	-29.54	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6445MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12890.527	49.86	9.07	58.93	88.20	-29.27	peak	P
2 *	12890.678	39.60	9.07	48.67	68.20	-19.53	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12890.328	39.64	9.07	48.71	68.20	-19.49	AVG	P
2	12890.578	50.61	9.07	59.68	88.20	-28.52	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6485MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12970.364	39.14	9.42	48.56	68.20	-19.64	AVG	P
2	12970.545	48.09	9.42	57.51	88.20	-30.69	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12970.168	40.43	9.42	49.85	68.20	-18.35	AVG	P
2	12970.227	49.31	9.42	58.73	88.20	-29.47	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6525MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13050.559	48.21	9.72	57.93	88.20	-30.27	peak	P
2 *	13050.567	39.84	9.72	49.56	68.20	-18.64	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13050.214	50.14	9.72	59.86	88.20	-28.34	peak	P
2 *	13050.635	39.07	9.72	48.79	68.20	-19.41	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6465MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12930.123	39.72	9.21	48.93	68.20	-19.27	AVG	P
2	12930.657	49.50	9.21	58.71	88.20	-29.49	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12930.336	49.55	9.21	58.76	88.20	-29.44	peak	P
2 *	12930.525	38.64	9.21	47.85	68.20	-20.35	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6545MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13090.297	48.56	9.82	58.38	88.20	-29.82	peak	P
2 *	13090.632	38.90	9.82	48.72	68.20	-19.48	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13090.577	47.67	9.82	57.49	88.20	-30.71	peak	P
2 *	13090.945	38.70	9.82	48.52	68.20	-19.68	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6505MHz (U-NII-6) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13010.234	48.51	9.62	58.13	88.20	-30.07	peak	P
2 *	13010.425	38.91	9.62	48.53	68.20	-19.67	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13010.114	37.92	9.61	47.53	68.20	-20.67	AVG	P
2	13010.542	48.81	9.62	58.43	88.20	-29.77	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6535MHz (U-NII-7)-BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13070.585	47.79	9.77	57.56	88.20	-30.64	peak	P
2 *	13070.625	38.98	9.77	48.75	68.20	-19.45	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13070.124	39.76	9.77	49.53	68.20	-18.67	AVG	P
2	13070.257	48.12	9.77	57.89	88.20	-30.31	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6695MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13390.376	49.72	10.14	59.86	74.00	-14.14	peak	P
2 *	13390.539	38.43	10.14	48.57	54.00	-5.43	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13390.578	48.59	10.14	58.73	74.00	-15.27	peak	P
2 *	13390.638	38.79	10.14	48.93	54.00	-5.07	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6855MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13710.426	38.48	10.28	48.76	68.20	-19.44	AVG	P
2	13710.525	48.39	10.28	58.67	88.20	-29.53	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13710.255	38.41	10.28	48.69	68.20	-19.51	AVG	P
2	13710.763	48.49	10.28	58.77	88.20	-29.43	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6875MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13750.274	38.58	10.21	48.79	68.20	-19.41	AVG	P
2	13750.685	48.98	10.21	59.19	88.20	-29.01	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13750.265	38.52	10.21	48.73	68.20	-19.47	AVG	P
2	13750.558	49.61	10.21	59.82	88.20	-28.38	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6565MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13130.265	38.90	9.83	48.73	68.20	-19.47	AVG	P
2	13130.587	48.89	9.84	58.73	88.20	-29.47	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13130.245	49.09	9.83	58.92	88.20	-29.28	peak	P
2 *	13130.567	39.98	9.84	49.82	68.20	-18.38	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6685MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13370.137	48.82	10.06	58.88	74.00	-15.12	peak	P
2 *	13370.269	39.79	10.06	49.85	54.00	-4.15	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13370.357	38.79	10.06	48.85	54.00	-5.15	AVG	P
2	13370.548	49.50	10.06	59.56	74.00	-14.44	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6845MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13690.468	38.47	10.26	48.73	68.20	-19.47	AVG	P
2	13690.534	47.26	10.26	57.52	88.20	-30.68	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13690.496	48.30	10.26	58.56	88.20	-29.64	peak	P
2 *	13690.568	39.27	10.26	49.53	68.20	-18.67	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6885MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13770.528	48.52	10.17	58.69	88.20	-29.51	peak	P
2 *	13770.612	39.68	10.17	49.85	68.20	-18.35	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13770.345	38.54	10.17	48.71	68.20	-19.49	AVG	P
2	13770.548	48.58	10.17	58.75	88.20	-29.45	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6625MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13250.316	38.80	9.79	48.59	54.00	-5.41	AVG	P
2	13250.645	48.07	9.79	57.86	74.00	-16.14	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13250.313	49.77	9.79	59.56	74.00	-14.44	peak	P
2 *	13250.567	38.04	9.79	47.83	54.00	-6.17	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6705MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13410.364	48.39	10.17	58.56	88.20	-29.64	peak	P
2 *	13410.581	37.09	10.17	47.26	68.20	-20.94	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13410.587	48.24	10.17	58.41	88.20	-29.79	peak	P
2 *	13410.961	38.00	10.17	48.17	68.20	-20.03	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6785MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13570.365	38.61	9.98	48.59	68.20	-19.61	AVG	P
2	13570.564	48.19	9.98	58.17	88.20	-30.03	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13570.167	48.21	9.98	58.19	88.20	-30.01	peak	P
2 *	13570.612	39.58	9.98	49.56	68.20	-18.64	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6865MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13730.625	39.28	10.25	49.53	68.20	-18.67	AVG	P
2	13730.825	48.29	10.25	58.54	88.20	-29.66	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13730.196	38.46	10.25	48.71	68.20	-19.49	AVG	P
2	13730.526	47.34	10.24	57.58	88.20	-30.62	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6665MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13330.124	38.80	9.91	48.71	54.00	-5.29	AVG	P
2	13330.545	47.65	9.91	57.56	74.00	-16.44	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13330.124	48.63	9.91	58.54	74.00	-15.46	peak	P
2 *	13330.345	37.67	9.91	47.58	54.00	-6.42	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6825MHz (U-NII-7) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13650.376	48.51	10.12	58.63	88.20	-29.57	peak	P
2 *	13650.457	37.41	10.12	47.53	68.20	-20.67	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13650.133	38.33	10.12	48.45	68.20	-19.75	AVG	P
2	13650.254	47.44	10.12	57.56	88.20	-30.64	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6895MHz (U-NII-8)-BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13790.251	37.55	10.14	47.69	68.20	-20.51	AVG	P
2	13790.677	48.79	10.14	58.93	88.20	-29.27	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13790.334	38.68	10.14	48.82	68.20	-19.38	AVG	P
2	13790.532	47.81	10.14	57.95	88.20	-30.25	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 6995MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13990.215	38.50	10.47	48.97	68.20	-19.23	AVG	P
2	13990.865	49.06	10.46	59.52	88.20	-28.68	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13990.224	39.39	10.47	49.86	68.20	-18.34	AVG	P
2	13990.354	48.32	10.47	58.79	88.20	-29.41	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE20) Mode 7095MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14190.253	39.31	10.25	49.56	68.20	-18.64	AVG	P
2	14190.671	47.34	10.25	57.59	88.20	-30.61	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14190.637	38.46	10.25	48.71	68.20	-19.49	AVG	P
2	14190.882	48.38	10.25	58.63	88.20	-29.57	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6925MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13850.324	37.25	10.57	47.82	68.20	-20.38	AVG	P
2	13850.558	48.34	10.57	58.91	88.20	-29.29	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13850.356	48.19	10.57	58.76	88.20	-29.44	peak	P
2 *	13850.463	37.95	10.57	48.52	68.20	-19.68	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 6965MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13930.324	48.33	10.83	59.16	88.20	-29.04	peak	P
2 *	13930.612	37.71	10.84	48.55	68.20	-19.65	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13930.447	39.03	10.83	49.86	68.20	-18.34	AVG	P
2	13930.585	47.33	10.84	58.17	88.20	-30.03	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE40) Mode 7085MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14170.441	38.52	10.23	48.75	68.20	-19.45	AVG	P
2	14170.454	48.48	10.23	58.71	88.20	-29.49	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14170.447	47.63	10.23	57.86	88.20	-30.34	peak	P
2 *	14170.616	39.30	10.23	49.53	68.20	-18.67	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)
3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode 6945MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13890.255	47.81	10.93	58.74	88.20	-29.46	peak	P
2 *	13890.315	37.66	10.93	48.59	68.20	-19.61	AVG	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13890.362	47.23	10.93	58.16	88.20	-30.04	peak	P
2 *	13890.625	36.65	10.93	47.58	68.20	-20.62	AVG	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE80) Mode7025MHz (U-NII-8) -BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14050.254	37.67	10.29	47.96	68.20	-20.24	AVG	P
2	14050.343	48.13	10.29	58.42	88.20	-29.78	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	14050.114	37.97	10.29	48.26	68.20	-19.94	AVG	P
2	14050.651	47.23	10.29	57.52	88.20	-30.68	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	TX 802.11ax(HE160) Mode 6985MHz (U-NII-8)-BF							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	13970.123	37.57	10.59	48.16	68.20	-20.04	AVG	P
2	13970.587	48.12	10.59	58.71	88.20	-29.49	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	13970.337	47.87	10.59	58.46	88.20	-29.74	peak	P
2 *	13970.346	36.94	10.59	47.53	68.20	-20.67	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)

2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)

3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)

4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.

5. No report for the emission which more than 20dB below the prescribed limit.



---Conducted Unwanted Emissions

TestMode	Antenna	Channel	FreqRange [MHz]	Max. Fre [MHz]	Max. Level [dBm]	Limit [dBm]	Verdict
11A-CDD	Ant1	5955	30~3000	2858.09	-41.66	≤-27	PASS
			3000~10000	7010.77	-37.04	≤-27	PASS
			10000~40000	39731.5	-32.7	≤-27	PASS
	Ant2	5955	30~3000	2605.85	-41.7	≤-27	PASS
			3000~10000	6173.57	-37.43	≤-27	PASS
			10000~40000	39983.5	-32.53	≤-27	PASS
	Ant3	5955	30~3000	2725.14	-42.35	≤-27	PASS
			3000~10000	7807.13	-37.09	≤-27	PASS
			10000~40000	38966.5	-32.28	≤-27	PASS
	Ant4	5955	30~3000	2886.8	-41.89	≤-27	PASS
			3000~10000	8038.37	-37.42	≤-27	PASS
			10000~40000	39503.5	-32.66	≤-27	PASS
	Ant1	6175	30~3000	2696.23	-42.19	≤-27	PASS
			3000~10000	7979.1	-37.68	≤-27	PASS
			10000~40000	39305.5	-32.61	≤-27	PASS
	Ant2	6175	30~3000	2552.39	-42.51	≤-27	PASS
			3000~10000	7943.4	-38.07	≤-27	PASS
			10000~40000	39966.5	-32.2	≤-27	PASS
	Ant3	6175	30~3000	2426.07	-41.98	≤-27	PASS
			3000~10000	7059.53	-37.91	≤-27	PASS
			10000~40000	39151.5	-32.87	≤-27	PASS
	Ant4	6175	30~3000	2759.29	-42.19	≤-27	PASS
			3000~10000	7027.8	-37.64	≤-27	PASS
			10000~40000	38962.5	-32.19	≤-27	PASS
	Ant1	6415	30~3000	2647.92	-41.35	≤-27	PASS
			3000~10000	7012.63	-37.28	≤-27	PASS
			10000~40000	39714.5	-31.57	≤-27	PASS
	Ant2	6415	30~3000	2829.78	-41.79	≤-27	PASS
			3000~10000	6896.9	-37.21	≤-27	PASS
			10000~40000	39998.5	-31.39	≤-27	PASS
	Ant3	6415	30~3000	2708.7	-41.8	≤-27	PASS
			3000~10000	7051.6	-37.71	≤-27	PASS
			10000~40000	39053.5	-32.29	≤-27	PASS
	Ant4	6415	30~3000	2719.99	-41.65	≤-27	PASS
			3000~10000	7831.17	-37.22	≤-27	PASS
			10000~40000	39169.5	-31.82	≤-27	PASS
	Ant1	6435	30~3000	2744.14	-40.96	≤-27	PASS
			3000~10000	7016.6	-36.43	≤-27	PASS
			10000~40000	38640.5	-32.59	≤-27	PASS
	Ant2	6435	30~3000	2746.42	-41.52	≤-27	PASS
			3000~10000	6199	-36.66	≤-27	PASS
			10000~40000	38959.5	-32.18	≤-27	PASS
	Ant3	6435	30~3000	2695.04	-41.19	≤-27	PASS
			3000~10000	7788	-36.76	≤-27	PASS
			10000~40000	39049.5	-31.98	≤-27	PASS
	Ant4	6435	30~3000	2716.62	-41.9	≤-27	PASS
			3000~10000	7000.73	-37.88	≤-27	PASS
			10000~40000	39520.5	-32.44	≤-27	PASS
	Ant1	6475	30~3000	2620.1	-41.45	≤-27	PASS
			3000~10000	7027.1	-37.67	≤-27	PASS
			10000~40000	39022.5	-32.39	≤-27	PASS
	Ant2	6475	30~3000	2930.85	-41.44	≤-27	PASS
			3000~10000	7008.9	-37.27	≤-27	PASS
			10000~40000	38979.5	-31.3	≤-27	PASS
	Ant3	6475	30~3000	2618.81	-41.76	≤-27	PASS
			3000~10000	7027.57	-36.12	≤-27	PASS
			10000~40000	39216.5	-31.74	≤-27	PASS
	Ant4	6475	30~3000	2566.05	-42.01	≤-27	PASS
			3000~10000	7116.23	-37.64	≤-27	PASS
			10000~40000	39471.5	-32.75	≤-27	PASS
	Ant1	6515	30~3000	2730.28	-41.14	≤-27	PASS
			3000~10000	7025.23	-37.94	≤-27	PASS
			10000~40000	39078.5	-32.71	≤-27	PASS
	Ant2	6515	30~3000	2626.44	-42.52	≤-27	PASS
			3000~10000	7023.37	-37.14	≤-27	PASS
			10000~40000	38954.5	-32.23	≤-27	PASS
	Ant3	6515	30~3000	2881.65	-42.27	≤-27	PASS



			3000~10000	7030.6	-37.25	≤-27	PASS
			10000~40000	39560.5	-32.1	≤-27	PASS
	Ant4	6515	30~3000	2692.76	-41.48	≤-27	PASS
			3000~10000	7002.37	-37.64	≤-27	PASS
			10000~40000	39550.5	-31.78	≤-27	PASS
	Ant1	6535	30~3000	2618.32	-42.28	≤-27	PASS
			3000~10000	8009.67	-36.88	≤-27	PASS
			10000~40000	39486.5	-32.36	≤-27	PASS
	Ant2	6535	30~3000	2583.37	-41.6	≤-27	PASS
			3000~10000	7009.37	-37.25	≤-27	PASS
			10000~40000	38647.5	-32.25	≤-27	PASS
	Ant3	6535	30~3000	2929.37	-41.99	≤-27	PASS
			3000~10000	8031.37	-36.9	≤-27	PASS
			10000~40000	39282.5	-32.37	≤-27	PASS
	Ant4	6535	30~3000	2686.03	-42.16	≤-27	PASS
			3000~10000	7824.17	-37.31	≤-27	PASS
			10000~40000	39961.5	-32.69	≤-27	PASS
	Ant1	6695	30~3000	2701.18	-42.62	≤-27	PASS
			3000~10000	7002.13	-37.65	≤-27	PASS
			10000~40000	39180.5	-32.25	≤-27	PASS
	Ant2	6695	30~3000	2687.32	-42.01	≤-27	PASS
			3000~10000	6961.77	-37.48	≤-27	PASS
			10000~40000	39082.5	-32.34	≤-27	PASS
	Ant3	6695	30~3000	2198.37	-42.04	≤-27	PASS
			3000~10000	7007.5	-36.04	≤-27	PASS
			10000~40000	39406.5	-32.36	≤-27	PASS
	Ant4	6695	30~3000	2768.2	-41.51	≤-27	PASS
			3000~10000	7050.43	-37.75	≤-27	PASS
			10000~40000	39486.5	-32.15	≤-27	PASS
	Ant1	6855	30~3000	2649.5	-41.28	≤-27	PASS
			3000~10000	7809.47	-37.39	≤-27	PASS
			10000~40000	39430.5	-31.61	≤-27	PASS
	Ant2	6855	30~3000	2696.63	-40.54	≤-27	PASS
			3000~10000	7947.37	-36.8	≤-27	PASS
			10000~40000	39410.5	-31.03	≤-27	PASS
	Ant3	6855	30~3000	2593.97	-41.5	≤-27	PASS
			3000~10000	9922.53	-37.14	≤-27	PASS
			10000~40000	38967.5	-31.89	≤-27	PASS
	Ant4	6855	30~3000	2691.38	-41.51	≤-27	PASS
			3000~10000	9252.17	-36.91	≤-27	PASS
			10000~40000	39499.5	-31.58	≤-27	PASS
	Ant1	6875	30~3000	2710.09	-41.44	≤-27	PASS
			3000~10000	7003.53	-36.69	≤-27	PASS
			10000~40000	39429.5	-32.01	≤-27	PASS
	Ant2	6875	30~3000	2790.37	-41.32	≤-27	PASS
			3000~10000	7013.33	-36.79	≤-27	PASS
			10000~40000	39959.5	-32.05	≤-27	PASS
	Ant3	6875	30~3000	1652.51	-41.05	≤-27	PASS
			3000~10000	7003.53	-36.09	≤-27	PASS
			10000~40000	39936.5	-31.6	≤-27	PASS
	Ant4	6875	30~3000	2644.95	-41.39	≤-27	PASS
			3000~10000	7077.03	-36.5	≤-27	PASS
			10000~40000	38615.5	-31.9	≤-27	PASS
	Ant1	6895	30~3000	2989.06	-41.42	≤-27	PASS
			3000~10000	7006.57	-36.95	≤-27	PASS
			10000~40000	39897.5	-31.91	≤-27	PASS
	Ant2	6895	30~3000	2658.91	-41.18	≤-27	PASS
			3000~10000	6592.17	-37.12	≤-27	PASS
			10000~40000	39890.5	-31.7	≤-27	PASS
	Ant3	6895	30~3000	2586.44	-41.39	≤-27	PASS
			3000~10000	7105.5	-36.76	≤-27	PASS
			10000~40000	39502.5	-31.33	≤-27	PASS
	Ant4	6895	30~3000	2509.52	-41.58	≤-27	PASS
			3000~10000	7975.13	-37.25	≤-27	PASS
			10000~40000	39484.5	-31.81	≤-27	PASS
	Ant1	6995	30~3000	2664.15	-41.82	≤-27	PASS
			3000~10000	6597.07	-37.63	≤-27	PASS
			10000~40000	39991.5	-31.32	≤-27	PASS
	Ant2	6995	30~3000	2993.81	-41.86	≤-27	PASS
			3000~10000	7980.27	-37.58	≤-27	PASS
			10000~40000	39396.5	-32.14	≤-27	PASS



11AX20CDD	Ant3	6995	30~3000	2461.21	-41.29	≤-27	PASS
			3000~10000	7964.4	-36.61	≤-27	PASS
			10000~40000	38608.5	-32.04	≤-27	PASS
	Ant4	6995	30~3000	2658.41	-40.91	≤-27	PASS
			3000~10000	7814.83	-37.23	≤-27	PASS
			10000~40000	38640.5	-32.37	≤-27	PASS
	Ant1	7095	30~3000	2556.74	-41.91	≤-27	PASS
			3000~10000	7003.07	-36.28	≤-27	PASS
			10000~40000	39991.5	-31.83	≤-27	PASS
	Ant2	7095	30~3000	2752.76	-41.49	≤-27	PASS
			3000~10000	7013.8	-36.65	≤-27	PASS
			10000~40000	39909.5	-31.54	≤-27	PASS
	Ant3	7095	30~3000	2751.27	-41.01	≤-27	PASS
			3000~10000	6894.8	-36.82	≤-27	PASS
			10000~40000	39968.5	-31.84	≤-27	PASS
	Ant4	7095	30~3000	2535.26	-41.87	≤-27	PASS
			3000~10000	7007.27	-37.33	≤-27	PASS
			10000~40000	39497.5	-31.93	≤-27	PASS
	Ant1	5955	30~3000	2642.77	-41.82	≤-27	PASS
			3000~10000	7013.33	-37.43	≤-27	PASS
			10000~40000	39989.5	-32.87	≤-27	PASS
	Ant2	5955	30~3000	2539.52	-42.09	≤-27	PASS
			3000~10000	7026.63	-37.58	≤-27	PASS
			10000~40000	39479.5	-32.82	≤-27	PASS
	Ant3	5955	30~3000	2004.04	-42.04	≤-27	PASS
			3000~10000	7001.2	-37.27	≤-27	PASS
			10000~40000	39989.5	-32.43	≤-27	PASS
	Ant4	5955	30~3000	2611.29	-41.98	≤-27	PASS
			3000~10000	8024.6	-37.4	≤-27	PASS
			10000~40000	39066.5	-32.09	≤-27	PASS
	Ant1	6175	30~3000	2675.84	-42.61	≤-27	PASS
			3000~10000	7035.73	-37.96	≤-27	PASS
			10000~40000	39470.5	-32.76	≤-27	PASS
	Ant2	6175	30~3000	2660.59	-42.2	≤-27	PASS
			3000~10000	7020.1	-36.65	≤-27	PASS
			10000~40000	38988.5	-32.46	≤-27	PASS
	Ant3	6175	30~3000	2659.4	-42.54	≤-27	PASS
			3000~10000	7034.33	-37.99	≤-27	PASS
			10000~40000	39491.5	-33.06	≤-27	PASS
	Ant4	6175	30~3000	2581.79	-42.31	≤-27	PASS
			3000~10000	7796.17	-37.93	≤-27	PASS
			10000~40000	39605.5	-33	≤-27	PASS
	Ant1	6415	30~3000	2575.95	-41.65	≤-27	PASS
			3000~10000	7025.23	-37.45	≤-27	PASS
			10000~40000	38962.5	-32.38	≤-27	PASS
	Ant2	6415	30~3000	2752.46	-41.74	≤-27	PASS
			3000~10000	7017.07	-36.64	≤-27	PASS
			10000~40000	39033.5	-32.06	≤-27	PASS
	Ant3	6415	30~3000	2740.28	-41.51	≤-27	PASS
			3000~10000	7459	-37.11	≤-27	PASS
			10000~40000	39507.5	-32	≤-27	PASS
	Ant4	6415	30~3000	2910.06	-41.57	≤-27	PASS
			3000~10000	7827.67	-37.27	≤-27	PASS
			10000~40000	39454.5	-31.8	≤-27	PASS
	Ant1	6435	30~3000	2808.89	-41.84	≤-27	PASS
			3000~10000	7037.6	-37.68	≤-27	PASS
			10000~40000	39893.5	-31.62	≤-27	PASS
	Ant2	6435	30~3000	2718.8	-41.26	≤-27	PASS
			3000~10000	7014.97	-37.02	≤-27	PASS
			10000~40000	39427.5	-32.28	≤-27	PASS
	Ant3	6435	30~3000	2502.29	-41.83	≤-27	PASS
			3000~10000	7427.73	-37.17	≤-27	PASS
			10000~40000	39605.5	-32.22	≤-27	PASS
	Ant4	6435	30~3000	2622.87	-41.31	≤-27	PASS
			3000~10000	6669.17	-37.24	≤-27	PASS
			10000~40000	39997.5	-31.94	≤-27	PASS
	Ant1	6475	30~3000	2465.47	-41.93	≤-27	PASS
			3000~10000	7638.9	-37.41	≤-27	PASS
			10000~40000	39968.5	-31.99	≤-27	PASS
	Ant2	6475	30~3000	2596.14	-41.59	≤-27	PASS
			3000~10000	7018.93	-37.37	≤-27	PASS



			10000~40000	38986.5	-32.12	≤-27	PASS
			30~3000	2657.92	-42.03	≤-27	PASS
	Ant3	6475	3000~10000	7032.47	-37.54	≤-27	PASS
			10000~40000	39014.5	-32.45	≤-27	PASS
			30~3000	2506.06	-41.5	≤-27	PASS
	Ant4	6475	3000~10000	7008.9	-36.44	≤-27	PASS
			10000~40000	39537.5	-32.05	≤-27	PASS
			30~3000	2643.86	-42.27	≤-27	PASS
	Ant1	6515	3000~10000	7012.17	-37.7	≤-27	PASS
			10000~40000	39634.5	-31.89	≤-27	PASS
			30~3000	2589.81	-42.37	≤-27	PASS
	Ant2	6515	3000~10000	8374.6	-37.88	≤-27	PASS
			10000~40000	39396.5	-32.31	≤-27	PASS
			30~3000	2598.42	-42.28	≤-27	PASS
	Ant3	6515	3000~10000	8071.5	-37.4	≤-27	PASS
			10000~40000	39605.5	-31.57	≤-27	PASS
			30~3000	2665.05	-41.93	≤-27	PASS
	Ant4	6515	3000~10000	7043.43	-37.69	≤-27	PASS
			10000~40000	39602.5	-32.23	≤-27	PASS
			30~3000	2455.07	-41.42	≤-27	PASS
	Ant1	6535	3000~10000	6840.43	-37.93	≤-27	PASS
			10000~40000	38624.5	-32.68	≤-27	PASS
			30~3000	2673.06	-41.93	≤-27	PASS
	Ant2	6535	3000~10000	7009.13	-36.7	≤-27	PASS
			10000~40000	39696.5	-32.27	≤-27	PASS
			30~3000	2637.62	-41.82	≤-27	PASS
	Ant3	6535	3000~10000	7008.67	-36.11	≤-27	PASS
			10000~40000	39958.5	-32.55	≤-27	PASS
			30~3000	2701.38	-41.62	≤-27	PASS
	Ant4	6535	3000~10000	7130.7	-37.41	≤-27	PASS
			10000~40000	39735.5	-31.78	≤-27	PASS
			30~3000	2630.5	-42.4	≤-27	PASS
	Ant1	6695	3000~10000	7991.7	-37.15	≤-27	PASS
			10000~40000	38975.5	-33.02	≤-27	PASS
			30~3000	2528.23	-41.85	≤-27	PASS
	Ant2	6695	3000~10000	7041.1	-36.59	≤-27	PASS
			10000~40000	38637.5	-32.55	≤-27	PASS
			30~3000	2691.58	-41.21	≤-27	PASS
	Ant3	6695	3000~10000	7025	-37.38	≤-27	PASS
			10000~40000	39991.5	-32.77	≤-27	PASS
			30~3000	2662.77	-41.42	≤-27	PASS
	Ant4	6695	3000~10000	7091.5	-37.23	≤-27	PASS
			10000~40000	39732.5	-32.65	≤-27	PASS
			30~3000	2888.98	-41.51	≤-27	PASS
	Ant1	6855	3000~10000	7004	-37.02	≤-27	PASS
			10000~40000	38967.5	-30.23	≤-27	PASS
			30~3000	2414.68	-41.32	≤-27	PASS
	Ant2	6855	3000~10000	7982.83	-36.38	≤-27	PASS
			10000~40000	39487.5	-32.15	≤-27	PASS
			30~3000	2672.07	-40.28	≤-27	PASS
	Ant3	6855	3000~10000	7824.87	-36.65	≤-27	PASS
			10000~40000	39846.5	-31.59	≤-27	PASS
			30~3000	2553.08	-41.47	≤-27	PASS
	Ant4	6855	3000~10000	8136.13	-36.74	≤-27	PASS
			10000~40000	38657.5	-31.99	≤-27	PASS
			30~3000	2666.63	-41.01	≤-27	PASS
	Ant1	6875	3000~10000	6649.33	-36.57	≤-27	PASS
			10000~40000	39964.5	-32.15	≤-27	PASS
			30~3000	2582.48	-40.77	≤-27	PASS
	Ant2	6875	3000~10000	7804.8	-36.58	≤-27	PASS
			10000~40000	39046.5	-31.25	≤-27	PASS
			30~3000	2619.51	-40.98	≤-27	PASS
	Ant3	6875	3000~10000	7004.47	-36.59	≤-27	PASS
			10000~40000	38977.5	-31.69	≤-27	PASS
			30~3000	2680.09	-41.51	≤-27	PASS
	Ant4	6875	3000~10000	7112.97	-36.3	≤-27	PASS
			10000~40000	39058.5	-31.02	≤-27	PASS
			30~3000	2636.93	-41.66	≤-27	PASS
	Ant1	6895	3000~10000	7024.53	-36.55	≤-27	PASS
			10000~40000	39749.5	-31.55	≤-27	PASS
	Ant2	6895	30~3000	2604.86	-41.55	≤-27	PASS



11AX40CDD	Ant3	6895	3000~10000	7798.97	-36.58	≤-27	PASS
			10000~40000	39049.5	-31.71	≤-27	PASS
			30~3000	2699.89	-41.21	≤-27	PASS
			3000~10000	7946.9	-36.92	≤-27	PASS
	Ant4	6895	10000~40000	39493.5	-31.19	≤-27	PASS
			30~3000	2657.82	-41.31	≤-27	PASS
			3000~10000	7317.6	-36.92	≤-27	PASS
	Ant1	6995	10000~40000	39963.5	-31.68	≤-27	PASS
			30~3000	2595.85	-41.53	≤-27	PASS
			3000~10000	6659.6	-36.88	≤-27	PASS
	Ant2	6995	10000~40000	39971.5	-32.88	≤-27	PASS
			30~3000	2537.54	-41.61	≤-27	PASS
			3000~10000	8081.77	-37.68	≤-27	PASS
	Ant3	6995	10000~40000	39984.5	-31.85	≤-27	PASS
			30~3000	2394.78	-41.82	≤-27	PASS
			3000~10000	6764.83	-36.46	≤-27	PASS
	Ant4	6995	10000~40000	39320.5	-31.71	≤-27	PASS
			30~3000	2711.28	-41.75	≤-27	PASS
			3000~10000	9516.53	-37.22	≤-27	PASS
	Ant1	7095	10000~40000	39529.5	-31.82	≤-27	PASS
			30~3000	2622.08	-40.84	≤-27	PASS
			3000~10000	5805.37	-37.06	≤-27	PASS
	Ant2	7095	10000~40000	39821.5	-32.47	≤-27	PASS
			30~3000	2660.59	-41.11	≤-27	PASS
			3000~10000	7000.97	-36.2	≤-27	PASS
	Ant3	7095	10000~40000	39085.5	-32.23	≤-27	PASS
			30~3000	2591.99	-41.45	≤-27	PASS
			3000~10000	9983.67	-37.25	≤-27	PASS
	Ant4	7095	10000~40000	39077.5	-31.39	≤-27	PASS
			30~3000	2627.72	-41.59	≤-27	PASS
			3000~10000	9870.03	-36.96	≤-27	PASS
11AX40CDD	Ant1	5965	10000~40000	39456.5	-32.27	≤-27	PASS
			30~3000	2928.97	-41.53	≤-27	PASS
			3000~10000	7074.47	-37.6	≤-27	PASS
	Ant2	5965	10000~40000	39179.5	-32.56	≤-27	PASS
			30~3000	2712.76	-41.65	≤-27	PASS
			3000~10000	7053.7	-37.87	≤-27	PASS
	Ant3	5965	10000~40000	39728.5	-32.57	≤-27	PASS
			30~3000	2651.28	-41.05	≤-27	PASS
			3000~10000	7047.4	-37.6	≤-27	PASS
	Ant4	5965	10000~40000	38601.5	-32.6	≤-27	PASS
			30~3000	2795.03	-42.13	≤-27	PASS
			3000~10000	6354.17	-37.5	≤-27	PASS
	Ant1	6165	10000~40000	39640.5	-30.93	≤-27	PASS
			30~3000	2675.24	-42.65	≤-27	PASS
			3000~10000	7058.37	-37.63	≤-27	PASS
	Ant2	6165	10000~40000	39971.5	-33.04	≤-27	PASS
			30~3000	2696.23	-42.22	≤-27	PASS
			3000~10000	6849.77	-37.03	≤-27	PASS
	Ant3	6165	10000~40000	39192.5	-32.32	≤-27	PASS
			30~3000	2723.85	-42.41	≤-27	PASS
			3000~10000	6618.07	-38.24	≤-27	PASS
	Ant4	6165	10000~40000	39883.5	-32.8	≤-27	PASS
			30~3000	2608.32	-42.32	≤-27	PASS
			3000~10000	7013.57	-37.5	≤-27	PASS
	Ant1	6405	10000~40000	39993.5	-32.55	≤-27	PASS
			30~3000	2574.36	-41.47	≤-27	PASS
			3000~10000	7800.37	-37.46	≤-27	PASS
	Ant2	6405	10000~40000	39994.5	-32.24	≤-27	PASS
			30~3000	2725.53	-41.51	≤-27	PASS
			3000~10000	8018.53	-36.94	≤-27	PASS
	Ant3	6405	10000~40000	39988.5	-32.5	≤-27	PASS
			30~3000	2638.71	-41.91	≤-27	PASS
			3000~10000	7815.07	-37.29	≤-27	PASS
	Ant4	6405	10000~40000	39077.5	-32.38	≤-27	PASS
			30~3000	2712.76	-41.28	≤-27	PASS
			3000~10000	6230.27	-37.21	≤-27	PASS
	Ant1	6445	10000~40000	39015.5	-31.93	≤-27	PASS
			30~3000	2732.96	-40.94	≤-27	PASS
			3000~10000	7005.17	-37.03	≤-27	PASS
	Ant2	6445	10000~40000	39378.5	-32.23	≤-27	PASS
			30~3000	2732.96	-40.94	≤-27	PASS
			3000~10000	7005.17	-37.03	≤-27	PASS



	Ant2	6445	30~3000	2443.39	-41.55	≤-27	PASS
			3000~10000	7010.77	-37.36	≤-27	PASS
			10000~40000	39974.5	-31.45	≤-27	PASS
	Ant3	6445	30~3000	2659.5	-41.36	≤-27	PASS
3000~10000			7041.1	-36.4	≤-27	PASS	
10000~40000			39113.5	-32.5	≤-27	PASS	
Ant4	6445	30~3000	2699.99	-41.61	≤-27	PASS	
		3000~10000	6624.6	-37.28	≤-27	PASS	
		10000~40000	39948.5	-32.14	≤-27	PASS	
Ant1	6485	30~3000	2989.95	-41.98	≤-27	PASS	
		3000~10000	7001.9	-37.63	≤-27	PASS	
		10000~40000	39908.5	-32.11	≤-27	PASS	
Ant2	6485	30~3000	2993.62	-41.47	≤-27	PASS	
		3000~10000	7829.53	-37.79	≤-27	PASS	
		10000~40000	39985.5	-32.2	≤-27	PASS	
Ant3	6485	30~3000	2575.55	-41.9	≤-27	PASS	
		3000~10000	7974.9	-36.89	≤-27	PASS	
		10000~40000	39961.5	-32.69	≤-27	PASS	
Ant4	6485	30~3000	2601.98	-41.83	≤-27	PASS	
		3000~10000	8085.97	-37.05	≤-27	PASS	
		10000~40000	39506.5	-32.37	≤-27	PASS	
Ant1	6525	30~3000	2799.09	-41.69	≤-27	PASS	
		3000~10000	7827.2	-37.69	≤-27	PASS	
		10000~40000	39011.5	-32.22	≤-27	PASS	
Ant2	6525	30~3000	2637.62	-42.36	≤-27	PASS	
		3000~10000	6921.63	-37.44	≤-27	PASS	
		10000~40000	39062.5	-32.8	≤-27	PASS	
Ant3	6525	30~3000	2641.38	-41.96	≤-27	PASS	
		3000~10000	6696.23	-37.68	≤-27	PASS	
		10000~40000	39642.5	-31.51	≤-27	PASS	
Ant4	6525	30~3000	2584.46	-41.29	≤-27	PASS	
		3000~10000	7003.77	-36.74	≤-27	PASS	
		10000~40000	39286.5	-32.22	≤-27	PASS	
Ant1	6565	30~3000	2990.25	-42.11	≤-27	PASS	
		3000~10000	7066.07	-37.29	≤-27	PASS	
		10000~40000	39851.5	-32.66	≤-27	PASS	
Ant2	6565	30~3000	2505.96	-41.84	≤-27	PASS	
		3000~10000	6199	-37.52	≤-27	PASS	
		10000~40000	39704.5	-31.82	≤-27	PASS	
Ant3	6565	30~3000	2735.63	-41.78	≤-27	PASS	
		3000~10000	7742.5	-37.29	≤-27	PASS	
		10000~40000	39482.5	-32.36	≤-27	PASS	
Ant4	6565	30~3000	2779.39	-41.81	≤-27	PASS	
		3000~10000	7052.77	-37.37	≤-27	PASS	
		10000~40000	39744.5	-32.35	≤-27	PASS	
Ant1	6685	30~3000	2746.72	-42.42	≤-27	PASS	
		3000~10000	7016.37	-38.1	≤-27	PASS	
		10000~40000	38993.5	-32.64	≤-27	PASS	
Ant2	6685	30~3000	2677.91	-42.02	≤-27	PASS	
		3000~10000	7587.1	-37.27	≤-27	PASS	
		10000~40000	39113.5	-32.75	≤-27	PASS	
Ant3	6685	30~3000	2741.67	-42.12	≤-27	PASS	
		3000~10000	7003.77	-37.31	≤-27	PASS	
		10000~40000	38624.5	-32.24	≤-27	PASS	
Ant4	6685	30~3000	2701.77	-42.12	≤-27	PASS	
		3000~10000	7027.57	-36.14	≤-27	PASS	
		10000~40000	39472.5	-32.36	≤-27	PASS	
Ant1	6845	30~3000	2572.68	-41.64	≤-27	PASS	
		3000~10000	7012.4	-36.73	≤-27	PASS	
		10000~40000	39974.5	-31.41	≤-27	PASS	
Ant2	6845	30~3000	2999.65	-41.61	≤-27	PASS	
		3000~10000	7012.4	-36.88	≤-27	PASS	
		10000~40000	39716.5	-31.47	≤-27	PASS	
Ant3	6845	30~3000	2605.05	-41.69	≤-27	PASS	
		3000~10000	7025.23	-36.66	≤-27	PASS	
		10000~40000	39964.5	-31.94	≤-27	PASS	
Ant4	6845	30~3000	2671.68	-40.65	≤-27	PASS	
		3000~10000	7002.83	-36.67	≤-27	PASS	
		10000~40000	38643.5	-31.46	≤-27	PASS	
Ant1	6885	30~3000	2616.14	-41.46	≤-27	PASS	
		3000~10000	7041.57	-37.11	≤-27	PASS	

