RADIO TEST REPORT
FCC ID: 2AW69-CWYSTR5G

Product: Celerway Stratus 5G

Trade Mark: Celerway Stratus 5G

Model No.: CWY-5.3-E5C2W2

Family Model: CWY-5.3-E5C1W2,CWY-5.3-E5C2W2BT1, CWY-5.3-E5C1W2BT1

Report No.: S22032401905001

Issue Date: Jul.08, 2022

Prepared for

Celerway Communication AS

Lilleakerveien 2B, 0283 Oslo, Norway

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: http://www.ntek.org.cn

TABLE OF CONTENTS

1 SUMMARY OF TEST RESULTS 4

2 FACILITIES AND ACCREDITATIONS 5

2.1 FACILITIES 5
2.2 LABORATORY ACCREDITATIONS AND LISTINGS 5
2.3 MEASUREMENT UNCERTAINTY 5

3 GENERAL DESCRIPTION OF EUT 6

4 DESCRIPTION OF TEST MODES 8

5 SETUP OF EQUIPMENT UNDER TEST 9

5.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM 9
5.2 SUPPORT EQUIPMENT 10
5.3 EQUIPMENTS LIST FOR ALL TEST ITEMS 11

6 TEST REQUIREMENTS 13

6.1 CONDUCTED EMISSIONS TEST 13
6.2 RADIATED SPURIOUS EMISSION 18
6.3 6DB BANDWIDTH 29
6.4 DUTY CYCLE 30
6.5 PEAK OUTPUT POWER 32
6.6 POWER SPECTRAL DENSITY 33
6.7 CONDUCTED BAND EDGE MEASUREMENT 35
6.8 SPURIOUS RF CONDUCTED EMISSIONS 36
6.9 ANTENNA APPLICATION 37

7 TEST RESULTS 38

TEST RESULT CERTIFICATION

Applicant's name .....:	Celerway Communication AS
Address .....:	Lilleakerveien 2B, 0283 Oslo, Norway
Manufacturer's Name .....:	Celerway Communication AS
Address .....:	Lilleakerveien 2B, 0283 Oslo, Norway
Product description	
Product name .....:	Celerway Stratus 5G
Model and/or type reference .....:	CWY-5.3-E5C2W2
Family Model .....:	CWY-5.3-E5C1W2, CWY-5.3-E5C2W2BT1, CWY-5.3-E5C1W2BT1
Test Sample Number……..:	S220324019002

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.
The test results of this report relate only to the tested sample identified in this report.

Date of Test : Apr. 20, 2022 ~ Jul.08, 2022

Testing Engineer : Mary. Hu
(Mary Hu)

Authorized Signatory : Alex
(Alex Li)

1 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:
1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

2 FACILITIES AND ACCREDITATIONS

2.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

2.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

2.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(＞6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	All emissions, radiated(9KHz~30MHz)	±6dB

3 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Celerway Stratus 5G
Trade Mark	Celerway Stratus 5G
FCC ID	2AW69-CWYSTR5G
Model No.	CWY-5.3-E5C2W2
Family Model	CWY-5.3-E5C1W2, CWY-5.3-E5C2W2BT1, CWY-5.3-E5C1W2BT1
Model Difference	All the model are the same circuit and RF module, except the Model names.
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK
Number of Channels	40 Channels
Antenna Type	External Antenna
Antenna Gain	5dBi
Adapter	Model: XDJ961D-240400 Input: 100-240V~50/60Hz 2.0A Output: 24V⎓4.0A 96.0W
Battery	N/A
Power supply	DC 56V from POE port or DC 24V from Adapter.
HW Version	V1.3
SW Version	V1.7.0-8

Note 1: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Note 2: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

Revision History

Report No.	Version	Description	Issued Date
S22032401905001	Rev.01	Initial issue of report	Jul.08, 2022

4 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps/2Mbps for GFSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2404
…	…
19	2440
20	2442
…	…
38	2478
39	2480

Note: fc=2402MHz+k×2MHz k=0 to 39

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Test Cases	
Test Item	Data Rate/ Modulation
AC Conducted Emission	Mode 1: normal link mode
Radiated Test Cases	Mode 1: normal link mode
	Mode 2: GFSK Tx Ch00_2402MHz_1Mbps/2Mbps
	Mode 3: GFSK Tx Ch19_2440MHz_1Mbps/2Mbps
	Mode 4: GFSK Tx Ch39_2480MHz_1Mbps/2Mbps
Conducted Test Cases	Mode 2: GFSK Tx Ch00_2402MHz_1Mbps/2Mbps
	Mode 3: GFSK Tx Ch19_2440MHz_1Mbps/2Mbps
	Mode 4: GFSK Tx Ch39_2480MHz_1Mbps/2Mbps

Note:
1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode(duty cycle =100% during the test)
2. AC power line Conducted Emission was tested under maximum output power.
3. For radiated test cases, the worst mode data rate 2Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

5 SETUP OF EQUIPMENT UNDER TEST

5.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	XDJ961D-240400	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	DC Cable	YES	NO	1.2m
C-3	RF Cable	YES	NO	0.1m

Notes:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

5.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Aglient	E4407B	MY45108040	2021.03.30 2022.03.30	2022.03.29 2023.03.29	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2021.07.01 2022.06.16	2022.06.30 2023.06.15	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2021.07.01 2022.06.16	2022.06.30 2023.06.15	1 year
4	Test Receiver	R&S	ESPI7	101318	2022.04.06	2023.04.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.30 2022.03.30	2022.03.29 2023.03.29	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2021.03.30 2022.03.31	2022.03.29 2023.03.30	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2021.11.07	2022.11.06	1 year
9	Amplifier	EMC	EMC051835SE	980246	2021.07.01 2022.06.17	2022.06.30 2023.06.16	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2021.11.07	2022.11.06	1 year
11	Power Meter	DARE	RPR3006W	15I00041SNO84	2021.07.01 2022.06.17	2022.06.30 2023.06.16	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	High Test Cable(1G-40GHz)	N/A	R-04	N/A	2019.08.06	2022.08.05	3 year
16	Filter	TRILTHIC	2400MHz	29	2020.04.07	2023.04.06	3 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:
We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2022.04.06	2023.04.05	1 year
2	LISN	R&S	ENV216	101313	2022.04.06	2023.04.05	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2022.04.06	2023.04.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

6 TEST REQUIREMENTS

6.1 CONDUCTED EMISSIONS TEST

6.1.1 Applicable Standard

According to FCC Part 15.207(a)

6.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.1.4 Test Configuration



6.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

6.1.6 Test Results

EUT:	Celerway Stratus 5G	Model Name :	CWY-5.3-E5C2W2
Temperature:	22 ℃	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 56V from POE AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1859	38.65	9.61	48.26	64.21	-15.95	QP
0.1859	30.85	9.61	40.46	54.21	-13.75	AVG
0.2058	35.20	9.61	44.81	63.37	-18.56	QP
0.2058	28.87	9.61	38.48	53.37	-14.89	AVG
0.2459	38.32	9.62	47.94	61.89	-13.95	QP
0.2459	34.66	9.62	44.28	51.89	-7.61	AVG
0.4899	33.15	9.65	42.80	56.17	-13.37	QP
0.4899	26.32	9.65	35.97	46.17	-10.20	AVG
1.3540	29.24	9.66	38.90	56.00	-17.10	QP
1.3540	23.37	9.66	33.03	46.00	-12.97	AVG
13.7819	31.12	10.08	41.20	60.00	-18.80	QP
13.7819	23.33	10.08	33.41	50.00	-16.59	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Celerway Stratus 5G	Model Name ：	CWY-5.3-E5C2W2
Temperature：	22℃	Relative Humidity：	57%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 56V from POE AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1940	38.10	9.63	47.73	63.86	-16.13	QP
0.1940	29.63	9.63	39.26	53.86	-14.60	AVG
0.2500	37.19	9.61	46.80	61.75	-14.95	QP
0.2500	33.08	9.61	42.69	51.75	-9.06	AVG
0.5299	33.85	9.65	43.50	56.00	-12.50	QP
0.5299	25.82	9.65	35.47	46.00	-10.53	AVG
0.9417	30.42	9.68	40.10	56.00	-15.90	QP
0.9417	24.05	9.68	33.73	46.00	-12.27	AVG
1.3340	29.34	9.66	39.00	56.00	-17.00	QP
1.3340	22.69	9.66	32.35	46.00	-13.65	AVG
15.0016	33.63	10.07	43.70	60.00	-16.30	QP
15.0016	24.84	10.07	34.91	50.00	-15.09	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Celerway Stratus 5G	Model Name ：	CWY-5.3-E5C2W2
Temperature：	22 ℃	Relative Humidity：	57%
Pressure：	1010hPa	Phase :	L
Test Voltage ：	DC 24V from Adapter AC120V/60HZ	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1564	42.38	9.60	51.98	65.65	-13.67	QP
0.1564	29.78	9.60	39.38	55.65	-16.27	AVG
0.2179	38.69	9.61	48.30	62.89	-14.59	QP
0.2179	30.56	9.61	40.17	52.89	-12.72	AVG
0.5936	33.04	9.66	42.70	56.00	-13.30	QP
0.5936	24.78	9.66	34.44	46.00	-11.56	AVG
1.1019	25.53	9.67	35.20	56.00	-20.80	QP
1.1019	16.97	9.67	26.64	46.00	-19.36	AVG
19.7419	24.90	10.20	35.10	60.00	-24.90	QP
19.7419	16.10	10.20	26.30	50.00	-23.70	AVG
26.8737	26.24	10.36	36.60	60.00	-23.40	QP
26.8737	19.34	10.36	29.70	50.00	-20.30	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Celerway Stratus 5G	Model Name ：	CWY-5.3-E5C2W2
Temperature：	22℃	Relative Humidity：	57%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 24V from Adapter AC120V/60HZ	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1621	45.35	9.65	55.00	65.35	-10.35	QP
0.1621	33.62	9.65	43.27	55.35	-12.08	AVG
0.2071	44.18	9.62	53.80	63.32	-9.52	QP
0.2071	34.27	9.62	43.89	53.32	-9.43	AVG
0.5299	32.85	9.65	42.50	56.00	-13.50	QP
0.5299	24.95	9.65	34.60	46.00	-11.40	AVG
1.2056	22.84	9.66	32.50	56.00	-23.50	QP
1.2056	16.45	9.66	26.11	46.00	-19.89	AVG
19.8819	25.62	10.18	35.80	60.00	-24.20	QP
19.8819	16.45	10.18	26.63	50.00	-23.37	AVG
27.1616	25.49	10.26	35.75	60.00	-24.25	QP
27.1616	19.17	10.26	29.43	50.00	-20.57	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



6.2 RADIATED SPURIOUS EMISSION

6.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

6.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz: Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz: Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

6.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.2.4 Test Configuration

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



6.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

6.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/ Mode4	Test By:	Mary Hu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

■ Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT:	Celerway Stratus 5G	Model Name :	CWY-5.3-E5C2W2
Temperature:	25 ℃	Relative Humidity:	55%
Pressure:	1010hPa	Test Mode:	Mode 1
Test Voltage :	DC 56V from POE AC 120V/60Hz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	34.6385	12.11	23.76	35.87	40.00	-4.13	QP
V	43.8119	17.81	18.67	36.48	40.00	-3.52	QP
V	111.3468	17.46	18.41	35.87	43.50	-7.63	QP
V	250.3009	22.82	18.68	41.50	46.00	-4.50	QP
V	375.9384	21.55	21.97	43.52	46.00	-2.48	QP
V	625.0778	14.27	25.87	40.14	46.00	-5.86	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	163.7548	13.46	17.79	31.25	43.50	-12.25	QP
H	250.3010	16.66	18.68	35.34	46.00	-10.66	QP
H	374.6225	21.24	21.96	43.20	46.00	-2.80	QP
H	501.1788	14.81	24.15	38.96	46.00	-7.04	QP
H	625.0778	15.58	25.87	41.45	46.00	-4.55	QP
H	875.2468	10.37	29.31	39.68	46.00	-6.32	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



EUT：	Celerway Stratus 5G	Model Name ：	CWY-5.3-E5C2W2
Temperature：	25 ℃	Relative Humidity：	55%
Pressure：	1010hPa	Test Mode：	Mode 1
Test Voltage ：	DC 24V from Adapter AC 120V/60Hz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	41.4215	16.25	19.98	36.23	40.00	-3.77	QP
V	57.9992	24.40	12.10	36.50	40.00	-3.50	QP
V	250.3009	21.06	18.68	39.74	46.00	-6.26	QP
V	373.3111	20.72	21.98	42.70	46.00	-3.30	QP
V	506.4791	16.54	24.16	40.70	46.00	-5.30	QP
V	752.7432	14.26	27.84	42.10	46.00	-3.90	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	185.7880	19.54	16.56	36.10	43.50	-7.40	QP
H	250.3009	22.32	18.68	41.00	46.00	-5.00	QP
H	375.9384	20.03	21.97	42.00	46.00	-4.00	QP
H	501.1788	18.24	24.15	42.39	46.00	-3.61	QP
H	625.0778	12.10	25.87	37.97	46.00	-8.03	QP
H	881.4067	12.05	29.25	41.30	46.00	-4.70	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Frequency	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2402 MHz)(GFSK)--Above 1G									
4802.15	64.82	5.21	35.59	44.30	61.32	74.00	-12.68	Pk	Vertical
4802.15	43.33	5.21	35.59	44.30	39.83	54.00	-14.17	AV	Vertical
7206.27	60.89	6.48	36.27	44.60	59.04	74.00	-14.96	Pk	Vertical
7206.27	43.52	6.48	36.27	44.60	41.67	54.00	-12.33	AV	Vertical
4804.07	64.94	5.21	35.55	44.30	61.40	74.00	-12.60	Pk	Horizontal
4804.07	43.80	5.21	35.55	44.30	40.26	54.00	-13.74	AV	Horizontal
7206.54	64.30	6.48	36.27	44.52	62.53	74.00	-11.47	Pk	Horizontal
7206.54	43.79	6.48	36.27	44.52	42.02	54.00	-11.98	AV	Horizontal
Mid Channel (2440 MHz)(GFSK)--Above 1G									
4880.09	62.09	5.21	35.66	44.20	58.76	74.00	-15.24	Pk	Vertical
4880.09	43.12	5.21	35.66	44.20	39.79	54.00	-14.21	AV	Vertical
7320.89	61.40	7.10	36.50	44.43	60.57	74.00	-13.43	Pk	Vertical
7320.89	43.71	7.10	36.50	44.43	42.88	54.00	-11.12	AV	Vertical
4880.15	61.38	5.21	35.66	44.20	58.05	74.00	-15.95	Pk	Horizontal
4880.15	43.52	5.21	35.66	44.20	40.19	54.00	-13.81	AV	Horizontal
7320.25	63.92	7.10	36.50	44.43	63.09	74.00	-10.91	Pk	Horizontal
7320.25	43.43	7.10	36.50	44.43	42.60	54.00	-11.40	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4960.17	62.94	5.21	35.52	44.21	59.46	74.00	-14.54	Pk	Vertical
4960.17	43.09	5.21	35.52	44.21	39.61	54.00	-14.39	AV	Vertical
7440.31	63.08	7.10	36.53	44.60	62.11	74.00	-11.89	Pk	Vertical
7440.31	43.69	7.10	36.53	44.60	42.72	54.00	-11.28	AV	Vertical
4960.44	61.80	5.21	35.52	44.21	58.32	74.00	-15.68	Pk	Horizontal
4960.44	43.19	5.21	35.52	44.21	39.71	54.00	-14.29	AV	Horizontal
7440.39	64.19	7.10	36.53	44.60	63.22	74.00	-10.78	Pk	Horizontal
7440.39	43.51	7.10	36.53	44.60	42.54	54.00	-11.46	AV	Horizontal

Note:

(1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2)All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Mary Hu

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
1Mbps(GFSK)									
2310.00	62.80	2.97	27.80	43.80	49.77	74	-24.23	Pk	Horizontal
2310.00	39.66	2.97	27.80	43.80	26.63	54	-27.37	AV	Horizontal
2310.00	60.73	2.97	27.80	43.80	47.70	74	-26.30	Pk	Vertical
2310.00	43.64	2.97	27.80	43.80	30.61	54	-23.39	AV	Vertical
2390.00	63.59	3.14	27.21	43.80	50.14	74	-23.86	Pk	Vertical
2390.00	43.99	3.14	27.21	43.80	30.54	54	-23.46	AV	Vertical
2390.00	64.55	3.14	27.21	43.80	51.10	74	-22.90	Pk	Horizontal
2390.00	43.70	3.14	27.21	43.80	30.25	54	-23.75	AV	Horizontal
2483.50	63.15	3.58	27.70	44.00	50.43	74	-23.57	Pk	Vertical
2483.50	43.61	3.58	27.70	44.00	30.89	54	-23.11	AV	Vertical
2483.50	61.09	3.58	27.70	44.00	48.37	74	-25.63	Pk	Horizontal
2483.50	43.39	3.58	27.70	44.00	30.67	54	-23.33	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Mary Hu

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	63.98	4.04	29.57	44.70	52.89	74	-21.11	Pk	Vertical
3260	43.13	4.04	29.57	44.70	32.04	54	-21.96	AV	Vertical
3260	60.06	4.04	29.57	44.70	48.97	74	-25.03	Pk	Horizontal
3260	43.23	4.04	29.57	44.70	32.14	54	-21.86	AV	Horizontal
3332	62.52	4.26	29.87	44.40	52.25	74	-21.75	Pk	Vertical
3332	43.73	4.26	29.87	44.40	33.46	54	-20.54	AV	Vertical
3332	64.32	4.26	29.87	44.40	54.05	74	-19.95	Pk	Horizontal
3332	43.01	4.26	29.87	44.40	32.74	54	-21.26	AV	Horizontal
17797	46.39	10.99	43.95	43.50	57.83	74	-16.17	Pk	Vertical
17797	34.92	10.99	43.95	43.50	46.36	54	-7.64	AV	Vertical
17788	47.14	11.81	43.69	44.60	58.04	74	-15.96	Pk	Horizontal
17788	34.87	11.81	43.69	44.60	45.77	54	-8.23	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

6.3 6DB BANDWIDTH

6.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.2.

6.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

6.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.3.4 Test Setup

Please refer to Section 6.1 of this test report.

6.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3*RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.6 Test Results

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

6.4 DUTY CYCLE

6.4.1 Applicable Standard

According to KDB 558074 D01 15.247 Meas Guidance v05r02s Section 6.

6.4.2 Conformance Limit

No limit requirement.

6.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.4.4 Test Setup

Please refer to Section 6.1 of this test report.

6.4.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if T ≤ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Zero Span
RBW = 8MHz(the largest available value)
VBW = 8MHz (≥ RBW)
Number of points in Sweep >100
Detector function = peak
Trace = Clear write
Measure T_{total} and T_{on}
Calculate Duty Cycle = T_{on} / T_{total}

6.4.6 Test Results

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	N/A	Test By:	N/A

Note：Not Applicable

6.5 PEAK OUTPUT POWER

6.5.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.3.1.

6.5.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

6.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.5.4 Test Setup

Please refer to Section 6.1 of this test report.

6.5.5 Test Procedure

The testing follows Subclause 11.9.1.1 of ANSI C63.10
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Set the RBW ≧DTS bandwidth.
Set VBW =3*RBW.
Set the span ≧3*RBW
Set Sweep time = auto couple.
Set Detector = peak.
Set Trace mode = max hold.
Allow trace to fully stabilize.
Use peak marker function to determine the peak amplitude level.

6.5.6 Test Results

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

6.6 POWER SPECTRAL DENSITY

6.6.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.4.

6.6.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.6.4 Test Setup

Please refer to Section 6.1 of this test report.

6.6.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10
This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5*DTS bandwidth.
c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ 3 RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.6.6 Test Results

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

6.7 CONDUCTED BAND EDGE MEASUREMENT

6.7.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

6.7.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

6.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.7.4 Test Setup

Please refer to Section 6.1 of this test report.

6.7.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
Repeat above procedures until all measured frequencies were complete.

6.7.6 Test Results

EUT:	Celerway Stratus 5G	Model No.:	CWY-5.3-E5C2W2
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Mary Hu

Test data reference attachment.

6.8 SPURIOUS RF CONDUCTED EMISSIONS

6.8.1 Conformance Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

6.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

6.8.3 Test Setup

Please refer to Section 6.1 of this test report.

6.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and measure frequency range from 30MHz to 26.5GHz.

6.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

6.9 ANTENNA APPLICATION

6.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.9.2 Result

The EUT antenna is permanent attached External antenna (Gain:5dBi). It comply with the standard requirement.

7 TEST RESULTS

7.1.1 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant 1	5.33	30	Pass
NVNT	BLE	2440	Ant 1	4.95	30	Pass
NVNT	BLE	2480	Ant 1	4.57	30	Pass

Power NVNT BLE 2402MHz Ant1



Power NVNT BLE 2440MHz Ant1



Power NVNT BLE 2480MHz Ant1



7.1.2 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant 1	0.6638	0.5	Pass
NVNT	BLE	2440	Ant 1	0.667	0.5	Pass
NVNT	BLE	2480	Ant 1	0.6794	0.5	Pass

-6 dB BW NVNT BLE 2402MHz Ant1



-6 dB BW NVNT BLE 2440MHz Ant1



-6 dB BW NVNT BLE 2480MHz Ant1



7.1.3 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE	2402	Ant 1	-10.75	8	Pass
NVNT	BLE	2440	Ant 1	-11.08	8	Pass
NVNT	BLE	2480	Ant 1	-11.52	8	Pass

PSD NVNT BLE 2402MHz Ant1



PSD NVNT BLE 2440MHz Ant1



PSD NVNT BLE 2480MHz Ant1



7.1.4 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant 1	-54.81	-20	Pass
NVNT	BLE	2480	Ant 1	-55.78	-20	Pass

Band Edge NVNT BLE 2402MHz Ant1 Ref



Band Edge NVNT BLE 2402MHz Ant1 Emission



Band Edge NVNT BLE 2480MHz Ant1 Ref



Band Edge NVNT BLE 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48005 GHz	4.02 dBm		
M2		1	2.4835 GHz	-54.03 dBm		
M3		1	2.5 GHz	-54.23 dBm		
M4		1	2.4881 GHz	-52.27 dBm		

7.1.5 CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant 1	-48.62	-20	Pass
NVNT	BLE	2440	Ant 1	-48.75	-20	Pass
NVNT	BLE	2480	Ant 1	-48.68	-20	Pass

Tx. Spurious NVNT BLE 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40249 GHz	3.39 dBm		
M2		1	15.027814 GHz	-45.13 dBm		
M3		1	4.979886 GHz	-49.87 dBm		
M4		1	7.387827 GHz	-49.66 dBm		
M5		1	9.720025 GHz	-50.02 dBm		

Tx. Spurious NVNT BLE 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 2440MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.43994 GHz	1.61 dBm		
M2		1	16.655858 GHz	-45.42 dBm		
M3		1	4.933276 GHz	-48.53 dBm		
M4		1	7.295438 GHz	-49.51 dBm		
M5		1	9.695887 GHz	-49.54 dBm		

Tx. Spurious NVNT BLE 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47989 GHz	2.94 dBm		
M2		1	20.194107 GHz	-45.82 dBm		
M3		1	5.150515 GHz	-50.18 dBm		
M4		1	7.408635 GHz	-50.04 dBm		
M5		1	10.024659 GHz	-49.80 dBm		

END OF REPORT