TEST REPORT

Product Name	:	VVFLY Massager Device
Brand Mark	:	Snore circle
Model No.	:	YA50
Extension Model	:	YA60,YA70,YA80,YA90YA50A,YA50G, YA50F,YA50C
FCC ID	:	2AW7X-YA50
Report Number	:	BLA-EMC-202305-A0803
Date of Sample Receipt	:	2023/5/4
Date of Test	:	2023/5/5 to 2023/5/17
Date of Issue	:	2023/5/17
Test Standard	:	47 CFR Part 15, Part1.1307 47 CFR Part 15, Part2.1093 KDB447498D04 General RF Exposure Guidance v01
Test Result	:	Pass

Prepared for:

VVFly Electronics Co.,Ltd.
Unit 2103-2104, Changhong Sci-tech Building,Science and Technology Park,Nanshan District

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Lucas

Review by: Sweely

Approved by: Blue.Zheng

Date: 2023/5/17

BlueAsia of Technical Services(Shenzhen) Co.,Ltd. BLA

REPORT REVISE RECORD

Version No.	Date	Description
00	2023/5/17	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY **4**

2 GENERAL INFORMATION **5**

3 GENERAL DESCRIPTION OF E.U.T. **5**

4 LABORATORY LOCATION **6**

5 RF EXPOSURE COMPLIANCE REQUIREMENT **7**

5.1 STANDARD REQUIREMENT 7

5.2 LIMITS 7

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS

BlueAsia

2 GENERAL INFORMATION

Applicant	VVFly Electronics Co.,Ltd.
Address	Unit 2103-2104, Changhong Sci-tech Building,Science and Technology Park,Nanshan District
Manufacturer	VVFly Electronics Co.,Ltd.
Address	Unit 2103-2104, Changhong Sci-tech Building,Science and Technology Park,Nanshan District
Factory	DONGGUAN TOHEI E.M.C.CO.,LTD
Address	Qingfeng Road,Jinlong Industrial District,Qingxi,Dongguan Guangdong
Product Name	VVFLY Massager Device
Test Model No.	YA50
Extension Model	YA60,YA70,YA80,YA90,YA50A,YA50G,YA50F,YA50C
Remark	Color only difference.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	N/A
Software Version	N/A

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Chip Antenna
Antenna Gain:	6.62 dBi(Provided by the customer)

BlueAsia

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

$$P_{\text{th}}\ (\text{mW}) = \begin{cases} ERP_{20\ \text{cm}}(d/20\ \text{cm})^x & d \le 20\ \text{cm} \\ ERP_{20\ \text{cm}} & 20\ \text{cm} < d \le 40\ \text{cm} \end{cases} \qquad \text{(B.2)}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\ \text{cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$P_{\text{th}}\ (\text{mW}) = ERP_{20\ \text{cm}}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases} \qquad \text{(B.1)}$$

EIRP = pt×gt = (E×d)2/30
where:
pt = transmitter output power in watts,
gt = numeric gain of the transmitting antenna (unitless),
E = electric field strength in V/m, --- 10((dBuV/m)/20)/106
d = measurement distance in meters (m)---3m
Sopt = (E×d)2/30 × gt

Ant gain = 6.62 dBi
Max Output power =-3.100dBm @EDR@ 2480MHz
ERP = -3.100dBm+6.62dBi-2.15=1.37dBm
So

worse case：

10^0.137=1.371mW < 2.79 mW
Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia