

TEST REPORT

Product Name : Smart Mini Pro Projector
Brand Mark : N/A
Model No. : M1200S
FCC ID : 2AW96-M1200S
Report Number : BLA-EMC-202012-A1502
Date of Sample Receipt : 2020/12/3
Date of Test : 2020/12/3 to 2020/12/17
Date of Issue : 2021/01/15
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Telstar USA LLC

9817 Valley View Road, Eden Prairie, MN, US

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

**Building C, No. 107, Shihuan Road, Shiyao Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481

Compiled by:

Ben Zang

Review by:

Sweet. Liang

Approved by:

Imen Li

Date:

2021/01/15



REPORT REVISE RECORD

Version No.	Date	Description
00	2021/01/15	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	6
2	GENERAL INFORMATION	7
3	GENERAL DESCRIPTION OF E.U.T.	7
4	TEST ENVIRONMENT	8
5	TEST MODE	8
6	MEASUREMENT UNCERTAINTY	8
7	DESCRIPTION OF SUPPORT UNIT.....	9
8	LABORATORY LOCATION.....	9
9	TEST INSTRUMENTS LIST	10
1	RADIATED SPURIOUS EMISSIONS.....	14
1.1	LIMITS	14
1.2	BLOCK DIAGRAM OF TEST SETUP	15
1.3	PROCEDURE	15
1.4	TEST DATA	17
2	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	25
2.1	LIMITS	25
2.2	BLOCK DIAGRAM OF TEST SETUP	26
2.3	PROCEDURE	26
2.4	TEST DATA	28
3	CONDUCTED SPURIOUS EMISSIONS	32
3.1	LIMITS	32
3.2	BLOCK DIAGRAM OF TEST SETUP	32
3.3	TEST DATA	33
4	CONDUCTED BAND EDGES MEASUREMENT.....	34
4.1	LIMITS	34
4.2	BLOCK DIAGRAM OF TEST SETUP	34
4.3	TEST DATA	35
5	DWELL TIME.....	36
5.1	LIMITS	36
5.2	BLOCK DIAGRAM OF TEST SETUP	36

5.3	TEST DATA	37
6	HOPPING CHANNEL NUMBER	38
6.1	LIMITS	38
6.2	BLOCK DIAGRAM OF TEST SETUP	38
6.3	TEST DATA	38
7	CARRIER FREQUENCIES SEPARATION	39
7.1	LIMITS	39
7.2	BLOCK DIAGRAM OF TEST SETUP	39
7.3	TEST DATA	39
8	20DB BANDWIDTH.....	40
8.1	BLOCK DIAGRAM OF TEST SETUP	40
8.2	TEST DATA	40
9	CONDUCTED PEAK OUTPUT POWER	41
9.1	LIMITS	41
9.2	BLOCK DIAGRAM OF TEST SETUP	41
9.3	TEST DATA	42
10	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	43
10.1	LIMITS	43
10.2	BLOCK DIAGRAM OF TEST SETUP	43
10.3	PROCEDURE	43
10.4	TEST DATA.....	45
11	ANTENNA REQUIREMENT	47
11.1	CONCLUSION	47
10	APPENDIX.....	48
10.1	APPENDIX:20DBEMISSION BANDWIDTH	48
	<i>Test Result.....</i>	48
	<i>Test Graphs</i>	49
10.2	APPENDIX:MAXIMUM CONDUCTED OUTPUT POWER.....	53
	<i>Test Result.....</i>	53
	<i>Test Graphs</i>	54
10.3	APPENDIX:CARRIER FREQUENCY SEPARATION	58
	<i>Test Result.....</i>	58

Test Graphs	59
10.4 APPENDIX:TIME OF OCCUPANCY	60
Test Result.....	60
Test Graphs	61
10.5 APPENDIX:NUMBER OF HOPPING CHANNELS	63
Test Result.....	63
Test Graphs	64
10.6 APPENDIX:BAND EDGE MEASUREMENTS	65
Test Result.....	65
Test Graphs	66
10.7 APPENDIX:CONDUCTED SPURIOUS EMISSION	72
Test Result.....	72
Test Graphs	73
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	83

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.9	47 CFR Part 15, Subpart C 15.215	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

2 GENERAL INFORMATION

Applicant	Telstar USA LLC
Address	9817 Valley View Road, Eden Prairie, MN, US
Manufacturer	Telstar USA LLC
Address	9817 Valley View Road, Eden Prairie, MN, US
Factory	N/A
Address	N/A
Product Name	Smart Mini Pro Projector
Test Model No.	M1200S

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	N/A
Software Version	N/A
Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Internal Antenna
Antenna Gain:	3dBi (Provided by the customer)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	+25°C	19Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned Only the GFSK, Pi/4QPSK 8DPSK of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen,
Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2018	5/7/2021
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Receiver	R&S	ESR7	101199	4/20/2020	4/19/2021
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2018	7/13/2021
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2018	7/13/2021
Amplifier	SKET	PA-000318G-45	N/A	7/1/2020	6/30/2021
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2019	2/13/2022
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2018	5/7/2021
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Receiver	R&S	ESR7	101199	4/20/2020	4/19/2021
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2018	7/13/2021
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2018	7/13/2021

Amplifier	SKET	PA-000318G-45	N/A	7/1/2020	6/30/2021
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2019	2/13/2022
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Dwell Time

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020

Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Hopping Channel Number

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Carrier Frequencies Separation

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of 20dB Bandwidth

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Conducted Peak Output Power

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	6/10/2018	6/9/2021
Receiver	R&S	ESPI3	101082	4/20/2020	4/19/2021
LISN	R&S	ENV216	3560.6550.15	7/1/2020	6/30/2021
LISN	AT	AT166-2	AKK1806000003	12/17/2019	12/16/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

1 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX Low channel;TX middle channel;TX high channel
Test Mode (Final Test)	TX Low channel;TX middle channel;TX high channel
Tester	Ben
Temperature	25℃
Humidity	60%

1.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

1.2 BLOCK DIAGRAM OF TEST SETUP



1.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

1.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.

[TestMode: TX Low channel]; [Polarity: Horizontal]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site Limit: FCC Part15 (PK) EUT: M/N: M1200S Mode: EDR-2441 Note:

Polarization: **Horizontal** Power: AC120V/60Hz Distance: 3m

Temperature: Humidity: %


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		7826.750	52.11	0.93	53.04	74.00	-20.96	peak		
2		10670.250	51.01	1.76	52.77	74.00	-21.23	peak		
3	*	12703.000	49.54	3.60	53.14	74.00	-20.86	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

2 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX Low channel;TX middle channel;TX high channel
Test Mode (Final Test)	TX Low channel;TX high channel
Tester	Ben
Temperature	25℃
Humidity	60%

2.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

2.2 BLOCK DIAGRAM OF TEST SETUP



2.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

2.4 TEST DATA

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.


[TestMode: TX highest channel]; [Polarity: Horizontal]



Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site
Limit: FCC Part15 (PK)
EUT:
M/N: M1200S
Mode: EDR-2480-PK
Note:

Polarization: **Vertical**
Power: AC120V/60Hz
Distance: 3m
Temperature:
Humidity: %


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		2483.500	70.07	-14.33	55.74	74.00	-18.26	peak			
2	*	2483.500	65.59	-14.33	51.26	54.00	-2.74	AVG	150	0	
3		2500.000	55.30	-14.27	41.03	74.00	-32.97	peak			
4		2500.000	42.98	-14.27	28.71	54.00	-25.29	AVG	150	0	

*:Maximum data x:Over limit !:over margin

(Reference Only)


Test Result: Pass

[TestMode: TX lowest channel]; [Polarity: Horizontal]



Test Result: Pass

[TestMode: TX lowest channel]; [Polarity: Vertical]



Test Result: Pass


3 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

3.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	---

3.2 BLOCK DIAGRAM OF TEST SETUP



3.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


4 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

4.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

4.2 BLOCK DIAGRAM OF TEST SETUP



4.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


5 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

5.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4Smultiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

5.2 BLOCK DIAGRAM OF TEST SETUP



5.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


6 HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

6.1 LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

6.2 BLOCK DIAGRAM OF TEST SETUP



6.3 TEST DATA

Pass: Please Refer To Appendix: For Details


7 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

7.1 LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W
---------------	--

7.2 BLOCK DIAGRAM OF TEST SETUP




7.3 TEST DATA

Pass: Please Refer To Appendix: For Details
--

8 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.9
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

8.1 BLOCK DIAGRAM OF TEST SETUP



8.2 TEST DATA

Pass: Please Refer To Appendix: For Details


9 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

9.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq \text{hopping channels} < 50$
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

9.2 BLOCK DIAGRAM OF TEST SETUP



9.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

10 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Ben
Temperature	25°C
Humidity	60%

10.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

10.2 BLOCK DIAGRAM OF TEST SETUP



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

10.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50?H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as

the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,


4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $\text{LISN} = \text{Read Level} + \text{Cable Loss} + \text{LISN Factor}$

10.4 TEST DATA

[TestMode: TX]; [Line: Line]



Test Result: Pass

[TestMode: TX]; [Line: Nutral]

Conducted Emission Measurement



Site: Limit: FCC Class B Conduction(QP) EUT: M/N: M1200S Mode: EDR Mode Note:

Phase: **N** Power: AC120V/60Hz Temperature: Humidity: %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1900	34.14	9.88	44.02	64.04	-20.02	QP	
2	0.1900	18.49	9.88	28.37	54.04	-25.67	AVG	
3	0.3558	36.58	9.76	46.34	58.83	-12.49	QP	
4	0.3558	23.53	9.76	33.29	48.83	-15.54	AVG	
5 *	0.4620	39.45	9.72	49.17	56.66	-7.49	QP	
6	0.4620	22.03	9.72	31.75	46.66	-14.91	AVG	
7	0.5980	37.53	9.74	47.27	56.00	-8.73	QP	
8	0.5980	19.39	9.74	29.13	46.00	-16.87	AVG	
9	0.7820	30.22	9.74	39.96	56.00	-16.04	QP	
10	0.7820	14.19	9.74	23.93	46.00	-22.07	AVG	
11	21.4980	27.38	10.04	37.42	60.00	-22.58	QP	
12	21.4980	20.14	10.04	30.18	50.00	-19.82	AVG	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

11 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

11.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3dBi.



10 APPENDIX


10.1 APPENDIX: 20DB EMISSION BANDWIDTH

Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	1.122	2401.454	2402.576	---	PASS
		2441	1.119	2440.454	2441.573	---	PASS
		2480	1.119	2479.454	2480.573	---	PASS
2DH1	Ant1	2402	1.410	2401.307	2402.717	---	PASS
		2441	1.413	2440.307	2441.720	---	PASS
		2480	1.410	2479.304	2480.714	---	PASS
3DH1	Ant1	2402	1.407	2401.313	2402.720	---	PASS
		2441	1.407	2440.313	2441.720	---	PASS
		2480	1.401	2479.316	2480.717	---	PASS

Test Graphs





2DH1 Ant1 2402



2DH1 Ant1 2441



2DH1 Ant1 2480






10.2 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER

Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	-3.16	<=20.97	PASS
		2441	-2.64	<=20.97	PASS
		2480	-2.56	<=20.97	PASS
2DH1	Ant1	2402	-4.59	<=20.97	PASS
		2441	-3.96	<=20.97	PASS
		2480	-3.87	<=20.97	PASS
3DH1	Ant1	2402	4.42	<=20.97	PASS
		2441	4.97	<=20.97	PASS
		2480	5.12	<=20.97	PASS

Test Graphs





2DH1 Ant1 2402




2DH1 Ant1 2441



2DH1 Ant1 2480



3DH1 Ant1 2402



3DH1 Ant1 2441



3DH1 Ant1 2480




10.3 APPENDIX: CARRIER FREQUENCY SEPARATION

Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	0.844	≥ 0.748	PASS
2DH1	Ant1	Hop	1.004	≥ 0.942	PASS
3DH1	Ant1	Hop	0.998	≥ 0.938	PASS

Test Graphs






10.4 APPENDIX: TIME OF OCCUPANCY

Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.38	330	0.125	<=0.4	PASS
DH3	Ant1	Hop	1.64	140	0.229	<=0.4	PASS
DH5	Ant1	Hop	2.88	120	0.346	<=0.4	PASS

Test Graphs







10.5 APPENDIX: NUMBER OF HOPPING CHANNELS**Test Result**

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥ 15	PASS
2DH1	Ant1	Hop	79	≥ 15	PASS
3DH1	Ant1	Hop	79	≥ 15	PASS

Test Graphs





10.6 APPENDIX: BAND EDGE MEASUREMENTS

Test Result

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH1	Ant1	Low	2402	-4.25	-56.17	<=-24.25	PASS
		High	2480	-3.33	-55.53	<=-23.33	PASS
		Low	Hop 2402	1.44	-56.49	-18.57	PASS
		High	Hop 2480	2.47	-55.14	-17.53	PASS
2DH1	Ant1	Low	2402	-8.88	-56.62	<=-28.88	PASS
		High	2480	-8.23	-55.82	<=-28.23	PASS
		Low	Hop 2402	7.46	-56.61	-12.54	PASS
		High	Hop 2480	8.67	-55.39	-11.33	PASS
3DH1	Ant1	Low	2402	-0.61	-56.14	<=-20.61	PASS
		High	2480	0.51	-55.75	<=-19.49	PASS
		Low	Hop 2402	7.24	-55.48	-12.76	PASS
		High	Hop 2480	7.87	-55.38	-12.13	PASS

Test Graphs



DH1 Ant1 Low Hop 2402




DH1 Ant1 High Hop 2480



2DH1 Ant1 Low 2402



2DH1 Ant1 High 2480



2DH1 Ant1 Low Hop 2402



2DH1 Ant1 High Hop 2480






3DH1 Ant1 Low Hop 2402



3DH1 Ant1 High Hop 2480





10.7 APPENDIX: CONDUCTED SPURIOUS EMISSION

Test Result

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH1	Ant1	2402	Reference	-4.29	-4.29	---	PASS
			30~1000	30~1000	-66.207	<=-34.291	PASS
			1000~26500	1000~26500	-54.367	<=-34.291	PASS
		2441	Reference	-3.36	-3.36	---	PASS
			30~1000	30~1000	-66.741	<=-33.36	PASS
			1000~26500	1000~26500	-53.138	<=-33.36	PASS
		2480	Reference	-3.33	-3.33	---	PASS
			30~1000	30~1000	-66.575	<=-33.328	PASS
			1000~26500	1000~26500	-54.334	<=-33.328	PASS
2DH1	Ant1	2402	Reference	-8.96	-8.96	---	PASS
			30~1000	30~1000	-67.355	<=-38.963	PASS
			1000~26500	1000~26500	-54.18	<=-38.963	PASS
		2441	Reference	-8.40	-8.40	---	PASS
			30~1000	30~1000	-66.551	<=-38.396	PASS
			1000~26500	1000~26500	-54.125	<=-38.396	PASS
		2480	Reference	-8.19	-8.19	---	PASS
			30~1000	30~1000	-66.379	<=-38.193	PASS
			1000~26500	1000~26500	-54.328	<=-38.193	PASS
3DH1	Ant1	2402	Reference	-0.71	-0.71	---	PASS
			30~1000	30~1000	-65.833	<=-30.712	PASS
			1000~26500	1000~26500	-54.207	<=-30.712	PASS
		2441	Reference	-0.06	-0.06	---	PASS
			30~1000	30~1000	-66.789	<=-30.06	PASS
			1000~26500	1000~26500	-53.799	<=-30.06	PASS
		2480	Reference	-0.01	-0.01	---	PASS
			30~1000	30~1000	-65.956	<=-30.012	PASS
			1000~26500	1000~26500	-53.032	<=-30.012	PASS

Test Graphs














2DH1 Ant1 2441 0~Reference




2DH1 Ant1 2441 30~1000




2DH1 Ant1 2441 1000~26500




2DH1 Ant1 2480 0~Reference




2DH1 Ant1 2480 30~1000




2DH1 Ant1 2480 1000~26500




3DH1 Ant1 2402 0~Reference



3DH1 Ant1 2402 30~1000



3DH1 Ant1 2402 1000~26500








APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Radiated Spurious Emissions



Conducted Emissions at AC Power Line (150kHz-30MHz)

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.